



ZHONGHAN

RF Exposure Evaluation

FCC ID:2A8A4-M833

Report No..... : ZHT-250626109W03-3

Product..... : Macaron Series 2.4G Wireless Mouse

Trademark..... : /

Model(s)..... : M833
F01, M834, M865, M864, M835

Model Difference..... : M833 is tested model, other models are derivative models .The models are identical in circuit, only different on the model names and color. So the test data of M833 can represent the remaining models.

Applicant..... : Dongguan Eranode Electronics Limited

Address..... : Building 2, No.17, Dahuan Road, Dalingshan Town, Dongguan City, Guangdong China

Manufacturer..... : Dongguan Eranode Electronics Limited

Address..... : Building 2, No.17, Dahuan Road, Dalingshan Town, Dongguan City, Guangdong China

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : June 26, 2025

Date of Test(s)..... : June 26, 2025-July 8, 2025

Date of Issue..... : July 24, 2025

Test Standard(s)..... : KDB 447498 D01 General RF Exposure Guidance v06

In the configuration tested, the EUT complied with the standards specified above.

Prepared by:

Reviewed by:

Approved by:

Kimi Lu

Kimi Lu/ Engineer

Baret Wu

Baret Wu/ Director

Levi Lee

Levi Lee/ Manager

Note: The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report shall not be reproduced except in full, without prior written approval of ZHT. This document may be altered or revised by ZHT, personnel only, and shall be noted in the revision of the document.



ZHONGHAN

Table of Contents

Page

1. VERSION	3
2. RF EXPOSURE EVALUATION	4



ZHONGHAN

1. VERSION

Report No.	Version	Description	Approved
ZHT-250626109W03-3	Rev.01	Initial issue of report	July 24, 2025



ZHONGHAN

2. RF EXPOSURE EVALUATION

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation The result is rounded to one decimal place for comparison

Here,

For Bluetooth,2.4G

Mode	Max Power (dBm)	Tune-up power (dBm)	Max Power (mW)	Frequency(MHz)	Min. Distance (mm)	Calc. thresholds	limit
2.4G	1.95	1±1	1.58	2402	5	0.490	3.0
BLE	1.79	1±1	1.58	2402	5	0.490	3.0

The device could support transmission with 2.4G, BLE simultaneously.

$\text{MPE1/LIMIT} + \text{MPE2/LIMIT} = 0.490/3 + 0.490/3 = 0.327 \leq 1.0$

Conclusion: $0.327 \leq 1.0$ or FCC SAR, No RF Exposure Evaluation/SAR test is required.