

RF Exposure evaluation

FCC ID: 2A8D2-DMP-A6G2

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

DMP-A6 Gen 2 can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
BT	/	External antenna	3.0dBi for 2400-2500MHz;	
2.4GWIFI	/	External antenna	3.0dBi for 2400-2500MHz for ANT 1&2	
5GWIFI	/	External antenna	3.0dBi for 5150-5250MHz for ANT 1&2 3.0dBi for 5750-5850MHz for ANT 1&2	
Directional gain=Antenna Gain(dBi) +log(N _{ant})=6.01dBi				

5. Manufacturing Tolerance

BT

Mode	Max. Peak Conducted Output Power (dBm)		Max. tune-up	
	Antenna		Antenna	
BT	-0.05		0.0 ± 1	
BLE	0.24		1.0 ± 1	

2.4GWIFI

Mode	Max. Peak Conducted Output Power (dBm)		Max. tune-up	
	Antenna0	Antenna1	Antenna0	Antenna1
2.4GWIFI	14.84	14.65	15.0 ± 1	15 ± 1

5GWIFI

Mode	Max. Average Conducted Output Power (dBm)		Max. tune-up	
	Antenna0	Antenna1	Antenna0	Antenna1
5.2GWIFI	13.88	13.33	13.0 ± 1	13.0 ± 1
5.8GAWIFI	12.73	12.12	13.0 ± 1	13.0 ± 1

Mode	Max. Peak Conducted Output Power (dBm)	Max. tune-up
2.4GWIFI MIMO	16.56	16.0 ± 1
Mode	Max. average Conducted Output Power (dBm)	Max. tune-up
5.2GWIFI MIMO	16.4	16.0 ± 1
5.8GWIFI MIMO	15.21	16.0 ± 1

6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT	1.0	1.2589	3.0	2	0.0005	1.0000
BLE	2.0	1.5849	3.0	2	0.0006	1.0000
2.4GWIFI ANT1	16.0	39.8107	3.0	2	0.0158	1.0000
5.2GWIFI ANT1	14.0	25.1189	3.0	2	0.0100	1.0000
5.8GWIFI ANT1	14.0	25.1189	3.0	2	0.0100	1.0000

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI ANT2	16.0	39.8107	3.0	2	0.0158	1.0000
5.2GWIFI ANT2	14.0	25.1189	3.0	2	0.0100	1.0000
5.8GWIFI ANT2	14.0	25.1189	3.0	2	0.0100	1.0000

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI MIMO	17.0	50.1187	6.01	4	0.0399	1.0000
5.2GWIFI MIMO	17.0	50.1187	6.01	4	0.0399	1.0000
5.8GWIFI MIMO	17.0	50.1187	6.01	4	0.0399	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;

2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7. simultaneous MPE Result

2.4GWIFI ANT1 MPE (mW/cm2)	2.4GWIFI ANT2 MPE (mW/cm2)	BLE MPE (mW/cm2)	simultaneous MPE (mW/cm2)	MPE Limits (mW/cm2)
0.0158	0.0158	0.0006	0.0322	1.0000
2.4GWIFI/5GWIFI MIMO MPE (mW/cm2)		BLE MPE (mW/cm2)	simultaneous MPE (mW/cm2)	MPE Limits (mW/cm2)
0.0399		0.0006	0.0405	1.0000

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----