

# TEST REPORT



Dt&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042  
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2305-0063

2. Customer

• Name (FCC) : CRAECA

• Address (FCC) : #1406, O'biz Tower, 126, Beolmal-ro, Dongan-gu Anyang-si, Gyeonggi-do  
South Korea

3. Use of Report : FCC Original Grant

4. Product Name / Model Name : 60GHz Object detection Sensor / V-PR100

FCC ID : 2A8FDVPR100

5. Test Method Used : ANSI C63.10-2013

Test Specification : Part 15.255


6. Date of Test : 2023.04.20 ~ 2023.04.28

7. Testing Environment : Refer to appended test report.

8. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by Name : SeungMin Gil 	Technical Manager Name : JaeJin Lee 
-------------	-------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------

2023 . 05 . 03 .

Dt&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to [report@dtnc.net](mailto:report@dtnc.net)

## Test Report Version

Test Report No.	Date	Description	Revised By	Reviewed By
DRTFCC2305-0063	May. 03, 2023	Initial issue	SeungMin Gil	JaeJin Lee

## Table of Contents

<b>1 EUT DESCRIPTION.....</b>	<b>4</b>
<b>2 INFORMATION ABOUT TESTING.....</b>	<b>5</b>
2.1 Transmitting configuration of EUT .....	5
2.2 Auxiliary equipment.....	5
2.3 Tested environment .....	6
2.4 EMI suppression Device(s) / Modifications.....	6
2.5 Measurement Uncertainty .....	6
<b>3 SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>4 TEST METHODOLOGY .....</b>	<b>8</b>
4.1 EUT configuration.....	8
4.2 EUT exercise .....	8
4.3 General test procedures.....	8
4.4 Description of test modes .....	8
<b>5 INSTRUMENT CALIBRATION.....</b>	<b>9</b>
<b>6 FACILITIES AND ACCREDITATIONS .....</b>	<b>9</b>
6.1 Facilities .....	9
6.2 Equipment .....	9
<b>7 ANTENNA REQUIREMENTS .....</b>	<b>9</b>
<b>8 TEST RESULTS.....</b>	<b>10</b>
8.1 Emission Bandwidth.....	10
8.2 Equivalent Isotropic Radiated Power & Peak Conducted Output Power.....	12
8.3 Unwanted emissions .....	15
8.4 Frequency stability .....	20
8.5 AC line conducted emissions .....	22
<b>9 LIST OF TEST EQUIPMENT .....</b>	<b>25</b>
<b>APPENDIX I.....</b>	<b>27</b>

## 1 EUT DESCRIPTION

<b>FCC Equipment Class</b>	DXX - Part 15 Low Power Communication Device Transmitter
<b>Product</b>	60GHz Object detection Sensor
<b>Model Name</b>	V-PR100
<b>Add Model Name</b>	-
<b>Power Supply</b>	DC 5 V
<b>Frequency Band</b>	57 ~ 71 GHz
<b>Max. RF Output Power (EIRP)</b>	-4.28 dBm
<b>Modulation Type</b>	Pulse and Frequency Modulation
<b>Antenna Specification</b>	<b>Antenna type:</b> Folded dipole antenna <b>Antenna gain(Max):</b> 6 dBi

## 2 INFORMATION ABOUT TESTING

### 2.1 Transmitting configuration of EUT

Test Mode	Test Frequency(GHz)
60GHz Radar	60.50 GHz

#### Operation test setup for EUT

- Test Software Version: 60GHz Radar Viewer\_v3.10.1
- Power Setting: default value

### 2.2 Auxiliary equipment

Equipment	Model No.	Serial No.	Manufacturer	Note
-	-	-	-	-
-	-	-	-	-

## 2.3 Tested environment

<b>Temperature</b>	: 21 °C ~ 22 °C
<b>Relative humidity content</b>	: 40 % ~ 42 %

## 2.4 EMI suppression Device(s) / Modifications

EMI suppression device(s) added and/or modifications made during testing  
→ None

## 2.5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014 and ANSI C 63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence.

<b>Test items</b>	<b>Measurement uncertainty</b>
AC power-line conducted emission	3.4 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (1 GHz Below)	4.8 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (1 GHz ~ 18 GHz)	5.0 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (18 GHz Above)	5.2 dB (The confidence level is about 95 %, $k = 2$ )

### 3 SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Status Note 1
15.215(c)	20dB Bandwidth	NA	Radiated	C
15.255(c)(3)	Equivalent Isotropic Radiated Power	Peak < 10 dBm		C <sup>Note2</sup>
15.255(c)(3)	Peak Conducted Output Power	< -10 dBm		C
15.255(d) 15.209	Unwanted Emissions	Below 40GHz < Part 15.209 limits 40 ~ 200GHz < 90 pW/cm <sup>2</sup> (Refer to section 8.3)		C <sup>Note2</sup>
15.255(f)	Frequency Stability	Within the 57 ~71GHz band		C
15.207	AC Power-Line Conducted Emissions	< Part 15.207 limits (Refer to section 8.5)	AC Line Conducted	C
15.203	Antenna Requirements	Part 15.203 (Refer to section 7)	-	C

Note 1: **C**=Comply   **NC**=Not Comply   **NT**=Not Tested   **NA**=Not Applicable  
Note 2: This test item was performed in three orthogonal EUT positions and the worst case data was reported.

## 4 TEST METHODOLOGY

The measurement procedures described in the ANSI C63.10-2013 was used in measurement of the EUT.

### 4.1 EUT configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 4.2 EUT exercise

The EUT was operated in the test mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.255 under the FCC Rules Part 15 Subpart C.

### 4.3 General test procedures

#### Conducted Emissions

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector

#### Radiated Emissions

The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axes.

### 4.4 Description of test modes

The EUT has been tested with all modes of operating conditions to determine the worst case emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode.

## 5 INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

## 6 FACILITIES AND ACCREDITATIONS

### 6.1 Facilities

<b>Dt&amp;C Co., Ltd.</b>		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.		
<ul style="list-style-type: none"><li>- FCC &amp; ISED MRA Designation No.: KR0034</li><li>- ISED#: 5740A</li></ul>		
<a href="http://www.dtnc.net">www.dtnc.net</a>		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

### 6.2 Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, loop, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 7 ANTENNA REQUIREMENTS

### 7.1 According to Part 15.203

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The antenna is permanently attached on the device.**

**Therefore this E.U.T Complies with the requirement of §15.203**

## 8 TEST RESULTS

### 8.1 Emission Bandwidth

#### Test Requirements and limit

##### **Part 15.215(c)**

The 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### Test Configuration

Refer to the APPENDIX I.

#### Test Procedure

##### **ANSI C63.10-2013 – Section 9.3**

The following procedure was used for measurement of the bandwidth for millimeter-wave devices;

- Spectrum analyzer settings:


- 1) Span equal to approximately two times to three times the EBW, centered on the carrier frequency.
- 2) RBW, as specified in the requirement.
- 3) VBW, as specified in the requirement, or  $VBW \geq RBW$  if not specified.
- 4) Sweep = auto.
- 5) Detector function = peak.
- 6) Trace = max hold. Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

**□ Test Results: Comply**

Test Mode	Frequency[GHz]	20 dB Bandwidth [MHz]	-
60GHz Radar	60.50	2 918.41	-

**□ Result plots****20 dB Bandwidth**

Test Frequency: 60.50 GHz



## 8.2 Equivalent Isotropic Radiated Power & Peak Conducted Output Power

### Test Requirements and limit

#### Part 15.255:

(c) Within the 57–71 GHz band, emission levels shall not exceed the following equivalent isotropically radiated power (EIRP):

(1) Products other than fixed field disturbance sensors and short-range devices for interactive motion sensing shall comply with one of the following emission limits, as measured during the transmit interval:

(i) The average power of any emission shall not exceed 40 dBm and the peak power of any emission shall not exceed 43 dBm; or

(ii) For fixed point-to-point transmitters located outdoors, the average power of any emission shall not exceed 82 dBm, and shall be reduced by 2 dB for every dB that the antenna gain is less than 51 dBi. The peak power of any emission shall not exceed 85 dBm, and shall be reduced by 2 dB for every dB that the antenna gain is less than 51 dBi.

(A) The provisions in this paragraph (c) for reducing transmit power based on antenna gain shall not require that the power levels be reduced below the limits specified in paragraph (c)(1)(i) of this section.

(B) The provisions of § 15.204(c)(2) and (4) that permit the use of different antennas of the same type and of equal or less directional gain do not apply to intentional radiator systems operating under this provision. In lieu thereof, intentional radiator systems shall be certified using the specific antenna(s) with which the system will be marketed and operated. Compliance testing shall be performed using the highest gain and the lowest gain antennas for which certification is sought and with the intentional radiator operated at its maximum available output power level. The responsible party, as defined in § 2.909 of this chapter, shall supply a list of acceptable antennas with the application for certification.

(2) For fixed field disturbance sensors that occupy 500 MHz or less of bandwidth and that are contained wholly within the frequency band 61.0–61.5 GHz, the average power of any emission, measured during the transmit interval, shall not exceed 40 dBm, and the peak power of any emission shall not exceed 43 dBm. In addition, the average power of any emission outside of the 61.0–61.5 GHz band, measured during the transmit interval, but still within the 57–71 GHz band, shall not exceed 10 dBm, and the peak power of any emission shall not exceed 13 dBm.

**(3) For fixed field disturbance sensors other than those operating under the provisions of paragraph (c)(2) of this section, and short-range devices for interactive motion sensing, the peak transmitter conducted output power shall not exceed -10 dBm and the peak EIRP level shall not exceed 10 dBm.**

(4) The peak power shall be measured with an RF detector that has a detection bandwidth that encompasses the 57–71 GHz band and has a video bandwidth of at least 10 MHz. The average emission levels shall be measured over the actual time period during which transmission occurs.

**■ Test Configuration**

Refer to the APPENDIX I.

**■ Test Procedure****ANSI C63.10-2013 – Section 9.11**

The following procedure was used for measurement of the output power for millimeter-wave devices;

- 1) The measurements were performed at 3m test site.
- 2) The EUT is placed on a non-conductive table is 1.6 meter above test site ground plane.
- 3) The measurement procedure described in ANSI C63.10-2013 Section 9.9 was followed, to find maximum signal.
- 4) The average and peak voltages was recorded from the DSO.
- 5) Replace the EUT with mm-wave source to the RF input port of the instrumentation system.
- 6) The mm-wave source is unmodulated.
- 7) Adjust the amplitude of the mm-wave source such that the DSO indicates a voltage equal to the peak voltage recorded in step 4).
- 8) Without changing any settings, replace the DSO with the mm-wave power meter.
- 9) Measure and note the power.

**Far field distance ( $R_m$ )**

$$R_m = 2D^2 / \lambda,$$

Where, D=the largest dimension of the antenna /  $\lambda$ =the wavelength of the emissions

Frequency Range(GHz)	$\lambda$ (cm)	D (cm)	$R_m$ (m)	Measurement Distance(m)
60.5	0.50	5.68	1.29	1.60

Note: The dimension of the antenna of the EUT antenna or measurement antenna, whichever is largest, was used.

## □ Test Results: Comply

### Peak Power(e.i.r.p)

Measurement distance(D)	Frequency (GHz)	ANT Pol	DSO Reading [mV]	Power Meter Level[dBm]	Antenna Gain [dBi]	E (dB $\mu$ V/m)	EIRP (dBm)	Limit (dBm)	Margin (dB)
1.6m	60.50	V	93.60	-51.65	24.90	96.34	-4.28	10.00	14.28

#### Note.

1. Sample calculation.

$$E = 126.8 - 20\log(\lambda) + P - G$$

where

E is the field strength of the emission at the measurement distance, in dB $\mu$ V/m

P is the power measured at the output of the test antenna, in dBm

$\lambda$  is the wavelength of the emission under investigation [300/fMHz], in m

G is the gain of the test antenna, in dBi

$$EIRP = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

$E_{\text{Meas}}$  is the field strength of the emission at the measurement distance, in dB $\mu$ V/m

$d_{\text{Meas}}$  is the measurement distance, in m

### Peak Conducted Output Power:

Frequency (GHz)	EIRP(dBm)	EUT Antenna Gain(dBi)	Conducted Output Power(dBm)	Limit (dBm)	Margin (dB)
60.50	-4.28	6.00	-10.28	-10.00	0.28

**Note.** Calculate the conducted output power (in watts) from the EIRP using Equation:

$$P_{\text{cond}} = EIRP_{\text{Linear}} / G_{\text{EUT}}$$

Where

$P_{\text{cond}}$  is the conducted output power, in W

$EIRP_{\text{Linear}}$  is the equivalent isotropically radiated power, in W

$G_{\text{EUT}}$  is numeric gain of the EUT radiating element (antenna)

## 8.3 Unwanted emissions

### Test Requirements and limit

#### **FCC Part 15.255(d):** Limits on spurious emissions

- (1) The power density of any emissions outside the 57-71 GHz band shall consist solely of spurious emissions.
- (2) Radiated emissions below 40 GHz shall not exceed the general limits in §15.209.
- (3) Between 40 GHz and 200 GHz, the level of these emissions shall not exceed 90 pW/cm<sup>2</sup> at a distance of 3 meters.
- (4) The levels of the spurious emissions shall not exceed the level of the fundamental emission.

**FCC Part 15.209(a):** the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 – 0.490	2 400/F (kHz)	300
0.490 – 1.705	24 000/F (kHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

\*\* Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

### Test Configuration

Refer to the APPENDIX I.

**■ Test Procedure****ANSI C63.10-2013 – Section 9.12 & 9.13**

The following procedure was used for measurement of the radiated spurious emissions.

- 1) The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements at above 1 GHz, the table height is 1.5 m
- 2) The table was rotated 360 degrees to determine the position of the highest radiation.
- 3) During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 0.5 ~ 3 meter away from the interference-receiving antenna.
- 4) For measurements above 1GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.
- 5) The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 6) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 7) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**- Spectrum analyzer settings:**

1. Frequency Range: Below 1 GHz

RBW = 100 or 120 kHz, VBW = 3 x RBW, Detector = Peak or Quasi Peak

2. Frequency Range: 1 – 40 GHz

Peak Measurement

RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes

Average Measurement

RBW = 1 MHz, VBW  $\geq$  1/T, Detector = Peak, Sweep Time = Auto, Trace Mode = Max Hold until the trace stabilizes

3. Frequency Range: Above 40 GHz

RBW = 1 MHz, VBW = 1 or 3 MHz, Detector = Peak or average, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes

**Far field distance (R<sub>m</sub>)**

$$R_m = 2D^2 / \lambda,$$

Where, D=the largest dimension of the measurement antenna /  $\lambda$ =the wavelength of the emissions

Frequency Range(GHz)	$\lambda$ (cm)	D(cm)	R <sub>m</sub> (m)	Measurement Distance(m)
40 ~ 60	0.50	6.24	1.56	1.60
60 ~ 90	0.33	4.82	1.39	1.40
90 ~ 140	0.21	2.74	0.70	1.00
140 ~ 200	0.15	1.89	0.48	0.80

## ☒ Test Results: Comply

**Frequency Range: 9 kHz ~ 1 GHz**

**Test Frequency: 60.50 GHz**

Frequency (MHz)	ANT Pol	Detector Mode	Measured Level(dBuV)	TF (dB/m)	DCF(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
408.30	H	PK	35.20	-2.07	NA	33.13	46.00	12.87
514.03	V	PK	32.40	-0.10	NA	32.30	46.00	13.70

**Note.**

1. The worst case data was reported. No other spurious and harmonic emissions were found above listed frequencies.

2. Information of DCF(Distance Correction Factor)

For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.

In this case, the distance factor is applied to the result.

- Calculation of distance correction factor

At frequencies below 30 MHz =  $40 \log(\text{tested distance} / \text{specified distance})$

At frequencies at or above 30 MHz =  $20 \log(\text{tested distance} / \text{specified distance})$

When distance factor is "NA", the measurements were performed at the specified distance and distance factor is not applied.

3. Sample Calculation.

Margin = Limit – Result / Result = Measured Level + TF + Distance factor / TF = AF + CL – AG

Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

4. \* Noise floor.

**Frequency Range: 1 ~ 40 GHz**

**Tested Frequency: 60.50 GHz**

Frequency (MHz)	ANT Pol	Detector Mode	Measured Level(dBuV)	TF (dB/m)	DCF(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*16 167.10	V	PK	44.22	20.80	-9.54	55.48	74.00	18.52
*16 627.40	V	AV	33.24	22.38	-9.54	46.08	54.00	7.92

**Note.**

1. No other spurious and harmonic emissions were found above listed frequencies.

2. Information of DCF(Distance Factor)

For finding emissions, the test distance might be reduced. In this case, the distance factor is applied to the result.

- Calculation of distance factor =  $20 \log(\text{applied distance} / \text{required distance})$

When distance factor is "N/A", the distance is 3 m and distance factor is not applied.

3. Sample Calculation.

Margin = Limit – Result / Result = Measured Level + TF + Distance factor / TF = AF + CL – AG

Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain

4. \* Noise floor.

## Measured Level(Noise floor) Y axis &amp; Ver



**Frequency Range: 40 ~ 200 GHz**  
**Tested Frequency: 60.50 GHz**

Measurement distance(m)	Frequency (MHz)	ANT Pol	Measured Level(dBm)	AFCLAG (dB/m)	E (dBuV/m)	EIRP (dBm)	Power Density (pW/cm <sup>2</sup> )	Limit (pW/cm <sup>2</sup> )
1.6	*55 192.73	V	-58.38	-3.41	45.21	-55.41	0.003	90.00
1.4	*84 008.44	V	-53.82	5.08	58.26	-43.52	0.039	90.00
1.4	*88 551.68	V	-84.35	46.42	69.07	-32.71	0.470	90.00
1.0	*127 997.70	V	-66.36	48.26	88.90	-15.80	23.260	90.00
0.8	*151 296.30	V	-72.85	51.43	85.58	-21.06	6.930	90.00

**Note.**

1. The radiated emissions were investigated up to 200GHz. And no other spurious and harmonic emissions were found above listed frequencies.

2. Sample Calculation.

$$E(\text{dBuV/m}) = \text{Measured level (dBuV)} + 107 + \text{AFCLAG(dB/m)}$$

where, E=field strength / AFCLAG = Antenna Factor(dB/m) + Cable Loss(dB/m) – Amplifier Gain(dB)

$EIRP(\text{dBm}) = E(\text{dBuV/m}) + 20\log(D) - 104.7$ ; where, D is measurement distance (in the far field region) in m.

$$PD = EIRP_{\text{Linear}} / 4\pi d^2$$

Where, PD = the power density at the distance specified by the limit, in W/m<sup>2</sup>


$EIRP_{\text{Linear}} = EIRP$ , in watts

D = the distance at which the power density limit is specified, in m

3. The mixer loss was applied to the measured level by SA correction factor.

4. \* Noise floor

**Measured Level(Noise floor) Y axis & Ver**




09:25:53 AM 04/27/2023

## 8.4 Frequency stability

### ■ Test Requirements and limit

**FCC Part 15.255(f):** Fundamental emissions must be contained within the frequency bands specified in this section during all conditions of operation. Equipment is presumed to operate over the temperature range -20 to + 50 degrees Celsius with an input voltage variation of 85% to 115% of rated input voltage, unless justification is presented to demonstrate otherwise.

### ■ Test Configuration



### ■ Test Procedure

#### ANSI C63.10-2013 – Section 9.14

- 1) With the EUT at ambient temperature (approximately 25 °C) and voltage source set to the EUT nominal operating voltage (100%), record the spectrum mask of the EUT emission on the spectrum analyzer.
- 2) Vary EUT power supply between 85% and 115% of nominal, and record the frequency excursion of the EUT emission mask.
- 3) Set the power supply to 100% nominal setting, and raise EUT operating temperature to 50 °C. Record the frequency excursion of the EUT emission mask.
- 4) Repeat step 3) at each 10 °C increment down to -20 °C.

**Test Results: Comply**

VOLTAGE (%)	POWER (V DC)	TEMP (°C)	Tested Frequency: 60.50 GHz	
			Measured low frequency( $F_L$ )(GHz), 20dBc	Measured High frequency( $F_H$ )(GHz), 20dBc
100%	5.00	+25(Ref)	59.530	62.442
100%		-20	59.548	62.441
100%		-10	59.544	62.444
100%		0	59.544	62.445
100%		+10	59.545	62.447
100%		+20	59.539	62.441
100%		+30	59.532	62.447
100%		+40	59.533	62.449
100%		+50	59.541	62.441
115%	5.75	+25	59.533	62.444
85%	4.25	+25	59.531	62.445

Note: Fundamental emissions were contained within the frequency bands.

## 8.5 AC line conducted emissions

### Test Requirements and limit, Part 15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration:

See test photographs for the actual connections between EUT and support equipment.

### Test Procedure:

#### ANSI C63.10-2013 – Section 6.2

- 1) The EUT is placed on a wooden table 80 cm above the reference ground plane.
- 2) The EUT is connected via LISN to the test power supply.
- 3) The measurement results are obtained as described below:
- 4) Detectors – Quasi Peak and Average Detector.

**Test Results: Comply****AC Line Conducted Emissions (Graph)**

60.50 GHz

Results of Conducted Emission

DTNC

Date 2023-04-28

Order No.  
Model No.  
Serial No.  
Test Condition


V-PR100  
60GHz Radar

Reference No.  
Power Supply  
Temp/Humi.  
Operator

21 'C / 40 %  
S.M.Gil

## Memo

LIMIT : FCC P15.207 AV  
FCC P15.207 QP



**AC Line Conducted Emissions (List)**

60.50 GHz

**Results of Conducted Emission**

DTNC

Date 2023-04-28

Order No.		Referrence No.
Model No.	V-PR100	Power Supply
Serial No.		Temp/Humi.
Test Condition	60GHz Radar	Operator

21 'C / 40 %  
S.M.Gil

Memo

LIMIT : FCC P15.207 AV  
FCC P15.207 QP

NO	FREQ [MHz]	READING		C.FACTOR	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.15529	30.93	15.28	10.01	40.94	25.29	65.71	55.71	24.77	30.42	N
2	0.46939	27.11	14.51	10.00	37.11	24.51	56.52	46.52	19.41	22.01	N
3	0.53673	23.60	10.39	10.00	33.60	20.39	56.00	46.00	22.40	25.61	N
4	13.25140	17.41	11.59	10.48	27.89	22.07	60.00	50.00	32.11	27.93	N
5	0.15454	31.48	15.66	9.91	41.39	25.57	65.75	55.75	24.36	30.18	L
6	0.17029	33.61	20.64	9.90	43.51	30.54	64.95	54.95	21.44	24.41	L
7	0.48464	27.54	14.66	9.90	37.44	24.56	56.26	46.26	18.82	21.70	L
8	0.53949	25.14	11.40	9.90	35.04	21.30	56.00	46.00	20.96	24.70	L
9	13.97680	19.52	14.05	10.35	29.87	24.40	60.00	50.00	30.13	25.60	L

## 9 LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal. Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent	N9020A	22/06/24	23/06/24	US47360812
Spectrum Analyzer	Rohde Schwarz	FSW85	22/08/04	23/08/04	101778
Thermohygrometer	XIAOMI	MHO-C201	22/12/16	23/12/16	00089675
Thermohygrometer	BODYCOM	BJ5478	22/12/16	23/12/16	120612-2
Loop Antenna	ETS-Lindgren	6502	22/12/16	24/12/16	00226186
BILOG ANTENNA	Schwarzbeck	VULB 9160	22/12/16	23/12/16	3362
HORN ANT	ETS	3117	22/12/16	23/12/16	00140394
HORN ANT	A.H.Systems	SAS-574	22/06/24	23/06/24	155
Horn Antenna	MI Wave	RX ANT-5 261U+410U	22/06/24	23/06/24	108
Horn Antenna	MI Wave	RX ANT-6 261V+410V	22/06/24	23/06/24	110
Horn Antenna	MI Wave	RX ANT-7 261E	22/06/24	23/06/24	112
Horn Antenna	MI Wave	RX ANT-8 261F	22/06/24	23/06/24	114
Horn Antenna	MI Wave	RX ANT-9 261G	22/06/24	23/06/24	116
PreAmplifier	H.P	8447D	22/12/16	23/12/16	2944A07774
PreAmplifier	Agilent	8449B	22/06/24	23/06/24	3008A02108
PreAmplifier	tsj	MLA-1840-J02-45	22/06/24	23/06/24	16966-10728
PreAmplifier	Norden Millimeter Inc.	NA4060G50N8P12	22/12/16	24/12/16	1003
PreAmplifier	ERAVABT	SBL-5037533550- 151-E1-ET	22/12/16	23/12/16	10394-01
PreAmplifier	Norden Millimeter Inc.	NN6090G40N5P-2	22/12/16	24/12/16	1001
High-pass filter	Wainwright	WHKX12-935-1000- 15000-40SS	22/06/24	23/06/24	7
High-pass filter	Wainwright	WHKX10-2838- 3300-18000-60SS	22/06/24	23/06/24	2
High-pass filter	Wainwright	WHKX6-6320-8000- 26500-40CC	22/06/24	23/06/24	2
Harmonic mixers	Rohde Schwarz	FS-Z90	22/08/04	23/08/04	101714
Harmonic mixers	Rohde Schwarz	FS-Z140	22/08/04	23/08/04	101009
Harmonic mixers	Rohde Schwarz	FS-Z220	21/10/07	23/10/07	101012
V-Band Amplitude Detector	SAGE Millimeter	SFD-503753-15SF- P1	22/12/16	23/12/16	17841-01
DIGITAL Phosphor OSCILLOSCOPE	Tektronix	DPO2024B	22/12/16	23/12/16	C012114
Power meter & Power sensor	Rohde Schwarz	NRP2, NRP110T	22/12/16	23/12/16	106060 101002
mmW Multiplier	OML, Inc.	S15MS	22/08/04	23/08/04	170821-1
DC Power Supply	SM techno	SDP30-5D	22/06/24	23/06/24	305DMG305
Multimeter	FLUKE	17B+	22/12/16	23/12/16	36390701WS
Temp Test Chamber	ESPEC	SU-261	22/06/22	23/06/22	92006578
EMI Test Receiver	ROHDE&SCHWARZ	ESCI7	23/01/31	24/01/31	100910
PULSE LIMITER	Rohde Schwarz	ESH3-Z2	22/08/22	23/08/22	101333
LISN	SCHWARZBECK	NSLK 8128 RC	22/10/26	23/10/26	8128 RC-387
Thermo Hygro Meter	TESTO	608-H1	23/01/13	24/01/13	45084791
Cable	HUBER+SUHNER	SUCOFLEX100	23/01/04	24/01/04	M-01
Cable	HUBER+SUHNER	SUCOFLEX100	23/01/04	24/01/04	M-02
Cable	JUNKOSHA	MWX241/B	23/01/04	24/01/04	M-03
Cable	JUNKOSHA	MWX221	23/01/04	24/01/04	M-04
Cable	JUNKOSHA	MWX221	23/01/04	24/01/04	M-05
Cable	JUNFLON	J12J101757-00	23/01/04	24/01/04	M-07
Cable	HUBER+SUHNER	SUCOFLEX104	23/01/04	24/01/04	M-08
Cable	HUBER+SUHNER	SUCOFLEX106	23/01/04	24/01/04	M-09
Cable	JUNKOSHA	MWX315	23/01/04	24/01/04	M-10
Cable	Dt&C	Cable	23/01/04	24/01/04	RFC-69
Cable	Junkosha	MWX241	23/01/03	24/01/03	mmW-1

Cable	Junkosha	MWX241	23/01/03	24/01/03	mmW-4
Cable	Junkosha	MWX261	23/01/03	24/01/03	mmW-6
Cable	HUBER+SUHNER	SUCOFLEX 104	23/01/03	24/01/03	mmW-8
Cable	HUBER+SUHNER	SUCOFLEX 104	23/01/03	24/01/03	mmW-9
Cable	SAGE MILLIMETER Inc	SCW-1M1M024-F1	23/01/03	24/01/03	mmW-10
Test Software	tsj	Radiated Emission Measurement	NA	NA	Version 2.00.0177
Test Software	tsj	Noise Terminal Measurement	NA	NA	Version 2.00.0170

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by Dt&C itself.

Note3: \* The mm-wave instruments were calibrated by the manufacturer.

## APPENDIX I

### Test set up diagrams

