

FCC TEST REPORT

FCC ID: 2A8I3-BRM-V4

Report Number : ZKT-220406L2202-01

Date of Test : Mar. 16, 2022 to Aug.30, 2022

Date of issue : Aug.30, 2022

Total number of pages : 41

Test Result : PASS

Testing Laboratory : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Laser Tag Pro Inc.

Address : 9100 S. Nicholson Rd. Oak Creek, WI 53154 USA

Manufacturer's name : Dongguan Drosun Co., Ltd.

Address : No.20, Yewu 1st Road, Shipai Town, Dongguan City, Guangdong Province

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test procedure : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name : BRM

Trademark : N/A


Model/Type reference : BRM-V4

Ratings : DC7.4V from battery
AC 120V 60Hz

Testing procedure and testing location:

Testing Laboratory Shenzhen ZKT Technology Co., Ltd.

Address 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature) Alen He 

Reviewer (name + signature)..... Joe Liu 

Approved (name + signature) Lake Xie 



Table of Contents

| | Page |
|--|-----------|
| 1. VERSION | 5 |
| 2. SUMMARY OF TEST RESULTS | 6 |
| 2.1 TEST FACILITY | 7 |
| 2.2 MEASUREMENT UNCERTAINTY | 7 |
| 3. GENERAL INFORMATION | 8 |
| 3.1 GENERAL DESCRIPTION OF EUT | 8 |
| 3.2 DESCRIPTION OF TEST MODES | 9 |
| 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 10 |
| 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) | 10 |
| 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS | 11 |
| 4. EMC EMISSION TEST | 12 |
| 4.1 CONDUCTED EMISSION MEASUREMENT | 12 |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS | 12 |
| 4.1.2 TEST PROCEDURE | 12 |
| 4.1.3 DEVIATION FROM TEST STANDARD | 12 |
| 4.1.4 TEST SETUP | 13 |
| 4.1.5 EUT OPERATING CONDITIONS | 13 |
| 4.1.6 TEST RESULT | 14 |
| 4.2 RADIATED EMISSION MEASUREMENT | 16 |
| 4.2.1 RADIATED EMISSION LIMITS | 16 |
| 4.2.2 TEST PROCEDURE | 16 |
| 4.2.3 DEVIATION FROM TEST STANDARD | 17 |
| 4.2.4 TEST SETUP | 17 |
| 4.2.5 EUT OPERATING CONDITIONS | 18 |
| 4.2.6 TEST RESULTS | 19 |
| 5. RADIATED BAND EMISSION MEASUREMENT | 23 |
| 5.1 TEST REQUIREMENT: | 23 |
| 5.2 TEST PROCEDURE | 23 |
| 5.3 DEVIATION FROM TEST STANDARD | 23 |
| 5.4 TEST SETUP | 24 |
| 5.5 EUT OPERATING CONDITIONS | 24 |
| 5.6 TEST RESULT | 25 |
| 6. POWER SPECTRAL DENSITY TEST | 26 |
| 6.1 APPLIED PROCEDURES / LIMIT | 26 |
| 6.2 TEST PROCEDURE | 26 |
| 6.3 DEVIATION FROM STANDARD | 26 |
| 6.4 TEST SETUP | 26 |
| 6.5 EUT OPERATION CONDITIONS | 26 |

| | |
|---|-----------|
| 6.6 TEST RESULT | 27 |
| 7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH | 29 |
| 7.1 APPLIED PROCEDURES / LIMIT | 29 |
| 7.2 TEST PROCEDURE | 29 |
| 7.3 DEVIATION FROM STANDARD | 29 |
| 7.4 TEST SETUP | 29 |
| 7.5 EUT OPERATION CONDITIONS | 29 |
| 7.6 TEST RESULT | 30 |
| 8. PEAK OUTPUT POWER TEST | 32 |
| 8.1 APPLIED PROCEDURES/LIMIT | 32 |
| 8.2 TEST PROCEDURE | 32 |
| 8.3 DEVIATION FROM STANDARD | 32 |
| 8.4 TEST SETUP | 32 |
| 8.5 EUT OPERATION CONDITIONS | 32 |
| 8.6 TEST RESULT | 32 |
| 9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION | 33 |
| 9.1 APPLICABLE STANDARD | 33 |
| 9.2 TEST PROCEDURE | 33 |
| 9.3 DEVIATION FROM STANDARD | 33 |
| 9.4 TEST SETUP | 33 |
| 9.5 EUT OPERATION CONDITIONS | 33 |
| 9.6 TEST RESULTS | 33 |
| 10. ANTENNA REQUIREMENT | 38 |
| 11. TEST SETUP PHOTO | 39 |
| 12. EUT CONSTRUCTIONAL DETAILS | 41 |

1. VERSION

| Report No. | Version | Description | Approved |
|--------------------|---------|-------------------------|--------------|
| ZKT-220406L2202-01 | Rev.01 | Initial issue of report | Aug.30, 2022 |
| | | | |
| | | | |

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C | | | |
|---------------------------------|----------------------------------|--------|--------|
| Standard Section | Test Item | Result | Remark |
| FCC part 15.203/15.247 (c) | Antenna requirement | PASS | |
| FCC part 15.207 | AC Power Line Conducted Emission | PASS | |
| FCC part 15.247 (b)(3) | Conducted Peak Output Power | PASS | |
| FCC part 15.247 (a)(2) | Channel Bandwidth& 99% OCB | PASS | |
| FCC part 15.247 (e) | Power Spectral Density | PASS | |
| FCC part 15.247(d) | Band Edge | PASS | |
| FCC part 15.205/15.209 | Spurious Emission | PASS | |

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|------------------------------|-------------------------|
| 1 | Conducted Emission Test | $\pm 1.38\text{dB}$ |
| 2 | RF power conducted | $\pm 0.16\text{dB}$ |
| 3 | Spurious emissions conducted | $\pm 0.21\text{dB}$ |
| 4 | All emissions radiated(<1G) | $\pm 4.68\text{dB}$ |
| 5 | All emissions radiated(>1G) | $\pm 4.89\text{dB}$ |
| 6 | Temperature | $\pm 0.5^\circ\text{C}$ |
| 7 | Humidity | $\pm 2\%$ |

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

| | |
|------------------------|---|
| Product Name: | BRM |
| Model No.: | BRM-V4 |
| Serial No.: | N/A |
| Hardware Version: | V2.0 |
| Software Version: | V1.0 |
| Sample(s) Status: | Engineer sample |
| Channel numbers: | 40 |
| Channel separation: | 2402MHz~2480MHz |
| Modulation technology: | GFSK |
| Antenna Type: | Ceramic Antenna |
| Antenna gain: | 0.5 dBi |
| Power supply: | DC7.4V from battery AC 120V 60Hz |
| POWER ADAPTER: | Model: XSC-0901200S Input: 100-240V~50/60Hz 0.4 A Output: 9V --- 1200mA |

| Operation Frequency each of channel | | | | | | | |
|-------------------------------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|
| Channe l | Frequency | Chann el | Frequency | Chann el | Frequency | Chann el | Frequency |
| 1 | 2402 | 11 | 2422 | 21 | 2442 | 31 | 2462 |
| 2 | 2404 | 12 | 2424 | 22 | 2444 | 32 | 2464 |
| 3 | 2406 | 13 | 2426 | 23 | 2446 | 33 | 2466 |
| 4 | 2408 | 14 | 2428 | 24 | 2448 | 34 | 2468 |
| 5 | 2410 | 15 | 2430 | 25 | 2450 | 35 | 2470 |
| 6 | 2412 | 16 | 2432 | 26 | 2452 | 36 | 2472 |
| 7 | 2414 | 17 | 2434 | 27 | 2454 | 37 | 2474 |
| 8 | 2416 | 18 | 2436 | 28 | 2456 | 38 | 2476 |
| 9 | 2418 | 19 | 2438 | 29 | 2458 | 39 | 2478 |
| 10 | 2420 | 20 | 2440 | 30 | 2460 | 40 | 2480 |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Test channel | Frequency |
|---------------------|-----------|
| The lowest channel | 2402MHz |
| The middle channel | 2440MHz |
| The Highest channel | 2480MHz |

3.2 DESCRIPTION OF TEST MODES

| | |
|--|--|
| Transmitting mode | Keep the EUT in continuously transmitting mode |
| Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. | |
| We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows: | |
| Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case. | |

| | |
|-------------------|-------------------|
| Test Software | Realtek Test Tool |
| Power level setup | <0dBm |

3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|------|-----------|-----------|---|------------|-------------------|
| 1 | adapter | / | Model: XSC-0901200S Input: 100-240V~50/60Hz 0.4 A Output: 9V 1200mA | N/A | Provide by client |
| | | | | | |
| | | | | | |
| | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| | | | | |
| | | | | |
| | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

| Item | Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|------|----------------------------------|----------------|-----------------|------------|------------------|------------------|
| 1 | Spectrum Analyzer (9kHz-26.5GHz) | KEYSIGHT | 9020A | MY45109572 | Sep. 21, 2021 | Sep. 22, 2022 |
| 2 | Spectrum Analyzer (1GHz-40GHz) | Agilent | E4446A | 100363 | Sep. 21, 2021 | Sep. 22, 2022 |
| 3 | Test Receiver (9kHz-7GHz) | R&S | ESCI7 | 101169 | Sep. 21, 2021 | Sep. 22, 2022 |
| 4 | Bilog Antenna (30MHz-1400MHz) | Schwarzbeck | VULB9168 | 00877 | Sep. 21, 2021 | Sep. 22, 2022 |
| 5 | Horn Antenna (1GHz-18GHz) | SCHWARZBEC K | BBHA9120D | 1541 | Sep. 21, 2021 | Sep. 22, 2022 |
| 6 | Horn Antenna (18GHz-40GHz) | A.H. System | SAS-574 | 588 | Sep. 21, 2021 | Sep. 22, 2022 |
| 7 | Amplifier (30-1000MHz) | EM Electronics | EM330 Amplifier | N/A | Sep. 21, 2021 | Sep. 22, 2022 |
| 8 | Amplifier (1GHz-40GHz) | QUANJUDA | DLE-161 | 097 | Sep. 21, 2021 | Sep. 22, 2022 |
| 9 | Loop Antenna (9KHz-30MHz) | SCHWARZBEC K | FMZB1519B | 014 | Sep. 21, 2021 | Sep. 22, 2022 |
| 10 | RF cables1 (9kHz-30MHz) | N/A | 9kHz-30MHz | N/A | Sep. 21, 2021 | Sep. 22, 2022 |
| 11 | RF cables2 (30MHz-1GHz) | N/A | 30MHz-1GHz | N/A | Sep. 21, 2021 | Sep. 22, 2022 |
| 12 | RF cables3 (1GHz-40GHz) | N/A | 1GHz-40GHz | N/A | Sep. 21, 2021 | Sep. 22, 2022 |
| 13 | CMW500 Test | R&S | CMW500 | 106504 | Sep. 21, 2021 | Sep. 22, 2022 |
| 14 | ESG Signal Generator | Agilent | E4421B | GB40051203 | Sep. 21, 2021 | Sep. 22, 2022 |
| 15 | Signal Generator | Agilent | N5182A | MY47420215 | Sep. 21, 2021 | Sep. 22, 2022 |
| 16 | D.C. Power Supply | LongWei | TPR-6405D | \ | \ | \ |
| 17 | Software | Frad | EZ-EMC | FA-03A2 RE | \ | \ |

Conduction Test equipment

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|------|-------------------|--------------|----------|-------------|------------------|------------------|
| 1 | LISN | R&S | ENV216 | 101471 | Sep. 21, 2021 | Sep. 22, 2022 |
| 2 | LISN | CYBERTEK | EM5040A | E1850400149 | Sep. 21, 2021 | Sep. 22, 2022 |
| 3 | Test Cable | N/A | C01 | N/A | Sep. 21, 2021 | Sep. 22, 2022 |
| 4 | Test Cable | N/A | C02 | N/A | Sep. 21, 2021 | Sep. 22, 2022 |
| 5 | EMI Test Receiver | R&S | ESRP3 | 101946 | Sep. 21, 2021 | Sep. 22, 2022 |
| 6 | Absorbing Clamp | DZ | ZN23201 | N/A | Sep. 21, 2021 | Sep. 22, 2022 |

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

| | |
|-----------------------|--------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.207 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | 150KHz to 30MHz |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto |

4.1.1 POWER LINE CONDUCTED EMISSION Limits

| FREQUENCY (MHz) | Limit (dBuV) | | Standard |
|-----------------|--------------|-----------|----------|
| | Quasi-peak | Average | |
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 60.00 | 50.00 | FCC |

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

| | | | |
|----------------|--------------|--------------------|-----|
| Temperature : | 26°C | Relative Humidity: | 54% |
| Pressure : | 101kPa | Phase : | L |
| Test Voltage : | AC 120V/60Hz | | |



| | | | |
|----------------|--------------|--------------------|-----|
| Temperature : | 26°C | Relative Humidity: | 54% |
| Pressure : | 101kPa | Phase : | N |
| Test Voltage : | AC 120V/60Hz | | |



4.2 RADIATED EMISSION MEASUREMENT

| | | | | | |
|-----------------------|-----------------------------|------------|--------|--------|------------|
| Test Requirement: | FCC Part15 C Section 15.209 | | | | |
| Test Method: | ANSI C63.10:2013 | | | | |
| Test Frequency Range: | 9kHz to 25GHz | | | | |
| Test site: | Measurement Distance: 3m | | | | |
| Receiver setup: | Frequency | Detector | RBW | VBW | Value |
| | 9KHz-150KHz | Quasi-peak | 200Hz | 600Hz | Quasi-peak |
| | 150KHz-30MHz | Quasi-peak | 9KHz | 30KHz | Quasi-peak |
| | 30MHz-1GHz | Quasi-peak | 120KHz | 300KHz | Quasi-peak |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | | Peak | 1MHz | 10Hz | Average |

4.2.1 RADIATED EMISSION LIMITS

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

LIMITS OF RADIATED EMISSION MEASUREMENT

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) | |
|-----------------|------------------------|---------|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

| | | | |
|---------------|---------------------|--------------------|------------|
| Temperature: | 26°C | Relative Humidity: | 54% |
| Pressure: | 101 kPa | Polarization: | Horizontal |
| Test Voltage: | DC7.4V from battery | | |



| | | | |
|---------------|---------------------|--------------------|----------|
| Temperature: | 26°C | Relative Humidity: | 54% |
| Pressure: | 101kPa | Polarization: | Vertical |
| Test Voltage: | DC7.4V from battery | | |



Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.

1GHz~25GHz

| Polar (H/V) | Frequency | Meter Reading | Pre-ampl ifier | Cable Loss | Antenna Factor | Emission Level | Limits | Margin | Detect or Type |
|---------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
| | (MHz) | (dBuV) | (dB) | (dB) | (dB) | (dBuV/m) | (dBuV/ m) | (dB) | |
| Low Channel:2402MHz | | | | | | | | | |
| V | 4804.00 | 56.24 | 30.55 | 5.77 | 24.66 | 56.12 | 74.00 | -17.88 | PK |
| V | 4804.00 | 39.87 | 30.55 | 5.77 | 24.66 | 39.75 | 54.00 | -14.25 | AV |
| V | 7206.00 | 53.81 | 30.33 | 6.32 | 24.55 | 54.35 | 74.00 | -19.65 | PK |
| V | 7206.00 | 41.07 | 30.33 | 6.32 | 24.55 | 41.61 | 54.00 | -12.39 | AV |
| V | 9608.00 | 51.84 | 30.85 | 7.45 | 24.69 | 53.13 | 74.00 | -20.87 | PK |
| V | 9608.00 | 38.07 | 30.85 | 7.45 | 24.69 | 39.36 | 54.00 | -14.64 | AV |
| H | 4804.00 | 44.15 | 30.55 | 5.77 | 24.66 | 44.03 | 74.00 | -29.97 | PK |
| H | 4804.00 | 46.54 | 30.55 | 5.77 | 24.66 | 46.42 | 54.00 | -7.58 | AV |
| H | 7206.00 | 45.49 | 30.33 | 6.32 | 24.55 | 46.03 | 74.00 | -27.97 | PK |
| H | 7206.00 | 45.41 | 30.33 | 6.32 | 24.55 | 45.95 | 54.00 | -8.05 | AV |
| H | 9608.00 | 44.79 | 30.85 | 7.45 | 24.69 | 46.08 | 74.00 | -27.92 | PK |
| H | 9608.00 | 43.60 | 30.85 | 7.45 | 24.69 | 44.89 | 54.00 | -9.11 | AV |

| Polar (H/V) | Frequency | Meter Reading | Pre-ampl ifier | Cable Loss | Antenna Factor | Emission Level | Limits | Margin | Detect or Type |
|------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
| | (MHz) | (dBuV) | (dB) | (dB) | (dB) | (dBuV/m) | (dBuV/ m) | (dB) | |
| Middle Channel:2440MHz | | | | | | | | | |
| V | 4880.00 | 53.82 | 30.55 | 5.77 | 24.66 | 53.70 | 74.00 | -20.30 | PK |
| V | 4880.00 | 40.95 | 30.55 | 5.77 | 24.66 | 40.83 | 54.00 | -13.17 | AV |
| V | 7320.00 | 54.30 | 30.33 | 6.32 | 24.55 | 54.84 | 74.00 | -19.16 | PK |
| V | 7320.00 | 39.60 | 30.33 | 6.32 | 24.55 | 40.14 | 54.00 | -13.86 | AV |
| V | 9760.00 | 50.91 | 30.85 | 7.45 | 24.69 | 52.20 | 74.00 | -21.80 | PK |
| V | 9760.00 | 38.29 | 30.85 | 7.45 | 24.69 | 39.58 | 54.00 | -14.42 | AV |
| H | 4880.00 | 54.54 | 30.55 | 5.77 | 24.66 | 54.42 | 74.00 | -19.58 | PK |
| H | 4880.00 | 40.05 | 30.55 | 5.77 | 24.66 | 39.93 | 54.00 | -14.07 | AV |
| H | 7320.00 | 53.27 | 30.33 | 6.32 | 24.55 | 53.81 | 74.00 | -20.19 | PK |
| H | 7320.00 | 39.53 | 30.33 | 6.32 | 24.55 | 40.07 | 54.00 | -13.93 | AV |
| H | 9760.00 | 51.46 | 30.85 | 7.45 | 24.69 | 52.75 | 74.00 | -21.25 | PK |
| H | 9760.00 | 37.36 | 30.85 | 7.45 | 24.69 | 38.65 | 54.00 | -15.35 | AV |

| Polar (H/V) | Frequency | Meter Reading | Pre-ampli fier | Cable Loss | Antenna Factor | Emission Level | Limits | Margin | Detect or Type |
|----------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
| | (MHz) | (dBuV) | (dB) | (dB) | (dB) | (dBuV/m) | (dBuV/ m) | (dB) | |
| High Channel:2480MHz | | | | | | | | | |
| V | 4960.00 | 56.40 | 30.55 | 5.77 | 24.66 | 56.28 | 74.00 | -17.72 | PK |
| V | 4960.00 | 40.00 | 30.55 | 5.77 | 24.66 | 39.88 | 54.00 | -14.12 | AV |
| V | 7440.00 | 53.42 | 30.33 | 6.32 | 24.55 | 53.96 | 74.00 | -20.04 | PK |
| V | 7440.00 | 40.17 | 30.33 | 6.32 | 24.55 | 40.71 | 54.00 | -13.29 | AV |
| V | 9920.00 | 52.63 | 30.85 | 7.45 | 24.69 | 53.92 | 74.00 | -20.08 | PK |
| V | 9920.00 | 38.96 | 30.85 | 7.45 | 24.69 | 40.25 | 54.00 | -13.75 | AV |
| H | 4960.00 | 55.31 | 30.55 | 5.77 | 24.66 | 55.19 | 74.00 | -18.81 | PK |
| H | 4960.00 | 40.11 | 30.55 | 5.77 | 24.66 | 39.99 | 54.00 | -14.01 | AV |
| H | 7440.00 | 54.46 | 30.33 | 6.32 | 24.55 | 55.00 | 74.00 | -19.00 | PK |
| H | 7440.00 | 41.70 | 30.33 | 6.32 | 24.55 | 42.24 | 54.00 | -11.76 | AV |
| H | 9920.00 | 51.67 | 30.85 | 7.45 | 24.69 | 52.96 | 74.00 | -21.04 | PK |
| H | 9920.00 | 38.04 | 30.85 | 7.45 | 24.69 | 39.33 | 54.00 | -14.67 | AV |

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

| | | | | | |
|-----------------------|--|----------|------|------|---------|
| Test Requirement: | FCC Part15 C Section 15.209 and 15.205 | | | | |
| Test Method: | ANSI C63.10: 2013 | | | | |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed. | | | | |
| Test site: | Measurement Distance: 3m | | | | |
| Receiver setup: | Frequency | Detector | RBW | VBW | Value |
| | Above | Peak | 1MHz | 3MHz | Peak |
| | 1GHz | Average | 1MHz | 3MHz | Average |

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Class B (dBuV/m) (at 3M) | |
|-----------------|--------------------------|---------|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

| | Polar (H/V) | Fre. (MHz) | Meter Reading (dBuV) | Pre-amp lifier (dB) | Cable Loss (dB) | Antenna Factor (dB/m) | Emission level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector Type | Result |
|------|-----------------------|------------|----------------------|---------------------|-----------------|-----------------------|-------------------------|----------------|-------------|---------------|--------|
| GFSK | Low Channel 2402MHz | | | | | | | | | | |
| | H | 2390.00 | 53.21 | 30.22 | 4.85 | 23.98 | 51.82 | 74.00 | -22.18 | PK | PASS |
| | H | 2390.00 | 44.94 | 30.22 | 4.85 | 23.98 | 43.55 | 54.00 | -10.45 | AV | PASS |
| | H | 2400.00 | 55.81 | 30.22 | 4.85 | 23.98 | 54.42 | 74.00 | -19.58 | PK | PASS |
| | H | 2400.00 | 45.57 | 30.22 | 4.85 | 23.98 | 44.18 | 54.00 | -9.82 | AV | PASS |
| | V | 2390.00 | 54.18 | 30.22 | 4.85 | 23.98 | 52.79 | 74.00 | -21.21 | PK | PASS |
| | V | 2390.00 | 44.88 | 30.22 | 4.85 | 23.98 | 43.49 | 54.00 | -10.51 | AV | PASS |
| | V | 2400.00 | 55.36 | 30.22 | 4.85 | 23.98 | 53.97 | 74.00 | -20.03 | PK | PASS |
| | V | 2400.00 | 47.58 | 30.22 | 4.85 | 23.98 | 46.19 | 54.00 | -7.81 | AV | PASS |
| | High Channel: 2480MHz | | | | | | | | | | |
| | H | 2483.50 | 52.28 | 30.22 | 4.85 | 23.98 | 50.89 | 74.00 | -23.11 | PK | PASS |
| | H | 2485.50 | 45.06 | 30.22 | 4.85 | 23.98 | 43.67 | 54.00 | -10.33 | AV | PASS |
| | H | 2500.00 | 56.62 | 30.22 | 4.85 | 23.98 | 55.23 | 74.00 | -18.77 | PK | PASS |
| | H | 2500.00 | 45.02 | 30.22 | 4.85 | 23.98 | 43.63 | 54.00 | -10.37 | AV | PASS |
| | V | 2483.50 | 54.31 | 30.22 | 4.85 | 23.98 | 52.92 | 74.00 | -21.08 | PK | PASS |
| | V | 2485.50 | 44.99 | 30.22 | 4.85 | 23.98 | 43.60 | 54.00 | -10.4 | AV | PASS |
| | V | 2500.00 | 57.56 | 30.22 | 4.85 | 23.98 | 56.17 | 74.00 | -17.83 | PK | PASS |
| | V | 2500.00 | 47.45 | 30.22 | 4.85 | 23.98 | 46.06 | 54.00 | -7.94 | AV | PASS |

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. POWER SPECTRAL DENSITY TEST

| | |
|-------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (e) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v 05r02 |

6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|------------------------|-----------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247 | Power Spectral Density | 8dBm/3kHz | 2400-2483.5 | PASS |


6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP




6.5 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

| | | | |
|---------------|--------|---------------------|---------|
| Temperature : | 26°C | Relative Humidity : | 54% |
| Pressure : | 101kPa | Test Voltage : | DC 7.4V |
| Test Mode : | GFSK | | |

| Frequency | Power Spectral Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
|-----------|-----------------------------------|------------------|--------|
| 2402 MHz | -17.788 | 8 | PASS |
| 2440 MHz | -17.075 | 8 | PASS |
| 2480 MHz | -17.822 | 8 | PASS |





7. CHANNEL BANDWIDTH& 99% OCCUPY BANDWIDTH

| | |
|-------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

7.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|-----------|------------------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(a)(2) | Bandwidth | >= 500KHz (6dB bandwidth) | 2400-2483.5 | PASS |

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP




7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULT

| | | | |
|---------------|--------|---------------------|---------|
| Temperature : | 26°C | Relative Humidity : | 54% |
| Pressure : | 101kPa | Test Voltage : | DC 7.4V |
| Test Mode : | GFSK | | |

| Test CH | Channel Bandwidth (MHz) | Limit(KHz) | Result |
|---------|-------------------------|------------|--------|
| Lowest | 0.6809 | >500 | Pass |
| Middle | 0.6940 | | |
| Highest | 0.6965 | | |





8. PEAK OUTPUT POWER TEST

| | |
|-------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

8.1 APPLIED PROCEDURES/LIMIT

| FCC Part15 (15.247) , Subpart C | | | | |
|---------------------------------|-------------------|-----------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(b)(3) | Peak Output Power | 1 watt or 30dBm | 2400-2483.5 | PASS |


8.2 TEST PROCEDURE

- The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

| | | | |
|---------------|--------|---------------------|---------|
| Temperature : | 26°C | Relative Humidity : | 54% |
| Pressure : | 101kPa | Test Voltage : | DC 7.4V |

| Test CH | Peak Output Power (dBm) | Limit(dBm) | Result |
|---------|-------------------------|------------|--------|
| | | | |
| Lowest | -2.326 | | |
| Middle | -1.423 | | |
| Highest | -2.259 | 30.00 | Pass |

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

| | |
|-------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | KDB558074 D0115.247 Meas Guidance v05r02 |

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP




9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS

Test plot as follows:





Lowest channel



Highest channel

Test plot as follows:



GFSK Lowest channel



GFSK Middle channel



GFSK Highest channel



10. ANTENNA REQUIREMENT

| | |
|-------------------------------|--|
| Standard requirement: | FCC Part15 C Section 15.203 /247(c) |
| 15.203 requirement: | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |
| 15.247(c) (1)(i) requirement: | (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. |
| EUT Antenna: | <p>The antenna is Ceramic Antenna, the best case gain of the antennas are 0.5dBi, reference to the below photo for details</p> <p>ANT for BT/BLE</p> |

11. TEST SETUP PHOTO





12. EUT CONSTRUCTIONAL DETAILS

Please refer to external photos file and internal photos file

***** END OF REPORT *****