

MPE ESTIMATION

FCC ID: **2A8IN-SL200A1**

1, In accordance with KDB447498D01V06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

2, Estimation Result

For WIFI:

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
2.4G WIFI	17.79	17±1(18)	63.10	-0.66	0.86	0.01079
$Pd = \frac{P_{out} * G}{4\pi r^2}$;						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power.						
Conducted power see the test report HK2305061760-E , antenna gain=-0.66dBi						

Per KDB 447498 D01 V06, when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01079mW/cm² which is < 1.0 mW/cm², RF Exposure testing is not required.

-----The End-----