

WA-F-LB-02-238 Specification

1. Explanation of part number :

WA - F - LB - 02 - 238
(1) (2) (3) (4) (5)

- (1) Product Type: Wireless Antenna
- (2) Material: FPC+Cable
- (3) Frequency: 2400MHz-2500MHz&5100MHz-5800MHz
- (4) Coaxial Cable Type : With ϕ 1.13 Black
- (5) Suffix : 238

2. Operating Condition:

Temperature -40 to +70°C
Humidity 20 to 65% RH

3. Storage Condition:

Temperature -40 to +70°C
Humidity 10 to 85% RH

4. Electrical Specification :

*Those specifications were specially defined for **GCS5** model, and all characteristics were measured under the model's handset testing.*

4-1. Frequency Band:

Frequency Band	MHz
WIFI	2400~2500&5100~5800

4-2. Impedance

50 ohm nominal

4-3. Matching circuit

None

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

No. 5, Chunqiu Road, Huangdai Town, Xiangcheng District, Suzhou City

SCALE : / UNIT : mm

DRAWN BY : 陆晓华 CHECKED BY : 林娟

DESIGNED BY: 黄璐璐 APPROVED BY : 唐龙

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WA-F-LB-02-238 Specification

DOCUMENT
NO.

ENS000140150

PAGE REV.
P3


4-4. VSWR

4-4.1 Measuring Method

1. 50 Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the VSWR
2. Keeping this jig away from metal at least 20cm

4-4.2 Measurement frequency points and VSWR value

Mark	Frequency	VSWR
1	2400MHz	≤ 3.0
2	2500 MHz	≤ 3.0
3	5100MHz	≤ 4.5
4	5800MHz	≤ 4.5



4-5. Efficiency and Gain

4-5.1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane
3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
4. Using another standard gain horn antenna to calibrated those data

4-5.2 Chamber definition

1. An anechoic chamber (7mx4mx3m) which satisfied far-field condition was applied to

UNLESS OTHER SPECIFIED TOLERANCES ON : X=± X.X=± X.XX=± ANGLES=± HOLEDIA=±		 INPAQ TECHNOLOGY CO., LTD.	
SCALE : /	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : 陆晓华	CHECKED BY : 林娟		
DESIGNED BY: 黄璐璐	APPROVED BY : 唐龙		
TITLE : WA-F-LB-02-238 Specification		DOCUMENT NO.	PAGE REV.
		ENS000140150	P3

avoid multi-path effect

2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

4-5.3 Antenna Passive Test Result

Frequency (MHz)	Peak Gain(dBi)	Efficiency(dBi)	Efficiency(%)
2400	0.90	-4.62	34.48
2500	-0.29	-5.24	29.92
5100~5350	1.92	-2.28	59.15
5470~5900	0.15	-4.66	34.23

5. Mechanical Specification :

5-1 Mechanical Configuration (Unit: mm)



UNLESS OTHER SPECIFIED TOLERANCES ON :

X=± X.X=± X.XX=±
 ANGLES=± HOLEDIA=±



INPAQ TECHNOLOGY CO., LTD.

SCALE : /

UNIT : mm

DRAWN BY : 陆晓华

CHECKED BY : 林娟

DESIGNED BY: 黄璐璐

APPROVED BY : 唐龙

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : WA-F-LB-02-238 Specification

DOCUMENT
NO.


ENS000140150

PAGE REV.
P3


2.4G



5.2G



5.8G



UNLESS OTHER SPECIFIED TOLERANCES ON :		 INPAQ TECHNOLOGY CO., LTD.
X=±	X.X=±	
ANGLES=±	HOLEDIA=±	
SCALE : /	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
DRAWN BY : 陆晓华	CHECKED BY : 林娟	
DESIGNED BY: 黄璐璐	APPROVED BY : 唐龙	
TITLE : WA-F-LB-02-238 Specification		DOCUMENT NO. ENS000140150
		PAGE REV. P3