

RF EXPOSURE REPORT

Report No.: DDT-B23092109-2E04

Applicant	:	Honeywell International Inc
Address	:	12 Clintonville Rd , Northford , CT 06472 , USA
Equipment under Test	:	NA Connected Power Duplex receptacles
Model No.	:	CS2001202WHI, CS2001152WHI
Trade Mark	:	Honeywell
FCC ID	:	2A8LTNC0001
Manufacturer	:	MK Electric (M) Sdn Bhd
Address	:	Komplek Perusahaan LTAT, Jalan Pengapit 15/19, Batu 3 Industrial Estate, 40000 Shah Alam, Selangor.

Issued By: Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park
Development Area, Tianjin, China

Tel: +86-22-58038033, E-mail: ddt@ddttest.com, <http://www.ddttest.com>



REPORT

TABLE OF CONTENTS

Test report declares.....	3
1. General information.....	5
1.1. Description of Equipment.....	5
1.2. Assess laboratory.....	6
2. RF Exposure Evaluation	7
2.1. Requirement.....	7
2.2. Calculation method.....	7
2.3. Estimation result.....	8

TEST REPORT DECLARE

Applicant	:	Honeywell International Inc
Address	:	12 Clintonville Rd , Northford , CT 06472 , USA
Equipment under Test	:	NA Connected Power Duplex receptacles
Model No.	:	CS2001202WHI, CS2001152WHI
Trade mark	:	Honeywell
Manufacturer	:	MK Electric (M) Sdn Bhd
Address	:	Komplek Perusahaan LTAT, Jalan Pengapit 15/19, Batu 3 Industrial Estate, 40000 Shah Alam, Selangor.

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Tianjin Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Tianjin Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assessments.

After evaluation, our opinion is that the equipment In Accordance with above standard


Report No:	DDT-B23092109-2E04	
Date of Receipt:	Oct. 11, 2023	Date of Test: Oct. 11, 2023 ~ Oct. 26, 2023

Prepared By:



Novak Wei/Engineer

Approved By:



Aaron Zhang/Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Tianjin Dongdian Testing Service Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Oct. 23, 2023	

1. General information

1.1. Description of Equipment

EUT* Name	:	NA Connected Power Duplex receptacles
Model Number	:	CS2001202WHI, CS2001152WHI
EUT function description	:	Please reference user manual of this device
Power supply	:	AC 125V 60Hz
Radio Specification	:	BLE 5.0
Operation Frequency	:	2402 MHz - 2480 MHz
Modulation	:	GFSK
Transmitter Rate	:	1 Mbps, 2 Mbps
Antenna Type	:	PCB antenna, maximum PK gain: 2.11 dBi
Exposure category	:	General population/uncontrolled environment
Device Type	:	Mobile Device
target power and tolerance	:	10+- 2dBm

1.2. Assess laboratory

Tianjin Dongdian Testing Service Co., Ltd.

Address: Building D-1, No. 19, Weisi Road, Microelectronics Industrial Park Development Area, Tianjin, China.

Tel: +86-22-58038033, <http://www.ddttest.com>, Email: ddt@dqddt.com

NVLAP (National Voluntary Laboratory Accreditation Program) CODE: 500036-0

CNAS (China National Accreditation Service for Conformity Assessment) CODE: L13402

FCC Designation Number: CN5004; FCC Test Firm Registration Number: 368676

ISED (Innovation, Science and Economic Development Canada) Company Number: 27768

Conformity Assessment Body Identifier: CN0125

VCCI Facility Registration Number: C-20089, T-20093, R-20125, G-20122

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Worst Mode	Max. Tune UP power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BLE 1M	12.00	15.8	2.11	1.6	0.005	1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT