

Antenna Specification

Supplier name	Shenzhen Hoogwell Communication Technology Co., Ltd.
Supplier address	Room 230 Zhihui Creative,No 2005,Shajing Xihuan Road,Baoan District ,Shenzhen,Guangdong
Product model	ah148-2.4GFPC ANT
Product Name	ah148-BT-L-04
Application	ah148
Sample delivery time	2023-03-13
Customer material code	
Supplier Project Contact	Mingqiu Liu
Phone Number	18576402166

Supplier confirmation	RF	MD	Quality	Audit
Customer confirmation	RF	MD	Quality	Audit

Directory

1. Cover
2. Specifications
3. Electrical performance
4. Structural drawing
5. Appearance and Performance Test Report
6. Product Specification Size Test Report
7. Material Composition Declaration Form
8. Process flow chart


Description:

1. The samples and the acknowledgment shall be made in quadruplicate respectively. Each sample shall be nailed on the top left corner of the acknowledgment cover and sealed with electrostatic bag (electronic material) or thick PP bag.

1. The report mainly provides test data of passive performance parameters of AH148 L BT antenna,

The frequency band of AH148 BT is 2.4-2.483GHz.

The antenna sample is shown in picture (1).



picture (1)

2 Electrical performance


2-1 Specification

AH148 L BT antenna operating frequency band 2.4~2.483 GHz.

Below table is the return loss performance test index of AH148 L BT antenna.


Frequency band (MHz)	Return loss (dB)
2400~2483	≤ -6 dB

2-2 AH148 L BT Antenna Matching Circuit



3 Return Loss Test

3-1 Test setup




Return Loss Test Setup

3-2 Return Loss Test Data

As shown in the following table, the return loss test data of the edge frequency points of the BT antenna.

Band	Return Loss (dB)	
2400~2500MHz	2400	2485
Free space RL	-7.6	-6.3

3-3 Return Loss



3-4 Passive Efficiency (freed Space)


frequency (MHz)	2400	2410	2430	2440	2450	2460	2470	2480	2490	2500
gain (dBi)	0.73	1.05	1.23	1.47	1.59	1.25	0.78	0.6	0.13	-0.59
efficiency (%)	18.09	19.45	21.69	24.6	24.88	23.4	22.45	20.38	17.23	17.16

3-5 OTA


	L		
Channel	0	39	78
TRP (dBm)	-1.64	-1.13	-0.4
TIS (dBm)	-82.43	-83.11	-82.76

3-6 Polar Graphs


Phi=90 freq=2450MHz




Phi=0 freq=2450MHz



Theta=90 freq=2450MHz



4. Antenna Drawings



5.Appearance and Function Test Report

Item		Requirement	Results
Appearance	Date Code	☒ YYWW ☐ WWYY ☐ Other	☐ Acc ☐ Rej
Inspection	UL Indication		NA
	Visual Inspection	100% visual inspection and tally with customer specification.	☒ Acc ☐ Rej
Testing	FPC O/S Testing	100% visual inspection and no open/short is found.	☒ Acc ☐ Rej
	Insulation Resistance	1*108Ω or higher when DC500V	NA
	SolderabilityTest	No de-wetting or non-wetting is visible.	☐ Acc ☐ Rej
	AdhesionTest	No material shall be attached on the peeled tape.	☐ Acc ☐ Rej
	Au Coating Thk.	Au: 0.5-3 μ" Ni: 100-150 μ"	☒ Acc ☐ Rej
	Canned substances Confirm	Non-inclusion banned substances contained in products	☒ Acc ☐ Rej
	Heat-durability	Tin temperature: 280 ± 5 °C, immersion time: 10sec The base material / protective film shall be free of expansion, lifting, foaming and other phenomena	☒ Acc ☐ Rej
	Pulling test	0.5kg, 30sec, no electrical performance defect	☐ Acc ☐ Rej
	Bending test	R = 0.5mm, 180 ° , 10cyc, no electrical performance defect	NA

Num.	Profile tolerance	Requirement	Measured Data							Judge
1		13.24±0.2								√Acc□Rej
2		10.34±0.2								
3										
4										
5										
6										

Product composition or Parts List

[illegible]

8.Process flow chart

