



TEST REPORT

Applicant Name : TELECOMUNICACIONES Y SERVICIOS CONOSUR LTDA.

Address: PANAMERICANA NORTE 6199 OF.804, CONCHALI,

SANTIAGO-CHILE

Report Number: SZNS220909-40985E-SA

FCC ID: 2A8NN-V909T

Test Standard (s) FCC Part 2.1093

Sample Description

Product Type: 4G flip phone

Model No.: V909T Trade Mark: VISMOV

Serial Number: SZNS220909-40985E-SA-S1

Date Received: 2022/09/10

Date of Test: 2022/09/22~2022/09/23

Report Date: 2022/10/13

Test Result: Pass*

Prepared and Checked By:

Approved By:

Lance Li

EMC Engineer

runceli

Candy Li

EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "⋆ ".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

^{*} In the configuration tested, the EUT complied with the standards above.

Attestation of Test Results						
MO	DE	Max. SAR Level(s) Reported(W/kg)	Limit (W/kg)			
GSM 850	1g Head SAR 1g Body SAR	0.25 0.57				
PCS 1900	1g Head SAR 1g Body SAR	0.50 1.22				
WCDMA Band 2	1g Head SAR 1g Body SAR	0.61 1.55				
WCDMA Band 4	1g Head SAR 1g Body SAR	0.78 1.39				
WCDMA Band 5	1g Head SAR 1g Body SAR	0.79 1.52	1.6			
LTE Band 2	1g Head SAR 1g Body SAR	0.27 0.74	1.6			
LTE Band 7	1g Head SAR 1g Body SAR	0.04 0.65				
LTE Band 66&4	1g Head SAR 1g Body SAR	0.10 0.79				
Bluetooth	1g Head SAR 1g Body SAR	0.03 0.03				
Simultaneous	1g Head SAR 1g Body SAR	0.82 1.58				
	FCC 47 CFR part 2. Radiofrequency radia	1093 tion exposure evaluation: portable devices				
	RF Exposure Proced	lures: TCB Workshop April 2015(Overlapping LTI	E Bands)			
	IEEE1528:2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques					
Applicable Standards	IEC 62209-1:2016 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)					
	KDB 648474 D04 Ha KDB 865664 D01 SA KDB 865664 D02 RF KDB 941225 D01 3G	erim General RF Exposure Guidance v01 ndset SAR v01r03 .R Measurement 100 MHz to 6 GHz v01r04 Exposure Reporting v01r02 SAR Procedures v03r01 .R for LTE Devices v02r05				

Report No.: SZNS220909-40985E-SA

Note: This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in FCC 47 CFR part 2.1093 and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.

The results and statements contained in this report pertain only to the device(s) evaluated.

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
EUT DESCRIPTION	5
TECHNICAL SPECIFICATION	5
REFERENCE, STANDARDS, AND GUIDELINES	6
SAR LIMITS	7
FACILITIES	8
DESCRIPTION OF TEST SYSTEM	9
EQUIPMENT LIST AND CALIBRATION	14
EQUIPMENTS LIST & CALIBRATION INFORMATION	
SAR MEASUREMENT SYSTEM VERIFICATION	15
LIQUID VERIFICATION	15
SYSTEM ACCURACY VERIFICATION	
SAR SYSTEM VALIDATION DATA	
EUT TEST STRATEGY AND METHODOLOGY	
TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR	
EAR/TILT POSITION	
TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS	
TEST DISTANCE FOR SAR EVALUATION	
CONDUCTED OUTPUT POWER MEASUREMENT	
TEST PROCEDURE	
RADIO CONFIGURATION	27
MAXIMUM TARGET OUTPUT POWER	32
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	
ANTENNAS LOCATION:	
ANTENNA DISTANCE TO EDGE	
STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	
SAR MEASUREMENT RESULTS	49
SAR TEST DATA	49
SAR MEASUREMENT VARIABILITY	60
SAR SIMULTANEOUS TRANSMISSION DESCRIPTION	61
SAR PLOTS	63
APPENDIX A MEASUREMENT UNCERTAINTY	64
APPENDIX B EUT TEST POSITION PHOTOS	66
APPENDIX C PROBE CALIBRATION CERTIFICATES	67
APPENDIX D DIPOLE CALIBRATION CERTIFICATES	68

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision	
0	SZNS220909-40985E-SA	Original Report	2022/10/13	

EUT DESCRIPTION

This report has been prepared on behalf of *TELECOMUNICACIONES Y SERVICIOS CONOSUR LTDA*. and their product *4G flip phone*, Model: *V909T*, FCC ID: *2A8NN-V909T* or the EUT (Equipment under Test) as referred to in the rest of this report.

Report No.: SZNS220909-40985E-SA

Technical Specification

Device Type:	Portable	
Dimension	196×52×10 mm	
Exposure Category:	Population / Uncontrolled	
Antenna Type(s):	Internal Antenna	
DTM Type:	Class B	
Multi-slot Class:	GPRS(Class 12)	
Body-Worn Accessories:	Headset	
Face-Head Accessories:	None	
Operation Mode :	GSM Voice, GPRS Data, WCDMA(R99 (Voice+Data), HSDPA/HSUPA), FDD-LTE, Bluetooth	
Frequency Band:	GSM 850: 824-849 MHz(TX); 869-894 MHz(RX) PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) WCDMA Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX) WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX) LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX) LTE Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX) LTE Band 7: 2500-2570 MHz(TX); 2620-2690 MHz(RX) LTE Band 66: 1710-1780 MHz(TX); 2110-2180 MHz(RX) Bluetooth: 2402 -2480 MHz(TX&RX)	
Conducted RF Power:	GSM 850: 32.89 dBm; PCS 1900: 30.17 dBm WCDMA Band 2: 22.56 dBm; WCDMA Band 4: 21.45 dBm WCDMA Band 5: 22.66 dBm LTE Band 2: 21.42 dBm; LTE Band 4: 21.58 dBm LTE Band 7: 21.60 dBm; LTE Band 66: 21.53 dBm Bluetooth(BDR/EDR): 3.06 dBm	
Power Source:	Rechargeable Battery	
Normal Operation:	Head and Body-worn	

REFERENCE, STANDARDS, AND GUIDELINES

FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

Report No.: SZNS220909-40985E-SA

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

CE:

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by EN62209-1 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

Version 801: 2021-11-09 Page 6 of 68 FCC SAR 4G

SAR Limits

FCC Limit (1g Tissue)

Report No.: SZNS220909-40985E-SA

	SAR (W/kg)				
EXPOSURE LIMITS	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)			
Spatial Average (averaged over the whole body)	0.08	0.4			
Spatial Peak (averaged over any 1 g of tissue)	1.6	8.0			
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0			

CE Limit (10g Tissue)

	SAR (W/kg)				
EXPOSURE LIMITS	(General Population /	(Occupational /			
	Uncontrolled Exposure	Controlled Exposure			
	Environment)	Environment)			
Spatial Average (averaged over the whole body)	0.08	0.4			
Spatial Peak (averaged over any 10 g of tissue)	2.0	10			
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0			

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

FACILITIES

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358,the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01

Report No.: SZNS220909-40985E-SA

Listed by Innovation, Science and Economic Development Canada (ISEDC), the Registration Number is 5077A.

The test site has been registered with ISED Canada under ISED Canada Registration Number CN0016.

Version 801: 2021-11-09 Page 8 of 68 FCC SAR 4G

DESCRIPTION OF TEST SYSTEM


These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:

Report No.: SZNS220909-40985E-SA



DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



Version 801: 2021-11-09 Page 9 of 68 FCC SAR 4G

- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

Report No.: SZNS220909-40985E-SA

- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400 MHz Intel ULV Celeron, 128 MB chip-disk and 128 MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16-bit AD converter system for optical detection and digital I/O interface are contained on the DASY6 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluations of field measurements and surface detection, controls robot movements, and handles safety operations. The PC operating system cannot interfere with these time-critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port, which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Connection of devices from any other supplier could seriously damage the measurement server.

Data Acquisition Electronics

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

EX3DV4 E-Field Probes

Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	\pm 0.3 dB in TSL (rotation around probe axis) \pm 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: \pm 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

SAM Twin Phantom

The SAM Twin Phantom (shown in front of DASY5) is a fiberglass shell phantom with shell thickness 2 mm, except in the ear region where the thickness is increased to 6 mm.

When the phantom is mounted inside allocated slot of the DASY5 platform, phantom reference points can be taught directly in the DASY5 V5.2 software. When the DASY5 platform is used to mount the

Phantom, some of the phantom teaching points cannot be reached by the robot in DASY5 V5.2. A special tool called P1a-P2aX-Former is provided to transform two of the three points, P1 and P2, to reachable locations. To use these new teaching points, a revised phantom configuration file is required.

In addition to our standard broadband liquids, the phantom can be used with the following tissue simulating liquids:

Sugar-water-based liquids can be left permanently in the phantom. Always cover the liquid when the system is not in use to prevent changes in liquid parameters due to water evaporation.



Report No.: SZNS220909-40985E-SA

DGBE-based liquids should be used with care. As DGBE is a softener for most plastics, the liquid should be taken out of the phantom, and the phantom should be dried when the system is not in use (desirable at least once a week).

Do not use other organic solvents without previously testing the solvent resistivity of the phantom. Approximately 25 liters of liquid is required to fill the SAM Twin phantom.

Calibration Frequency	Frequency	Range(MHz)	Conversion Factor			
Point(MHz)	From	To	X	Y	Z	
750 Head	650	850	10.04	10.04	10.04	
900 Head	850	1000	9.61	9.61	9.61	
1450 Head	1350	1550	8.52	8.52	8.52	
1750 Head	1650	1850	8.32	8.32	8.32	
1900 Head	1850	1950	7.94	7.94	7.94	
2000 Head	1950	2100	7.99	7.99	7.99	
2300 Head	2200	2400	7.78	7.78	7.78	
2450 Head	2400	2550	7.54	7.54	7.54	
2600 Head	2550	2700	7.30	7.30	7.30	
3300 Head	3200	3400	7.09	7.09	7.09	
3500 Head	3400	3600	6.89	6.89	6.89	
3700 Head	3600	3800	6.55	6.55	6.55	
3900 Head	3800	4000	6.60	6.60	6.60	
4400 Head	4300	4500	6.34	6.34	6.34	
4600 Head	4500	4700	6.26	6.26	6.26	
4800 Head	4700	4900	6.16	6.16	6.16	
4950 Head	4900	5050	5.85	5.85	5.85	
5250 Head	5140	5360	5.35	5.35	5.35	
5600 Head	5490	5700	4.85	4.85	4.85	
5750 Head	5700	5860	4.83	4.83	4.83	

Report No.: SZNS220909-40985E-SA

Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

Version 801: 2021-11-09 Page 12 of 68 FCC SAR 4G

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1:2016

Recommended Tissue Dielectric Parameters for Head

Table A.3 - Dielectric properties of the head tissue-equivalent liquid

Report No.: SZNS220909-40985E-SA

Frequency	Relative permittivity	Conductivity (σ)	
MHz	$arepsilon_{ m r}$	S/m	
300	45,3	0,87	
450	43,5	0,87	
750	41,9	0,89	
835	41,5	0,90	
900	41,5	0,97	
1 450	40,5	1,20	
1 500	40,4	1,23	
1 640	40,2	1,31	
1 750	40,1	1,37	
1 800	40,0	1,40	
1 900	40,0	1,40	
2 000	40,0	1,40	
2 100	39,8	1,49	
2 300	39,5	1,67	
2 450	39,2	1,80	
2 600	39,0	1,96	
3 000	38,5	2,40	
3 500	37,9	2,91	
4 000	37,4	3,43	
4 500	36,8	3,94	
5 000	36,2	4,45	
5 200	36,0	4,66	
5 400	35,8	4,86	
5 600	35,5	5,07	
5 800	35,3	5,27	
6 000	35,1	5,48	

NOTE For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5 800 MHz are provided (i.e. the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6 000 MHz that were linearly extrapolated from the values at 3 000 MHz and 5 800 MHz.


EQUIPMENT LIST AND CALIBRATION

Equipments List & Calibration Information

Equipment	Model	S/N	Calibration Date	Calibration Due Date
DASY5 Test Software	DASY52 52.10.4	N/A	NCR	NCR
DASY5 Measurement Server	DASY5 6.0.31	N/A	NCR	NCR
Data Acquisition Electronics	DAE4	1211	2022/03/01	2023/02/28
E-Field Probe	EX3DV4	7441	2022/05/16	2023/05/15
Mounting Device	MD4HHTV5	SD 000 H01 KA	NCR	NCR
SAM Twin Phantom	SAM-Twin V5.0	1744	NCR	NCR
Dipole,835MHz	D835V2	4d103	2021/10/27	2024/10/26
Dipole,1800MHz	D1800V2	2d018	2020/10/15	2023/10/14
Dipole,1900MHz	D1900V2	5d128	2021/10/27	2024/10/26
Dipole,2450MHz	D2450V2	751	2020/10/13	2023/10/12
Dipole,2600MHz	D2600V2	1162	2019/10/2	2022/10/1
Simulated Tissue Liquid Head(500-9500MHz)	HBBL600-10000V6	180622-2	Each Time	/
Network Analyzer	8753D	3410A08288	2022/07/05	2023/07/04
Dielectric Assessment Kit	DAK-3.5	1320	NCR	NCR
Signal Generator	SMB100A	108362	2021/12/23	2022/12/22
USB wideband power sensor	U2021XA	MY52350001	2021/12/23	2022/12/22
Power Amplifier	CBA 1G-070	T44328	2021/12/23	2022/12/22
Linear Power Amplifier	AS0860-40/45	1060913	2021/12/23	2022/12/22
Directional Coupler	4223-20	3.113.277	2021/12/23	2022/12/22
6dB Attenuator	8493B	2708A 04769	2021/12/23	2022/12/22
Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
Wideband Radio Communication Tester	CMW500	143458	2022/02/27	2023/02/26

SAR MEASUREMENT SYSTEM VERIFICATION

Liquid Verification



Report No.: SZNS220909-40985E-SA

Liquid Verification Setup Block Diagram

Liquid Verification Results

Frequency	I : : d T	Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	ε _r	O' (S/m)	$\epsilon_{ m r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ (S/m)	(%)
824.2	Simulated Tissue Liquid Head	41.53	0.905	41.534	0.91	-0.01	-0.55	±5
826.4	Simulated Tissue Liquid Head	41.597	0.912	41.54	0.9	0.14	1.33	±5
835	Simulated Tissue Liquid Head	41.132	0.926	41.426	0.922	-0.71	0.43	±5
836.6	Simulated Tissue Liquid Head	41.369	0.942	41.512	0.933	-0.34	0.96	±5
846.6	Simulated Tissue Liquid Head	41.639	0.945	41.5	0.91	0.33	3.85	±5
848.8	Simulated Tissue Liquid Head	41.86	0.949	41.839	0.943	0.05	0.64	±5

^{*}Liquid Verification above was performed on 2022/09/22.

Frequency	I :: d Tame	Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	$\epsilon_{ m r}$	O' (S/m)	$\epsilon_{ m r}$	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)
1712.4	Simulated Tissue Liquid Head	40.085	1.365	40.13	1.35	-0.11	1.11	±5
1732.6	Simulated Tissue Liquid Head	39.158	1.38	40.12	1.36	-2.4	1.47	±5
1752.6	Simulated Tissue Liquid Head	40.239	1.385	40.09	1.37	0.37	1.09	±5
1720	Simulated Tissue Liquid Head	41.083	1.39	40.13	1.35	2.37	2.96	±5
1745	Simulated Tissue Liquid Head	39.281	1.392	40.1	1.37	-2.04	1.61	±5
1770	Simulated Tissue Liquid Head	41.316	1.393	40.1	1.39	3.03	0.22	±5
1800	Simulated Tissue Liquid Head	39.455	1.411	40	1.4	-1.36	0.79	±5

^{*}Liquid Verification above was performed on 2022/09/23.

Frequency	Liquid Tono	Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	$\epsilon_{ m r}$	O' (S/m)	£.		$\Delta \epsilon_{ m r}$	ΔΟ΄ (S/m)	(%)
1850.2	Simulated Tissue Liquid Head	39.785	1.397	39.882	1.397	-0.24	0	±5
1852.4	Simulated Tissue Liquid Head	40.362	1.403	40.122	1.407	0.6	-0.28	±5
1860	Simulated Tissue Liquid Head	40.238	1.408	40.021	1.41	0.54	-0.14	±5
1880	Simulated Tissue Liquid Head	40.054	1.41	40.129	1.409	-0.19	0.07	±5
1900	Simulated Tissue Liquid Head	39.656	1.43	39.482	1.426	0.44	0.28	±5
1907.6	Simulated Tissue Liquid Head	39.106	1.444	39.076	1.444	0.08	0	±5
1909.8	Simulated Tissue Liquid Head	39.496	1.441	39.462	1.432	0.09	0.63	±5

^{*}Liquid Verification above was performed on 2022/09/22.

F.		Liquid Parameter		Target Value		Delta (%)		
Frequency (MHz)	Liquid Type	£ _r	O' (S/ m)	$\epsilon_{ m r}$	O' (S/ m)	$\Delta arepsilon_{ m r}$	ΔΟ	Tolerance (%)
2402	Simulated Tissue Liquid Head	38.281	1.806	38.02	1.802	0.69	0.22	±5
2440	Simulated Tissue Liquid Head	38.387	1.822	38.12	1.836	0.7	-0.76	±5
2450	Simulated Tissue Liquid Head	38.018	1.852	38.111	1.859	-0.24	-0.38	±5
2480	Simulated Tissue Liquid Head	38.47	1.862	38.528	1.871	-0.15	-0.48	±5

^{*}Liquid Verification above was performed on 2022/09/23.

Frequency	Liquid Tuno	Liquid Parameter		Target Value		Delta (%)		Tolerance
(MHz)	Liquid Type	ε _r	O' (S/m)	ε _r	O' (S/m)	$\Delta \epsilon_{ m r}$	ΔΟ' (S/m)	(%)
2510	G' 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	20.524		20.550		0.06		
2510	Simulated Tissue Liquid Head	38.534	1.89	38.558	1.89	-0.06	0	±5
2535	Simulated Tissue Liquid Head	38.445	1.894	38.672	1.895	-0.59	-0.05	±5
2560	Simulated Tissue Liquid Head	39.94	1.905	39.828	1.915	0.28	-0.52	±5
2600	Simulated Tissue Liquid Head	40.02	1.934	39.897	1.932	0.31	0.1	±5

^{*}Liquid Verification above was performed on 2022/09/23.

System Accuracy Verification


Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of $\pm 10\%$. The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

Report No.: SZNS220909-40985E-SA

The spacing distances in the System Verification Setup Block Diagram is given by the following:

- a) $s = 15 \text{ mm} \pm 0.2 \text{ mm for } 300 \text{ MHz} \le f \le 1000 \text{ MHz};$
- b) $s = 10 \text{ mm} \pm 0.2 \text{ mm}$ for $1000 \text{ MHz} < f \le 3000 \text{ MHz}$;
- c) $s = 10 \text{ mm} \pm 0.2 \text{ mm}$ for 3 000 MHz $< f \le 6$ 000 MHz.

System Verification Setup Block Diagram



System Accuracy Check Results

Date	Frequency Band(MHz)	Liquid Type	Input Power (mW)		sured SAR //kg)	Normalized to 1W (W/kg)	Target Value (W/kg)	Delta (%)	Tolerance (%)
2022/9/22	835	Head	100	1g	0.874	8.74	9.65	-9.430	±10
2022/9/23	1800	Head	100	1g	4.07	40.7	39.3	3.562	±10
2022/9/22	1900	Head	100	1g	4.26	42.6	40.0	6.500	±10
2022/9/23	2450	Head	100	1g	5.27	52.7	53	-0.566	±10
2022/9/23	2600	Head	100	1g	5.72	57.2	55.4	3.249	±10

^{*}The SAR values above are normalized to 1 Watt forward power.

SAR SYSTEM VALIDATION DATA

System Performance 835 MHz

DUT: Dipole D835V2; Type: 835MHz; Serial: 4d013

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1 Medium parameters used: f = 835 MHz; σ = 0.926 S/m; ϵ_r = 41.132; ρ = 1000 kg/m³

Phantom section: Flat Section

DASY5 Configuration:

Probe: EX3DV4- SN7441; ConvF(10.04, 10.04, 10.04); Calibrated: 2022/05/16

• Sensor-Surface: 4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn1211; Calibrated: 2022/03/01

• Phantom: Twin SAM; Type: QD000P40CD; Serial: 1744

• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

System Performance Cheek at 835MHz/d=15mm, Pin=100mw/Area Scan (71x91x1): Measurement grid: dx=15mm, dy=15mm

Report No.: SZNS220909-40985E-SA

Maximum value of SAR (interpolated) = 0.928 W/kg

System Performance Cheek at 835MHz/d=15mm, Pin=100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 33.75 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.28 W/kg

SAR(1 g) = 0.874 W/kg; SAR(10 g) = 0.588 W/kg

Maximum value of SAR (measured) = 0.877 W/kg



0 dB = 0.877 W/kg = -0.57 dBW/kg

Version 801: 2021-11-09 Page 18 of 68 FCC SAR 4G

System Performance 1800 MHz

DUT: D1800V2; Type: 1800MHz; Serial: 2d018

Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty Cycle: 1:1 Medium parameters used: f = 1800 MHz; $\sigma = 1.411$ S/m; $\varepsilon_r = 39.455$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4- SN7441; ConvF(8.32, 8.32, 8.32); Calibrated: 2022/05/16
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1211; Calibrated: 2022/03/01
- Phantom: Twin SAM; Type: QD000P40CD; Serial: 1744
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

System Performance Cheek at 1800MHz/d=10mm, Pin=100mw/Area Scan (71x111x1): Measurement grid:

Report No.: SZNS220909-40985E-SA

dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 4.33 W/kg

System Performance Cheek at 1800MHz/d=10mm, Pin=100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 60.16 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 5.23 W/kg

SAR(1 g) = 4.07 W/kg; SAR(10 g) = 2.19 W/kg

Maximum value of SAR (measured) = 4.42 W/kg



0 dB = 4.42 W/kg = 6.45 dBW/kg

System Performance 1900MHz

DUT: D1900V2; Type: 1900 MHz; Serial: 5d128

Communication System: UID 0, CW (0); Frequency: 1900 MHz; Duty Cycle: 1:1 Medium parameters used: f = 1900 MHz; $\sigma = 1.43$ S/m; $\varepsilon_r = 39.656$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4- SN7441; ConvF(7.94, 7.94, 7.94); Calibrated: 2022/05/16
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1211; Calibrated: 2022/03/01
- Phantom: Twin SAM; Type: QD000P40CD; Serial: 1744
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

System Performance Cheek at 1900MHz/d=10mm, Pin=100mw/Area Scan (71x111x1): Measurement grid:

Report No.: SZNS220909-40985E-SA

dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 4.61 W/kg

System Performance Cheek at 1900MHz/d=10mm, Pin=100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 60.16 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 5.44 W/kg

SAR(1 g) = 4.26 W/kg; SAR(10 g) = 2.26 W/kg

Maximum value of SAR (measured) = 4.49 W/kg



0 dB = 4.49 W/kg = 6.52 dBW/kg

System Performance 2450MHz

DUT: D2450V2; Type: 2450 MHz; Serial: 751

Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2450 MHz; $\sigma = 1.852$ S/m; $\epsilon_r = 38.018$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4- SN7441; ConvF(7.54, 7.54, 7.54); Calibrated: 2022/05/16
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1211; Calibrated: 2022/03/01
- Phantom: Twin SAM; Type: QD000P40CD; Serial: 1744
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

System Performance Cheek at 2450MHz/d=10mm, Pin=100mw/Area Scan (101x111x1): Measurement grid:

Report No.: SZNS220909-40985E-SA

dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 5.29 W/kg

System Performance Cheek at 2450MHz/d=10mm, Pin=100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.08 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 6.57 W/kg

SAR(1 g) = 5.27 W/kg; SAR(10 g) = 2.67 W/kg

Maximum value of SAR (measured) = 5.48 W/kg



0 dB = 5.48 W/kg = 7.39 dBW/kg

System Performance 2600MHz

DUT: D2600V2; Type: 2600 MHz; Serial: 1162

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1 Medium parameters used: f = 2600 MHz; $\sigma = 1.934$ S/m; $\epsilon_r = 40.02$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4- SN7441; ConvF(7.3, 7.3, 7.3); Calibrated: 2022/05/16
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1211; Calibrated: 2022/03/01
- Phantom: Twin SAM; Type: QD000P40CD; Serial: 1744
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

System Performance Cheek at 2600MHz/d=10mm, Pin=100mw/Area Scan (101x131x1): Measurement grid:

Report No.: SZNS220909-40985E-SA

dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 6.09 W/kg

System Performance Cheek at 2600MHz/d=10mm, Pin=100mw/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 62.16 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 10.1 W/kg

SAR(1 g) = 5.72 W/kg; SAR(10 g) = 2.29 W/kg

Maximum value of SAR (measured) = 7.36 W/kg




0 dB = 7.36 W/kg = 8.67 dBW/kg


EUT TEST STRATEGY AND METHODOLOGY

Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ½ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point". The "test device reference point" should be located at the same level as the center of the earpiece region. The "vertical centerline" should bisect the front surface of the handset at its top and bottom edges. A "ear reference point" is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the "phantom reference plane" defined by the three lines joining the center of each "ear reference point" (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the "N-F" line defined along the base of the ear spacer that contains the "ear reference point". For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The "test device reference point" is aligned to the "ear reference point" on the head phantom and the "vertical centerline" is aligned to the "phantom reference plane". This is called the "initial ear position". While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:





Cheek/Touch Position

The device is brought toward the mouth of the head phantom by pivoting against the "ear reference point" or along the "N-F" line for the SCC-34/SC-2 head phantom.

Report No.: SZNS220909-40985E-SA


This test position is established:

When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

(or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

Cheek / Touch Position




Ear/Tilt Position

With the handset aligned in the "Cheek/Touch Position":

- 1) If the earpiece of the handset is not in full contact with the phantom's ear spacer (in the "Cheek/Touch position") and the peak SAR location for the "Cheek/Touch" position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the "initial ear position" by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.
- 2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both "ear reference points" (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the "test device reference point" until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both "ear reference points" until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.
- If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the "Cheek/Touch" and "Ear/Tilt" positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

Ear /Tilt 15° Position

Report No.: SZNS220909-40985E-SA



Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

Test Distance for SAR Evaluation

For this case the EUT(Equipment Under Test) is set 5mm away from the phantom, the test distance is 5mm.

SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.


- Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.
- Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:
 - 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.
 - All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
- Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

CONDUCTED OUTPUT POWER MEASUREMENT

Test Procedure

The RF output of the transmitter was connected to the input of the Spectrum Analyzer through Connector.

Report No.: SZNS220909-40985E-SA



GSM/WCDMA/LTE

Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

GSM/GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900

Press Connection control to choose the different menus

Press RESET > choose all the reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM + GPRS or GSM + EGSM

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

- > Slot configuration > Uplink/Gamma
- > 33 dBm for GPRS 850
- > 30 dBm for GPRS 1900
- > 27 dBm for EGPRS 850
- > 26 dBm for EGPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stabe)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0 > 4 dB

Slot Config > Unchanged (if already set under MS signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3

Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)

Bit Stream > 2E9-1 PSR Bit Stream

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal on to turn on the signal and change settings

WCDMA Release 99

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm $(\pm 1.7/-3.7)$.

Report No.: SZNS220909-40985E-SA

	Loopback Mode	Test Mode 1
WCDMA	Rel99 RMC	12.2kbps RMC
General Settings	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA			
	Subset	1	2	3	4			
	Loopback Mode			Test Mode	1			
	Rel99 RMC		1	12.2kbps RM	IC			
	HSDPA FRC		H-Set1					
	Power Control	Algorithm2						
WCDMA	Algorithm			Aigoriumiz	•			
General	$eta_{ m c}$	2/15	12/15	15/15	15/15			
Settings	$\beta_{ m d}$	15/15	15/15	8/15	4/15			
	$\beta_d(SF)$		64					
	$\beta_{\rm c}/\beta_{ m d}$	2/15	12/15	15/8	15/4			
	$eta_{ m hs}$	4/15	24/15	30/15	30/15			
	MPR(dB)	0	0	0.5	0.5			
	DACK			8				
HCDDA	DNAK			8				
HSDPA	DCQI			8				
Specifi	Ack-Nack repetition			3				
Setting	factor			3				
Setting	CQI Feedback	4ms						
S	CQI Repetition Factor			2				
	Ahs=βhs/ βc			30/15				

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA	
	Subset	1	2	3	4	5	
	Loopback Mode			Test Mode 1			
	Rel99 RMC		1	2.2kbps RM	C		
	HSDPA FRC			H-Set1			
	HSUPA Test		HS	UPA Loopba	ack		
	Power Control			Algorithm2			
WCDMA	Algorithm	4.4.5	C /4 =		0/4.5	1.7/1.7	
General	β_{c}	11/15	6/15	15/15	2/15	15/15	
Settings	β_d	15/15	15/15	9/15	15/15	0	
	$\beta_{\rm ec}$	209/225	12/15	30/15	2/15	5/15	
	$\beta_{\rm c}/\beta_{\rm d}$	11/15	6/15	15/9	2/15	-	
	$eta_{ m hs}$	22/15	12/15	30/15	4/15	5/15	
	CM(dB)	1.0	3.0	2.0	3.0	1.0	
	MPR(dB)	0	2	1	2	0	
	DACK	8					
	DNAK			8			
	DCQI			8			
HSDPA	Ack-Nack	4ms					
Specific	repetition factor						
Settings	CQI Feedback						
	CQI Repetition						
	Factor						
	Ahs= β_{hs}/β_{c}			30/15			
	DE-DPCCH	6	8	8	5	7	
	DHARQ	0	0	0	0	0	
	AG Index	20	12	15	17	21	
	ETFCI	75	67	92	71	81	
	Associated Max						
	UL Data Rate	242.1	174.9	482.8	205.8	308.9	
	kbps						
HSUPA		E-TFC		E-TFCI		CI 11 E	
Specific		E-TFC		11		CI PO 4	
Settings		E-TF		E-TFCI		CI 67	
Settings		E-TFC		PO4		I PO 18	
		E-TF		E-TFCI	E-TF		
	Reference E FCls	E-TFC		92		I PO23	
		E-TF		E-TFCI		CI 75	
		E-TFC		PO 18		I PO26	
		E-TFCI 81				CI 81	
		E-TFC1	PO 27		E-TFC	I PO 27	

HSPA+

Sub- test	β _c (Note3)	β _d	β _{HS} (Note1)	β _{ec}	β _{ed} (2xSF2) (Note 4)	β _{ed} (2xSF4) (Note 4)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 4)	E-TFCI (Note 5)	
1	1	0	30/15	30/15	β _{ed} 1: 30/15	β _{ed} 3: 24/15	3.5	2.5	14	105	105
					Bad2: 30/15	B _{ed} 4: 24/15					

Report No.: SZNS220909-40985E-SA

Note 1: $\Delta_{\rm ACK}$, $\Delta_{\rm NACK}$ and $\Delta_{\rm CQI}$ = 30/15 with β_{hs} = 30/15 * β_c .

Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).

Note 3: DPDCH is not configured, therefore the β_c is set to 1 and β_d = 0 by default.

Note 4: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm.

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

FDD-LTE

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

Report No.: SZNS220909-40985E-SA

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3

T	Modulation	Cha	nnel bandw	idth / Tra	ansmission	bandwidth (N _{RB})	MPR (dB)
1		1.4	3.0	5	10	15	20	
		MHz	MHz	MHz	MHz	MHz	MHz	
I	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
Ι	16 QAM	≤ 5	≤ 4	≤8	≤ 12	≤ 16	≤ 18	≤ 1
Τ	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (subclause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N _{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	N/A
			3	>5	≤ 1
		2 4 40 22 25	5	>6	≤ 1
NS_03	6.6.2.2.1	2, 4,10, 23, 25, 35, 36	10	>6	≤ 1
		35, 30	15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
_			10, 15, 20		6.2.4-4
NS_05	6.6.3.3.1	1	10,15,20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	N/A
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table	6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40 > 55	≤1 ≤2
NS_10		20	15, 20	Table	6.2.4-3
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10, 15, 20	Table	6.2.4-5
NS_12	6.6.3.3.5	26	1.4, 3, 5	Table	6.2.4-6
NS_13	6.6.3.3.6	26	5	Table	6.2.4-7
NS_14	6.6.3.3.7	26	10, 15	Table	6.2.4-8
NS_15	6.6.3.3.8	26	1.4, 3, 5, 10, 15	I	6.2.4-9 6.2.4-10
NS_16	6.6.3.3.9	27	3, 5, 10		, Table 6.2.4-12, 6.2.4-13
NS_17	6.6.3.3.10	28	5, 10	Table 5.6-1	N/A
NS_18	6.6.3.3.11	28	5 10, 15, 20	≥2 ≥1	≤ 1 ≤ 4
NS_19	6.6.3.3.12	44	10, 15, 20	Table	6.2.4-14
NS_20	6.2.2 6.6.2.2.1 6.6.3.2	23	5, 10, 15, 20		6.2.4-15
NS_32	-	-	-	-	-

Maximum Target Output Power

	Max Target Power(dBm)								
M 1 /D 1		Channel							
Mode/Band	Low	Middle	High						
GSM 850	33.0	33.0	33.0						
GPRS 1 TX Slot	33.0	33.0	33.0						
GPRS 2 TX Slot	30.5	30.5	30.5						
GPRS 3 TX Slot	29.0	29.0	29.0						
GPRS 4 TX Slot	27.5	27.5	27.5						
PCS 1900	30.5	30.5	30.5						
GPRS 1 TX Slot	30.1	30.1	30.1						
GPRS 2 TX Slot	28.5	28.5	28.5						
GPRS 3 TX Slot	27.0	27.0	27.0						
GPRS 4 TX Slot	25.5	25.5	25.5						
WCDMA Band 2	22.6	22.6	22.6						
HSDPA	22.0	22.0	22.0						
HSUPA	22.0	22.0	22.0						
WCDMA Band 4	21.5	21.5	21.5						
HSDPA	21.0	21.0	21.0						
HSUPA	21.0	21.0	21.0						
WCDMA Band 5	23.0	23.0	23.0						
HSDPA	22.0	22.0	22.0						
HSUPA	22.0	22.0	22.0						
LTE Band 2	21.5	21.5	21.5						
LTE Band 4	22.0	22.0	22.0						
LTE Band 7	22.0	22.0	22.0						
LTE Band 66	22.0	22.0	22.0						
Bluetooth BDR/EDR	3.5	3.5	3.5						

Test Results:

GSM:

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)
GSM 850	128	824.2	32.74
	190	836.6	32.79
	251	848.8	32.89
	512	1850.2	30.11
PCS 1900	661	1880	30.17
	810	1909.8	30.14

Report No.: SZNS220909-40985E-SA

GPRS:

Band	Channel	Frequency	RF Output Power (dBm)			
Danu	No.	(MHz)	1 slot	2 slots	3 slots	4 slots
	128	824.2	32.43	30.27	28.85	27.08
GSM 850	190	836.6	32.53	30.38	28.87	27.27
	251	848.8	32.47	30.34	28.81	27.19
PCS 1900	512	1850.2	30.05	28.35	26.62	25.09
	661	1880	30.03	28.40	26.58	25.10
	810	1909.8	30.03	28.42	26.61	25.21

For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.25 dB	-3 dB
Crest Factor	8	4	2.66	2

The time based average power for GPRS

Band	Channel No.	Frequency (MHz)	RF Output Power (dBm)				
			1 slot	2 slots	3 slots	4 slots	
GSM 850	128	824.2	23.43	24.27	24.60	24.08	
	190	836.6	23.53	24.38	24.62	24.27	
	251	848.8	23.47	24.34	24.56	24.19	
PCS 1900	512	1850.2	21.05	22.35	22.37	22.09	
	661	1880	21.03	22.40	22.33	22.10	
	810	1909.8	21.03	22.42	22.36	22.21	

- 1. Rohde & Schwarz Radio Communication Tester (CMU500) was used for the measurement of GSM peak
- and average output power for active timeslots.

 2. For GSM voice, 1 timeslot has been activated with power level 5 (850 MHz band) and 0 (1900 MHz band).

 3. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).

WCDMA Band 2:

Test Condition	Test Mode	3GPP Sub	Averaged Mean Power (dBm)			
		Test	Low Frequency	Mid Frequency	High Frequency	
	RMC12.2k		22.56	22.45	22.26	
	HSDPA	1	20.89	20.99	21.44	
Normal		2	21.16	21.24	21.35	
		3	21.42	20.91	21.33	
		4	21.23	21.12	21.06	
	HSUPA	1	21.56	21.43	21.32	
		2	21.57	21.42	21.47	
		3	21.31	21.29	21.22	
		4	21.61	21.38	21.05	
		5	21.68	21.25	21.06	

Report No.: SZNS220909-40985E-SA

WCDMA Band 4:

Test Condition	Test Mode	3GPP Sub	Averaged Mean Power (dBm)			
		Test	Low Frequency	Mid Frequency	High Frequency	
	RMC12.2k		21.24	21.45	21.25	
	HSDPA	1	20.22	20.34	20.07	
		2	20.37	20.21	20.27	
		3	20.46	20.42	20.31	
Normal		4	20.41	20.41	20.32	
Normai	HSUPA	1	19.88	20.01	20.15	
		2	19.58	20.00	19.25	
		3	19.19	19.62	19.31	
		4	19.93	19.43	19.64	
		5	19.58	19.54	19.41	

WCDMA Band 5:

Test Condition	Test Mode	3GPP Sub Test	Averaged Mean Power (dBm)			
			Low Frequency	Mid Frequency	High Frequency	
	RMC12.2k		22.36	22.66	22.35	
	HSDPA	1	21.22	21.30	21.41	
Normal		2	21.44	21.27	21.24	
		3	21.24	21.13	21.24	
		4	21.35	21.26	21.10	
	HSUPA	1	21.44	21.08	20.93	
		2	21.42	20.69	20.97	
		3	21.42	20.93	20.84	
		4	21.47	20.84	20.92	
		5	21.50	20.95	20.75	

Report No.: SZNS220909-40985E-SA

Note:

- 1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1.
- 2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/ HSPA+ when the maximum average output of each RF channel is less than $\frac{1}{4}$ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

LTE Band 2:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Target MPR	Meas MPR	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB1#0	0	0	21.16	21.09	20.25
		RB1#3	0	0	21.31	21.18	20.26
		RB1#5	0	0	21.15	21.16	20.16
	QPSK	RB3#0	1	1	20.42	20.12	19.28
		RB3#3	1	1	20.30	20.13	19.30
1.43.6		RB6#0	1	1	20.36	20.11	19.20
1.4M		RB1#0	1	1	20.30	19.96	19.47
		RB1#3	1	1	20.32	19.96	19.63
	16 0 4 14	RB1#5	1	1	20.43	19.99	19.37
	16-QAM	RB3#0	2	2	19.46	19.29	18.36
		RB3#3	2	2	19.34	19.22	18.32
		RB6#0	2	2	19.43	19.16	18.27
	ODGV	RB1#0	0	0	21.29	21.18	20.91
		RB1#8	0	0	21.42	21.25	21.03
		RB1#14	0	0	21.18	21.00	20.82
	QPSK	RB6#0	1	1	20.25	20.19	19.99
		RB6#9	1	1	20.28	20.06	19.85
3M		RB15#0	1	1	20.23	20.24	19.77
31VI		RB1#0	1	1	20.81	20.22	19.85
	16-QAM	RB1#8	1	1	20.92	20.56	19.97
		RB1#14	1	1	20.70	20.23	19.64
		RB6#0	2	2	19.38	19.10	18.98
		RB6#9	2	2	19.41	19.22	18.79
		RB15#0	2	2	19.23	19.19	18.81
		RB1#0	0	0	21.13	21.11	20.22
		RB1#13	0	0	21.24	21.16	20.27
	QPSK	RB1#24	0	0	21.12	21.06	20.13
	Qr3K	RB15#0	1	1	20.29	20.14	19.34
		RB15#10	1	1	20.24	20.05	19.23
53.4		RB25#0	1	1	20.29	20.07	19.15
5M		RB1#0	1	1	20.19	19.90	19.32
		RB1#13	1	1	20.43	20.01	19.55
	16 O A M	RB1#24	1	1	20.34	19.95	19.39
	16-QAM	RB15#0	2	2	19.34	19.19	18.33
		RB15#10	2	2	19.26	19.18	18.26
		RB25#0	2	2	19.33	19.05	18.30

19.71

18.95

18.81

18.90

RB1#99

RB50#0

RB50#50

RB100#0

16-QAM

1

2

2

2

1

2

2

2

20.69

19.37

19.24

19.26

20.15

19.24

19.13

19.20

LTE Band 4:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Target MPR	Meas MPR	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB1#0	0	0	21.14	21.03	20.24
		RB1#3	0	0	21.30	21.32	20.31
		RB1#5	0	0	21.12	21.15	20.21
	QPSK	RB3#0	1	1	20.35	20.19	19.31
		RB3#3	1	1	20.36	20.08	19.26
1.05		RB6#0	1	1	20.29	20.07	19.25
1.4M		RB1#0	1	1	20.33	20.02	19.43
		RB1#3	1	1	20.47	20.04	19.62
	160436	RB1#5	1	1	20.30	19.94	19.40
	16-QAM	RB3#0	2	2	19.37	19.31	18.37
		RB3#3	2	2	19.36	19.23	18.29
		RB6#0	2	2	19.30	19.16	18.23
	QPSK	RB1#0	0	0	21.29	21.10	20.86
		RB1#8	0	0	21.36	21.23	21.09
		RB1#14	0	0	21.17	21.04	20.92
		RB6#0	1	1	20.29	20.07	19.92
		RB6#9	1	1	20.29	20.14	19.89
23.4		RB15#0	1	1	20.35	20.10	19.85
3M		RB1#0	1	1	20.76	20.30	19.74
	16-QAM	RB1#8	1	1	21.01	20.56	20.00
		RB1#14	1	1	20.67	20.28	19.65
		RB6#0	2	2	19.50	19.27	19.00
		RB6#9	2	2	19.32	19.28	18.95
		RB15#0	2	2	19.30	19.12	18.77
		RB1#0	0	0	21.25	21.22	20.36
		RB1#13	0	0	21.43	21.30	20.46
	ODCK	RB1#24	0	0	21.17	21.07	20.33
	QPSK	RB15#0	1	1	20.44	20.18	19.32
		RB15#10	1	1	20.30	20.10	19.33
51.4		RB25#0	1	1	20.34	20.11	19.26
5M		RB1#0	1	1	20.41	20.00	19.50
		RB1#13	1	1	20.47	20.17	19.63
	16.0434	RB1#24	1	1	20.36	19.97	19.53
	16-QAM	RB15#0	2	2	19.50	19.27	18.37
		RB15#10	2	2	19.34	19.37	18.31
		RB25#0	2	2	19.32	19.27	18.28

2

2

RB50#50

RB100#0

2

2

19.21

19.30

18.96

18.99

19.43

19.42

LTE Band 7:

		Resource			Low	Middle	High
Test	Test	Block &	Target	Meas	Channel	Channel	Channel
Bandwidth	Modulation	RB offset	MPR	MPR	(dBm)	(dBm)	(dBm)
		RB1#0	0	0	20.82	20.97	20.91
		RB1#12	0	0	21.19	21.25	20.98
		RB1#24	0	0	21.07	20.90	20.78
	QPSK	RB12#0	1	1	19.65	20.19	19.97
		RB12#6	1	1	19.80	20.02	19.79
		RB12#11	1	1	20.17	19.94	20.07
		RB25#0	1	1	20.73	20.10	20.50
5M		RB1#0	1	1	20.76	20.19	20.04
		RB1#12	1	1	20.98	20.24	20.13
		RB1#24	1	1	19.23	19.00	18.79
	16-QAM	RB12#0	2	2	19.12	19.03	19.07
		RB12#6	2	2	18.93	19.19	18.67
		RB12#11	2	2	21.01	20.95	20.82
		RB25#0	2	2	21.31	21.41	21.13
		RB1#0	0	0	20.76	20.96	20.70
		RB1#24	0	0	20.06	20.11	20.42
		RB1#49	0	0	19.94	20.17	19.89
	QPSK	RB25#0	1	1	20.08	20.02	20.03
		RB25#12	1	1	20.25	20.12	20.38
		RB25#24	1	1	20.35	20.46	20.69
403.5		RB50#0	1	1	20.22	20.03	20.23
10M		RB1#0	1	1	19.18	19.23	19.06
		RB1#24	1	1	19.08	19.19	18.63
		RB1#49	1	1	19.10	19.30	19.03
	16-QAM	RB25#0	2	2	21.06	21.07	20.55
		RB25#12	2	2	21.31	20.93	20.87
		RB25#24	2	2	20.86	21.27	20.70
		RB50#0	2	2	19.95	20.18	19.67
		RB1#0	0	0	21.28	21.12	21.08
		RB1#37	0	0	21.10	21.56	20.88
		RB1#74	0	0	21.08	21.17	21.05
	QPSK	RB36#0	1	1	19.93	20.20	20.12
		RB36#18	1	1	20.03	20.35	20.00
		RB36#37	1	1	20.01	20.58	20.34
15M		RB75#0	1	1	20.93	20.23	20.98
1 3111		RB1#0	1	1	20.52	20.56	20.41
		RB1#37	1	1	20.97	20.55	20.34
		RB1#74	1	1	19.05	19.36	19.14
	16-QAM	RB36#0	2	2	19.18	19.29	18.85
		RB36#18	2	2	19.16	19.20	19.34
		RB36#37	2	2	20.91	21.09	20.75
		RB75#0	2	2	21.35	21.45	21.27

Test Bandwidth	Test Modulation	Resource Block & RB offset	Target MPR	Meas MPR	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB1#0	0	0	21.10	20.87	20.67
		RB1#49	0	0	20.26	20.46	20.72
		RB1#99	0	0	20.51	20.41	20.11
	QPSK	RB50#0	1	1	20.40	20.59	20.26
		RB50#24	1	1	20.31	20.26	20.49
		RB50#49	1	1	21.12	20.98	20.67
20M		RB100#0	1	1	20.65	20.17	20.22
20101		RB1#0	1	1	19.30	19.37	19.43
		RB1#49	1	1	19.06	19.77	19.34
		RB1#99	1	1	19.33	19.35	19.15
	16-QAM	RB50#0	2	2	20.90	20.90	20.92
		RB50#24	2	2	21.60	21.40	21.14
		RB50#49	2	2	21.28	21.14	20.95
		RB100#0	2	2	20.41	20.15	20.10

LTE Band 66:

Test Bandwidth	Test Modulation	Resource Block & RB offset	Target MPR	Meas MPR	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
		RB1#0	0	0	20.91	20.34	20.71
		RB1#0	0	0	21.01	20.54	20.71
		RB1#5	0	0	20.98	20.34	20.80
	QPSK	RB1#3 RB3#0	1	1	19.90	19.44	19.64
		RB3#3	1	1	19.90	19.44	19.64
		RB6#0	1	1	19.80	19.43	19.07
1.4M		RB1#0	1	1	20.14	19.44	19.74
		RB1#0	1	1	20.14	19.40	19.53
						19.37	19.68
	16-QAM	RB1#5	1	1	20.15		
		RB3#0	2	2	18.83	18.48	18.73
		RB3#3	2	2	18.83	18.44	18.67
		RB6#0	2	2	18.90	18.49	18.79
		RB1#0	0	0	20.79	20.90	21.16
		RB1#8	0	0	21.07	21.15	21.53
	QPSK	RB1#14	0	0	20.77	20.84	21.21
		RB6#0	1	1	19.96	19.95	20.37
		RB6#9	1	1	19.92	20.04	20.22
3M		RB15#0	1	1	19.87	20.01	20.26
		RB1#0	1	1	20.33	19.92	20.25
	16-QAM	RB1#8	1	1	20.50	20.21	20.43
		RB1#14	1	1	20.27	19.90	19.95
		RB6#0	2	2	19.01	19.08	19.41
		RB6#9	2	2	18.99	18.97	19.45
		RB15#0	2	2	18.93	18.96	19.34
		RB1#0	0	0	20.82	20.29	20.64
		RB1#13	0	0	21.03	20.53	20.82
	QPSK	RB1#24	0	0	20.98	20.30	20.56
	QI SII	RB15#0	1	1	19.85	19.45	19.71
		RB15#10	1	1	19.88	19.49	19.74
5M		RB25#0	1	1	19.88	19.45	19.68
2171		RB1#0	1	1	20.14	19.28	19.51
		RB1#13	1	1	20.14	19.51	19.65
	16-QAM	RB1#24	1	1	20.03	19.40	19.33
	10-QAIVI	RB15#0	2	2	18.99	18.49	18.75
		RB15#10	2	2	18.90	18.40	18.77
		RB25#0	2	2	18.99	18.44	18.75

2

2

2

2

18.61

18.65

18.02

18.05

18.30

18.50

RB50#50


RB100#0

Bluetooth:

Mode	Channel frequency	Maximum conducted
Mode	(MHz)	Peak Output Power
	2402	1.87
BDR(GFSK)	2441	0.77
	2480	0.08
	2402	3.06
EDR(π/4-DQPSK)	2441	1.92
	2480	1.18
	2402	2.92
EDR(8DPSK)	2441	1.88
	2480	1.29

Standalone SAR test exclusion considerations

Antennas Location:



Report No.: SZNS220909-40985E-SA

EUT Back With View

Antenna Distance To Edge

Antenna Distance To Edge(mm)									
Antenna	Front	Back	Left	Right	Top	Bottom			
Bluetooth	< 5	< 5	< 5	46	47	30			
Main ant (GSM/WCDMA/LTE)	< 5	< 5	< 5	< 5	< 5	64			


Body-worn Exposure Conditions

The general informing principle is that the selected test configurations must conservatively capture the various body-worn accessory use conditions expected by users. For instance, devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, must be tested for SAR compliance using a conservative minimum test separation distance not to exceed 5 mm for all use conditions required by the device.

This phone is a body-worn device that does not support hotspot mode. Therefore, only head mode and body-worn back modes are supported.

Standalone SAR test exclusion considerations

General Sequence for Determination of Procedure (exemption or evaluation) to Establish Compliance with Exposure Limits for a Single RF Source:



Mode	Frequency (MHz)	Max Target Power (dBm)	Antenna gain (dBi)	P _{Max} (dBm)	P _{Max} (mW)	Distance (mm)	P _{th} (mW)	SAR Test Exclusion?
Bluetooth	2480	3.5	0.9	3.5	2.239	< 5	2.717	Yes*

Note:

- 1. ERP= Max Target Power+ Antenna gain-2.15
- 2. P_{Max} refers to the greater value in the Max Target Power and ERP.
- 3. The formula for calculating P_{th} is given below, with distances ranging from 20cm to 40cm.

$$P_{\rm th} \; (\mathrm{mW}) = ERP_{\rm 20 \; cm} \; (\mathrm{mW}) = \begin{cases} 2040f & 0.3 \; \mathrm{GHz} \leq f < 1.5 \; \mathrm{GHz} \\ \\ 3060 & 1.5 \; \mathrm{GHz} \leq f \leq 6 \; \mathrm{GHz} \end{cases}$$

4. The formula for calculating P_{th} is given below, with distances ranging from 0.5cm to 40cm.

$$P_{\rm th} \; ({\rm mW}) = \begin{cases} ERP_{\rm 20\; cm} (d/20\; {\rm cm})^x & d \le 20\; {\rm cm} \\ \\ ERP_{\rm 20\; cm} & 20\; {\rm cm} < d \le 40\; {\rm cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (Note 3).

- 5. When the separation distance is less than 0.5cm, 0.5cm is used as the calculation distance
- 6. Yes*: Bluetooth evaluation does not require testing, which is listed to better demonstrate the SAR characteristics of the product.

SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

Report No.: SZNS220909-40985E-SA

SAR Test Data

Environmental Conditions

Temperature:	22.3-23.5 °C	22.5-23.2 °C
Relative Humidity:	50-58%	41-55 %
ATM Pressure:	101.5 kPa	101.4 kPa
Test Date:	2022/9/22	2022/9/23

Testing was performed by Seven Liang, Jack Yang, Ryse Chai.

GSM 850:

EUT	Engguener	Test	Max. Meas.	Max. Rated		1g SAR	R (W/kg)	
Position	Frequency (MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	824.2	GSM	/	/	/	/	/	/
Head Left Cheek	836.6	GSM	32.79	33.0	1.050	0.235	0.25	1#
	848.8	GSM	/	/	/	/	/	/
	824.2	GSM	/	/	/	/	/	/
Head Left Tilt	836.6	GSM	32.79	33.0	1.050	0.085	0.09	2#
	848.8	GSM	/	/	/	/	/	/
	824.2	GSM	/	/	/	/	/	/
Head Right Cheek	836.6	GSM	32.79	33.0	1.050	0.131	0.14	3#
	848.8	GSM	/	/	/	/	/	/
	824.2	GSM	/	/	/	/	/	/
Head Right Tilt	836.6	GSM	32.79	33.0	1.050	0.020	0.02	4#
	848.8	GSM	/	/	/	/	/	/
	824.2	GSM	/	/	/	/	/	/
Body Worn Back (5mm)	836.6	GSM	32.79	33.0	1.050	0.541	0.57	5#
(Sillili)	848.8	GSM	/	/	/	/	/	/
5 1 5 1	824.2	GPRS	/	/	/	/	/	/
Body Back (5mm)	836.6	GPRS	28.87	29.0	1.030	0.550	0.57	6#
(311111)	848.8	GPRS	/	/	/	/	/	/

Report No.: SZNS220909-40985E-SA

Note:

- 1. When the 1-g SAR is \leq 0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same GSM antenna while testing SAR.
- 3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
- 4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
- 5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.

PCS 1900:

EUT	Frequency	Test	Max. Meas.	Max. Rated		1g SAR	(W/kg)	
Position	(MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1850.2	GSM	/	/	/	/	/	/
Head Left Cheek	1880	GSM	30.17	30.5	1.079	0.139	0.15	7#
	1909.8	GSM	/	/	/	/	/	/
	1850.2	GSM	/	/	/	/	/	/
Head Left Tilt	1880	GSM	30.17	30.5	1.079	0.143	0.15	8#
	1909.8	GSM	/	/	/	/	/	/
	1850.2	GSM	/	/	/	/	/	/
Head Right Cheek	1880	GSM	30.17	30.5	1.079	0.465	0.50	9#
	1909.8	GSM	/	/	/	/	/	/
	1850.2	GSM	/	/	/	/	/	/
Head Right Tilt	1880	GSM	30.17	30.5	1.079	0.045	0.05	10#
	1909.8	GSM	/	/	/	/	/	/
	1850.2	GSM	30.11	30.5	1.094	0.991	1.08	11#
Body Worn Back (5mm)	1880	GSM	30.17	30.5	1.079	1.13	1.22	12#
(311111)	1909.8	GSM	30.14	30.5	1.086	0.973	1.06	13#
5 1 5 1	1850.2	GPRS	28.35	28.5	1.035	1.12	1.16	14#
Body Back (5mm)	1880	GPRS	28.40	28.5	1.023	1.16	1.19	15#
(Sillii)	1909.8	GPRS	28.42	28.5	1.019	1.10	1.12	16#

Report No.: SZNS220909-40985E-SA

Note:

- 1. When the 1-g SAR is \leq 0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same GSM antenna while testing SAR.
- 3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
- 4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
 - 5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 3DL+2UL is the worst case.

WCDMA Band 2:

EUT	Engguenay	Test	Max. Meas.	Max. Rated		1g SAR	(W/kg)	
Position	Frequency (MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1852.4	RMC	/	/	/	/	/	/
Head Left Cheek	1880	RMC	22.45	22.6	1.035	0.587	0.61	17#
	1907.6	RMC	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	/	/
Head Left Tilt	1880	RMC	22.45	22.6	1.035	0.134	0.14	18#
	1907.6	RMC	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	/	/
Head Right Cheek	1880	RMC	22.45	22.6	1.035	0.072	0.07	19#
	1907.6	RMC	/	/	/	/	/	/
	1852.4	RMC	/	/	/	/	/	/
Head Right Tilt	1880	RMC	22.45	22.6	1.035	0.076	0.08	20#
	1907.6	RMC	/	/	/	/	/	/
	1852.4	RMC	22.56	22.6	1.009	1.53	1.54	21#
Body Back (5mm)	1880	RMC	22.45	22.6	1.035	1.35	1.40	22#
(Sillin)	1907.6	RMC	22.56	22.6	1.009	1.54	1.55	23#

WCDMA Band 4:

DUT	Euggnones	Tost	Max.	Max.		1g SAR	(W/kg)	
EUT Position	Frequency (MHz)	Test Mode	Meas. Power (dBm)	Rated Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1712.4	RMC	/	/	/	/	/	/
Head Left Cheek	1732.6	RMC	21.45	21.5	1.012	0.776	0.78	24#
	1752.6	RMC	/	/	/	/	/	/
	1712.4	RMC	/	/	/	/	/	/
Head Left Tilt	1732.6	RMC	21.45	21.5	1.012	0.014	0.01	25#
	1752.6	RMC	/	/	/	/	/	/
	1712.4	RMC	/	/	/	/	/	/
Head Right Cheek	1732.6	RMC	21.45	21.5	1.012	0.210	0.21	26#
	1752.6	RMC	/	/	/	/	/	/
	1712.4	RMC	/	/	/	/	/	/
Head Right Tilt	1732.6	RMC	21.45	21.5	1.012	0.027	0.03	27#
	1752.6	RMC	/	/	/	/	/	/
D 1 D 1	1712.4	RMC	21.24	21.5	1.062	0.974	1.03	28#
Body Back (5mm)	1732.6	RMC	21.45	21.5	1.012	1.13	1.14	29#
(311111)	1752.6	RMC	21.25	21.5	1.059	1.31	1.39	30#

WCDMA Band 5:

EUT	Enggueney	Test	Max. Meas.	Max. Rated		1g SAR	(W/kg)	
Position	Frequency (MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	826.4	RMC	/	/	/	/	/	/
Head Left Cheek	836.6	RMC	22.66	23.0	1.081	0.12	0.13	31#
	846.6	RMC	/	/	/	/	/	/
	826.4	RMC	/	/	/	/	/	/
Head Left Tilt	836.6	RMC	22.66	23.0	1.081	0.039	0.04	32#
	846.6	RMC	/	/	/	/	/	/
	826.4	RMC	/	/	/	/	/	/
Head Right Cheek	836.6	RMC	22.66	23.0	1.081	0.735	0.79	33#
	846.6	RMC	/	/	/	/	/	/
	826.4	RMC	/	/	/	/	/	/
Head Right Tilt	836.6	RMC	22.66	23.0	1.081	0.041	0.04	34#
	846.6	RMC	/	/	/	/	/	/
	826.4	RMC	22.36	23.0	1.159	1.31	1.52	35#
Body Back (5mm)	836.6	RMC	22.66	23.0	1.081	1.30	1.41	36#
(Jillii)	846.6	RMC	22.35	23.0	1.161	1.27	1.48	37#

Report No.: SZNS220909-40985E-SA

Note:

- 1. When the 1-g SAR is \leq 0.8W/Kg, testing for other channels are optional.
- 2. The EUT transmit and receive through the same antenna while testing SAR.
- 3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model.
- 4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/ HSPA+ when the maximum average output of each RF channel is less than ½ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.
- 5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

LTE Band 2:

EUT	Emagnanav	Bandwidth	Test	Max. Meas.	Max. Rated		1g SAR	(W/kg)	
Position	Frequency (MHz)	(MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1860	20	1RB	/	/	/	/	/	/
Head Left Cheek	1880	20	1RB	21.20	21.5	1.072	0.254	0.27	38#
Head Left Cheek	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	20.20	21.5	1.349	0.157	0.21	39#
	1860	20	1RB	/	/	/	/	/	/
Head Left Tilt	1880	20	1RB	21.20	21.5	1.072	0.038	0.04	40#
nead Left Till	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	20.20	21.5	1.349	0.023	0.03	41#
	1860	20	1RB	/	/	/	/	/	/
Hand Diale Charle	1880	20	1RB	21.20	21.5	1.072	0.166	0.18	42#
Head Right Cheek	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	20.20	21.5	1.349	0.132	0.18	43#
	1860	20	1RB	/	/	/	/	/	/
H 4 D:-14 T:14	1880	20	1RB	21.20	21.5	1.072	0.022	0.02	44#
Head Right Tilt	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	20.20	21.5	1.349	0.019	0.03	45#
	1860	20	1RB	/	/	/	/	/	/
Body Back	1880	20	1RB	21.20	21.5	1.072	0.654	0.70	46#
(5mm)	1900	20	1RB	/	/	/	/	/	/
	1880	20	50%RB	20.20	21.5	1.349	0.551	0.74	47#

LTE Band 7:

EUT	Enggueney	Bandwidth	Test	Max. Meas.	Max. Rated		1g SAR	(W/kg)	
Position	Frequency (MHz)	(MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	2510	20	1RB	/	/	/	/	/	/
Head Left Cheek	2535	20	1RB	20.87	22.0	1.297	0.011	0.01	48#
Head Left Cheek	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	20.59	22.0	1.384	0.0061	0.01	49#
	2510	20	1RB	/	/	/	/	/	/
Hand Laft Tilt	2535	20	1RB	20.87	22.0	1.297	0.000339	0.01	50#
Head Left Tilt	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	20.59	22.0	1.384	0.000162	0.01	51#
	2510	20	1RB	/	/	/	/	/	/
Hand Diale Charle	2535	20	1RB	20.87	22.0	1.297	0.011	0.01	52#
Head Right Cheek	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	20.59	22.0	1.384	0.031	0.04	53#
	2510	20	1RB	/	/	/	/	/	/
II 4 D:-14 T:14	2535	20	1RB	20.87	22.0	1.297	0.00292	0.01	54#
Head Right Tilt	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	20.59	22.0	1.384	0.00495	0.01	55#
	2510	20	1RB	/	/	/	/	/	/
Body Back	2535	20	1RB	20.87	22.0	1.297	0.500	0.65	56#
(5mm)	2560	20	1RB	/	/	/	/	/	/
	2535	20	50%RB	20.59	22.0	1.384	0.459	0.64	57#

LTE Band 66:

EUT	Frequency	Bandwidth	Test	Max. Meas.	Max. Rated		1g SAR	R (W/kg)	
Position	(MHz)	(MHz)	Mode	Power (dBm)	Power (dBm)	Scaled Factor	Meas. SAR	Scaled SAR	Plot
	1720	20	1RB	/	/	/	/	/	/
Head Left Cheek	1745	20	1RB	20.42	22.0	1.439	0.057	0.08	58#
Head Left Cheek	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	19.57	22.0	1.750	0.043	0.08	59#
	1720	20	1RB	/	/	/	/	/	/
Head Left Tilt	1745	20	1RB	20.42	22.0	1.439	0.0081	0.01	60#
Head Left Till	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	19.57	22.0	1.750	0.00653	0.01	61#
	1720	20	1RB	/	/	/	/	/	/
Hand Dialet Charle	1745	20	1RB	20.42	22.0	1.439	0.056	0.08	62#
Head Right Cheek	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	19.57	22.0	1.750	0.060	0.10	63#
	1720	20	1RB	/	/	/	/	/	/
II 1 D:1.4 T:14	1745	20	1RB	20.42	22.0	1.439	0.014	0.02	64#
Head Right Tilt	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	19.57	22.0	1.750	0.00587	0.01	65#
	1720	20	1RB	/	/	/	/	/	/
Body Back	1745	20	1RB	20.42	22.0	1.439	0.530	0.76	66#
(5mm)	1770	20	1RB	/	/	/	/	/	/
	1745	20	50%RB	19.57	22.0	1.750	0.450	0.79	67#

Report No.: SZNS220909-40985E-SA

Note*:

^{1.} The E-UTRA Operating Band 4 is a subset of band 66, and they are same in modulation type, therefore, they were considered as one frequency band during SAR measurement, LTE Band 66 (the wide frequency range) was selected to test.

Note:

- 1. When the 1-g SAR is \leq 0.8W/Kg, testing for other channels are optional.
- 2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.

- 3. KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is > 0.5 dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg
- 4. KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is <1.45 W/kg, tests for the remaining required test channels are optional.
- 5.KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg.
- 6. KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
- 7. KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is > 0.5 dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.
- 8. Worst case SAR for 50% RB allocation is selected to be tested.

Bluetooth(EDR):

			Max.	Max.		1g	SAR (W/l	kg)	
EUT Position	Frequency (MHz)	Test Mode	Meas. Power (dBm)	Rated Power (dBm)	Scaled Factor	Duty Cycle (%)	Meas. SAR	Scaled SAR	Plot
	2402	π/4-DQPSK	3.06	3.5	1.107	76.74	0.014	0.03	68#
Head Left Cheek	2440	π/4-DQPSK	/	/	/	/	/	/	/
	2480	π/4-DQPSK	/	/	/	/	/	/	/
	2402	π/4-DQPSK	3.06	3.5	1.107	76.74	0.00908	0.01	69#
Head Left Tilt	2440	π/4-DQPSK	/	/	/	/	/	/	/
	2480	π/4-DQPSK	/	/	/	/	/	/	/
	2402	π/4-DQPSK	3.06	3.5	1.107	76.74	0.016	0.03	70#
Head Right Cheek	2440	π/4-DQPSK	/	/	/	/	/	/	/
	2480	π/4-DQPSK	/	/	/	/	/	/	/
	2402	π/4-DQPSK	3.06	3.5	1.107	76.74	0.00979	0.01	71#
Head Right Tilt	2440	π/4-DQPSK	/	/	/	/	/	/	/
	2480	π/4-DQPSK	/	/	/	/	/	/	/
	2402	π/4-DQPSK	3.06	3.5	1.107	76.74	0.016	0.03	72#
Body Back (5mm)	2440	π/4-DQPSK	/	/	/	/	/	/	/
	2480	π/4-DQPSK	/	/	/	/	/	/	/

- When the 1-g SAR is≤ 0.8W/Kg, testing for other channels are optional.
 When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
 According 2016 Oct. TCB, for SAR testing of EDR signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".

SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

Report No.: SZNS220909-40985E-SA

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

The Highest Measured SAR Configuration in Each Frequency Band

Head

SAR probe	Frequency	Freq.(MHz)	EUT Desition	Meas. SA	AR (W/kg)	Largest to Smallest
calibration point	Band	rieq.(Miriz)	EUT Position	Original	Repeated	SAR Ratio
/	/	/	/	/	/	/

Body

SAR probe	Frequency	E (MII-)	EUT D:4:	Meas. SA	AR (W/kg)	Largest to Smallest
calibration point	Band	Freq.(MHz)	EUT Position	Original	Repeated	SAR Ratio
1900MHz (1800-2000MHz)	PCS 1900	1880	Body Back	1.16	1.12	1.03
1900MHz (1800-2000MHz)	WCDMA Band 2	1907.6	Body Back	1.54	1.50	1.02
1800MHz (1700-1900MHz)	WCDMA Band 4	1752.6	Body Back	1.31	1.29	1.02
750MHz (650-850MHz)	WCDMA Band 5	826.4	Body Back	1.31	1.28	1.02

Note:

- 1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20.
- 2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
- 3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements..

Version 801: 2021-11-09 Page 60 of 68 FCC SAR 4G

SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

Simultaneous Transmission:

Description of Simultaneous Tran	smit Capabilities	
Transmitter Combination	Simultaneous?	Hotspot?
WWAN(GSM/WCDMA/LTE) + Bluetooth	√	×

Report No.: SZNS220909-40985E-SA

Simultaneous SAR test exclusion considerations:

Mode(SAR1+SAR2)	Position	Reported S	SAR(W/kg)	ΣSAR <
ividue(Siliti · Silitz)	T OSITION	SAR1	SAR2	1.6W/kg
	Head Left Cheek	0.25	0.03	0.280
	Head Left Tilt	0.09	0.01	0.100
CCM 950 Dloods at	Head Right Cheek	0.14	0.03	0.170
GSM 850+Bluetooth	Head Right Tilt	0.02	0.01	0.030
	Body Worn Back	0.57	0.03	0.600
	Body Back	0.57	0.03	0.600
	Head Left Cheek	0.15	0.03	0.180
	Head Left Tilt	0.15	0.01	0.160
PCS 1900+ Bluetooth	Head Right Cheek	0.50	0.03	0.530
PCS 1900+ Bluetooth	Head Right Tilt	0.05	0.01	0.060
	Body Worn Back	1.22	0.03	1.250
	Body Back	1.19	0.03	1.220
	Head Left Cheek	0.61	0.03	0.640
	Head Left Tilt	0.14	0.01	0.150
WCDMA Band 2+ Bluetooth	Head Right Cheek	0.07	0.03	0.100
	Head Right Tilt	0.08	0.01	0.090
	Body Back	1.55	0.03	1.580
	Head Left Cheek	0.78	0.03	0.810
	Head Left Tilt	0.01	0.01	0.020
WCDMA Band 4+ Bluetooth	Head Right Cheek	0.21	0.03	0.240
	Head Right Tilt	0.03	0.01	0.040
	Body Back	1.39	0.03	1.420
	Head Left Cheek	0.13	0.03	0.160
	Head Left Tilt	0.04	0.01	0.050
WCDMA Band 5+ Bluetooth	Head Right Cheek	0.79	0.03	0.820
	Head Right Tilt	0.04	0.01	0.050
	Body Back	1.52	0.03	1.550

Mode(SAR1+SAR2)	Position	Reported S	SAR(W/kg)	ΣSAR <
ivioue(Siliti · Siliti)	1 03111011	SAR1	SAR2	1.6W/kg
	Head Left Cheek	0.27	0.03	0.300
	Head Left Tilt	0.04	0.01	0.050
LTE Band 2+ Bluetooth	Head Right Cheek	0.18	0.03	0.210
	Head Right Tilt	0.03	0.01	0.040
	Body Back	0.74	0.03	0.770
	Head Left Cheek	0.01	0.03	0.040
	Head Left Tilt	0.01	0.01	0.020
LTE Band 7+ Bluetooth	Head Right Cheek	0.04	0.03	0.070
	Head Right Tilt	0.01	0.01	0.020
	Body Back	0.65	0.03	0.680
	Head Left Cheek	0.08	0.03	0.110
	Head Left Tilt	0.01	0.01	0.020
LTE Band 66&4+ Bluetooth	Head Right Cheek	0.10	0.03	0.130
	Head Right Tilt	0.02	0.01	0.030
	Body Back	0.79	0.03	0.820

Plots Refer to the Attachment.	
Refer to the Attachment.	
Refer to the Attachment.	

APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

Report No.: SZNS220909-40985E-SA

Measurement uncertainty evaluation for IEEE1528-2013 SAR test

Source of uncertainty	Tolerance/ uncertaint y ± %	Probability distributio n	Divisor	ci (1 g)	ci (10 g)	Standard uncertai nty ± %, (1 g)	Standard uncertai nty ± %, (10 g)
		Measurement	system				
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0	0	0.0	0.0
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	R	$\sqrt{3}$	1	1	2.7	2.7
Detection limits	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
Integration time	0.0	R	$\sqrt{3}$	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	$\sqrt{3}$	1	1	0.6	0.6
RF ambient conditions–reflections	1.0	R	√3	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	√3	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	$\sqrt{3}$	1	1	3.9	3.9
Post-processing	2.0	R	$\sqrt{3}$	1	1	1.2	1.2
		Test sample	related			<u> </u>	<u>. </u>
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Device holder uncertainty	6.3	N	1	1	1	6.3	6.3
Drift of output power	5.0	R	$\sqrt{3}$	1	1	2.9	2.9
		Phantom and	set-up				
Phantom uncertainty (shape and thickness tolerances)	4.0	R	$\sqrt{3}$	1	1	2.3	2.3
Liquid conductivity target)	5.0	R	√3	0.64	0.43	1.8	1.2
Liquid conductivity meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity target)	5.0	R	√3	0.6	0.49	1.7	1.4
Liquid permittivity meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Combined standard uncertainty		RSS				12.2	12.0
Expanded uncertainty 95 % confidence interval)						24.3	23.9

Measurement uncertainty evaluation for IEC 62209-2 SAR test

Source of uncertainty	Tolerance/ uncertai nty ± %	Probability distributio n	Divisor	ci (1 g)	ci (10 g)	Standard uncertai nty ± %, (1 g)	Standard uncertai nty ± %, (10 g)
		Measurement	system			<u> </u>	<u> </u>
Probe calibration	6.55	N	1	1	1	6.6	6.6
Axial Isotropy	4.7	R	√3	1	1	2.7	2.7
Hemispherical Isotropy	9.6	R	√3	0	0	0.0	0.0
Linearity	4.7	R	√3	1	1	2.7	2.7
Modulation Response	0.0	R	√3	1	1	0.0	0.0
Detection limits	1.0	R	√3	1	1	0.6	0.6
Boundary effect	1.0	R	√3	1	1	0.6	0.6
Readout electronics	0.3	N	1	1	1	0.3	0.3
Response time	0.0	R	√3	1	1	0.0	0.0
Integration time	0.0	R	√3	1	1	0.0	0.0
RF ambient conditions – noise	1.0	R	√3	1	1	0.6	0.6
RF ambient conditions-reflections	1.0	R	√3	1	1	0.6	0.6
Probe positioner mech. Restrictions	0.8	R	$\sqrt{3}$	1	1	0.5	0.5
Probe positioning with respect to phantom shell	6.7	R	√3	1	1	3.9	3.9
Post-processing	2.0	R	√3	1	1	1.2	1.2
		Test sample	related				
Device holder Uncertainty	6.3	N	1	1	1	6.3	6.3
Test sample positioning	2.8	N	1	1	1	2.8	2.8
Power scaling	4.5	R	√3	1	1	2.6	2.6
Drift of output power	5.0	R	√3	1	1	2.9	2.9
		Phantom and	l set-up				
Phantom uncertainty (shape and thickness tolerances)	4.0	R	√3	1	1	2.3	2.3
Algorithm for correcting SAR for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.1	0.9
Liquid conductivity (meas.)	2.5	N	1	0.64	0.43	1.6	1.1
Liquid permittivity (meas.)	2.5	N	1	0.6	0.49	1.5	1.2
Temp. unc Conductivity	1.7	R	√3	0.78	0.71	0.8	0.7
Temp. unc Permittivity	0.3	R	√3	0.23	0.26	0.0	0.0
Combined standard uncertainty		RSS				12.2	12.1
Expanded uncertainty 95 % confidence interval)						24.5	24.2

Shenzhen Accurate Technology Co., Ltd.	Report No.: SZNS220909-40985E-SA			
APPENDIX B EUT TEST POSITION PH	OTOS			
Please Refer to the Attachment.				

Version 801: 2021-11-09 Page 66 of 68 FCC SAR 4G

Shenzhen Accurate Technology Co., Ltd.	Report No.: SZNS220909-40985E-SA			
APPENDIX C PROBE CALIBRATION CERTIFICATES Please Refer to the Attachment.				

Version 801: 2021-11-09 Page 67 of 68 FCC SAR 4G

Shenzhen Accurate Technology Co., Ltd.	Report No.: SZNS220909-40985E-S			
APPENDIX D DIPOLE CALIBRATION CERTIFICATES				
Please Refer to the Attachment.				
**** END OF	REPORT *****			

Version 801: 2021-11-09 Page 68 of 68 FCC SAR 4G