

RF exposure Estimation

1. Introduction

Product	RADIO V_METER
Model no	MEVA0088
FCC ID:	2A8QHMEVA0088
Ratings	Rated Input: 12V/24VDC
RF Transmission Frequency (MHz)	2402MHz-2480 MHz
Modulation	GFSK
Antenna Type	Integrated antenna
Max Antenna Gain	-0.58dBi
Description of the EUT	The Equipment is a RADIO V_METER, which contains BLE function inside
Reference report	68.950.22.0951.01

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06, Mobile Portable RF Exposure, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

For 8DPSK Modulation 2480MHz

Radiated Power + tune up tolerance = 0.70 mW

Distance = 5 mm

$f = 2.48 \text{ GHz}$

$$[0.70/5] * \text{SQRT}(2.48) = 0.22$$

$0.22 \leq 3.0$

Therefore, excluded from SAR testing.

TUV SUD China, Shenzhen Branch

Reviewed by:

Prepared By:



John Zhi/ EMC Project Manager

Date: 2023-02-13



Grace Gao/EMC Project Engineer

Date: 2023-02-13