

RF EXPOSURE

Test Report

Report No. : MTi250506019-0201E2

Date of issue : 2025-07-10

Applicant : Shenzhen Rihuida Electronics Co., Ltd.

Product : LED Light

Model(s) : SLS2323RGB

FCC ID : 2A8R6-SLS2323RGB

Shenzhen Microtest Co., Ltd.

TEST REPORT

Report No.: MTI250506019-0201E2

Table of contents

1	RF EXPOSURE EVALUATION	4
2	Measurement Result	5

TEST REPORT

Report No.: MTI250506019-0201E2

Test Result Certification	
Applicant	Shenzhen Rihuida Electronics Co., Ltd.
Applicant Address	The fourth building&the 02,03 and 04 floors of the third building of Fuzhong Industrial Park, Huaide Community,Fuyong Street, Bao'an District, Shenzhen, China
Manufacturer	Shenzhen Rihuida Electronics Co., Ltd.
Manufacturer Address	The fourth building&the 02,03 and 04 floors of the third building of Fuzhong Industrial Park, Huaide Community,Fuyong Street, Bao'an District, Shenzhen, China
Product description	
Product name	LED Light
Trademark	N/A
Model name	SLS2323RGB
Series Model(s)	N/A
Standards	47 CFR Part 2.1091
Test method	KDB 447498 D01 v06
Testing Information	
Date of test	2025-05-13 to 2025-06-28
Test Result	Pass
Prepared by:	Letter Lan
Reviewed by:	David Lee
Approved by:	Lewis Lian

1 RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1415926$

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2 Measurement Result

BLE:

Operation Frequency: 2402-2480MHz,
Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna

Antenna gain: 0.55dBi

R=20cm

mW=10^(dBm/10)

Antenna gain Numeric=10^(dBi/10)= 10^(0.55/10)=1.14

BLE:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)	
				tune-up power (dBm)	Gain (mW)				
		(dBm)		(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK-1M	-0.04	0±1	1	1.259	0.55	1.14	0.0003	1
2440		-0.70	0±1	1	1.259	0.55	1.14	0.0003	1
2480		-0.64	0±1	1	1.259	0.55	1.14	0.0003	1

Conclusion:

Simultaneous:

For the max result: 0.003≤ 1.0 test exclusion threshold, No SAR is required.

Statement

1. This report is invalid without the seal and signature of the laboratory.
2. The test results of this report are only responsible for the samples submitted. Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

***** END OF REPORT *****