



3 Activate a Ediag Mini Device Click on "Activate" to open the activation page, You need to input the serial number and an 8-digit activation code, to complete the process of activation and account binding for your Ediag Mini device. Activation



Insert the Ediag Mini Device into the OBD port in your vehicle

Usually, the OBDII port is located under the dashboard, above the pedal on the driver's side. Here are the 5 common positions for the OBDI port (as shown in the figure right). Insert the Ediag Mini device, there will be a green light which indicates the device is powered on.



5 Bluetooth Connection

Open the Ediag App, it will automatically search for activated devices. Select your device and connect to it via Bluetooth in the App.Note: Please do not directly connect the device to your phone via Bluetooth settings in your phone OS. Make sure to pair your device within the App



6 Download Diagnostics Software

In the "Diagnostics" interface of the App, you will need to download the corresponding diagnostics software when first time perform "All System Diagnostic" and "OBD Functions". And there is no need to download again next time.



Start to Use Your Ediag Mini Device

After the bluetooth connection, you can use all the functions of your Ediag Mini device, such as:All Systems Diagnostics, Maintenance & Service Functions, OBDII Diagnostics,



8 FAQ

- Q: What do the different lights on Ediag Mini indicate? A: There are four different lights on Ediag Mini: Continuous Red Light: Ediag Mini device is powered on. Continuous Blue Light: Bluetooth is connected Flashing Blue Light: Bluetooth is in communication.

 Q: Why do I need to download the diagnostics software after
- downloading the App?
- A: Due to a variety of vehicle manufacturers on the market, different vehicle manufacturers require corresponding diagnostics software. Therefore, Ediag Mini will recognize the vehicle manufacturer first while diagnosing, then it will download the corresponding diagnostics software to work.

 Q: What vehicles can Ediag Mini diagnose?
- A: Ediag Mini is compatible with all vehicles supporting OBDII/EOBD protocols after 1996. Note: Depending on your vehicle, the diagnostics software size
- varies and download speed is different as well. When first downloading the diagnostics software, it might require a good network connection.
- network connection.

 Q: What are the special functions of Ediag Mini?

 A: Ediag Mini supports 15 special functions, including: AFS
 RESET, Elec.Throttle RLRN, Immobilizer/Keys, INJECTOR, RESET

BRAKE, RESET OIL, RESET SAS, RESETBLEED, RESETBMS, RESETBOX, RESETDPF, RESETEGR, RESETTPMS, SUNROOF, RESET SUS. According to different vehicle manufacturers' diagnostics software, there will be more special functions to come.

- O: Does Ediag Mini need firmware upgrade?
 A: Yes, it does. When the Ediag Mini device is connected via Bluetooth to your smartphone, it will automatically check if the firmware on your
- device is the latest version. If it's not, it will upgrade automatically.

 Q: What smartphones can download Ediag App?

 A: Ediag App supports smartphones with Android 5.0 and above, IOS
- 9.0 and above. It cannot be used on PC with WINDOWS system.
- Q: Can the same App account bind with multiple devices?

 A: Yes, you can set them up in the App.
- 9 Warranty Card
- 1. In addition to the legal withdrawal right, you benefit from a 30-day money back guarantee. The device is also guaranteed for a period of
- 2. Before replacement, please ensure complete packaging; Before replacement/repair, please call the service number to get the
- shipping address.
 3. Product warranty starting date is based on the payment date. Service Line: 0755-23445106
- Customer Service Email: support@kingbolen.com
- Official Website: www.kingbolen.com Youtube: Kingbolen auto scanner center
- Facebook: @kingbolen.fans
- Instagram: @kingbolen.fans



ΕN

FCC Warning

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -Reorient or relocate the receiving antenna.
- -Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
 - -Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

IC Warning

This device complies with Industry Canada's licence-exempt RSSs. Operation is subject to the following two conditions:

- (1) This device may not cause interference; and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.

Cet appareil est conforme aux CNR exemptes de licence d'Industrie Canada . Son fonctionnement est soumis aux deux conditions suivantes :

- (1) Ce dispositif ne peut causer d'interférences ; et
- (2) Ce dispositif doit accepter toute interférence, y compris les interférences qui peuvent causer un mauvais fonctionnement de l'appareil.

Le dispositif a été conçu pour répondre à la demande générale de radioexposition.