

# Test Report C-3614D

---

<b>Equipment Under Test:</b>	Voltron20x
<b>Requirement(s):</b>	FCC 1.1310 ISED RSS-102
<b>Test Date(s):</b>	8/30/2022
<b>Prepared for:</b>	Husqvarna Attn: Matt Albinger 9335 Harris Corners Parkway Suite Charlotte, NC 28269

---

**Report Issued by:** Anthony Smith, EMC Engineering Specialist

Signature: 

Date: 11/16/2022

**Report Reviewed by:** Adam Alger, Laboratory Manager

Signature: 

Date: 11/16/2022

**Report Constructed by:** Anthony Smith, EMC Engineering Specialist

Signature: 

Date: 11/16/2022

*This test report may not be reproduced, except in full, without approval of Laird Connectivity LLC*

Company: Husqvarna	Page 1 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## CONTENTS

Contents.....	2
Laird Connectivity Test Services in Review .....	3
1    Test Report Summary .....	4
2    Client Information.....	5
2.1    Equipment Under Test (EUT) Information .....	5
2.2    Product Description .....	5
2.3    Modifications Incorporated for Compliance.....	5
2.4    Deviations and Exclusions from Test Specifications .....	5
2.5    Additional Information.....	5
3    References .....	6
4    Uncertainty Summary .....	7
5    Test Data .....	8
5.1    Antenna Port Conducted Emissions.....	8
6    FCC 1-G SAR Test Exclusion Calculations .....	11
6.1    Power Calculations.....	11
6.2    Distance.....	11
6.3    SAR Test Exclusion Calculation.....	11
6.4    Result .....	11
7    IC Exemption Calculation for Routine SAR Evaluation.....	12
7.1    Power Calculations.....	12
7.2    Distance.....	12
7.3    Exemption Limits.....	12
7.4    SAR Test Exclusion Calculation.....	12
7.5    Result .....	12
8    Revision History .....	13

Company: Husqvarna	Page 2 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## Laird Connectivity Test Services in Review

The Laird Connectivity LLC laboratory located at W66 N220 Commerce Court Cedarburg, Wisconsin, 53012 USA is recognized through the following organizations:



### A2LA – American Association for Laboratory Accreditation

*Accreditation based on ISO/IEC 17025:2017 with Electrical (EMC) Scope*

*A2LA Certificate Number: 1255.01*

*Scope of accreditation includes all test methods listed herein unless otherwise noted*

---



### Federal Communications Commission (FCC) – USA

*Accredited Test Firm Registration Number: 953492*

*Recognition of two 3 meter Semi-Anechoic Chambers*

---



Government  
of Canada

### Innovation, Science and Economic Development Canada

*Accredited U.S. Identification Number: US0218*

*Recognition of two 3 meter Semi-Anechoic Chambers*

Company: Husqvarna	Page 3 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 1 TEST REPORT SUMMARY

During **8/30/2022** the Equipment Under Test (EUT), **Voltron**, as provided by **Husqvarna** was tested to the following requirements:

Requirements	Description	Method	Result
FCC: 1.1310 IC: RSS-102	Radiofrequency Radiation Exposure Limits	Distance $\leq$ 5mm 1g-SAR	Reported

### Notice:

The results relate only to the item tested as configured and described in this report. Any additional configurations, modes of operation, or modifications made to the equipment under test after the specified test date(s) are at the decision of the client and may not apply to the data seen in this test report.

The decision rule for Pass / Fail assessment to the specification or standard listed in this test report has been agreed upon by the client and laboratory to be as follows:

Measurement Type	Rule
Emissions – Amplitude	1 dB below specified limit
Emissions – Frequency	1% less than the specification
Immunity	Tested at specified level

Company: Husqvarna	Page 4 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 2 CLIENT INFORMATION

Company Name	Husqvarna
Contact Person	Matt Albinger
Address	9335 Harris Corners Parkway Suite 500 Charlotte, NC 28269

### 2.1 Equipment Under Test (EUT) Information

*The following information has been supplied by the client*

Product Name	Voltron20x
Model Number	599426001
Serial Number	Engineering Sample
FCC ID	2A8U7-VLTR01
IC ID	23218-VLTR01

### 2.2 Product Description

Connect to mobile devices and enable use of Husqvarna Connect app.

### 2.3 Modifications Incorporated for Compliance

None noted at time of test

### 2.4 Deviations and Exclusions from Test Specifications

None noted at time of test

### 2.5 Additional Information

Channels used: 37 (Low 2402 MHz), 17 (Mid 2440 MHz), 39 (High 2480 MHz). Device powered with +12VDC via DC Variable Power Supply. Device radio controlled by HCI\_Tester (Version 3.0.0.37) software through a USB-UART FTDI cable from a laptop computer.

Company: Husqvarna	Page 5 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

### 3 REFERENCES

Publication	Edition	Date	AMD 1
FCC eCFR	-	2022	-
RSS-102	5	2015	2021
KDB 447498	-	2015	-

Company: Husqvarna	Page 6 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 4 UNCERTAINTY SUMMARY

Using the guidance of the following publications the calculated measurement uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of  $k = 2$ .

References
CISPR 16-4-1
CISPR 16-4-2
CISPR 32
ANSI C63.23
A2LA P103
A2LA P103c
ETSI TR 100-028

Measurement Type	Configuration	Uncertainty $\pm$
Radiated Emissions	Biconical Antenna	5.0 dB
Radiated Emissions	Log Periodic Antenna	5.3 dB
Radiated Emissions	Horn Antenna	4.7 dB
AC Line Conducted Emissions	Artificial Mains Network	3.4 dB
Telecom Conducted Emissions	Asymmetric Artificial Network	4.9 dB
Disturbance Power Emissions	Absorbing Clamp	4.1 dB
Radiated Immunity	3 Volts/meter	2.2 dB
Conducted Immunity	CDN/EM/BCI	2.4/3.5/3.4 dB
EFT Burst/Surge	Peak pulse voltage	164 volts
ESD Immunity	15 kV level	1377 Volts

Parameter	ETSI U.C. $\pm$	U.C. $\pm$
Radio Frequency, from F0	$1 \times 10^{-7}$	$0.55 \times 10^{-7}$
Occupied Channel Bandwidth	5 %	2 %
RF conducted Power (Power Meter)	1.5 dB	1.2 dB
RF conducted emissions (Spectrum Analyzer)	3.0 dB	1.7 dB
All emissions, radiated	6.0 dB	5.3 dB
Temperature	1° C	0.65° C
Humidity	5 %	2.9 %
Supply voltages	3 %	1 %


Company: Husqvarna	Page 7 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 5 TEST DATA

### 5.1 Antenna Port Conducted Emissions

<b>Description of Measurement</b>	<p>The direct measurement of emissions at the antenna port of the EUT is achieved by use of a RF connection to a spectrum analyzer or power meter.</p> <p>The cable and attenuator factors are loaded into the analyzer or power meter allowing for direct measurement readings without the need for further corrections.</p>
<b>Example Calculations</b>	<p>Measurement (dBm) + Cable factor (dB) + External Attenuator (dB) = Corrected Reading (dBm)</p> <p>Margin (dB) = Limit (dBm) – Corrected Reading (dBm)</p>

#### Block Diagram



#### Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960172	Cable	A.H. Systems, Inc.	SAC-26G-1	387	3/22/2022	3/22/2023	Active Verification
EE 960087	Analyzer - Spectrum	Agilent	N9010A	MY53400296	4/12/2022	4/12/2023	Active Calibration

Company: Husqvarna	Page 8 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

### 5.1.1 Peak Output Power

<b>Operator</b>	Anthony Smith	<b>QA</b>	Adam Alger
<b>Temperature</b>	21.6°C	<b>R.H. %</b>	51.70%
<b>Test Date</b>	8/30/2022	<b>Location</b>	Conducted RF Bench
<b>Requirement</b>	FCC: 15.247 (b)(3) IC: RSS-247 5.4 (d)	<b>Method</b>	ANSI C63.10 §11.9

**Limits:** 30 dBm

#### Test Parameters

<b>Frequency</b>	2402, 2440, 2480 MHz	<b>Setup</b>	Conducted
<b>RBW</b>	3 MHz	<b>VBW</b>	50 MHz
<b>Detector(s)</b>	Max Peak Hold	<b>Sweep Time</b>	Auto

#### EUT Parameters


<b>Input Power</b>	12VDC	<b>Mode</b>	BLE Tx
<b>Frequency</b>	2402, 2440, 2480 MHz	<b>Channel</b>	37, 17, 39
<b>Data Rate</b>	BLE 1 Mbps		

Company: Husqvarna	Page 9 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## Data Table

Channel	Peak Output Power (dBm)	Limit (dBm)	Margin (dB)
37	1.0	30	29.0
17	1.1	30	28.9
39	0.8	30	29.2

## Plots



Company: Husqvarna	Page 10 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 6 FCC 1-G SAR TEST EXCLUSION CALCULATIONS

### 6.1 Power Calculations

Max Power of Channel = 1.1 dBm

Tune Up Tolerance = 1 dB

Total Channel Power = 2.1 dBm = 1.6 mW = 2 mW

### 6.2 Distance

≤5 mm

### 6.3 SAR Test Exclusion Calculation

$[(\text{Maximum power of channel, including tune-up tolerance, mW}) / (\text{Minimum test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3 \text{ for 1-g SAR}$

Where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The value 3.0 is referred to as numeric thresholds

$$\left(\frac{2 \text{ mW}}{5 \text{ mm}}\right) \times (\sqrt{2.48}) \leq 3.0$$

$$0.4 \times 1.562 \leq 3.0$$

$$0.6 \leq 3.0$$

### 6.4 Result

The EUT is excluded from routine SAR testing as 0.6 is less than 3.0.

Company: Husqvarna	Page 11 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 7 IC EXEMPTION CALCULATION FOR ROUTINE SAR EVALUATION

### 7.1 Power Calculations

Max Power of Channel = 1.1 dBm

Tune Up Tolerance = 1 dB

Peak Antenna Gain = 3.5 dBi

Total Channel Power = 5.6 dBm = 3.6 mW EIRP

### 7.2 Distance

≤ 5 mm

### 7.3 Exemption Limits

**Table 1: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>**

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

#### Interpolated Limit at 2480 MHz

$$4 + (2480 - 2450) \times \left( \frac{2 - 4}{3500 - 2450} \right) = 3.9$$

At 2480 and 5 mm the exemption limit is 3.9 mW

### 7.4 SAR Test Exclusion Calculation

3.6 mW ≤ 3.9 mW

### 7.5 Result

The EUT is excluded from routine SAR testing at ≤5 mm as 3.6 mW is less than 3.9 mW.

Company: Husqvarna	Page 12 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample

## 8 REVISION HISTORY

Version	Date	Notes	Person
0.0	11/16/2022	Initial Draft	Anthony Smith

**END OF REPORT**

Company: Husqvarna	Page 13 of 13	Name: Voltron20x
Report: TR3614D		Model: 599426001
Quote: 319494		Serial: Engineering Sample