



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

TEST REPORT

FCC PART 15 SUBPART C 15.247 & RSS-247

Report Reference No.....: CTA23061600301

FCC ID.: 2A8UJ-LZ1201

IC.: 30817-LZ1201

Compiled by

(position+printed name+signature) ...: File administrators Kevin Liu

Kevin Liu

Kevin Liu

Supervised by

(position+printed name+signature) ...: Project Engineer Kevin Liu

Approved by

(position+printed name+signature) ...: RF Manager Eric Wang

Eric Wang

Date of issue.....: June 20, 2023

Testing Laboratory Name: **Shenzhen CTA Testing Technology Co., Ltd.**

Address: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: **SHENZHEN GIANT LIGHTING CO., LTD**

Address: 3rd Floor, Building C, No. 6 Private 2nd Road, Shilong Community, Shiyan Street, Bao'an District, Shenzhen, China

Test specification

47 CFR FCC Part 15 Subpart C 15.247

Standard: **RSS-247 Issue 2, February 2017**

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: **Intelligent floor lamp**

Trade Mark: **N/A**

Manufacturer: **SHENZHEN GIANT LIGHTING CO., LTD**

Model/Type reference(HVIN).....: **LZ-1201000A**

Listed Models(HVIN): **TH01**

Modulation: **GFSK, $\Pi/4$ DQPSK**

Frequency.....: **From 2402MHz to 2480MHz**

Rating: **DC12V from adapter**

Result: **PASS**

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

TEST REPORT

Equipment under Test : Intelligent floor lamp

Model /Type(HVIN) : LZ-1201000A

Listed Models(HVIN) : TH01

Applicant : **SHENZHEN GIANT LIGHTING CO., LTD**

Address : 3rd Floor, Building C, No. 6 Private 2nd Road, Shilong Community, Shiyan Street, Bao'an District, Shenzhen, China

Manufacturer : **SHENZHEN GIANT LIGHTING CO., LTD**

Address : 3rd Floor, Building C, No. 6 Private 2nd Road, Shilong Community, Shiyan Street, Bao'an District, Shenzhen, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1</u>	<u>TEST STANDARDS</u>	4
<u>2</u>	<u>SUMMARY</u>	5
2.1	General Remarks	5
2.2	Product Description	5
2.3	Equipment Under Test	5
2.4	Short description of the Equipment under Test (EUT)	5
2.5	EUT operation mode	5
2.6	Block Diagram of Test Setup	6
2.7	Related Submittal(s) / Grant (s)	6
2.8	Modifications	6
<u>3</u>	<u>TEST ENVIRONMENT</u>	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Environmental conditions	7
3.4	Summary of measurement results	8
3.5	Statement of the measurement uncertainty	8
3.6	Equipments Used during the Test	9
<u>4</u>	<u>TEST CONDITIONS AND RESULTS</u>	10
4.1	AC Power Conducted Emission	10
4.2	Radiated Emission	13
4.3	Maximum Peak Output Power	19
4.4	20dB Bandwidth	20
4.5	Occupied Bandwidth	23
4.6	Frequency Separation	26
4.7	Number of hopping frequency	28
4.8	Time of Occupancy (Dwell Time)	30
4.9	Out-of-band Emissions	33
4.10	Pseudorandom Frequency Hopping Sequence	39
4.11	Antenna Requirement	40
<u>5</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	41
<u>6</u>	<u>PHOTOS OF THE EUT</u>	42

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[RSS-247-Issue 2](#): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

[RSS-Gen Issue 5](#): General Requirements for Compliance of Radio Apparatus

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	June 08, 2023
Testing commenced on	:	June 19, 2023
Testing concluded on	:	June 20, 2023

2.2 Product Description

Product Name:	Intelligent floor lamp
Model/(HVIN):	LZ-1201000A
Power supply:	DC 12V From adapter
Hardware version:	ZXZN-3016K3R24G24-W-V10
Software version:	V1.0
Adapter information:	Model: GKYZY0100120US1 Input:100-240V~ 50/60Hz 0.5A MAX. Output:12V---1A 12.0W
Testing sample ID:	CTA230616003-1# (Engineer sample) CTA230616003-2# (Normal sample)

Bluetooth :

Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, π/4DQPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	0 dBi

Note:Antenna gain is provide by the manufacturer.

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/>	230V / 50 Hz	<input type="radio"/>	120V / 60Hz
		<input type="radio"/>	12 V DC	<input type="radio"/>	24 V DC
		<input checked="" type="radio"/>	Other (specified in blank below)		

DC 12V From adapter

2.4 Short description of the Equipment under Test (EUT)

This is an Intelligent floor lamp.

For more details, refer to the user's manual of the EUT.

2.5 EUT operation mode


The Applicant provides communication tools software(FCC_assist_1.0.2.2) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

Operation Frequency:

Channel	Frequency (MHz)
00	2402
01	2403
:	:
38	2440
39	2441
40	2442
:	:
77	2479
78	2480

2.6 Block Diagram of Test Setup**2.7 Related Submittal(s) / Grant (s)**

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C and RSS-247.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

IC Registered No.: 27890

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	24 ° C
Humidity:	46 %
Atmospheric pressure:	950-1050mbar

AC Power Conducted Emission:

Temperature:	25 ° C
Humidity:	47 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	46 %
Atmospheric pressure:	950-1050mbar

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

3.4 Summary of measurement results

Test Specification clause	Test case	Test Sample	Test Mode	Test Channel	Recorded In Report	Test result	
§15.247(a)(1) RSS-247 5.1 (b)	Carrier Frequency separation	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest	Compliant
§15.247(a)(1) RSS-247 5.1 (d)	Number of Hopping channels	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Full	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Full	Compliant
§15.247(a)(1) RSS-247 5.1 (d)	Time of Occupancy (dwell time)	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Middle	Compliant
§15.247(a)(1) RSS-247 5.1 (a)	Spectrum bandwidth of a FHSS system20dB bandwidth	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(b)(1) RSS-247 5.1 (b)	Maximum output power	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d) RSS-247 5.5	Band edge compliance conducted	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	Compliant
§15.205 RSS-Gen 8.10	Band edge compliance radiated	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d) RSS-247 5.5	TX spurious emissions conducted	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d) §15.209(a) RSS-Gen 8.9	TX spurious emissions Radiated above 1GHz	CTA23061600 3-1#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d) §15.209(a) RSS-Gen 8.9	TX spurious Emissions radiated Below 1GHz	CTA23061600 3-2#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Middle	Compliant
§15.207(a) RSS-Gen 8.8	Conducted Emissions 9KHz-30 MHz	CTA23061600 3-2#	GFSK Π/4DQPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Middle	Compliant

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18~40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	CTA-308	2022/08/03	2023/08/02
LISN	R&S	ENV216	CTA-314	2022/08/03	2023/08/02
EMI Test Receiver	R&S	ESPI	CTA-307	2022/08/03	2023/08/02
EMI Test Receiver	R&S	ESCI	CTA-306	2022/08/03	2023/08/02
Spectrum Analyzer	Agilent	N9020A	CTA-301	2022/08/03	2023/08/02
Spectrum Analyzer	R&S	FSP	CTA-337	2022/08/03	2023/08/02
Vector Signal generator	Agilent	N5182A	CTA-305	2022/08/03	2023/08/02
Analog Signal Generator	R&S	SML03	CTA-304	2022/08/03	2023/08/02
Universal Radio Communication	CMW500	R&S	CTA-302	2022/08/03	2023/08/02
Temperature and humidity meter	Chigo	ZG-7020	CTA-326	2022/08/03	2023/08/02
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	CTA-310	2021/08/07	2024/08/06
Horn Antenna	Schwarzbeck	BBHA 9120D	CTA-309	2021/08/07	2024/08/06
Loop Antenna	Zhinan	ZN30900C	CTA-311	2021/08/07	2024/08/06
Horn Antenna	Beijing Hangwei Dayang	OBH100400	CTA-336	2021/08/07	2024/08/06
Amplifier	Schwarzbeck	BBV 9745	CTA-312	2022/08/03	2023/08/02
Amplifier	Taiwan chengyi	EMC051845B	CTA-313	2022/08/03	2023/08/02
Directional coupler	NARDA	4226-10	CTA-303	2022/08/03	2023/08/02
High-Pass Filter	XingBo	XBLBQ-GTA18	CTA-402	2022/08/03	2023/08/02
High-Pass Filter	XingBo	XBLBQ-GTA27	CTA-403	2022/08/03	2023/08/02
Automated filter bank	Tonscend	JS0806-F	CTA-404	2022/08/03	2023/08/02
Power Sensor	Agilent	U2021XA	CTA-405	2022/08/03	2023/08/02
Amplifier	Schwarzbeck	BBV9719	CTA-406	2022/08/03	2023/08/02

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. All modes of GFSK, $\pi/4$ DQPSK were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Power supply:	DC 12V from Adapter AC 120V/60Hz	Polarization	L																																																																																				
Test Graph																																																																																							
Final Data List <table border="1"> <thead> <tr> <th>NO.</th> <th>Freq. [MHz]</th> <th>Factor [dB]</th> <th>QP Reading[dB μV]</th> <th>QP Value [dBμV]</th> <th>QP Limit [dBμV]</th> <th>QP Margin [dB]</th> <th>AV Reading [dBμV]</th> <th>AV Value [dBμV]</th> <th>AV Limit [dBμV]</th> <th>AV Margin [dB]</th> <th>Verdict</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.5595</td> <td>10.50</td> <td>37.83</td> <td>48.33</td> <td>56.00</td> <td>7.67</td> <td>29.59</td> <td>40.09</td> <td>46.00</td> <td>5.91</td> <td>PASS</td> </tr> <tr> <td>2</td> <td>1.122</td> <td>10.50</td> <td>35.36</td> <td>45.86</td> <td>56.00</td> <td>10.14</td> <td>22.04</td> <td>32.54</td> <td>46.00</td> <td>13.46</td> <td>PASS</td> </tr> <tr> <td>3</td> <td>3.048</td> <td>10.50</td> <td>28.32</td> <td>38.82</td> <td>56.00</td> <td>17.18</td> <td>17.94</td> <td>28.44</td> <td>46.00</td> <td>17.56</td> <td>PASS</td> </tr> <tr> <td>4</td> <td>5.622</td> <td>10.50</td> <td>32.12</td> <td>42.62</td> <td>60.00</td> <td>17.38</td> <td>14.52</td> <td>25.02</td> <td>50.00</td> <td>24.98</td> <td>PASS</td> </tr> <tr> <td>5</td> <td>12.0075</td> <td>10.50</td> <td>38.08</td> <td>48.58</td> <td>60.00</td> <td>11.42</td> <td>20.67</td> <td>31.17</td> <td>50.00</td> <td>18.83</td> <td>PASS</td> </tr> <tr> <td>6</td> <td>17.007</td> <td>10.50</td> <td>32.75</td> <td>43.25</td> <td>60.00</td> <td>16.75</td> <td>15.54</td> <td>26.04</td> <td>50.00</td> <td>23.96</td> <td>PASS</td> </tr> </tbody> </table> <p>Note: 1). QP Value (dBμV) = QP Reading (dBμV) + Factor (dB) 2). Factor (dB) = insertion loss of LISN (dB) + Cable loss (dB) 3). QP Margin (dB) = QP Limit (dBμV) - QP Value (dBμV) 4). AV Margin (dB) = AV Limit (dBμV) - AV Value (dBμV)</p>				NO.	Freq. [MHz]	Factor [dB]	QP Reading[dB μ V]	QP Value [dB μ V]	QP Limit [dB μ V]	QP Margin [dB]	AV Reading [dB μ V]	AV Value [dB μ V]	AV Limit [dB μ V]	AV Margin [dB]	Verdict	1	0.5595	10.50	37.83	48.33	56.00	7.67	29.59	40.09	46.00	5.91	PASS	2	1.122	10.50	35.36	45.86	56.00	10.14	22.04	32.54	46.00	13.46	PASS	3	3.048	10.50	28.32	38.82	56.00	17.18	17.94	28.44	46.00	17.56	PASS	4	5.622	10.50	32.12	42.62	60.00	17.38	14.52	25.02	50.00	24.98	PASS	5	12.0075	10.50	38.08	48.58	60.00	11.42	20.67	31.17	50.00	18.83	PASS	6	17.007	10.50	32.75	43.25	60.00	16.75	15.54	26.04	50.00	23.96	PASS
NO.	Freq. [MHz]	Factor [dB]	QP Reading[dB μ V]	QP Value [dB μ V]	QP Limit [dB μ V]	QP Margin [dB]	AV Reading [dB μ V]	AV Value [dB μ V]	AV Limit [dB μ V]	AV Margin [dB]	Verdict																																																																												
1	0.5595	10.50	37.83	48.33	56.00	7.67	29.59	40.09	46.00	5.91	PASS																																																																												
2	1.122	10.50	35.36	45.86	56.00	10.14	22.04	32.54	46.00	13.46	PASS																																																																												
3	3.048	10.50	28.32	38.82	56.00	17.18	17.94	28.44	46.00	17.56	PASS																																																																												
4	5.622	10.50	32.12	42.62	60.00	17.38	14.52	25.02	50.00	24.98	PASS																																																																												
5	12.0075	10.50	38.08	48.58	60.00	11.42	20.67	31.17	50.00	18.83	PASS																																																																												
6	17.007	10.50	32.75	43.25	60.00	16.75	15.54	26.04	50.00	23.96	PASS																																																																												



Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Reading[dB μV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	A/V Reading [dBμV]	A/V Value [dBμV]	A/V Limit [dBμV]	A/V Margin [dB]	Verdict
1	0.5505	10.50	40.80	51.30	56.00	4.70	21.83	32.33	46.00	13.67	PASS
2	1.113	10.50	35.47	45.97	56.00	10.03	16.95	27.45	46.00	18.55	PASS
3	2.967	10.50	28.55	39.05	56.00	16.95	13.04	23.54	46.00	22.46	PASS
4	5.622	10.50	30.87	41.37	60.00	18.63	17.06	27.56	50.00	22.44	PASS
5	11.5215	10.50	41.05	51.55	60.00	8.45	21.26	31.76	50.00	18.24	PASS
6	17.007	10.50	32.38	42.88	60.00	17.12	14.46	24.96	50.00	25.04	PASS

Note:1).QP Value (dB μ V)= QP Reading (dB μ V)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)


3). QPMargin(dB) = QP Limit (dB μ V) - QP Value (dB μ V)

4). AVMargin(dB) = AV Limit (dB μ V) - AV Value (dB μ V)


4.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz – 1GHz; the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF + CL - AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.


The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
2. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz



For 1GHz to 25GHz

Note: GFSK, π/4 DQPSK mode have been tested, only worse case GFSK is reported.

GFSK (above 1GHz)

Frequency(MHz):		2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	47.22	PK	74.00	26.78	51.49	32.33	5.12	41.72
4804.00	--	AV	54.00	--	--	--	--	--
7206.00	49.11	PK	74.00	24.89	49.63	36.60	6.49	43.61
7206.00	--	AV	54.00	--	--	--	--	--

Frequency(MHz):		2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	48.22	PK	74.00	25.78	52.49	32.33	5.12	41.72
4804.00	--	AV	54.00	--	--	--	--	--
7206.00	50.11	PK	74.00	23.89	50.63	36.60	6.49	43.61
7206.00	--	AV	54.00	--	--	--	--	--

Frequency(MHz):		2441		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882.00	47.35	PK	74.00	26.65	51.23	32.60	5.34	41.82
4882.00	--	AV	54.00	--	--	--	--	--
7323.00	48.39	PK	74.00	25.61	48.50	36.80	6.81	43.72
7323.00	--	AV	54.00	--	--	--	--	--

Frequency(MHz):		2441		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882.00	47.95	PK	74.00	26.05	51.83	32.60	5.34	41.82
4882.00	--	AV	54.00	--	--	--	--	--
7323.00	49.69	PK	74.00	24.31	49.80	36.80	6.81	43.72
7323.00	--	AV	54.00	--	--	--	--	--

Frequency(MHz):		2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	48.62	PK	74.00	25.38	51.70	32.73	5.66	41.47
4960.00	--	AV	54.00	--	--	--	--	--
7440.00	50.18	PK	74.00	23.82	49.73	37.04	7.25	43.84
7440.00	--	AV	54.00	--	--	--	--	--

Frequency(MHz):		2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	49.92	PK	74.00	24.08	53.00	32.73	5.66	41.47
4960.00	--	AV	54.00	--	--	--	--	--
7440.00	50.78	PK	74.00	23.22	50.33	37.04	7.25	43.84
7440.00	--	AV	54.00	--	--	--	--	--

REMARKS:

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

1. Emission level (dB_uV/m) =Raw Value (dB_uV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

Results of Band Edges Test (Radiated)

Note: GFSK, Pi/4 DQPSK all have been tested, only worse case GFSK is reported.

GFSK

Frequency(MHz):		2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Raw Value (dB _u V)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	51.44	PK	74.00	22.56	61.86	27.42	4.31	42.15
2390.00	--	AV	54.00	--	--	--	--	--
Frequency(MHz):		2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Raw Value (dB _u V)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	53.84	PK	74.00	20.16	64.26	27.42	4.31	42.15
2390.00	44.89	AV	54.00	9.11	55.31	27.42	4.31	42.15
Frequency(MHz):		2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Raw Value (dB _u V)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	48.25	PK	74.00	25.75	58.36	27.70	4.47	42.28
2483.50	--	AV	54.00	--	--	--	--	--
Frequency(MHz):		2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dB _u V/m)	Limit (dB _u V/m)	Margin (dB)	Raw Value (dB _u V)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	50.15	PK	74.00	23.85	60.26	27.70	4.47	42.28
2483.50	--	AV	54.00	--	--	--	--	--

REMARKS:

1. Emission level (dB_uV/m) =Raw Value (dB_uV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

4.3 Maximum Peak Output Power

Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

Type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	-1.81	20.97	Pass
	39	-2.03		
	78	-2.36		
$\pi/4$ DQPSK	00	-0.85	20.97	Pass
	39	-1.13		
	78	-1.56		

Note: 1.The test results including the cable lose.

4.4 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

Modulation	Channel	20dB bandwidth (MHz)	Result
GFSK	CH00	0.953	Pass
	CH39	0.884	
	CH78	0.882	
$\pi/4$ DQPSK	CH00	1.309	Pass
	CH39	1.316	
	CH78	1.309	

Test plot as follows:





4.5 Occupied Bandwidth

Limit

N/A

Test Procedure

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

RBW=1% to 5% of the OBW

VBW=approximately 3 X RBW

Detector=Peak

Trace Mode: Max Hold

Use the 99% power bandwidth function of the instrument to measure the Occupied Bandwidth and recoded.


Test Configuration



Test Results

Modulation	Channel	OCB [MHz]	Result
GFSK	CH00	0.854	Pass
	CH39	0.855	
	CH78	0.854	
$\pi/4$ DQPSK	CH00	1.178	Pass
	CH39	1.181	
	CH78	1.182	

Test plot as follows:





4.6 Frequency Separation

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

Modulation	Channel	Channel Separation (MHz)	Limit(MHz)	Result
GFSK	CH00	0.996	25KHz or 2/3*20dB bandwidth	Pass
	CH01			
$\pi/4$ DQPSK	CH00	0.999	25KHz or 2/3*20dB bandwidth	Pass
	CH01			

Note:

We have tested all mode at high, middle and low channel, and recorded worst case at middle

Test plot as follows:



4.7 Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.


Test Configuration



Test Results

Modulation	Number of Hopping Channel	Limit	Result
GFSK	79	≥15	Pass
π/4DQPSK	79		

Test plot as follows:



4.8 Time of Occupancy (Dwell Time)

Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.


Test Configuration




Test Results

Modulation	Packet	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit (s)	Result
GFSK	DH1	0.378	320.00	120.960	0.40	Pass
	DH3	1.634	158.00	258.172		
	DH5	2.882	108.00	311.256		
$\pi/4$ DQPSK	2-DH1	0.441	320.00	141.120	0.40	Pass
	2-DH3	1.640	169.00	277.160		
	2-DH5	2.887	105.00	303.135		

Test plot as follows:





4.9 Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector , and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration





Test Results


Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data.


We measured all conditions (DH1, DH3, DH5) and recorded worst case at DH5

Test plot as follows:









Band-edge Measurements for RF Conducted Emissions:**GFSK****Left Band edge hoping off****Left Band edge hoping on**

MNR	MODE	TRC	SLC	X	Y	FUNCTION	FUNCTION/HOTH	FUNCTION VALUE
1	N	1	f	2.402 055 GHz	-2.035 dBm			
2	N	1	f	2.400 000 GHz	-27.836 dBm			
3	N	1	f	2.399 965 GHz	-27.836 dBm			

Right Band edge hoping off**Right Band edge hoping on**

MNR	MODE	TRC	SLC	X	Y	FUNCTION	FUNCTION/HOTH	FUNCTION VALUE
1	N	1	f	2.476 000 GHz	-2.829 dBm			
2	N	1	f	2.483 500 GHz	-48.922 dBm			
3	N	1	f	2.483 525 GHz	-48.913 dBm			



4.10 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

4.11 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.




Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction



The maximum gain of antenna was 0 dBi.



5 Test Setup Photos of the EUT



6 Photos of the EUT



External photos









Internal photos





***** End of Report *****

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: <http://www.cta-test.cn>