Applica	nt/Crantoo	I KS GI	ORAI	Co	I td					
Applicant/Grantee LKS GLOBAL Co., Ltd. FCC ID: 2A8VH-GKM-MD5G										
Section 15.212 Modular Transmitters										
Request for Modular Request for Limited Modular										
_					oproval					
Approval Ap Requirements			A	EUT Conditions	Comply (Y/N)					
	Req			lar	Approval Requirements	Comply (1/14)				
1	The radio ale			lai .	All the radio elements are in	Y				
1	The radio elements of the modular transmitter must have			VA.	its own shield can.	1				
	their own shielding. The			. V C	its own shield can.					
	physical crystal and tuning									
	capacitors may be located									
	external to the shielded radio			0						
	elements.	ie siliela	ou ruur	0						
2	The modular	r transmi	tter mu	st	OK	Y				
_	have buffere									
	modulation/o		ıts (if							
	such inputs a	-	•							
	ensure that the	-	,							
	comply with	Part 15								
	requirements	s under c	onditio	ns						
	of excessive	data rate	es or							
	over-modula	ition.								
3	The modular	r transmi	tter mu	st	A DC-DC converter is	Y				
	have its own	power s	supply		configured for internal supply					
	regulation.				of the module.					
4	The modular transmitter must				Connected to antenna with	Y				
	comply with		nna and	1	internal transmission line and					
	transmission requirements				matching.					
	1									
		15.203, 15.204(b) and 15.204(c). The antenna must								
	either be per			ι						
	attached or e		•	و''						
	antenna coup		-							
	connections									
	module and									
	including the									
	"professiona	,								
	provision of			is						
	not applicab									
	can apply to									
	approvals un									
	of this section	n.	- `							
	mi 1.1					<b>T</b> 7				
5	The modular			st	The module is tested in a	Y				
	be tested in a	a stand-a	lone		stand-alone configuration.					

	_	,	
	configuration, <i>i.e.</i> , the module		
	must not be inside another		
	device during testing for		
	compliance with Part 15		
	requirements. Unless the		
	transmitter module will be		
	battery powered, it must		
	comply with the AC line		
	conducted requirements found		
	in Section 15.207. AC or DC		
	power lines and data		
	<del>-</del>		
	input/output lines connected		
	to the module must not		
	contain ferrites, unless they		
	will be marketed with the		
	module (see Section		
	15.27(a)). The length of these		
	lines shall be the length		
	typical of actual use or, if that		
	length is unknown, at least 10		
	centimeters to insure that		
	there is no coupling between		
	the case of the module and		
	supporting equipment. Any		
	accessories, peripherals, or		
	support equipment connected		
	to the module during testing		
	shall be unmodified and		
	commercially available (see		
	Section 15.31(i)).		
6	The modular transmitter must	It has a label printed ECC ID	Y
0		It has a label printed FCC ID	Y
	be equipped with either a	on top of the module.	
	permanently affixed label or		
	must be capable of		
	electronically displaying its		
	FCC identification number.		
	(A) If using a permanently affixed		
	label, the modular transmitter must be labeled with its own FCC		
	identification number, and, if the		
	FCC identification number is not		
	visible when the module is installed		
	inside another device, then the		
	outside of the device into which the		
	module is installed must also		
	display a label referring to the enclosed module. This exterior label		
	can use wording such as the		
	following: "Contains Transmitter		
	Module		
	FCC ID: XYZMODEL1" or		
	"Contains FCC ID:		

	VV7MODEL 1 " A::1		1
	XYZMODEL1." Any similar wording		
	that expresses the same meaning		
	may be used. The Grantee may		
	either provide such a label, an		
	example of which must be included		
	in the application for equipment		
	authorization, or, must provide		
	adequate instructions along with the		
	module which explain this		
	requirement. In the latter case, a		
	copy of these instructions must be		
	included in the application for		
	equipment authorization.		
	(B) If the modular transmitter uses		
	an electronic display of the FCC		
	identification number, the		
	information must be readily		
	accessible and visible on the		
	modular transmitter or on the		
	device in which it is installed. If the		
	module is installed inside another		
	device, then the outside of the device		
	into which the module is installed		
	must display a label referring to the		
	enclosed module. This exterior label can use wording such as the		
	following:		
	"Contains FCC certified transmitter		
	module(s)." Any similar wording		
	that expresses the same meaning		
	may be used. The user manual must		
	include instructions on how to		
	access the electronic display. A copy		
	of these instructions must be		
	included in the application for		
	equipment authorization.		
7	The modular transmitter must	Module usage manuals were	Y
	comply with any specific	provided.	
	rules or operating	1	
	requirements that		
	*		
	ordinarily apply to a complete		
	transmitter and the		
	manufacturer must provide		
	adequate instructions along		
	with the module to explain		
	any such requirements. A		
	copy of these instructions		
	must be included in the		
	application for equipment		
	authorization.		
8	The modular transmitter must	The modular transmitter	Y
	comply with any applicable	complies with any applicable	
	RF exposure requirements in	RF exposure requirements.	
	its final configuration.	The exposure requirements.	
	165 Illiai Collingurauoli.	<u> </u>	<u> </u>

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.