



# FCC TEST REPORT

## FCC ID: 2A8YK-MINI02

Product	:	DASH CAM
Model Name	:	MINI02, MINI01, MINI03, MINI04, MINI05, MINI06, MINI07, MINI08, MINI09, MINIONE01, MINIONE02, MINIONE03, MINIONE04, MINIONE05, MINIONE06, MINIONE07, MINIONE08, MINIONE09, YC200, YC240, YC300, YC400, YC500, YC600, YC700, YC800, MM935, MM960, MM988, MM1088, MM1126, MM1166, MM1188
Brand	:	N/A
Report No.	:	PTC22080505101E-FC02

### Prepared for

Shenzhen Yeestek Tech Co., Ltd.

Room 201, Building A, Shenzhen Hong Kong cooperation zone, No.1 Qianwan 1st Road, Qianhai, Shenzhen, Guangdong, China

### Prepared by

Precise Testing & Certification Co., Ltd.

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.



## TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Yeestek Tech Co., Ltd.  
Address : Room 201, Building A, Shenzhen Hong Kong cooperation zone, No.1 Qianwan 1st Road, Qianhai, Shenzhen, Guangdong, China  
Manufacturer's name : Shenzhen Yeestek Tech Co., Ltd.  
Address : Room 201, Building A, Shenzhen Hong Kong cooperation zone, No.1 Qianwan 1st Road, Qianhai, Shenzhen, Guangdong, China  
Product name : DASH CAM  
Model name : MINI02, MINI01, MINI03, MINI04, MINI05, MINI06, MINI07, MINI08, MINI09, MINIONE01, MINIONE02, MINIONE03, MINIONE04, MINIONE05, MINIONE06, MINIONE07, MINIONE08, MINIONE09, YC200, YC240, YC300, YC400, YC500, YC600, YC700, YC800, MM935, MM960, MM988, MM1088, MM1126, MM1166, MM1188  
Test procedure : FCC CFR47 Part 1.1307(b)(1)  
Test Date : Sep. 29, 2022 to Oct. 13, 2022  
Date of Issue : Oct. 29, 2022  
Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Dr. Liu".

Ronnie Liu / Manager



## Contents

	<b>Page</b>
<b>2 TEST SUMMARY .....</b>	<b>4</b>
<b>3 GENERAL INFORMATION .....</b>	<b>5</b>
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
<b>4 RF EXPOSURE .....</b>	<b>6</b>
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT .....	6
4.3 MPE CALCULATION METHOD .....	7
4.4 TEST RESULT .....	7



## 2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		

### 3 General Information

#### 3.1 General Description of E.U.T.

Product Name	:	DASH CAM
Model Name	:	MINI02
Additional model	:	MINI02, MINI01, MINI03, MINI04, MINI05, MINI06, MINI07, MINI08, MINI09, MINIONE01, MINIONE02, MINIONE03, MINIONE04, MINIONE05, MINIONE06, MINIONE07, MINIONE08, MINIONE09, YC200, YC240, YC300, YC400, YC500, YC600, YC700, YC800, MM935, MM960, MM988, MM1088, MM1126, MM1166, MM1188
Model differences	:	Product appearance color is different, model name is different, other are the same.
Specification	:	802.11b/g/n HT20
Operation Frequency	:	2412-2462MHz for 802.11b/g/n(HT20)
Number of Channel	:	11 channels for 802.11b/g/n(HT20)
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Antenna installation	:	Integral antenna
Antenna Gain	:	1.84 dBi
Power supply	:	DC 5V/2.5A
Hardware Version	:	V1.0
Software Version	:	V1.0



## 4 RF Exposure

Test Requirement : 15.247 (i)

Evaluation Method : FCC Part 2.1091

### 4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



### 4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

### 4.4 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )	Result
2412	1.84dBi/1.53	6.07	6.07±1	5.093309	0.001548	1	Pass

\*\*\*\*\*THE END REPORT\*\*\*\*\*