



TEST REPORT

Applicant: Intrepid Control Systems, Inc.
Address: 1850 Research Dr., Troy Michigan 48083 USA
Equipment Type: neoVI-Connect
Model Name: 110-0071-02
Brand Name: Intrepid
FCC ID: 2A923241206ROEM1
ISED Number: 29961-241206ROEM1
Test Standard: 47 CFR Part 15 Subpart C
RSS-Gen Issue 5
RSS-247 Issue 3
(refer to section 3.1)
Sample Arrival Date: Feb. 19, 2025
Test Date: Feb. 19, 2025 - Feb. 26, 2025
Date of Issue: Apr. 14, 2025

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

Tested by: Hai Su

Checked by: Zhang Yanqing

Approved by: Chen Zidong

(Technical Director)

Hai Su

Zhang Yanqing

Chen Zidong

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Apr. 08, 2025</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Apr. 14, 2025</u>	<u>Modify the Antenna Gain and Total directional gain in Section 2.4.</u> <u>Modify the E.I.R.P Test Data (For ISED) in ANNEX A.1.</u> <u>The original report is invalid.</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location.....	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information.....	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS.....	8
3.1	Test Standards	8
3.2	Test Verdict	9
4	GENERAL TEST CONFIGURATIONS.....	10
4.1	Test Environments	10
4.2	Test Equipment List.....	10
4.3	Test Software List.....	10
4.4	Decision Rule	11
4.5	Measurement Uncertainty	11
4.6	Description of Test Setup	12
4.7	Measurement Results Explanation Example.....	15
5	TEST ITEMS.....	16
5.1	Antenna Requirements.....	16
5.2	Output Power	17
5.3	Occupied Bandwidth	19

5.4	Conducted Spurious Emission	20
5.5	Band Edge (Authorized-band band-edge).....	22
5.6	Conducted Emission	24
5.7	Radiated Spurious Emission	25
5.8	Band Edge (Restricted-band band-edge).....	29
5.9	Power Spectral density (PSD)	30
ANNEX A	TEST RESULT	31
A.1	Output Power	31
A.2	Occupied Bandwidth	37
A.3	Conducted Spurious Emission	37
A.4	Band Edge (Authorized-band band-edge).....	37
A.5	Conducted Emission	37
A.6	Radiated Emission	38
A.7	Band Edge (Restricted-band band-edge).....	56
A.8	Power Spectral Density (PSD)	72
ANNEX B	TEST SETUP PHOTOS	73
ANNEX C	EUT EXTERNAL PHOTOS	73
ANNEX D	EUT INTERNAL PHOTOS	73

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1st to 2nd floors, Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1st to 2nd floors, Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 29671.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Intrepid Control Systems, Inc.
Address	1850 Research Dr., Troy Michigan 48083 USA

2.2 Manufacturer Information

Manufacturer	Intrepid Control Systems, Inc.
Address	1850 Research Dr., Troy Michigan 48083 USA

2.3 General Description for Equipment under Test (EUT)

EUT Name	neoVI-Connect
Model Name Under Test	110-0071-02
Series Model Name	N/A
Description of Model name differentiation	N/A
Sample Number	SC-SH2510055-S02(conducted) SC-SH2510055-S05(radiated)
Hardware Version	110-0071
Software Version	R2C1224
Dimensions (Approx.)	L:155.0mm* W:209.7mm* H:43.75mm*
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	2G Network GSM 850/1900 MHz 3G Network WCDM Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/12/13/25/26/66 TDD Band 38/41 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80)
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1) \times 5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11. 802.11n(40 MHz): 2.422 GHz - 2.452 GHz $f_c = 2412 \text{ MHz} + (N-1) \times 5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 3 to 9.	
Modulation Type	DSSS, OFDM	
Antenna System (eg., MIMO, Smart Antenna)	Cyclic Delay Diversity (CDD) for 802.11b/g Multi Input Multi Output (MIMO) for 802.11n	
Categorization as Correlated or Completely Uncorrelated	Categorization as Correlated for 802.11b/g Categorization as Uncorrelated for 802.11n	
Antenna Type	Main Antenna	Rod Antenna
	Aux. Antenna	
Antenna Gain	Main Antenna	3.20 dBi
	Aux. Antenna	
Total directional gain	For power spectral density(PSD) measurements	Correlated: 6.21 dBi Formulas: Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi Uncorrelated: 3.20 dBi Formulas: Directional gain = G_{ANT}
	For power measurements	Correlated: 6.21 dBi Formulas: Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi Uncorrelated: 3.20 dBi Formulas: Directional gain = G_{ANT}
	For Conducted Out-of-Band and Spurious Measurements	Correlated: 6.21 dBi Formulas: Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi Uncorrelated: 3.20 dBi

	Formulas: Directional gain = $GANT$
About the Product	Only the WIFI 802.11b, 802.11g, 802.11n (HT20/40) was tested in this report.

Mode	Antenna		
	Main Antenna	Aux. Antenna	MIMO
802.11b	√	√	--
802.11g	√	√	--
802.11n20	√	√	√
802.11n40	√	√	√
Note: All the configurations were tested, but only the worst data was shown in this report.			

Modulation technology	Modulation Type	Transfer Rate (Mbps)(Single RF path)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n-20 MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2
OFDM (802.11n-40 MHz)	BPSK	13.5/15
	QPSK	27/40.5/30/45
	16QAM	54/81/60/90
	64QAM	108/121.5/135/120/150

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
6dB Bandwidth	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Intentional radiators of radio frequency equipment
2	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
3	RSS-247 Issue 3	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	KDB Publication 662911 D01v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
5	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
6	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC PART No.	ISED Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (f)	N/A	Pass ^{Note 1}
2	Output Power	15.247 (b)	RSS-247, 5.4 (d)	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247 (a)	RSS-GEN, 6.7; RSS-247, 5.2 (a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247 (d)	RSS-247, 5.5	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247 (d)	RSS-GEN, 8.9; RSS-247, 5.5	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	--	N/A ^{Note 3}
7	Radiated Spurious Emission	15.209; 15.247 (d)	RSS-247, 5.5	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247 (d)	RSS-247, 5.5	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247 (e)	RSS-247, 5.2 (b)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	RSS-Gen, 7.3	N/A	N/A ^{Note 2}

Note¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note²: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

Note³: The EUT is only used in vehicle environment. So the Conducted Emission test is not applicable.

Note⁴: For FCC standard, the RF module installed in the EUT is electronically and mechanically identical to the original certified module in the test report, No. SUHR/2021/B001003 (FCC ID: XMR202201AF51Y) which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 02, 2022. Therefore, Output Power, Radiated Spurious Emissions and Band Edge(Restricted-band band-edge) were tested in this report, other test projects refer to the original report, No. SUHR/2021/B001003 (FCC ID: XMR202201AF51Y) which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 02, 2022.

Note⁵: For IC standard, the RF module installed in the EUT is electronically and mechanically identical to the original certified module in the test report, No. SUHR/2021/B001009 (ISED Number: 10224A-202201AF51Y) which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 06, 2022. Therefore, Output Power, Radiated Spurious Emissions and Band Edge(Restricted-band band-edge) were tested in this report, other test projects refer to the original report, No. SUHR/2021/B001009 (ISED Number: 10224A-202201AF51Y) which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 06, 2022.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	53% to 59%	
Atmospheric Pressure	101 kPa	
Temperature	NT (Normal Temperature)	+22.8°C to +23.9°C
Working Voltage of the EUT	NV (Normal Voltage)	12 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420147	2025.02.12	2026.02.11
Spectrum Analyzer	KEYSIGHT	N9010B	MY60240977	2025.02.12	2026.02.11
Signal Generator	Anritsu	MG3710E	6262063515	2025.02.12	2026.02.11
Wideband Radio Communication Tester	R&S	CMW500	168792	2025.02.11	2026.02.10
EMI Receiver	KEYSIGHT	N9038A	MY55330122	2024.07.09	2025.07.08
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-177	2024.03.11	2027.03.10
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-1203	2024.03.11	2027.03.10
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-2134	2024.03.11	2027.03.10
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400-KF	J211060307	2024.03.11	2027.03.10
Anechoic Chamber	YiHeng	9m*6m*6m	EMC001	2024.04.18	2027.04.17
EMI Receiver	KEYSIGHT	N9038A	MY55330115	2025.02.12	2026.02.11
LISN	SCHWARZBECK	NSLK 8127	8127-940	2025.02.11	2026.02.10
10dB Limiter	SCHWARZBECK	VTSD 9561-F	9561-F N00409	2025.02.11	2026.02.10
Shielded Room	YiHeng	5m*4m*3.2 m	EMC006	2024.02.22	2027.02.21

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable Test Setup
BL410R	BALUN	V2.1.1.496	N/A	The section 4.6.1
BL410E	BALUN	V21.919	N/A	The section 4.6.2&4.6.3&4.6.4&4.6.5

4.4 Decision Rule

☐ No Need

☒ Use General conformity decision rule (Consider uncertainty or not ☒No ☐Yes)

☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐No ☐Yes)

4.5 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.4 %
RF output power, conducted	0.41 dB
Power Spectral Density, conducted	1.73 dB
Unwanted Emissions, conducted	1.73 dB
All emissions, radiated	4.57 dB
Temperature	0.82 °C
Humidity	4.1 %


4.6 Description of Test Setup

4.6.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5 dB used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.6.2 For AC Power Supply Port Test




(Diagram 2)

4.6.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.6.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.6.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.7 Measurement Results Explanation Example

4.7.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.7.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP = Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203; RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b); RSS-247, 5.4 (d)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The EUT shall be transmitted at its maximum power control level.

$EIRP = \text{Maximum peak conducted output power} + \text{Antenna Gain}$.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between

bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-GEN, 6.7; RSS-247, 5.2 (a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-GEN, 8.9, RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) $\pm$ 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission $\pm$ 0.5 MHz.

Standard method (The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.6.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.6.3 to 4.6.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) $RBW = 1$ MHz (unless otherwise specified).
- d) $VBW \geq 3$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (RBW/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (b)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.6.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Note: All the configurations were pre tested, only the worst configuration has been reported in this report.

Duty Cycle

Test Mode	On Time (ms)	On+Off time (ms)	Duty Cycle
802.11b	12.19	12.24	99.59%
802.11g	2.02	2.06	98.06%
802.11n-20 MHz	1.70	1.74	97.47%
802.11n-40 MHz	0.83	0.89	93.87%

Peak Power Test Data

Main Antenna:

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	19.21	83.37	30	1000	Pass
Middle	19.30	85.11			Pass
High	19.56	90.36			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.54	113.24	30	1000	Pass
Middle	20.45	110.92			Pass
High	20.77	119.40			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	21.79	151.01	30	1000	Pass
Middle	21.50	141.25			Pass
High	21.89	154.53			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.12	51.52	30	1000	Pass
Middle	17.29	53.58			Pass
High	17.11	51.40			Pass

Aux. Antenna:

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.02	100.46	30	1000	Pass
Middle	19.97	99.31			Pass
High	19.93	98.40			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	21.00	125.89	30	1000	Pass
Middle	21.10	128.82			Pass
High	21.30	134.90			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	21.78	150.66	30	1000	Pass
Middle	21.87	153.82			Pass
High	22.11	162.55			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	17.94	62.23	30	1000	Pass
Middle	17.54	56.75			Pass
High	17.92	61.94			Pass

MIMO

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	24.80	301.67	30	1000	Pass
Middle	24.70	295.07			Pass
High	25.01	317.08			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.56	113.75	30	1000	Pass
Middle	20.43	110.33			Pass
High	20.54	113.35			Pass

E.I.R.P Test Data (For ISED)Main Antenna:

802.11b Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	22.41	174.18	36	4	Pass
Middle	22.50	177.83			Pass
High	22.76	188.80			Pass

802.11g Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	23.74	236.59	36	4	Pass
Middle	23.65	231.74			Pass
High	23.97	249.46			Pass

802.11n-20 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	24.99	315.50	36	4	Pass
Middle	24.70	295.12			Pass
High	25.09	322.85			Pass

802.11n-40 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	20.32	107.65	36	4	Pass
Middle	20.49	111.94			Pass
High	20.31	107.40			Pass

Aux. Antenna:

802.11b Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	23.22	209.89	36	4	Pass
Middle	23.17	207.49			Pass
High	23.13	205.59			Pass

802.11g Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	24.20	263.03	36	4	Pass
Middle	24.30	269.15			Pass
High	24.50	281.84			Pass

802.11n-20 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	24.98	314.77	36	4	Pass
Middle	25.07	321.37			Pass
High	25.31	339.63			Pass

802.11n-40 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	21.14	130.02	36	4	Pass
Middle	20.74	118.58			Pass
High	21.12	129.42			Pass

MIMO

802.11n-20 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	28.00	630.28	36	4	Pass
Middle	27.90	616.49			Pass
High	28.21	662.47			Pass

802.11n-40 MHz Mode:

Channel	E.I.R.P		Limit		Verdict
	dBm	mW	dBm	W	
Low	23.76	237.66	36	4	Pass
Middle	23.63	230.52			Pass
High	23.74	236.82			Pass

A.2 Occupied Bandwidth

Note: The Occupied Channel Bandwidth, please refer to the Report No. SUHR/2021/B001003 which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 02, 2022. Chapters Appendix.

A.3 Conducted Spurious Emission

Note: The Conducted Spurious Emission, please refer to the Report No. SUHR/2021/B001003 which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 02, 2022. Chapters Appendix.

A.4 Band Edge (Authorized-band band-edge)

Note: The Band Edge (Authorized-band band-edge), please refer to the Report No. SUHR/2021/B001003 which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 02, 2022. Chapters Appendix.

A.5 Conducted Emission

Note: Not applicable.

A.6 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Test Data and Plots

30 MHz to 1 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.000	32.71	-28.88	40.0	7.29	Peak	360.00	200	Horizontal	Pass
2	53.425	31.06	-24.86	40.0	8.94	Peak	130.00	200	Horizontal	Pass
3	168.176	29.43	-28.44	43.5	14.07	Peak	75.00	200	Horizontal	Pass
4	250.869	36.09	-24.05	46.0	9.91	Peak	0.00	100	Horizontal	Pass
5	350.246	42.01	-21.46	46.0	3.99	Peak	127.00	100	Horizontal	Pass
6	843.102	39.35	-10.58	46.0	6.65	Peak	247.00	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	43.774	32.38	-24.95	40.0	7.62	Peak	77.00	100	Vertical	Pass
2	54.444	38.16	-25.01	40.0	1.84	Peak	346.00	100	Vertical	Pass
3	263.091	37.02	-24.12	46.0	8.98	Peak	168.00	100	Vertical	Pass
4	388.124	41.76	-20.66	46.0	4.24	Peak	276.00	100	Vertical	Pass
5	595.073	36.09	-15.10	46.0	9.91	Peak	210.00	100	Vertical	Pass
6	843.248	42.78	-10.57	46.0	3.22	Peak	186.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.


Note 3: All antenna were pre tested, but only the worst case has been reported in this report.

Note 4: All the configurations were pre tested, only the worst configuration has been reported in this report.

Main Antenna:

1 GHz to 18 GHz, ANT H 802.11b Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1041.500	41.47	-15.37	74.0	32.53	Peak	300.00	150	Horizontal	Pass
1**	1041.500	36.32	-15.37	54.0	17.68	AV	300.00	150	Horizontal	Pass
2	2046.500	41.89	-13.46	74.0	32.11	Peak	271.00	150	Horizontal	Pass
2**	2046.500	31.12	-13.46	54.0	22.88	AV	271.00	150	Horizontal	Pass
3	2438.000	88.60	-12.38	74.0	-14.60	Peak	224.00	150	Horizontal	N/A
3**	2438.000	85.70	-12.38	54.0	-31.70	AV	224.00	150	Horizontal	N/A
4	2927.000	46.33	-8.10	74.0	27.67	Peak	0.00	150	Horizontal	Pass
4**	2927.000	35.49	-8.10	54.0	18.51	AV	0.00	150	Horizontal	Pass
5	6829.500	53.63	0.83	74.0	20.37	Peak	340.00	150	Horizontal	Pass
5**	6829.500	42.52	0.83	54.0	11.48	AV	340.00	150	Horizontal	Pass
6	14593.000	49.26	-2.09	74.0	24.74	Peak	270.00	150	Horizontal	Pass
6**	14593.000	38.93	-2.09	54.0	15.07	AV	270.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.250	43.33	-15.99	74.0	30.67	Peak	158.00	150	Vertical	Pass
1**	1330.250	30.73	-15.99	54.0	23.27	AV	158.00	150	Vertical	Pass
2	2299.500	43.68	-13.10	74.0	30.32	Peak	251.00	150	Vertical	Pass
2**	2299.500	32.58	-13.10	54.0	21.42	AV	251.00	150	Vertical	Pass
3	2438.000	89.36	-12.38	74.0	-15.36	Peak	269.00	150	Vertical	N/A
3**	2438.000	86.52	-12.38	54.0	-32.52	AV	269.00	150	Vertical	N/A
4	3000.000	45.91	-8.74	74.0	28.09	Peak	360.00	150	Vertical	Pass
4**	3000.000	35.74	-8.74	54.0	18.26	AV	360.00	150	Vertical	Pass
5	7740.500	54.36	1.34	74.0	19.64	Peak	39.00	150	Vertical	Pass
5**	7740.500	43.51	1.34	54.0	10.49	AV	39.00	150	Vertical	Pass
6	13973.500	49.27	-1.92	74.0	24.73	Peak	360.00	150	Vertical	Pass
6**	13973.500	37.96	-1.92	54.0	16.04	AV	360.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1041.500	40.82	-15.37	74.0	33.18	Peak	295.00	150	Horizontal	Pass
1**	1041.500	36.03	-15.37	54.0	17.97	AV	295.00	150	Horizontal	Pass
2	2101.250	42.65	-13.52	74.0	31.35	Peak	258.00	150	Horizontal	Pass
2**	2101.250	31.45	-13.52	54.0	22.55	AV	258.00	150	Horizontal	Pass
3	2435.250	87.01	-12.29	74.0	-13.01	Peak	227.00	150	Horizontal	N/A
3**	2435.250	78.05	-12.29	54.0	-24.05	AV	227.00	150	Horizontal	N/A
4	2996.000	46.32	-8.83	74.0	27.68	Peak	360.00	150	Horizontal	Pass
4**	2996.000	35.56	-8.83	54.0	18.44	AV	360.00	150	Horizontal	Pass
5	6298.500	53.40	-0.03	74.0	20.60	Peak	130.00	150	Horizontal	Pass
5**	6298.500	41.61	-0.03	54.0	12.39	AV	130.00	150	Horizontal	Pass
6	14146.500	50.29	-1.10	74.0	23.71	Peak	8.00	150	Horizontal	Pass
6**	14146.500	38.76	-1.10	54.0	15.24	AV	8.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1041.500	41.05	-15.37	74.0	32.95	Peak	0.00	150	Vertical	Pass
1**	1041.500	35.76	-15.37	54.0	18.24	AV	0.00	150	Vertical	Pass
2	1711.750	40.15	-16.30	74.0	33.85	Peak	0.00	150	Vertical	Pass
2**	1711.750	28.78	-16.30	54.0	25.22	AV	0.00	150	Vertical	Pass
3	2438.750	87.45	-12.37	74.0	-13.45	Peak	266.00	150	Vertical	N/A
3**	2438.750	78.99	-12.37	54.0	-24.99	AV	266.00	150	Vertical	N/A
4	2964.000	46.58	-8.61	74.0	27.42	Peak	44.00	150	Vertical	Pass
4**	2964.000	35.32	-8.61	54.0	18.68	AV	44.00	150	Vertical	Pass
5	5978.500	52.48	-0.11	74.0	21.52	Peak	6.00	150	Vertical	Pass
5**	5978.500	41.43	-0.11	54.0	12.57	AV	6.00	150	Vertical	Pass
6	14729.500	49.79	-1.70	74.0	24.21	Peak	68.00	150	Vertical	Pass
6**	14729.500	39.23	-1.70	54.0	14.77	AV	68.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1125.250	41.49	-15.64	74.0	32.51	Peak	347.00	100	Horizontal	Pass
1**	1125.250	34.11	-15.64	54.0	19.89	AV	347.00	100	Horizontal	Pass
2	2102.500	42.56	-13.54	74.0	31.44	Peak	264.00	100	Horizontal	Pass
2**	2102.500	31.40	-13.54	54.0	22.60	AV	264.00	100	Horizontal	Pass
3	2438.500	87.60	-12.37	74.0	-13.60	Peak	87.00	100	Horizontal	N/A
3**	2438.500	79.86	-12.37	54.0	-25.86	AV	87.00	100	Horizontal	N/A
4	4936.500	49.54	-1.97	74.0	24.46	Peak	0.00	100	Horizontal	Pass
4**	4936.500	39.16	-1.97	54.0	14.84	AV	0.00	100	Horizontal	Pass
5	10776.001	47.69	-2.93	74.0	26.31	Peak	206.00	100	Horizontal	Pass
5**	10776.001	36.58	-2.93	54.0	17.42	AV	206.00	100	Horizontal	Pass
6	14840.001	49.16	-0.25	74.0	24.84	Peak	178.00	100	Horizontal	Pass
6**	14840.001	38.52	-0.25	54.0	15.48	AV	178.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.500	44.43	-15.94	74.0	29.57	Peak	172.00	100	Vertical	Pass
1**	1328.500	29.59	-15.94	54.0	24.41	AV	172.00	100	Vertical	Pass
2	2128.500	42.84	-13.25	74.0	31.16	Peak	10.00	100	Vertical	Pass
2**	2128.500	31.98	-13.25	54.0	22.02	AV	10.00	100	Vertical	Pass
3	2440.000	82.44	-12.37	74.0	-8.44	Peak	150.00	100	Vertical	N/A
3**	2440.000	73.57	-12.37	54.0	-19.57	AV	150.00	100	Vertical	N/A
4	5024.500	49.95	-2.09	74.0	24.05	Peak	207.00	100	Vertical	Pass
4**	5024.500	38.75	-2.09	54.0	15.25	AV	207.00	100	Vertical	Pass
5	10407.000	47.36	-3.22	74.0	26.64	Peak	0.00	100	Vertical	Pass
5**	10407.000	36.75	-3.22	54.0	17.25	AV	0.00	100	Vertical	Pass
6	14852.000	49.41	-0.74	74.0	24.59	Peak	0.00	100	Vertical	Pass
6**	14852.000	38.01	-0.74	54.0	15.99	AV	0.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1375.000	41.20	-16.01	74.0	32.80	Peak	215.00	150	Horizontal	Pass
1**	1375.000	35.11	-16.01	54.0	18.89	AV	215.00	150	Horizontal	Pass
2	2439.250	85.01	-12.37	74.0	-11.01	Peak	292.00	150	Horizontal	N/A
2**	2439.250	76.65	-12.37	54.0	-22.65	AV	292.00	150	Horizontal	N/A
3	3405.500	46.79	-5.43	74.0	27.21	Peak	356.00	150	Horizontal	Pass
3**	3405.500	36.28	-5.43	54.0	17.72	AV	356.00	150	Horizontal	Pass
4	6219.500	52.79	-0.83	74.0	21.21	Peak	261.00	150	Horizontal	Pass
4**	6219.500	41.22	-0.83	54.0	12.78	AV	261.00	150	Horizontal	Pass
5	11022.000	48.13	-3.11	74.0	25.87	Peak	349.00	150	Horizontal	Pass
5**	11022.000	36.73	-3.11	54.0	17.27	AV	349.00	150	Horizontal	Pass
6	16897.000	50.26	-0.64	74.0	23.74	Peak	10.00	150	Horizontal	Pass
6**	16897.000	39.51	-0.64	54.0	14.49	AV	10.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.500	44.81	-16.00	74.0	29.19	Peak	132.00	150	Vertical	Pass
1**	1332.500	30.95	-16.00	54.0	23.05	AV	132.00	150	Vertical	Pass
2	2438.250	87.50	-12.38	74.0	-13.50	Peak	277.00	150	Vertical	N/A
2**	2438.250	79.49	-12.38	54.0	-25.49	AV	277.00	150	Vertical	N/A
3	3415.500	46.88	-5.15	74.0	27.12	Peak	58.00	150	Vertical	Pass
3**	3415.500	36.76	-5.15	54.0	17.24	AV	58.00	150	Vertical	Pass
4	5978.500	51.99	-0.11	74.0	22.01	Peak	136.00	150	Vertical	Pass
4**	5978.500	40.70	-0.11	54.0	13.30	AV	136.00	150	Vertical	Pass
5	10809.500	47.83	-3.21	74.0	26.17	Peak	350.00	150	Vertical	Pass
5**	10809.500	36.98	-3.21	54.0	17.02	AV	350.00	150	Vertical	Pass
6	14773.000	48.99	-0.79	74.0	25.01	Peak	63.00	150	Vertical	Pass
6**	14773.000	39.23	-0.79	54.0	14.77	AV	63.00	150	Vertical	Pass

Aux. Antenna:**1 GHz to 18 GHz, ANT H 802.11b Middle Channel**


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1248.750	40.69	-16.16	74.0	33.31	Peak	169.00	150	Horizontal	Pass
1**	1248.750	31.03	-16.16	54.0	22.97	AV	169.00	150	Horizontal	Pass
2	2438.250	92.24	-12.38	74.0	-18.24	Peak	329.00	150	Horizontal	N/A
2**	2438.250	89.36	-12.38	54.0	-35.36	AV	329.00	150	Horizontal	N/A
3	3465.000	47.62	-5.10	74.0	26.38	Peak	1.00	150	Horizontal	Pass
3**	3465.000	39.69	-5.10	54.0	14.31	AV	1.00	150	Horizontal	Pass
4	5988.500	51.65	-0.11	74.0	22.35	Peak	349.00	150	Horizontal	Pass
4**	5988.500	41.15	-0.11	54.0	12.85	AV	349.00	150	Horizontal	Pass
5	9744.000	47.47	-3.97	74.0	26.53	Peak	0.00	150	Horizontal	Pass
5**	9744.000	36.42	-3.97	54.0	17.58	AV	0.00	150	Horizontal	Pass
6	16804.000	50.43	-1.18	74.0	23.57	Peak	0.00	150	Horizontal	Pass
6**	16804.000	39.85	-1.18	54.0	14.15	AV	0.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1375.750	40.69	-16.00	74.0	33.31	Peak	111.00	150	Vertical	Pass
1**	1375.750	31.71	-16.00	54.0	22.29	AV	111.00	150	Vertical	Pass
2	2435.750	94.05	-12.32	74.0	-20.05	Peak	180.00	150	Vertical	N/A
2**	2435.750	91.03	-12.32	54.0	-37.03	AV	180.00	150	Vertical	N/A
3	3401.000	47.37	-5.63	74.0	26.63	Peak	245.00	150	Vertical	Pass
3**	3401.000	36.16	-5.63	54.0	17.84	AV	245.00	150	Vertical	Pass
4	6451.000	53.90	-0.09	74.0	20.10	Peak	349.00	150	Vertical	Pass
4**	6451.000	41.79	-0.09	54.0	12.21	AV	349.00	150	Vertical	Pass
5	9890.000	47.34	-4.18	74.0	26.66	Peak	206.00	150	Vertical	Pass
5**	9890.000	36.82	-4.18	54.0	17.18	AV	206.00	150	Vertical	Pass
6	17263.000	49.77	-1.48	74.0	24.23	Peak	33.00	150	Vertical	Pass
6**	17263.000	39.42	-1.48	54.0	14.58	AV	33.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1532.000	40.01	-16.05	74.0	33.99	Peak	28.00	150	Horizontal	Pass
1**	1532.000	28.96	-16.05	54.0	25.04	AV	28.00	150	Horizontal	Pass
2	2439.250	91.54	-12.37	74.0	-17.54	Peak	331.00	150	Horizontal	N/A
2**	2439.250	83.44	-12.37	54.0	-29.44	AV	331.00	150	Horizontal	N/A
3	3430.000	47.60	-5.02	74.0	26.40	Peak	92.00	150	Horizontal	Pass
3**	3430.000	36.51	-5.02	54.0	17.49	AV	92.00	150	Horizontal	Pass
4	6315.500	52.18	-0.27	74.0	21.82	Peak	188.00	150	Horizontal	Pass
4**	6315.500	41.49	-0.27	54.0	12.51	AV	188.00	150	Horizontal	Pass
5	10370.000	47.47	-3.40	74.0	26.53	Peak	59.00	150	Horizontal	Pass
5**	10370.000	36.67	-3.40	54.0	17.33	AV	59.00	150	Horizontal	Pass
6	14087.999	49.14	-1.72	74.0	24.86	Peak	89.00	150	Horizontal	Pass
6**	14087.999	38.48	-1.72	54.0	15.52	AV	89.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1228.250	41.92	-15.99	74.0	32.08	Peak	128.00	150	Vertical	Pass
1**	1228.250	29.97	-15.99	54.0	24.03	AV	128.00	150	Vertical	Pass
2	2440.000	93.66	-12.37	74.0	-19.66	Peak	183.00	150	Vertical	N/A
2**	2440.000	84.97	-12.37	54.0	-30.97	AV	183.00	150	Vertical	N/A
3	3465.000	47.88	-5.10	74.0	26.12	Peak	300.00	150	Vertical	Pass
3**	3465.000	38.95	-5.10	54.0	15.05	AV	300.00	150	Vertical	Pass
4	6133.000	51.99	-0.38	74.0	22.01	Peak	100.00	150	Vertical	Pass
4**	6133.000	40.88	-0.38	54.0	13.12	AV	100.00	150	Vertical	Pass
5	10861.000	47.63	-3.29	74.0	26.37	Peak	65.00	150	Vertical	Pass
5**	10861.000	37.22	-3.29	54.0	16.78	AV	65.00	150	Vertical	Pass
6	16891.000	49.39	-0.47	74.0	24.61	Peak	94.00	150	Vertical	Pass
6**	16891.000	39.87	-0.47	54.0	14.13	AV	94.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1273.750	40.61	-15.83	74.0	33.39	Peak	33.00	150	Horizontal	Pass
1**	1273.750	28.62	-15.83	54.0	25.38	AV	33.00	150	Horizontal	Pass
2	2436.000	91.75	-12.33	74.0	-17.75	Peak	332.00	150	Horizontal	N/A
2**	2436.000	83.24	-12.33	54.0	-29.24	AV	332.00	150	Horizontal	N/A
3	3370.500	47.06	-4.86	74.0	26.94	Peak	82.00	150	Horizontal	Pass
3**	3370.500	36.65	-4.86	54.0	17.35	AV	82.00	150	Horizontal	Pass
4	5940.500	51.67	-0.28	74.0	22.33	Peak	349.00	150	Horizontal	Pass
4**	5940.500	41.10	-0.28	54.0	12.90	AV	349.00	150	Horizontal	Pass
5	10555.500	47.51	-3.35	74.0	26.49	Peak	210.00	150	Horizontal	Pass
5**	10555.500	36.45	-3.35	54.0	17.55	AV	210.00	150	Horizontal	Pass
6	15262.000	49.66	-1.09	74.0	24.34	Peak	125.00	150	Horizontal	Pass
6**	15262.000	39.25	-1.09	54.0	14.75	AV	125.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.500	41.53	-16.00	74.0	32.47	Peak	157.00	150	Vertical	Pass
1**	1332.500	30.39	-16.00	54.0	23.61	AV	157.00	150	Vertical	Pass
2	2435.500	95.15	-12.31	74.0	-21.15	Peak	184.00	150	Vertical	N/A
2**	2435.500	85.01	-12.31	54.0	-31.01	AV	184.00	150	Vertical	N/A
3	3457.000	47.02	-4.91	74.0	26.98	Peak	349.00	150	Vertical	Pass
3**	3457.000	36.41	-4.91	54.0	17.59	AV	349.00	150	Vertical	Pass
4	5999.000	52.28	-0.12	74.0	21.72	Peak	285.00	150	Vertical	Pass
4**	5999.000	40.69	-0.12	54.0	13.31	AV	285.00	150	Vertical	Pass
5	11396.500	48.00	-3.50	74.0	26.00	Peak	9.00	150	Vertical	Pass
5**	11396.500	37.21	-3.50	54.0	16.79	AV	9.00	150	Vertical	Pass
6	16126.500	49.84	-1.35	74.0	24.16	Peak	349.00	150	Vertical	Pass
6**	16126.500	39.07	-1.35	54.0	14.93	AV	349.00	150	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Middle Channel


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1537.250	39.65	-16.04	74.0	34.35	Peak	353.00	150	Horizontal	Pass
1**	1537.250	28.87	-16.04	54.0	25.13	AV	353.00	150	Horizontal	Pass
2	2440.250	87.21	-12.37	74.0	-13.21	Peak	157.00	150	Horizontal	N/A
2**	2440.250	78.29	-12.37	54.0	-24.29	AV	157.00	150	Horizontal	N/A
3	3465.000	47.62	-5.10	74.0	26.38	Peak	50.00	150	Horizontal	Pass
3**	3465.000	40.21	-5.10	54.0	13.79	AV	50.00	150	Horizontal	Pass
4	6065.000	51.99	-0.34	74.0	22.01	Peak	127.00	150	Horizontal	Pass
4**	6065.000	41.20	-0.34	54.0	12.80	AV	127.00	150	Horizontal	Pass
5	9728.000	47.61	-4.24	74.0	26.39	Peak	360.00	150	Horizontal	Pass
5**	9728.000	36.39	-4.24	54.0	17.61	AV	360.00	150	Horizontal	Pass
6	16065.000	49.72	-1.28	74.0	24.28	Peak	360.00	150	Horizontal	Pass
6**	16065.000	38.94	-1.28	54.0	15.06	AV	360.00	150	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Middle Channel

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.500	43.76	-15.99	74.0	30.24	Peak	135.00	150	Vertical	Pass
1**	1331.500	28.62	-15.99	54.0	25.38	AV	135.00	150	Vertical	Pass
2	2438.750	89.17	-12.37	74.0	-15.17	Peak	181.00	150	Vertical	N/A
2**	2438.750	80.51	-12.37	54.0	-26.51	AV	181.00	150	Vertical	N/A
3	3464.500	47.45	-5.08	74.0	26.55	Peak	357.00	150	Vertical	Pass
3**	3464.500	37.02	-5.08	54.0	16.98	AV	357.00	150	Vertical	Pass
4	6005.000	52.23	-0.41	74.0	21.77	Peak	360.00	150	Vertical	Pass
4**	6005.000	40.70	-0.41	54.0	13.30	AV	360.00	150	Vertical	Pass
5	10328.500	47.96	-3.23	74.0	26.04	Peak	359.00	150	Vertical	Pass
5**	10328.500	36.52	-3.23	54.0	17.48	AV	359.00	150	Vertical	Pass
6	16385.000	49.25	-1.39	74.0	24.75	Peak	359.00	150	Vertical	Pass
6**	16385.000	39.23	-1.39	54.0	14.77	AV	359.00	150	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note 1: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note 2: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note 3: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 4: All the configurations were pre tested, only the worst configuration has been reported in this report.

Note 5: All antenna were pre tested, but only the worst case has been reported in this report.

Test Data and Plots


Main Antenna:

802.11b LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	50.36	-4.87	74.0	23.64	Peak	277.09	150	Horizontal	Pass
1**	2390.000	40.29	-4.87	54.0	13.71	AV	277.09	150	Horizontal	Pass
2	2370.700	52.47	-4.02	74.0	21.53	Peak	360.00	150	Horizontal	Pass
2**	2370.700	40.83	-4.02	54.0	13.17	AV	360.00	150	Horizontal	Pass

802.11b HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	51.90	-3.78	74.0	22.10	Peak	0.00	150	Horizontal	Pass
1**	2483.500	42.13	-3.78	54.0	11.87	AV	0.00	150	Horizontal	Pass
2	2499.820	54.10	-3.99	74.0	19.90	Peak	292.00	150	Horizontal	Pass
2**	2499.820	41.64	-3.99	54.0	12.36	AV	292.00	150	Horizontal	Pass

802.11g LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	50.73	-4.87	74.0	23.27	Peak	36.40	150	Vertical	Pass
1**	2390.000	40.75	-4.87	54.0	13.25	AV	36.40	150	Vertical	Pass
2	2366.700	53.02	-4.36	74.0	20.98	Peak	187.00	150	Vertical	Pass
2**	2366.700	41.33	-4.36	54.0	12.67	AV	187.00	150	Vertical	Pass

802.11g HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.35	-3.78	74.0	20.65	Peak	273.00	150	Horizontal	Pass
1**	2483.500	44.66	-3.78	54.0	9.34	AV	273.00	150	Horizontal	Pass
2	2483.560	55.23	-3.78	74.0	18.77	Peak	332.00	150	Horizontal	Pass
2**	2483.560	43.73	-3.78	54.0	10.27	AV	332.00	150	Horizontal	Pass

802.11n20 LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	51.02	-4.87	74.0	22.98	Peak	148.17	150	Horizontal	Pass
1**	2390.000	40.73	-4.87	54.0	13.27	AV	148.17	150	Horizontal	Pass
2	2369.700	52.75	-4.04	74.0	21.25	Peak	213.00	150	Horizontal	Pass
2**	2369.700	41.15	-4.04	54.0	12.85	AV	213.00	150	Horizontal	Pass

802.11n20 HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	57.14	-3.78	74.0	16.86	Peak	326.00	150	Horizontal	Pass
1**	2483.500	47.60	-3.78	54.0	6.40	AV	326.00	150	Horizontal	Pass
2	2483.530	59.05	-3.78	74.0	14.95	Peak	329.00	150	Horizontal	Pass
2**	2483.530	47.43	-3.78	54.0	6.57	AV	329.00	150	Horizontal	Pass

802.11n40 LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	52.77	-4.87	74.0	21.23	Peak	178.03	150	Horizontal	Pass
1**	2390.000	42.36	-4.87	54.0	11.64	AV	178.03	150	Horizontal	Pass
2	2385.100	53.32	-4.59	74.0	20.68	Peak	351.00	150	Horizontal	Pass
2**	2385.100	42.23	-4.59	54.0	11.77	AV	351.00	150	Horizontal	Pass

802.11n40 HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	52.03	-3.78	74.0	21.97	Peak	339.00	150	Horizontal	Pass
1**	2483.500	42.90	-3.78	54.0	11.10	AV	339.00	150	Horizontal	Pass
2	2483.770	53.58	-3.78	74.0	20.42	Peak	284.00	150	Horizontal	Pass
2**	2483.770	43.05	-3.78	54.0	10.95	AV	284.00	150	Horizontal	Pass

Aux. Antenna:**802.11b LOW CHANNEL**

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	50.81	-4.87	74.0	23.19	Peak	360.00	150	Horizontal	Pass
1**	2390.000	40.69	-4.87	54.0	13.31	AV	360.00	150	Horizontal	Pass
2	2389.900	52.60	-4.87	74.0	21.40	Peak	360.00	150	Horizontal	Pass
2**	2389.900	40.41	-4.87	54.0	13.59	AV	360.00	150	Horizontal	Pass

802.11b HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	51.23	-3.78	74.0	22.77	Peak	146.00	150	Vertical	Pass
1**	2483.500	41.51	-3.78	54.0	12.49	AV	146.00	150	Vertical	Pass
2	2483.980	53.17	-3.78	74.0	20.83	Peak	320.00	150	Vertical	Pass
2**	2483.980	41.11	-3.78	54.0	12.89	AV	320.00	150	Vertical	Pass

802.11g LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	50.80	-4.87	74.0	23.20	Peak	200.74	150	Horizontal	Pass
1**	2390.000	40.83	-4.87	54.0	13.17	AV	200.74	150	Horizontal	Pass
2	2369.300	52.92	-4.08	74.0	21.08	Peak	348.00	150	Horizontal	Pass
2**	2369.300	40.97	-4.08	54.0	13.03	AV	348.00	150	Horizontal	Pass

802.11g HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.36	-3.78	74.0	17.64	Peak	332.00	150	Horizontal	Pass
1**	2483.500	43.37	-3.78	54.0	10.63	AV	332.00	150	Horizontal	Pass
2	2484.460	54.95	-3.78	74.0	19.05	Peak	329.00	150	Horizontal	Pass
2**	2484.460	42.92	-3.78	54.0	11.08	AV	329.00	150	Horizontal	Pass

802.11n20 LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	50.74	-4.87	74.0	23.26	Peak	159.84	150	Vertical	Pass
1**	2390.000	41.43	-4.87	54.0	12.57	AV	159.84	150	Vertical	Pass
2	2375.600	52.71	-4.17	74.0	21.29	Peak	86.00	150	Vertical	Pass
2**	2375.600	40.71	-4.17	54.0	13.29	AV	86.00	150	Vertical	Pass

802.11n20 HIGH CHANNEL




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.45	-3.78	74.0	19.55	Peak	328.00	150	Horizontal	Pass
1**	2483.500	44.95	-3.78	54.0	9.05	AV	328.00	150	Horizontal	Pass
2	2484.850	55.66	-3.78	74.0	18.34	Peak	338.00	150	Horizontal	Pass
2**	2484.850	43.05	-3.78	54.0	10.95	AV	338.00	150	Horizontal	Pass

802.11n40 LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2390.000	52.41	-4.87	74.0	21.59	Peak	227.99	150	Horizontal	Pass
1**	2390.000	42.83	-4.87	54.0	11.17	AV	227.99	150	Horizontal	Pass
2	2383.500	54.23	-4.50	74.0	19.77	Peak	224.00	150	Horizontal	Pass
2**	2383.500	41.88	-4.50	54.0	12.12	AV	224.00	150	Horizontal	Pass

802.11n40 HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin(dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	53.81	-3.78	74.0	20.19	Peak	337.00	150	Horizontal	Pass
1**	2483.500	43.78	-3.78	54.0	10.22	AV	337.00	150	Horizontal	Pass
2	2484.190	53.91	-3.78	74.0	20.09	Peak	339.00	150	Horizontal	Pass
2**	2484.190	43.61	-3.78	54.0	10.39	AV	339.00	150	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Note: The Power Spectral Density (PSD), please refer to the Report No. SUHR/2021/B001003 which issued by SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd on Apr. 02, 2022.Appendix.

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SH2510057-AR-1.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SH2510057-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SH25510057-AI.PDF”.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--