

RF Exposure

The Equipment Under Test (EUT) is a Robot Vacuum and Mop with Bluetooth and Wi-Fi function operating at 2402-2480 and 2412-2462MHz. The EUT is powered by DC 14.4V from battery. For more detailed features description, please refer to the user's manual.

Bluetooth(BLE) function

Antenna Type: Monopole Antenna

Antenna Gain: 2.0dBi

Modulation Type: GFSK

The normal conducted output power is: 7dBm (tolerance: +/-1dB).

The maximum conducted output power for the EUT is 7.32dBm in the frequency 2440MHz which is within the production variation.

The minimum conducted output power for the EUT is 7.28dBm in the frequency 2402MHz which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 7dBm + 1dB + 2dBi = 10dBm = 10mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, MPE Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The MPE limit is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

Note:

The BLE and 2.4G Wi-Fi can't transmission simultaneously.

EIRP is higher than ERP, thus EIRP is compared with the Exclusion Threshold.

2.4G Wi-Fi function:

Antenna Type: Monopole Antenna

Antenna Gain: 1dBi

Modulation Type: CCK, DQPSK, DBPSK, BPSK, QPSK, 16QAM, 64QAM

The normal conducted output power is 19dBm (tolerance: +/-3dB).

The maximum conducted output power for the EUT is 21.02dBm in the frequency 2.412GHz 802.11g mode which is within the production variation.

The minimum conducted output power for the EUT is 16.00dBm in the frequency 2.462GHz 802.11b mode which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 19dBm + 3dB +1dBi = 23dBm
= 199.53mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, MPE Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The MPE limit is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.

Note:

The BLE and 2.4G Wi-Fi can't transmission simultaneously.

EIRP is higher than ERP, thus EIRP is compared with the Exclusion Threshold.

FCC ID: 2A942YJCC023