# TEST REPORT



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (1) / (35) Pages

1	Α	p	р	Ιi	C	a	n	t

• Name : LUPLE Inc.

· Address: B-305, 3rd floor, 47, Maeheon-ro 8-gil, Seocho-gu, Seoul, South Korea

Date of Receipt: 2022-05-23

#### 2. Manufacturer

• Name: LUPLE Inc.

· Address: B-305, 3rd floor, 47, Maeheon-ro 8-gil, Seocho-gu, Seoul, South Korea

## 3. Factory

• Name: ESOL

• Address : 4th Floor, 44, Ojeong-ro 39beon-gil, Bucheon-si, Gyeonggi-do, 14445,

Rep. of KOREA

4. Use of Report: For FCC & ISED Certification

5. Test Sample / Model: iOlly / OA01

6. Date of Test: 2022-11-20 to 2023-02-06

7. Test Standard(method) used: FCC 47 CFR part 15 subpart C 15.247

ANSI C63.10-2013, RSS-247, RSS-Gen

**8. Testing Environment :** Temp.:  $(23 \pm 1) \, ^{\circ}$ C, Humidity:  $(48 \pm 5) \, ^{\circ}$ R.H.

9. Test Results: Compliance

**10. Location of Test**: ☐ Permanent Testing Lab ☐ On Site Testing

(Address: 5, Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, 17141 Korea)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This report cannot be reproduced or copied without the written consent of CTK

Approval Seoung-uk Park: (Signature) Technical Manager

Young-taek Lee: (Signature)

Remark. This report is not related to KOLAS accreditation and relevant regulation

2023-02-06

CTK Co., Ltd.



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (2) / (35) Pages

## REPORT REVISION HISTORY

Date	Revision	Page No
2022-02-06	Issued (CTK-2023-00314)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.



Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (3) / (35) Pages

# **CONTENTS**

1. General Product Description4	ŀ
1.1 Applicant Information4	ł
1.2 Product Information4	ŀ
1.3 Peripheral Devices4	ŀ
2. Accreditations5	5
2.1 Laboratory Accreditations and Listings5	5
2.2 Calibration Details of Equipment Used for Measurement5	5
3. Test Specifications6	5
3.1 Standards6	;
3.2 Mode of operation during the test6	j
3.3 Maximum Measurement Uncertainty7	,
4. Technical Characteristic Test8	3
4.1 6 dB Bandwidth and 99 % Bandwidth8	3
4.2 Maximum peak Conducted Output Power10	)
4.3 Power Spectral Density	3
4.4 Band Edge & Conducted Spurious emission	5
4.5 Radiated Emission	)
4.6 AC Power Line Conducted Emissions31	L
5. APPENDIX A – Test Equipment Used For Tests	5



Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (4) / (35) Pages

# 1. General Product Description

## 1.1 Applicant Information

Company	LUPLE Inc.	
Contact Point	B-305, 3rd floor, 47, Maeheon-ro 8-gil, Seocho-gu, Seoul, South Korea	
Contact Person	Name: HYUN JUN PARK E-mail: leo@luple.co.kr Tel: +82-10-7388-5834	

## 1.2 Product Information

FCC ID	2A945-OA01
Certification Number ISED	29923-OA01
Product Description	iOlly
Basic model (HVIN)	OA01
Variant Model name	-
Operating Frequency	2 402 MHz - 2 480 MHz
RF Output Power	-3.071 dBm (0.493 mW)
Antenna type	Chip Antenna
Antenna gain	1.80 dBi
Number of channels	40
Channel Spacing	2 MHz
Type of Modulation	GFSK
Power Source	DC 3.7 V (Battery)
FVIN	V1.0

## 1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Notebook	HP Inc.	HP Probook 455 G7	5CD0234DWW
AC Adapter	HP Inc.	TPN-LA16	PA-1650-20HL



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (5) / (35) Pages

## 2. Accreditations

## 2.1 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A
KOREA	NRRA	KR0025

## 2.2 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (6) / (35) Pages

## 3. Test Specifications

## 3.1 Standards

Section in FCC	Section in RSS	Requirement(s)	Status (Note 1)	Test Condition	
15.247(a)	RSS-247 5.2(a)	6 dB Bandwidth	С		
15.247(e)	RSS-247 5.2(b)	Transmitter power spectral density	С	Conducted	
15.247(b)	RSS-247 5.4(d)	Maximum peak conducted output power	С	Conducted	
15.247(d)	RSS-247 5.5	Unwanted emission	С		
15.209	RSS-Gen 6.13	Transmitter emission	С	Radiated	
15.207(a) RSS-Gen 8.8 AC Conducted Emission		С	Line Conducted		
Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable					

Note 2: The data in this test report are traceable to the national or international standards.

Note 3: The sample was tested according to the following specification: FCC Part 15.247, ANSI C63.10-2013, RSS-247 Issue 2, RSS-GEN Issue 5

Note 4: The tests were performed according to the method of measurements prescribed in KDB No.558074, ANSI C63.10-2013

## 3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments. During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests. The results are only attached worst cases.

#### **Test Frequency**

Lowest channel	Middle channel	Highest channel	
2 402 MHz	2 440 MHz	2 480 MHz	

#### **Test Mode**

i est mode					
Modulation	Duty Cycle	Duty Cycle Factor			
GFSK	0.86 %	0.66 dB			



Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (7) / (35) Pages

## 3.3 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter. Coverage factor k = 2, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	1.5 dB (C.L. : Approx. 95 %, k = 2)
Power Spectral Density	1.5 dB (C.L. : Approx. 95 %, k = 2)
Occupied Bandwidth	0.1 MHz (C.L. : Approx. 95 %, <i>k</i> = 2)
Unwanted Emission(conducted)	3.0 dB (C.L. : Approx. 95 %, k = 2)
Radiated Emissions (f ≤ 30 MHz)	1.5 dB (C.L. : Approx. 95 %, k = 2)
Radiated Emissions ( $f \le 1 \text{ GHz}$ )	3.88 dB (C.L. : Approx. 95 %, <i>k</i> = 2)
Radiated Emissions (f > 1 GHz)	4.62 dB (C.L. : Approx. 95 %, k = 2)



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (8) / (35) Pages

## 4. Technical Characteristic Test

#### 4.1 6 dB Bandwidth and 99 % Bandwidth

#### **Test Procedures**

KDB 558074 D01 – Section 8.2 ANSI C63.10–2013 – Section 6.9.2 RSS-Gen – Section 6.7

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### **Test Procedures**

ANSI C63.10-2013 - Section 6.9.3 RSS-Gen - Section 6.7

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission.

Use the 99 % power bandwidth function of the instrument and report the measured bandwidth.

## **Test Settings:**

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz (6dB Bandwidth)

b) RBW = 1% to 5% of the OBW

(99 % Bandwidth)

c) VBW  $\geq$  3 x RBW

d) Detector = peak

e) Trace mode = Max hold

f) Sweep = auto couple

- g) Allow trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Limit: 6 dB Bandwidth

6 dB Bandwidth > 500 kHz

Limit: 99 % Bandwidth

N/A



Report No.: CTK-2023-00314 Page (9) / (35) Pages

## Test Data:

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	99 % Bandwidth [MHz]	Result
Lowest	2 402	0.703	1.054	
Middle	2 440	0.735	1.053	Complies
Highest	2 480	0.708	1.056	

See next pages for actual measured spectrum plots.




(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501


Report No.: CTK-2023-00314 Page (10) / (35) Pages

## Lowest channel (2 402 MHz)

#### 6 dB Bandwidth



## 99 % Bandwidth




## Middle channel (2 440 MHz)

#### 6 dB Bandwidth



## 99 % Bandwidth




## Highest channel (2 480 MHz)

#### 6 dB Bandwidth



## 99 % Bandwidth





(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (11) / (35) Pages

## 4.2 Maximum peak Conducted Output Power

#### **Test Procedures**

KDB 558074 D01 - Section 8.3.1.1 ANSI C63.10-2013 - Section 11.9.1.1 RSS-Gen - Section 6.12

The following procedure can be used when the maximum available RBW of the instrument is greater than the DTS bandwidth:

### **Test Settings:**

Center frequency = the highest, middle and the lowest channels

a) RBW ≥ DTS Bandwidth

b) VBW  $\geq$  3 x RBW

c) span  $\geq$  3 x RBW

d) Sweep time = auto couple

e) Detector = peak

f) Trace mode= max hold

- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.

#### Limit:

Maximum Output Power < 1 W (30 dBm)

### Test Data:

Channel	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
Lowest	2 402	-3.071	30	
Middle	2 440	-4.172	30	Complies
Highest	2 480	-6.885	30	

See next pages for actual measured spectrum plots.




(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970


Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (12) / (35) Pages






## Middle channel (2 440 MHz)



Highest channel (2 480 MHz)





(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (13) / (35) Pages

## 4.3 Power Spectral Density

#### **Test Procedures**

KDB 558074 D01 - Section 8.4 ANSI C63.10-2013 - Section 11.10.2

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

## Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW :  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ 

b) VBW  $\geq$  3 x RBW

c) span  $\geq 1.5 \times DTS$  bandwidth

d) Sweep time = auto couple

e) Detector = peak

f) Trace mode= max hold

g) Allow trace to fully stabilize

h) Use the peak marker function to determine the maximum amplitude level within the RBW.

#### Limit:

Power Spectral Density < 8 dBm @ 3 kHz BW

#### Test Data:

Channel	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
Lowest	2 402	-19.412		
Middle	2 440	-20.133	8	Complies
Highest	2 480	-22.739		

See next pages for actual measured spectrum plots.



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970


Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (14) / (35) Pages






Middle channel (2 440 MHz)



Highest channel (2 480 MHz)





(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (15) / (35) Pages

## 4.4 Band Edge & Conducted Spurious emission

#### **Test Procedures**

KDB 558074 D01 - Section 8.5 ANSI C63.10-2013 - Section 11.11.3 RSS-Gen - Section 6.13

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2013.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

#### Test Settings:

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz

b)  $VBW \ge 3 \times RBW$ 

c) Detector = peak

d) Sweep time = auto couple

- e) Trace mode= max hold
- f) Allow trace to fully stabilize
- g) Use the peak marker function to determine the maximum amplitude level.

## Limit:

Emission level < 20 dBc

#### **Test results: Complies**

 All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.

See next pages for actual measured spectrum plots.





(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (16) / (35) Pages

## Band-edge







(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501


Report No.: CTK-2023-00314 Page (17) / (35) Pages

## **Conducted Spurious emission**

Lowest channel (2 402 MHz)



Middle channel (2 440 MHz)






(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (18) / (35) Pages

Highest channel (2 480 MHz)





(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (19) / (35) Pages

#### 4.5 Radiated Emission

	Test	Loca	tion
--	------	------	------

 $\boxtimes$  10 m SAC (test distance :  $\square$  10 m,  $\boxtimes$  3 m)

□ 3 m SAC (test distance : 3 m)

#### **Test Procedures**

KDB 558074 - Section 8.5, 8.6 ANSI C63.10-2013 - Section 11.11, 11.12 RSS-Gen - Section 6.13

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency rage above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3 m away from the EUT. Test Antenna height is carried from 1 m to 4 m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

### <u>Test Settings:</u>

Frequency Range = 9 kHz ~ 1 GHz

- a) RBW = 100 kHz for f < 1 GHz, 9 kHz for f < 30 MHz
- b) VBW ≥ RBW
- c) Detector = CISPR Quasi-peak
- d) Sweep time = auto couple

- Peak

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10<sup>th</sup> harmonic)

- a) RBW = 1 MHz
- b) VBW  $\geq$  3 x RBW

c) Detector = Peak

d) Sweep time = auto

e) Trace mode = max hold

- Average (duty cycle ≥ 98%)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10<sup>th</sup> harmonic)

- a) RBW = 1 MHz
- b) VBW  $\geq$  3 x RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea

Tel: +82-31-339-9970 Fax: +82-31-624-9501 Report No.: CTK-2023-00314 Page (20) / (35) Pages

- Average (duty cycle < 98%, duty cycle variations are less than ±2%)

Frequency Range = 1 GHz ~ 25 GHz (2.4 GHz 10<sup>th</sup> harmonic)

a) RBW = 1 MHz

b) VBW  $\geq$  3 x RBW

c) Detector = RMS

d) Sweep time = auto

e) Averaging type = power (i.e., RMS)

f) Trace mode = average (at least 100 traces)

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.

If power averaging (RMS) mode, then the applicable correction factor is

10  $\log(1/x)$ , where x is the duty cycle.

Test Mode	Duty Cycle Factor
BLE 1 Mbps	0.66 dB

#### Limit:

Unwanted emissions that do not fall within the restricted frequency bands of Table 1 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

**Table 1. Restricted Frequency Bands** 

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
<sup>1</sup> 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475- 156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	<sup>2</sup> Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

<sup>&</sup>lt;sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions.

<sup>&</sup>lt;sup>2</sup> Above 38.6



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (21) / (35) Pages

The provisions in Section 15.35 apply to these measurements.

\*Certain frequency bands listed in Table 1 and in band above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to the devices are set out in the 200- and 300-series of RSSs, such as RSS-210 and RSS-310, which contain the requirements that apply to licence-exempt radio apparatus



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (22) / (35) Pages

FCC Part 15 § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 2:

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in table 2 Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 2. General Field Strength Limits for Licence-Exempt Transmitters

Frequency(MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Deasurement Distance (meters)
0.009-0.490	2400/F(kHz)	48.5 - 13.8	300
0.490-1.705	24000/F(kHz)	33.8 - 23	30
1.705-30	30	29.5	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3

<sup>\*\*</sup> Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz, 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

#### Note:

- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3 m (AV) and 74 dBuV/m@3 m (PK)
- 3) For measurement above 1 GHz, the resolution bandwidth is set to 1 MHz and video bandwidth is set to 3 MHz for peak measurement.




Fax: +82-31-624-9501


Report No.: CTK-2023-00314 Page (23) / (35) Pages

## **Test Setup:**

For field strength of emissions from 9 kHz to 30 MHz



For field strength of emissions from 30 MHz to 1 GHz






Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (24) / (35) Pages

3) For field strength of emissions above 1 GHz





(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970


Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (25) / (35) Pages

#### **Test results**

## 1) Restricted Frequency Bands

### 1. 2 310 MHz to 2 390 MHz



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
2 326.228	Н	41.2	-6.0			35.2		54.0		18.8	Average
2 348.700	٧	53.5	-6.0	0.66	48.2		74.0		25.8		Peak
2 366.565	٧	48.1	-6.0			35.1		54.0		18.9	Average
2 388.350	Н	58.0	-5.9	0.66	52.7		74.0		21.3		Peak

### Remark:

- 1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
- Peak Result = Reading + c.f(Correction factor)
   Average Result = Reading + c.f(Correction factor) + Duty Cycle Factor
- 3. Correction factor = Antenna factor + Cable loss Amp Gain




(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (26) / (35) Pages

#### 2. 2 483.5 MHz - 2 500 MHz



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
2 483.683	Н	67.6	-5.3		62.3		74.0		11.7		Peak
2 483.885	٧	63.7	-5.3		58.4		74.0		15.6		Peak
2 487.312	٧	40.5	-5.3	0.66		35.9		54.0		18.1	Average
2 488.512	Н	40.8	-5.3	0.66		36.2		54.0		17.8	Average

## Remark:

- 1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
- 2. Peak Result = Reading + c.f(Correction factor)
  Average Result = Reading + c.f(Correction factor) + Duty Cycle Factor
- 3. Correction factor = Antenna factor + Cable loss Amp Gain



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (27) / (35) Pages


## 2) Spurious

#### 1. 9 kHz to 30 MHz

## Test mode: Transmit, Low Channel (Worst case)

#### The requirements are:

## 



Spec	trum Select	tion							
No.	Frequency	Pol	Reading PK	c.f	Result PK	Limit QP	Margin QP-PK	Height	Angle
	[MHz]		[dB(µV)]	[dB(1/m)]	$[dB(\mu V/m)]$	[dB(µV/m)]	[dB]	[cm]	deg]
1	0.813	H	27.9	25.0	52.9	69.4	16.5	100.0	119.0
2	0.834	V	20.6	25.0	45.6	69.2	23.6	100.0	82.6
3	1.243	H	19.2	25.0	44.2	65.7	21.5	100.0	67.6
4	1.251	V	13.9	25.0	38.9	65.7	26.8	100.0	20.9
5	1.631	H	19.7	25.0	44.7	63.4	18.7	100.0	119.0
6	1.666	V	13.9	25.0	38.9	63.2	24.3	100.0	62.0

#### Note:

- 1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
- Result = Reading + c.f(correction factor)
- 3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator

<sup>\*</sup> Reading data is the peak value.



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501


Report No.: CTK-2023-00314 Page (28) / (35) Pages

## 2. 30 MHz to 1 GHz

Test mode: Transmit, Low Channel (Worst case)

The requirements are:

#### **Test Data**



Spec	trum Select	tion								
No.	Frequency	Pol	Reading PK	c.f	Result PK	Limit QP	Margin QP-PK	Height	Angle	Remark
	[MHz]		[dB(µV)]	[dB(1/m)]	[dB(µV/m)]	[dB(µV/m)]	[dB]	[cm] [	deg]	
1	168.031	Н	51.2	-14.3	36.9	43.5	6.6	200.0	359.2	
2	191.990	H	49.8	-14.8	35.0	43.5	8.5	100.1	25.0	
3	597.935	V	41.7	-1.8	39.9	46.0	6.1	99.9	168.4	
4	599.099	V	39.5	-1.8	37.7	46.0	8.3	99.9	168.4	
5	932.294	H	30.8	4.8	35.6	46.0	10.4	100.1	143.0	
6	957.029	V	29.3	6.1	35.4	46.0	10.6	99.9	280.2	

#### Remark:

- 1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
- Result = Reading + c.f(Correction factor)
- 3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator Amp Gain

<sup>\*</sup> Reading data is the peak value.



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501


Report No.: CTK-2023-00314 Page (29) / (35) Pages

#### 3. 1 GHz to 18 GHz

Test mode: Transmit, High Channel (Worst case)

The requirements are:

#### **Test Data**



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
4 959.798	Н	36.2	2.8	0.66		39.7		54.0		14.3	Average
4 959.798	٧	36.8	2.8	0.66		40.3		54.0		13.7	Average
4 960.478	Н	48.7	2.8		51.5		74.0		22.5		Peak
4 960.478	٧	47.1	2.8		49.9		74.0		24.1		Peak
7 439.177	٧	47.6	8.0		55.6		74.0		18.4		Peak
7 439.857	Н	46.0	8.0		54.0		74.0		20.0		Peak
7 439.857	٧	36.5	8.0	0.66		45.2		54.0		8.8	Average
7 441.897	Н	35.3	8.1	0.66		44.1		54.0		9.9	Average



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (30) / (35) Pages

#### Remark:

- 1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
- 3. Peak Result = Reading + c.f(Correction factor)
  Average Result = Reading + c.f(Correction factor) + Duty Cycle Factor
- 3. Correction factor = Antenna factor + Cable loss Amp Gain



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501


Report No.: CTK-2023-00314 Page (31) / (35) Pages

#### 4. 18 GHz to 26.5 GHz

Test mode: Transmit, High Channel (Worst case)

The requirements are:

#### **Test Data**



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Duty Cycle Factor [dB]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
24 803.330	٧	46.5	9.0		55.5		74.0		18.5		Peak
26 213.710	Н	34.0	9.3	0.66		44.0		54.0		10.0	Average
26 215.070	Н	46.5	9.3		55.8		74.0		18.2		Peak
26 246.690	٧	34.0	9.4	0.66		44.1		54.0		9.9	Average

#### Remark:

- 1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
- Peak Result = Reading + c.f(Correction factor)
   Average Result = Reading + c.f(Correction factor) + Duty Cycle Factor
- 3. Correction factor = Antenna factor + Cable loss Amp Gain



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970

Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (32) / (35) Pages

## 4.6 AC Power Line Conducted Emissions

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz-30 MHz, shall not exceed the limits.

## **Instrument Settings**

IF Band Width: 9 kHz

#### **Test Procedures**

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

#### Limit

Frequency	Conducted Limit (dBuV)				
(MHz)	Quasi-peak	Average**			
0.15 ~ 0.5	66 to 56*	56 to 46*			
0.5 ~ 5	56	46			
5 ~ 30	60	50			

<sup>\*</sup> The level decreases linearly with the logarithm of the frequency.

<sup>\*\*</sup> A linear average detector is required.




Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (33) / (35) Pages

## **Test Results:**

Test mode : BLE\_F1(Worst case) [L1]

Full Spectrum



## Final Result

I III III I I I I I I I I I I I I I I	••••								
Frequency	QuasiPeak	CAverage	Limit	Margin	Meas. Time	Bandwidth	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)	(ms)	(kHz)			(dB)
0.469500	25.61		56.52	30.91	15000.0	9.000	L1	ON	10.0
0.474000	-	10.93	46.44	35.52	15000.0	9.000	L1	ON	10.0
0.537000		8.67	46.00	37.33	15000.0	9.000	L1	ON	10.0
0.537000	22.61		56.00	33.39	15000.0	9.000	L1	ON	10.0
0.672000	20.02		56.00	35.98	15000.0	9.000	L1	ON	10.0
0.694500	-	6.74	46.00	39.26	15000.0	9.000	L1	ON	10.0
1.248000	-	7.02	46.00	38.98	15000.0	9.000	L1	ON	9.9
1.378500	21.54		56.00	34.46	15000.0	9.000	L1	ON	9.9
1.387500		7.36	46.00	38.64	15000.0	9.000	L1	ON	9.9
2.314500	19.99		56.00	36.01	15000.0	9.000	L1	ON	9.8
2.359500	-	6.37	46.00	39.63	15000.0	9.000	L1	ON	9.8
4.321500	17.63		56.00	38.37	15000.0	9.000	L1	ON	9.9




Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (34) / (35) Pages

## [NEUTRAL]

Full Spectrum



## Final Result

riidi Kesuit									
Frequency	QuasiPeak	CAverage	Limit	Margin	Meas. Time	Bandwidth	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)	(ms)	(kHz)			(dB)
0.460500	31.81		56.68	24.87	15000.0	9.000	N	ON	10.0
0.465000		15.14	46.60	31.47	15000.0	9.000	N	ON	10.0
0.541500		12.32	46.00	33.68	15000.0	9.000	N	ON	10.0
0.573000	27.82		56.00	28.18	15000.0	9.000	N	ON	10.1
0.685500		10.05	46.00	35.95	15000.0	9.000	N	ON	10.0
1.225500	26.11		56.00	29.89	15000.0	9.000	N	ON	9.9
1.243500		10.41	46.00	35.59	15000.0	9.000	N	ON	9.9
1.297500	26.64		56.00	29.36	15000.0	9.000	N	ON	9.9
1.369500		11.04	46.00	34.96	15000.0	9.000	N	ON	9.9
2.283000		9.94	46.00	36.06	15000.0	9.000	N	ON	9.8
2.346000	26.39		56.00	29.61	15000.0	9.000	N	ON	9.8
3.165000	24.83		56.00	31.18	15000.0	9.000	N	ON	9.9



Fax: +82-31-624-9501

Report No.: CTK-2023-00314 Page (35) / (35) Pages

# 5. APPENDIX A - Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Signal Analyzer	Agilent	N9020A	MY50510240	2022-07-13	2023-07-13
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2022-03-25	2023-03-25
3	EMI TEST RECEIVER	Rohde & Schwarz	ESW44	102039	2022-05-04	2023-05-04
4	Bilog Antenna	TESEQ	CBL6111D	60654	2021-09-03	2023-09-03
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-125	2022-04-15	2024-04-15
6	Attenuator	PASTERNACK	PE7AP006-06	L20210504000 023	2022-08-10	2023-08-10
7	AMPLIFIER	SONOMA	310N	411011	2022-08-10	2023-08-10
8	Spectrum Analyzer	Rohde & Schwarz	FSV40	101574	2023-01-11	2024-01-11
9	Preamplifier	Agilent	8449B	3008A00620	2022-05-10	2023-05-10
10	Double Ridged Guide Antenna	ETS-Lindgren	3115	00078895	2022-04-14	2023-04-14
11	Horn Antenna	SCHWARZBECK	BBHA9170	01153	2022-10-31	2023-10-31
12	Band Reject Filter	Micro Tronics	BRM50702	G444	2022-10-13	2023-10-13
13	Low Noise Amplifier	TESTEK	TK-PA1840H	210124-L	2022-11-09	2023-11-09
14	Dual-Tracking DC Power Supply	Topward Electric Instruments Co.,Ltd.	6303D	711196	2022-04-18	2023-04-18
15	DC POWER SUPPLY	HP	E3632A	KR75305831	2022-07-14	2023-07-14
16	EMI Test Receiver	R&S	ESR3	102826	2022-05-04	2023-05-04
17	LISN	R&S	ENV216	102698	2022-05-13	2023-05-13

	Cable	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable (Conducted)	Junkosha Inc.	MWX221	2008S240	2022-11-20
2	RF Cable (9kHz-1GHz Radiated)	Canare Corporation	L-5D2W	N/A	2022-11-20
3	RF Cable (9kHz-1GHz Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2022-11-20
4	RF Cable (1GHz-18GHz Radiated)	Junkosha Inc.	MWX221	2008S246	2022-04-14
5	RF Cable (1GHz-18GHz Radiated)	Rosenberger	NONE	1520.9927.00	2022-04-14
6	RF Cable (1GHz-18GHz Radiated)	Sensorview Co., LTD	9S18	TPC2204060007	2022-04-14
7	RF Cable (18GHz-26.5GHz Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY2372/2	2022-04-14
8	RF Cable (18GHz-26.5GHz Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY073/2	2022-04-14
9	RF Cable (18GHz-26.5GHz Radiated)	Sensorview Co., LTD	9S40	TP210713-001	2022-04-14