



시험 성적서

TEST REPORT

페이지(page) : (1) / (총(Total) 7)

성적서 번호 Report No.		ICRT-TR-E231005-0A	
신청자 Client	기관명 Name	Aerobits Sp. z o.o.	
	주 소 Address	Przestrzenna 11, 70-800 Szczecin, poland	
시험대상품목 Sample description		idME (remotelD)	
모델명 Type designation		idME Pro	
정 격 Ratings		DC 5.0 V	
시험장소 Place of test		☒ 고정시험(Inside test) ☐ 현장시험(Field test) 주소지(Address): 112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea	
시험기간 Date of test		28. Mar. 2023 ~ 10. Apr. 2023	
시험방법/항목 Test Method/Item		FCC rule §1.1310	
시험결과 Test Results		Refer to 3. Maximum Permissible Exposure	
확 인 Affirmation	작성자 Tested by	기술책임자 Technical Manager	
	성 명 Name Seong-Hun, Jeong	성 명 Name Tae-Yang, Yoon	
☐ 위 성적서는 고객이 제공한 시료에 대한 시험결과 입니다. The above test report is certified that the above mentioned products have been tested for the sample. ☐ 위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다. The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme. ☐ 위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다. The test report is prohibited for some reproduction without the approval of the ICR.			
2023. 05. 04 주식회사 아이씨알 대표이사 The head of INTERNATIONAL CERTIFICATION REGISTRAR			



본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6



Contents

1. Applicant & Manufacturer & Test Laboratory Information.....	4
1.1 Applicant information.....	4
1.2 Manufacturer Information.....	4
1.3 Test Laboratory Information.....	4
2. Equipment under Test(EUT) Information.....	5
2.1 General Information	5
2.2 Additional Information	5
2.3 Mode of operation during the test.....	5
2.4 Modifications of EUT	5
3. Maximum Permissible Exposure	6
3.1 RF Exposure calculation	6
3.2 Result.....	7



Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E231005-0A	2023.05.04	Initial Issue	All



1. Applicant & Manufacturer & Test Laboratory Information

1.1 Applicant information

Applicant	Aerobits Sp. z o.o.
Address	Przestrzenna 11, 70-800 Szczecin, poland
Contact Person	Rafał Osypiuk
Telephone No.	0048 500 310 810
Fax No.	-
E-mail	rafal.osypiuk@aerobits.pl

1.2 Manufacturer Information

Manufacturer	Aerobits Sp. z o.o.
Address	Przestrzenna 11, 70-800 Szczecin, poland

1.3 Test Laboratory Information

Conducted tests were performed at	
Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
RRA No.	KR0165
KOLAS No.	KT652



2. Equipment under Test(EUT) Information

2.1 General Information

Product Name	idME (remoteID)
Brand Name	-
Model Name	idME Pro,
Additional Model Name	idME+, idME
FCC ID	2A94B-13EA2A94B
Power Supply	DC 5.0 V

2.2 Additional Information

Equipment Class	DTS-Digital Transmission System	
Device Type	Stand-alone	
Operating Frequency	802.11b/g/n(HT20)	2 412 MHz ~ 2 462 MHz
	802.11n(HT40)	2 422 MHz ~ 2 452 MHz
	Bluetooth LE (1M/2M/Coded 500k/Coded 125k)	2 402 MHz ~ 2 480 MHz
RF Output Power	802.11b	11.45 dBm
	802.11g	10.88 dBm
	802.11n(HT20)	9.94 dBm
	802.11n(HT40)	9.15 dBm
	Bluetooth LE 1Mbps	12.72 dBm
	Bluetooth LE 2Mbps	12.75 dBm
	Bluetooth LE Coded 500kbps	12.44 dBm
	Bluetooth LE Coded 125kbps	12.31 dBm
Number of Channel	802.11b/g/n(HT20)	11
	802.11n(HT40)	7
	Bluetooth LE (1M/2M/Coded 500k/Coded 125k)	40
Modulation Type	802.11b/g/n	BPSK, QPSK, QAM
	Bluetooth LE	GFSK
Antenna Type	Wire Antenna	
Antenna Gain	2.0 dBi	
Antenna Operating Mode	Single Antenna Equipment with only one antenna	

2.3 Mode of operation during the test

- The EUT is continuous transmission mode during the test with set at Low Channel, Middle Channel, and High Channel. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, YZ, XZ planes.

2.4 Modifications of EUT

- None



3. Maximum Permissible Exposure

3.1 RF Exposure calculation

According to the FCC rule §1.1310 the limit for General Population/Uncontrolled exposure is 1 mW/cm² for the device operating 1 500 MHz ~ 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G)} / D, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

P = Power input to the external antenna

(Output power from the EUT antenna port (dBm) – cable loss (dB)),

E = Electric field strength in V/m, G = Numeric antenna gain, and D = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$D = \sqrt{(30 * P * G)} / (377 * 10 S)$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$D = 0.282 * \sqrt{(P * G)} / S$$



3.2 Result

According to above equation, the following result was obtained.

Operating Mode	Target Power W / tolerance	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(mW)	Log	Linear			
BT LE 1Mbps	12.72 ± 1.0	13.72	23.55	2	1.58	1.72	0.0074	1.00
BT LE 2Mbps	12.75 ± 1.0	13.75	23.71			1.73	0.0075	
BT LE coded 500kbps	12.44 ± 1.0	13.44	22.08			1.67	0.0070	
BT LE coded 125kbps	12.31 ± 1.0	13.31	21.43			1.64	0.0068	
802.11b	11.45 ± 1.0	12.45	17.58			1.49	0.0055	
802.11g	10.88 ± 1.0	11.88	15.42			1.39	0.0049	
802.11n20	9.94 ± 1.0	10.94	12.42			1.25	0.0039	
802.11n40	9.15 ± 1.0	10.15	10.35			1.14	0.0033	

- Bluetooth and WIFI of this product use one ESP32 module. Since this module operates as one radio and only one transmission protocol is used per transmission slot for actual transmission, simultaneously transmission is not evaluated.

END OF REPORT.