

FCC ID: 2A95E-SKZV2

According to KDB 447498 D04 Interim General RF Exposure Guidance v01

1. 1-mW Test Exemption

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

2. Test Result

Mode	Frequency Range (MHz)	Minimum Separation Distance (cm)	Maximum Average Target Power (dBm)	Maximum Tune up (dB)	Maximum Average Output Power (dBm)	Antenna Gain (dBi)	ERP		Limit (mW)	Result
							(dBm)	(mW)		
Bluetooth Low energy	2 402 ~ 2 480	0	-4.5	1.0	-3.5	2.76	-0.74	0.843	1	Pass

Note :

$$\text{ERP (dBm)} = \text{EIRP (dBm)} - 2.15 \text{ (dB)} = (\text{AVG PWR} + \text{Antenna Gain}) - 2.15 = (-3.5 + 2.76) - 2.15 \\ = -0.74$$

- Maximum Average Target Power is the manufacturer's declared rated power.
- Maximum Average Output Power = Maximum Average Target Power (dBm) + Maximum Tune up (dB)

3. Conclusion: No SAR is required.