


TEST REPORT

FCC ID.....:	2A95UINF50W3D	
Test Report No.:	TCT221013E012	
Date of issue	Feb. 21, 2023	
Testing laboratory.....:	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name	Katmai Technology Limited	
Address	Flat 1201, Floor 12, HARVEST BUILDING 29-37, WING KUT ST CENTRAL, HONGKONG, CHINA	
Manufacturer's name:	Huizhou Zihanxuan Household Electrical Co., Ltd.	
Address	Yinglong Industrial park, Tiantou Village, Yuanzhou Town, Boluo County, Huizhou City, Guangdong, China	
Standard(s).....:	FCC CFR Title 47 Part 2.1091	
Product Name	ELECTRIC FIREPLACE	
Trade Mark.....:	N/A	
Model/Type reference	INF50W-3D, INF50W-3D, INF36W-3D, INF42W-3D, INF60W-3D, INF72W-3D, EF26-PB Smart, EF26-LG Smart, EF30-PB Smart, EF30-LG Smart, EF23-PB Smart, EF23-LG Smarts	
Rating(s)	AC 120V, 60Hz, 1500W	
Date of receipt of test item	Oct. 13, 2022	
Date (s) of performance of test	Oct. 08, 2022 - Oct. 18, 2022	
Tested by (+signature)....:	Onnado YE	
Check by (+signature):	Beryl ZHAO	
Approved by (+signature):	Tomsin	

**General disclaimer:**

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description.....	3
1.2. Model(s) list	3
2. Facilities and Accreditations	4
2.1. Facilities	4
2.2. Location.....	4
3. Test Results and Measurement Data	5

1. General Product Information

1.1. EUT description

Test item description	ELECTRIC FIREPLACE
Model/Type reference.....	INF50W-3D
Sample Number.....	TCT221013E004-0101
Operation Frequency	For BLE: 2402MHz~2480MHz For WIFI: 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20))
Modulation Type	For BLE: GFSK For WIFI: DSSS(802.11b), OFDM (802.11g/802.11n)
Antenna Type.....	PCB Antenna
Antenna Gain.....	2.54 dBi
Rating(s).....	AC 120V, 60Hz, 1500W
Remark.....	This test report was based on FCC ID: 2AVTWZHXRFPS; Change model name, applicant and applicant's address.

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	INF50W-3D	☒
Other models	INF50W-3D, INF36W-3D, INF42W-3D, INF60W-3D, INF72W-3D, EF26-PB Smart, EF26-LG Smart, EF30-PB Smart, EF30-LG Smart, EF23-PB Smart, EF23-LG Smarts	☐

Note: INF50W-3D is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of INF50W-3D can represent the remaining models.

2. Facilities and Accreditations

2.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

2.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

3. Test Results and Measurement Data

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b), Limits for Maximum Permissible Exposure (MPE),

Frequency range (MHz)	Electric field strength(V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	f/300	6
1500-100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz

EVALUATION METHOD

Transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW, G = gain of antenna in linear scale;

P_i = 3.1416, R = distance between observation point and center of the radiator in cm

Assessment Result

☒ Passed ☐ Not Applicable

Frequency range (MHz)	Type	Conducted Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
2402-2480	BLE	-2.52	-2.00	0.0002	1.0000	Pass
2402-2480	WIFI	17.63	18.00	0.2215	1.0000	Pass

Note: The exposure evaluation safety distance is 20cm.

*******END OF REPORT*******