



■ Report No.: DDT-R23011007-3E02

■ Issued Date: Feb. 23, 2023

RF EXPOSURE REPORT

FOR

Applicant	:	KineticsXR , Incorporated
Address	:	3411 Silverside RD STE 104, Wilmington, DE 19810-4809
Equipment under Test	:	K106
Model No.	:	K106
Trade Mark	:	N/A
FCC ID	:	2A96ZKXRK106
Manufacturer	:	KineticsXR , Incorporated
Address	:	3411 Silverside RD STE 104, Wilmington, DE 19810-4809

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

Test report declares.....	3
1. General Information	5
1.1. Description of equipment	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC	6

Test Report Declare

Applicant	:	KineticsXR , Incorporated
Address	:	3411 Silverside RD STE 104, Wilmington, DE 19810-4809
Equipment under Test	:	K106
Model No.	:	K106
Trade mark	:	N/A
Manufacturer	:	KineticsXR , Incorporated
Address	:	3411 Silverside RD STE 104, Wilmington, DE 19810-4809

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R23011007-3E02		
Date of Receipt:	Feb. 08, 2023	Date of Test:	Feb. 08, 2023 ~ Feb. 17, 2023

Prepared By:

Sanvin Zheng

Sanvin Zheng/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Feb. 23, 2023	

1. General Information

1.1. Description of equipment

EUT* Name	:	K106
Model Number	:	K106
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	Battery 1.5V ("AAA" Size)
Radio Specification	:	2.4G SRD
Operation Frequency	:	2402 MHz - 2480 MHz
Modulation	:	GFSK
Data Rate	:	1Mbps, 2 Mbps
Antenna Gain	:	Left-handle Maximum PK gain: 0.5 dBi Right-handle Maximum PK gain: 0.9 dBi
Sample Number	:	S23011007-02 for conductive S23011007-03 for radiation

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance

Left-handle:

GFSK_1M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-16.39	-18.53	-17.37
Tolerance \pm (dB)	1	1	1
GFSK_2M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-16.26	-18.60	-17.22
Tolerance \pm (dB)	1	1	1

Right-handle:

GFSK_1M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-6.18	-5.34	-5.07
Tolerance \pm (dB)	1	1	1
GFSK_2M (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	-6.18	-5.35	-5.07
Tolerance \pm (dB)	1	1	1

Estimation Result

Worse case is as below: [2480 MHz, -4.07 dBm, (0.39 mW) output power]

$(0.39/5) \cdot [\sqrt{2.480(\text{GHz})}] = 0.12 < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required.

END OF REPORT