

FCC RF Exposure

EUT Description: Smart lever lock with fingerprint

Test type: B203A PRO

Series model: B201A PRO, B201A mini, B201A PLUS, B201A MAX, B202A PRO, B202A mini, B202A PLUS, B202A MAX, B203 PRO, B203A mini, B203A PLUS, B203A MAX, B204A PRO, B204A mini, B204A PLUS, B204A MAX, B205A PRO, B205A mini, B205A PLUS, B205A MAX, B206A PRO, B206A mini, B206A PLUS, B206A MAX, B207A PRO, B207A mini, B207A PLUS, B207A MAX, B208A PRO, B208A mini, B208A PLUS, B208A MAX,

FCC ID: 2A97U-B203APRO

Equipment type: Mobile equipment

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where :

P_d = power density in mW/cm²,

P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale,

π = 3.14;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Test Result of RF Exposure Evaluation

Modulation	Channel Freq. (MHz)	Conducted power (dBm)	Max tune-up power (mW)	Antenna Gain (dBi)	Antenna gain numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2402	0.97	1.250259	1.97	1.58	0.0004056	1
	2440	0.73	1.183041	1.97	1.58	0.0003838	1
	2480	1.23	1.327394	1.97	1.58	0.0004306	1

Conclusion: the max result : 0.0004306 ≤ 1.0 compliance with FCC's RF Exposure.

Conclusion: No SAR is required