

A	1		2		3		4		5		6		A	
							版本	标记	变更描述		修定者	修定日期		生效日期
							A0		初版发行		邱平秀宇	2024-5-22		
B														B
C														C
D														D

OSCAL Portable Power Station(Lithium-ion battery) Model: PowerMax 1800 Total Output Power: 1800W AC Output*3: 120V~ 50Hz/60Hz,Total 1800W Wireless Output: 15W Max USB-A Output: 5V~3A,15W USB-A QC3.0 Output: 5V~3A,9V~2A,12V~1.5A,18W Max Type-C PD3.0 Output*2: 5/9/12/15V~3A,20V~5A,Total 200W DC5521 Output*2: 12V~6A Max,Total 72W Car Charge Output: 12V~10A Max,120W Max Battery Capacity: 25.6V~,40Ah,1024Wh Extra Battery Port: 25.6V~,40A Max AC Input: 100-120V~,15A Max 50Hz/60Hz Solar Input: 12-60V~,20A Max,800W Max Discharging Temperature: -10°C~45°C Charging Temperature Of Cells: 0°C~45°C FCC ID: 2A98M-POWERMAL1800 8IFpR41/136-2 Made in China Manufacturer:Shenzhen Doke Communication Co., Ltd Warnings 1. Do not disconnect, disassemble or repair by yourself. 2. Do not drop, deform, impact, cut or spearing with a sharp object. 3. Do not place near open fame or incinerate. 4. Do not sit or put heavy things on battery. Keep away from moisture or liquid. 5. Do not parallel connection with different batteries. 6. Do not connect batteries in series. 7. Recharge battery in every six months. 8. Disposal of batteries should follow local regulations. S/N LI-Ion 30 RoHS													B

美规铭牌													
料号：													
技术要求													
尺寸：139.6*69.6mm													
材质：哑银龙													
印刷：黑底银字													

尺寸公差		制定			名称		
0~5	±0.05	审核			编码		
5~10	±0.08	批准			图号		
10~25	±0.10		THIRD ANGLE PROJECTION		比例	1:1	单位
25~50	±0.12	版本			A0	页码	
≥50	±0.15					1 OF 1	

1		2		3		4		5		6	
---	--	---	--	---	--	---	--	---	--	---	--

Label location:

