

## **FCC ID : 2A99YPE-1000**

### ➤ **Test Standards and Limits**

#### **1. According to KDB 447498 D01 v06, Section 4.3.1**

#### **2. FCC Radiofrequency radiation exposure limits:**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max power of channel})/(\text{min test separation distance})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

For 2.4G band device, the limit of worse case is

$$P_{\text{max}} \leq 3.0 \cdot D_{\text{min}} / f = 3.0 \cdot 5 / 2.480 = 9.525 \text{ mW}$$

### ➤ **Measurement and Calculation**

#### **1. Maximum transmit power**

Antenna Gain: 2.53 dBi

Operation Mode	Modulation	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)
Bluetooth DTS_1M	GFSK	0	2402	4.34	4 to 6	6.00
		19	2440	4.30	4 to 6	6.00
		39	2480	4.72	4 to 6	6.00
Bluetooth DTS_2M	GFSK	0	2402	5.51	4 to 6	6.00
		19	2440	4.50	4 to 6	6.00
		39	2480	5.97	4 to 6	6.00

#### **2. MPE Calculation**

The Max Conducted Peak Output Power is 6.00 dBm.

The Max Antenna Gain is 2.53 dBi.

According to the formula, calculate the EIRP test result:

$$\text{EIRP} = P \times G = 7.129 \text{ mW} < 9.525 \text{ mW}$$

**So the SAR report is not required.**

-End of the Report-