



Certification Exhibit

FCC ID: 2A9ATIN-5001

FCC Rule Part: 47 CFR Part 2.1093

TÜV SÜD Project Number: 72183115

Manufacturer: Innara Health Inc.
Model: IN-5001, Rev 1

RF Exposure

TÜV SÜD America
5610 West Sligh Ave., Suite
100
Tampa, FL 33634

Phone: 813-284-2715
www.tuv-sud-america.com

TÜV SÜD

TÜV®

General Information:

Applicant: Innara Health Inc.
Environment: General Population/Uncontrolled Exposure
Exposure Conditions: Portable

Technical Information:

Minimum Test Separation Distance: 5 mm
Highest Operating Frequency: 915 MHz
Antenna Type: Chip
Antenna Gain: 0.5 dBi
Maximum Transmitter Conducted Power: -7.02 dBm, 0.19860949 mW
Maximum Transmitter EIRP: -6.52 dBm, 0.22284351 mW

*Maximum Transmitter conducted power derived from radiated field strength measurement and corrected for antenna gain.

Justification for SAR Test Exclusion:**Standalone SAR Test Exclusion:**

Per KDB 447498 D01 General RF Exposure Guidance v05r02, the standalone 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$= (0.19860949 / 5) * (\sqrt{0.91}) = 0.03800$$

0.03800 < 3.0

Standalone SAR test exclusion is applied.