

产品规格书

Product specification book



规格编号 Specification number	20220829004
生效日期 effective date	2022/8/29

公司名称 company name	东莞市佳家通塑胶模具有限公司 Dongguan jiajiaotong plastic mould Co., Ltd
产品类型 product type	A11线圈/A11 coil
天线增益 antenna gain	0dBi
料号 P/N(Part Number)	TX-HBY20220829004-45开双槽12TS L=30MM
客户料号 Customer Material Number	

【☒新版发行, ☐版本修订】 【本规范含目录共 3页】 【RoHS Compliant Parts】

编制 authorized strength	审核 audit	批准 ratify

本承认书在客户收到30天内, 请务必签章返回, 逾期视为生产时按此承认书的标准执行。
Please be sure to sign and seal this letter of acceptance within 30 days after receipt by the customer. If the deadline is overdue, it will be deemed that the production shall be performed according to the standard of this letter of acceptance.

【客户核准/Customer approval】

日期/date:

承认状态/Admit status: ☐完全承认/ ☐条件承认 ☐拒绝承认


批准/ratify	审核/audit	复检/recheck	检查/check

说明/explain:

产品规格书
Product specification book

客户名称 customer name	东莞市佳家通塑胶模具有限公司 Dongguan jiajiaotong plastic mould Co., Ltd	客户料号 Customer Material Number	
料号 P/N(Part Number)	TX-HBY20220829004-45开双槽12TS L=30MM	规格编号 Specification	20220829004
发行/修订记录 Record of issues/revisions			
版本versions	生效日期 effective date	变更内容/原因 Change content/reason	核准 examine and approve
01	2022/8/29	新规格发行 New specifications issued	
编制 authorized strength		审核 audit	批准 ratify

产品规格书
Product specification book

客户名称 customer name		东莞市佳家通塑胶模具有限公司 Dongguan jiajiaotong plastic mould Co., Ltd		客户料号 Customer Material Number							
料号 P/N(Part Number)		TX-HBY20220829004-45开双槽12TS L=30MM		规格编号 Specification number		20220829004		版本		01	
◆、外形尺寸/boundary dimension 								(单位/unit: mm)			
								A		44.0 ±1	
								B		40.0 ±0.5	
								C		13.5 ±0.5	
								D		5.3Ref ±0.5	
								E		10.0 Ref	
								F		3.0 ±1.0	
								G		2.2 ±0.5	
								H		30.0 ±1.0	
								I		±0.1(磁片厚度) The thickness of 0.8 the disk	
								(1)线径: 0.08*105P 丝包线 (1) Wire diameter: 0.08*105P covered wire			
								(2)绕线圈数:12TS (2) Number of winding turns :12TS			
								(3)起尾线是否交叉: 是 (3) Whether the starting line is crossed: Yes			
								(4)线圈包8mm宽高温胶带 (4) Coil package 8mm wide high temperature tape			
(5)线圈与磁片需粘居中 (5) The coil and the magnetic chip shall be stuck in the center											
(6)磁片背43双槽圆双面胶 (6) Magnetic disc back 43 double groove round double-sided adhesive											
◆、电气特性/electrical specificatio:											
参数/parameter		规格/specification		测试条件/test condition		测试仪器/test instrument					
L0		6.6 ±5%		μH		100KHz/1V		■TH1816B			
Q		>60		min		100KHz/1V		■TH1816B			
DCR		<50		mΩ		@ 25℃		■CH-502BC			
◆、温度等级/temperature grade:											
操作温度 operatingtemperature		-40℃~ 125℃									
◆、材料清单: bill of materials											
序号 serial number		品名 Trade name		材料规格 material specification		供应商 supplier		备注 remark			
1		磁片 magnetic sheet		43.5*0.8*10T 开双槽				PC95猛锌 PC95 fierce zinc			
2		铜线 copper wire		0.08*105P				丙铜丝包线 Propane copper covered wire			
3		高温胶带 high temperature tape		8MM				环保胶带 Masking tape			
4		锡 tin		107H				千岛环保锡 Thousand island environmental tin			
5		胶 glue		黄胶 cement				环保胶水 Environmental protection glue			
6		胶/glue		43双槽圆双面胶 43 double groove round double-sided adhesive				环保 environmental protection			
编制 authorized strength				审核 audit				批准 ratify			