



RF exposure Estimation

1. Introduction

Product: Display

Model no.: DP E161.CAN

FCC ID: 2A9GN-DPE161C

The EUT is a Display which contain BLE function inside.

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Conducted Power + tune up tolerance = $1.95 \text{ dBm} = 1.57 \text{ mW}$

Distance = 5 mm

$f = 2.480 \text{ GHz}$

$[1.57/5] * \text{SQRT}(2.480) = 0.4935$

$0.4935 \leq 3.0$

Therefore, excluded from SAR testing.



Exemption from Routine Evaluation – SAR Evaluation

4. Introduction

The EUT is a Display operated at 2402-2480MHz for BLE.

Model: DP E161.CAN

IC: 29737-DPE161C

5. Limit and Guidelines on Exposure to Electromagnetic Fields

According to RSS-102 § (2.5.1), SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in below Table:

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance^{4,5}

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of 50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

6. Calculation method

Maximum conducted peak output power of the EUT is 1.567mW (1.95dBm), and the specified separation distance defined by the client is at least 5mm. According to the above table 1, the output power level is less than 4mw meet Exemption from Routine Evaluation Limits – RF Exposure Evaluation, so SAR evaluation is not necessary.



- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
Reviewed by: Prepared by: Tested by:

A handwritten signature in blue ink, appearing to read "Hui TONG".

Hui TONG
EMC Section Manager
Date: 2023-04-18

A handwritten signature in blue ink, appearing to read "Wenqiang LU".

Wenqiang LU
EMC Project Engineer
Date: 2023-04-18

A handwritten signature in blue ink, appearing to read "Yiquan WANG".

Yiquan WANG
EMC Test Engineer
Date: 2023-04-18