

FCC SAR Test Report

Client Name : XKey Solutions LLC

Client Address : 930 Roosevelt #333, Irvine, CA 92620, United States

Product Name : LTE Tablet

Report Date : Jan. 03, 2022

Shenzhen Anbotek Compliance Laboratory Limited



Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com

Code: AB-RF-05-b



Hotline

400 003 0500

www.anbotek.com.cn



Contents

1. Statement of Compliance	6
2. General Information	7
2.1. Client Information	7
2.2. Description of Equipment Under Test (EUT)	7
2.3. Device Category and SAR Limits	8
2.4. Applied Standard	8
2.5. Environment of Test Site	8
2.6. Test Configuration	8
3. Specific Absorption Rate (SAR)	9
3.1. Introduction	9
3.2. SAR Definition	9
4. SAR Measurement System	10
4.1. E-Field Probe	11
4.2. Data Acquisition Electronics (DAE)	11
4.3. Robot	12
4.4. Measurement Server	13
4.5. Phantom	13
4.6. Device Holder	14
4.7. Data Storage and Evaluation	15
5. Test Equipment List	18
6. Tissue Simulating Liquids	19
7. System Verification Procedures	21
8. EUT Testing Position	23
8.1. Body Position	23
8.2. Hotspot Mode Exposure conditions	23
9. Measurement Procedures	24
9.1. Spatial Peak SAR Evaluation	24
9.2. Power Reference Measurement	25
9.3. Area Scan Procedures	25
9.4. Zoom Scan Procedures	26
9.5. Volume Scan Procedures	27
9.6. Power Drift Monitoring	27
10. Conducted Power	28
11. Antenna Location	50
12. SAR Test Results Summary	52
12.1. Body-worn and Hotspot SAR Results	53
13. Simultaneous Transmission Analysis	57
Simultaneous TX SAR Considerations	57



Evaluation of Simultaneous SAR.....	58
14. Measurement Uncertainty.....	60
Appendix A. EUT Photos and Test Setup Photos	62
Appendix B. Plots of SAR System Check.....	63
Appendix C. Plots of SAR Test Data	71
Appendix D. DASY System Calibration Certificate.....	81



TEST REPORT

Applicant : XKey Solutions LLC
Manufacturer : XKey Solutions LLC
Product Name : LTE Tablet
Model No. : RG1, XK8 ,MK8, SC8, MT8
Trade Mark : N.A.
Rating(s) : Input: DC 5V, 2A(with DC 3.7V, 4000mAh battery inside)

**Test Standard(s) : IEC 62209-2:2010; IEEE 1528:2013; FCC 47 CFR Part 2 (2.1093:2013);
ANSI/IEEE C95.1:2005; Reference FCC KDB 447498; KDB 248227;
KDB 616217; KDB 941225; KDB 865664**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the IEEE 1528-2013, FCC 47 CFR Part 2 (2.1093), ANSI/IEEE C95.1:2005 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Nov. 24, 2022

Date of Test

Dec. 01 - 15, 2022

Prepared By

Ella Liang

(Ella Liang)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Version

Version No.	Date	Description
R00	Jan. 03, 2022	Original



1. Statement of Compliance

<Highest SAR Summary>

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013. The maximum results of Specific Absorption Rate (SAR) found during testing are as follows.

<Highest SAR Summary>

FrequencyBand	Highest Reported 1g-SAR(W/Kg)	SAR Test Limit (W/Kg)
	Body-worn and Hotspot(10mm)	
LTE Band 2	0.639	1.6
LTE Band 5	0.640	
LTE Band 12	0.648	
LTE Band 13	0.576	
LTE Band 41	0.706	
LTE Band 66	0.699	
WLAN2.4G	0.510	
WLAN5.2G	0.262	
WLAN5.8G	0.240	
Simultaneous Reported SAR (W/Kg)	1.214	
Test Result	PASS	

Note: FDD band 12 and band 17 works at the overlap frequency band, the maximum power of band 12 is 23.76dBm which higher than band 17, so we only select band 12 for test. The same method for FDD band 4 and band 66, only band 66(the maximum power is 22.86dBm) is selected for test.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.



2. General Information

2.1. Client Information

Applicant	:	XKey Solutions LLC
Address	:	930 Roosevelt #333, Irvine, CA 92620, United States
Manufacturer	:	XKey Solutions LLC
Address	:	930 Roosevelt #333, Irvine, CA 92620, United States

2.2. Description of Equipment Under Test (EUT)

Product Name	:	LTE Tablet
Model No.	:	RG1, XK8 ,MK8, SC8, MT8 (Note: All samples are the same except the model number, so we prepare "RG1" for test only.)
Trade Mark	:	N.A.
Test Power Supply	:	DC 3.7V
Test Sample No.	:	1-2-1(Engineering Sample)
TX Frequency	:	BT BDR+EDR/BT BLE: 2402-2480MHz 2.4G WIFI: 2412-2462MHz 5.2G WIFI: 5180MHz~5240MHz 5.8G WIFI: 5745MHz~5825MHz LTE-FDD Band 2: TX:1850.7 ~ 1909.3 MHz LTE-FDD Band 4: TX:1710.7 ~ 1754.3 MHz LTE-FDD Band 5: TX: 824.7 ~ 848.3 MHz LTE-FDD Band 12: TX: 699.7 ~ 715.3 MHz LTE-FDD Band 13: TX: 779.5 ~ 784.5 MHz LTE-FDD Band 17: TX: 706.5 ~ 713.5 MHz LTE-TDD Band 41: TX: 2567.5 ~ 2642.5 MHz LTE-FDD Band 66: TX:1710.7 ~ 1779.3 MHz
Type of Modulation	:	GSM:GMSK, 8PSK WCDMA:QPSK,16QAM LTE:QPSK,16QAM BT: GFSK, $\pi/4$ -DQPSK, 8DPSK 2.4G WIFI:BPSK,QPSK,16QAM,64QAM 5G WIFI:OFDM with BPSK/QPSK/16QAM/64QAM/256QAM
Category of device	:	Portable device
Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.		



2.3. Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

2.4. Applied Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093:2013)
- ANSI/IEEE C95.1:2005
- IEEE Std 1528:2013
- KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- KDB 865664 D02 RF Exposure Reporting v01r02
- KDB 447498 D01 General RF Exposure Guidance v06
- KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- KDB 941225 D05 SAR for LTE Devicesv02r05
- KDB 941225 D06 Hotspot SARv02r01
- KDB 648474 D04 Handset SAR v01r03

2.5. Environment of Test Site

Items	Required	Actual
Temperature (°C)	18-25	22~23
Humidity (%RH)	30-70	55~65

2.6. Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests. For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.



3. Specific Absorption Rate (SAR)

3.1. Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2. SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by


$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.



4. SAR Measurement System



DASY System Configurations

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

components are described in details in the following sub-sections.



4.1. E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

➤ E-Field Probe Specification

<EX3DV4 Probe>

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 W/kg; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Photo of EX3DV4

➤ E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

4.2. Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



**Photo of DAE**

4.3. Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX60XL) type from Stäubli SA (France). For the 6-axis controllersystem, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäublirobot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

**Photo of DASY5**

4.4. Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Photo of Server for DASY5

4.5. Phantom

<SAM Twin Phantom>


Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.



<ELI4 Phantom>


Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

4.6. Device Holder

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



**Device Holder**

4.7. Data Storage and Evaluation

➤ Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [W/kg]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-loss media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

➤ Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The



parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm _i , a _{i0} , a _{i1} , a _{i2}
	- Conversion factor	ConvF _i
	- Diode compression point	dcp _i
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i, (i = x, y, z)

U_i = input signal of channel i, (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated:

$$\text{E-field Probes: } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field Probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with V_i = compensated signal of channel i, (i = x, y, z)

Norm_i = sensor sensitivity of channel i, (i = x, y, z), $\mu\text{V}/(\text{V/m})^2$ for E-field Probes

ConvF = sensitivity enhancement in solution

a_{ij} = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]



E_i = electric field strength of channel i in V/m

H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in W/kg

E_{tot} = total field strength in V/m

σ = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm³

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.



5. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1163	Jun. 08,2021	Jun. 07,2024
SPEAG	835MHz System Validation Kit	D835V2	4d154	Jun. 16,2021	Jun. 15,2024
SPEAG	1750MHz System Validation Kit	D1750V2	1021	Jul. 01,2021	Jun. 30,2024
SPEAG	1900MHz System Validation Kit	D1900V2	5d175	Jun. 15,2022	Jun. 14,2025
SPEAG	2450MHz System Validation Kit	D2450V2	910	Jun. 15,2021	Jun. 14,2024
SPEAG	2600MHz System Validation Kit	D2600V2	1058	Jun. 19,2021	Jun. 18,2024
SPEAG	5GHz System Validation Kit	D5GHzV2	1160	Oct. 02, 2021	Oct. 01, 2024
Rohde & Schwarz	UNIVERSAL RADIO COMMUNICATION TESTER	CMW500	167336	Oct.13, 2022	Oct.12, 2023
SPEAG	Data Acquisition Electronics	DAE4	387	Sept.06,2022	Sept.05,2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7396	May 06,2022	May 05,2023
Agilent	ENA Series Network Analyzer	E5071C	MY46317418	Oct.26, 2022	Oct.25, 2023
SPEAG	DAK	DAK-3.5	1226	NCR	NCR
SPEAG	SAM Twin Phantom	QD000P40CD	1802	NCR	NCR
SPEAG	ELI Phantom	QDOVA004A A	2058	NCR	NCR
AR	Amplifier	ZHL-42W	QA1118004	NCR	NCR
Agilent	Power Meter	N1914A	MY50001102	Oct.26, 2022	Oct.25, 2023
Agilent	Power Sensor	N8481H	MY51240001	Oct.26, 2022	Oct.25, 2023
R&S	Spectrum Analyzer	N9020A	MY51170037	Oct.26, 2022	Oct.25, 2023
Agilent	Signal Generation	N5182A	MY48180656	Oct.26, 2022	Oct.25, 2023
Worken	Directional Coupler	0110A05601O -10	COM5BNW1A2	Oct.26, 2022	Oct.25, 2023

Note:

1. The calibration certificate of DASY can be referred to appendix C of this report.
2. The dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The Insertion Loss calibration of Dual Directional Coupler and Attenuator were characterized via the network analyzer and compensated during system check.
4. The dielectric probe kit was calibrated via the network analyzer, with the specified procedure (calibrated in pure water) and calibration kit (standard) short circuit, before the dielectric measurement. The specific procedure and

Shenzhen Anbotek Compliance Laboratory Limited

Address:1/F.,Building D,Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86) 0755-26066440 Fax:(86) 0755-26014772 Email:service@anbotek.com

Code:AB-RF-05-b



Hotline

400 003 0500

www.anbotek.com.cn



calibration kit are provided by Agilent.

5. In system check we need to monitor the level on the power meter, and adjust the power amplifier level to have precise power level to the dipole; the measured SAR will be normalized to 1W input power according to the ratio of 1W to the input power to the dipole. For system check, the calibration of the power amplifier is deemed not critically required for correct measurement; the power meter is critical and we do have calibration for it.

6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown as followed:



Photo of Liquid Height for Head SAR



Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	40.9	57.1	0.2	1.5	0.3	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1750	55.2	0	0	0.3	0	44.5	1.37	40.1
1800,1900,2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
5200	65.5	0	17.2	0	17.3	0	4.66	36.0
5800	65.4	0	17.3	0	17.3	0	5.27	35.3



For Body								
750	50.8	48.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1750	70.2	0	0	0.4	0	29.4	1.49	53.4
1800,1900,2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	65.5	0	0	0	0	31.5	2.16	52.5
5200	78.6	0	10.7	0	10.7	0	5.27	49.0
5800	78.5	0	10.8	0	10.7	0	6.00	48.2

The following table shows the measuring results for simulating liquid.

Measured Frequency (MHz)	Target Tissue		Measured Tissue				Liquid Temp.	Test Data
	ϵ_r	σ	ϵ_r	Dev. (%)	σ	Dev. (%)		
750	41.9	0.89	41.69	-0.50	0.93	4.49	22.8	12/01/2022
835	41.5	0.90	41.58	0.19	0.94	4.44	22.6	12/02/2022
1750	40.1	1.37	40.21	0.27	1.42	3.65	22.6	12/07/2022
1900	40.0	1.40	40.19	0.47	1.44	2.86	22.7	12/09/2022
2450	39.2	1.80	39.07	-0.33	1.82	1.11	22.6	12/12/2022
2600	39.0	1.96	39.31	0.79	2.05	4.59	22.8	12/13/2022
5200	36.0	4.66	36.27	0.75	4.77	2.36	22.5	12/14/2022
5800	35.3	5.27	35.69	1.10	5.38	2.09	22.7	12/15/2022



7. System Verification Procedures


Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

➤ Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

➤ System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



System Setup for System Evaluation






Photo of Dipole Setup

➤ Validation Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10%. The table below shows the target SAR and measured SAR after normalized to 1W input power. It indicates that the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Power fed onto reference dipole (mW)	Targeted SAR (W/kg)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
12/01/2022	750	250	8.53	2.18	8.64	2.23
12/02/2022	835	250	9.57	2.33	9.44	-2.61
12/07/2022	1750	250	36.7	9.69	38.68	5.61
12/09/2022	1900	250	40.1	10.18	40.64	1.55
12/12/2022	2450	250	51.8	12.95	51.64	0.00
12/13/2022	2600	250	55.3	13.91	55.68	0.61
12/14/2022	5200	100	77.8	7.97	79.7	2.44
12/15/2022	5800	100	78.3	7.92	79.2	1.15

Target and Measurement SAR after Normalized




8. EUT Testing Position

8.1.Body Position

Devices that support transmission while used with body-worn accessories must be tested for body-worn accessory SAR compliance, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics.

Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance $\leq 5\text{mm}$ to support compliance.




Picture 4 Test positions for body-worn devices

8.2.Hotspot Mode Exposure conditions

The hotspot mode and body-worn accessory SAR test configurations may overlap for handsets. When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations. This typically applies to the back and front surfaces of a handset when SAR is required for both hotspot mode and body-worn accessory exposure conditions.

Depending on the form factor and dimensions of a device, the test separation distance used for hotspot mode SAR measurement is either

10 mm or that used in the body-worn accessory configuration, whichever is less for devices with dimension $> 9\text{ cm} \times 5\text{ cm}$. For smaller devices with dimensions $\leq 9\text{ cm} \times 5\text{ cm}$ because of a greater potential for next to body use a test separation of $\leq 5\text{ mm}$ must be used.



Picture 5 Test positions for Hotspot Mode



9. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the middle channel.
- (b) Keep EUT to radiate maximum output power or 100% duty factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as setup photos demonstrates.
- (e) Set scan area, grid size and other setting on the DASY software.
- (f) Measure SAR transmitting at the middle channel for all applicable exposure positions.
- (g) Identify the exposure position and device configuration resulting the highest SAR
- (h) Measure SAR at the lowest and highest channels at the worst exposure position and device configuration if applicable.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1. Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface



(f) Calculation of the averaged SAR within masses of 1g and 10g

9.2. Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3. Area Scan Procedures

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	$5 \pm 1 \text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	



9.4. Zoom Scan Procedures

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				



9.5. Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6. Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.



10. Conducted Power

<LTE Conducted Power>

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band2	1.4MHz	18607	1RB#0	23.17	22.12	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18607	1RB#2	23.37	22.33	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18607	1RB#5	23.13	22.11	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18607	3RB#0	23.16	22.03	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18607	3RB#1	23.16	22.02	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18607	3RB#3	23.12	21.97	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18607	6RB#0	22.19	21.00	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	1RB#0	22.96	21.84	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	1RB#2	23.04	21.94	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	1RB#5	22.95	21.80	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	3RB#0	23.05	21.87	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	3RB#1	23.07	21.90	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	3RB#3	23.09	21.85	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	18900	6RB#0	21.99	21.03	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	1RB#0	22.61	21.70	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	1RB#2	22.73	21.77	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	1RB#5	22.63	21.69	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	3RB#0	22.71	21.62	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	3RB#1	22.70	21.63	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	3RB#3	22.73	21.63	22.5±1.0	21.5±1.0
NTNV	Band2	1.4MHz	19193	6RB#0	21.73	20.62	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	1RB#0	22.79	22.21	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	1RB#8	22.97	22.09	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	1RB#14	22.76	22.05	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	8RB#0	22.11	21.08	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	8RB#4	22.11	21.07	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	8RB#7	22.17	21.06	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18615	15RB#0	22.04	21.03	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18900	1RB#0	22.96	22.14	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18900	1RB#8	22.91	22.00	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18900	1RB#14	22.92	22.00	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18900	8RB#0	21.92	21.03	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18900	8RB#4	21.95	20.99	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	18900	8RB#7	21.94	20.95	22.5±1.0	21.5±1.0



NTNV	Band2	3MHz	18900	15RB#0	21.94	20.89	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	1RB#0	22.60	21.53	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	1RB#8	22.67	21.54	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	1RB#14	22.62	21.53	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	8RB#0	21.67	20.70	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	8RB#4	21.69	20.70	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	8RB#7	21.71	20.76	22.5±1.0	21.5±1.0
NTNV	Band2	3MHz	19185	15RB#0	21.66	20.62	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	1RB#0	22.85	21.93	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	1RB#12	22.90	21.96	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	1RB#24	23.09	21.83	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	12RB#0	21.91	20.91	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	12RB#6	21.88	20.91	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	12RB#13	22.08	21.03	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18625	25RB#0	22.03	20.99	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	1RB#0	22.87	22.12	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	1RB#12	22.99	22.13	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	1RB#24	22.88	22.00	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	12RB#0	21.92	21.07	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	12RB#6	21.90	21.08	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	12RB#13	21.89	21.01	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	18900	25RB#0	21.96	21.01	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	1RB#0	22.64	21.64	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	1RB#12	22.74	21.68	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	1RB#24	22.62	21.60	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	12RB#0	21.50	20.68	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	12RB#6	21.57	20.63	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	12RB#13	21.66	20.75	22.5±1.0	21.5±1.0
NTNV	Band2	5MHz	19175	25RB#0	21.67	20.86	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	1RB#0	22.94	22.10	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	1RB#24	23.10	22.10	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	1RB#49	23.01	22.02	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	25RB#0	21.94	20.82	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	25RB#12	21.92	20.81	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	25RB#25	22.14	21.09	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18650	50RB#0	22.01	20.98	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18900	1RB#0	22.94	22.14	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18900	1RB#24	23.04	22.23	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18900	1RB#49	22.94	21.91	22.5±1.0	21.5±1.0



NTNV	Band2	10MHz	18900	25RB#0	22.09	21.14	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18900	25RB#12	22.07	21.19	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18900	25RB#25	22.00	21.10	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	18900	50RB#0	22.00	21.11	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	1RB#0	22.69	21.59	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	1RB#24	22.73	21.63	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	1RB#49	22.63	21.56	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	25RB#0	21.83	20.94	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	25RB#12	21.82	20.94	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	25RB#25	21.85	20.92	22.5±1.0	21.5±1.0
NTNV	Band2	10MHz	19150	50RB#0	21.81	20.86	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	1RB#0	22.98	22.06	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	1RB#38	23.06	22.04	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	1RB#74	22.87	22.03	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	38RB#0	22.13	22.13	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	38RB#18	22.16	22.15	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	38RB#37	22.19	22.16	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18675	75RB#0	22.18	21.01	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	1RB#0	22.91	22.21	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	1RB#38	22.96	22.17	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	1RB#74	22.90	21.92	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	38RB#0	22.12	22.14	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	38RB#18	22.13	22.13	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	38RB#37	22.12	22.11	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	18900	75RB#0	22.12	21.12	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	1RB#0	22.66	21.52	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	1RB#38	22.75	21.70	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	1RB#74	22.57	21.49	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	38RB#0	21.92	21.91	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	38RB#18	21.91	21.87	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	38RB#37	21.88	21.90	22.5±1.0	21.5±1.0
NTNV	Band2	15MHz	19125	75RB#0	21.90	20.93	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	1RB#0	22.89	21.79	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	1RB#49	23.25	22.01	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	1RB#99	22.81	21.83	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	50RB#0	21.64	20.62	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	50RB#25	21.68	20.64	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	50RB#50	21.93	20.96	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18700	100RB#0	21.83	20.80	22.5±1.0	21.5±1.0



NTNV	Band2	20MHz	18900	1RB#0	22.82	22.02	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18900	1RB#49	23.12	22.30	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18900	1RB#99	22.69	21.65	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18900	50RB#0	22.14	21.26	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18900	50RB#25	22.17	21.25	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18900	50RB#50	22.02	21.05	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	18900	100RB#0	22.09	21.16	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	1RB#0	22.47	21.46	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	1RB#49	22.77	21.89	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	1RB#99	22.32	21.40	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	50RB#0	21.85	20.94	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	50RB#25	21.87	20.99	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	50RB#50	21.73	20.81	22.5±1.0	21.5±1.0
NTNV	Band2	20MHz	19100	100RB#0	21.80	20.87	22.5±1.0	21.5±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band4	1.4MHz	19957	1RB#0	22.06	21.23	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	19957	1RB#2	22.16	21.37	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	19957	1RB#5	22.04	21.25	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	19957	3RB#0	22.14	21.13	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	19957	3RB#1	22.12	21.11	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	19957	3RB#3	22.17	21.13	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	19957	6RB#0	21.09	20.19	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	1RB#0	22.54	21.55	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	1RB#2	22.75	21.67	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	1RB#5	22.66	21.57	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	3RB#0	22.68	21.57	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	3RB#1	22.68	21.56	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	3RB#3	22.73	21.55	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20175	6RB#0	21.69	20.66	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	1RB#0	22.52	21.71	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	1RB#2	22.71	21.93	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	1RB#5	22.47	21.72	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	3RB#0	22.61	21.63	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	3RB#1	22.62	21.61	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	3RB#3	22.62	21.59	22.0±1.0	21.0±1.0
NTNV	Band4	1.4MHz	20393	6RB#0	21.61	20.68	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	19965	1RB#0	22.07	21.35	22.0±1.0	21.0±1.0



NTNV	Band4	3MHz	19965	1RB#8	22.14	21.36	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	19965	1RB#14	22.16	21.38	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	19965	8RB#0	21.15	20.22	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	19965	8RB#4	21.14	20.19	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	19965	8RB#7	21.21	20.25	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	19965	15RB#0	21.13	20.14	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	1RB#0	22.61	21.80	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	1RB#8	22.60	21.84	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	1RB#14	22.62	21.85	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	8RB#0	21.66	20.65	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	8RB#4	21.67	20.66	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	8RB#7	21.63	20.67	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20175	15RB#0	21.67	20.56	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	1RB#0	22.70	21.54	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	1RB#8	22.70	21.56	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	1RB#14	22.65	21.61	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	8RB#0	21.64	20.70	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	8RB#4	21.67	20.69	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	8RB#7	21.64	20.64	22.0±1.0	21.0±1.0
NTNV	Band4	3MHz	20385	15RB#0	21.60	20.58	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	1RB#0	22.06	21.14	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	1RB#12	22.23	21.30	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	1RB#24	22.15	21.25	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	12RB#0	21.14	20.13	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	12RB#6	21.07	20.14	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	12RB#13	21.23	20.21	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	19975	25RB#0	21.20	20.23	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	1RB#0	22.52	21.84	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	1RB#12	22.68	21.87	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	1RB#24	22.63	21.84	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	12RB#0	21.62	20.73	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	12RB#6	21.64	20.73	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	12RB#13	21.64	20.75	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20175	25RB#0	21.69	20.67	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20375	1RB#0	22.64	21.65	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20375	1RB#12	22.71	21.74	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20375	1RB#24	22.60	21.67	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20375	12RB#0	21.65	20.74	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20375	12RB#6	21.65	20.71	22.0±1.0	21.0±1.0



NTNV	Band4	5MHz	20375	12RB#13	21.68	20.72	22.0±1.0	21.0±1.0
NTNV	Band4	5MHz	20375	25RB#0	21.72	20.78	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	1RB#0	22.05	21.36	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	1RB#24	22.37	21.52	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	1RB#49	22.28	21.58	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	25RB#0	21.21	20.20	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	25RB#12	21.20	20.22	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	25RB#25	21.45	20.45	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20000	50RB#0	21.28	20.27	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	1RB#0	22.52	21.73	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	1RB#24	22.74	21.90	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	1RB#49	22.72	21.90	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	25RB#0	21.72	20.72	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	25RB#12	21.69	20.69	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	25RB#25	21.72	20.73	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20175	50RB#0	21.70	20.71	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	1RB#0	22.67	21.64	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	1RB#24	22.82	21.75	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	1RB#49	22.59	21.60	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	25RB#0	21.83	20.86	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	25RB#12	21.80	20.88	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	25RB#25	21.78	20.85	22.0±1.0	21.0±1.0
NTNV	Band4	10MHz	20350	50RB#0	21.79	20.78	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	1RB#0	22.01	21.23	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	1RB#38	22.31	21.55	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	1RB#74	22.35	21.60	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	38RB#0	21.39	21.37	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	38RB#18	21.40	21.38	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	38RB#37	21.38	21.41	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20025	75RB#0	21.40	20.34	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	1RB#0	22.41	21.70	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	1RB#38	22.69	22.02	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	1RB#74	22.66	21.99	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	38RB#0	21.72	21.69	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	38RB#18	21.70	21.70	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	38RB#37	21.70	21.70	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20175	75RB#0	21.71	20.65	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20325	1RB#0	22.74	21.61	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20325	1RB#38	22.85	21.76	22.0±1.0	21.0±1.0



NTNV	Band4	15MHz	20325	1RB#74	22.62	21.55	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20325	38RB#0	21.78	21.81	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20325	38RB#18	21.81	21.79	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20325	38RB#37	21.76	21.81	22.0±1.0	21.0±1.0
NTNV	Band4	15MHz	20325	75RB#0	21.80	20.78	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	1RB#0	21.91	20.96	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	1RB#49	22.47	21.49	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	1RB#99	22.48	21.49	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	50RB#0	21.18	20.18	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	50RB#25	21.12	20.16	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	50RB#50	21.58	20.55	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20050	100RB#0	21.37	20.40	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	1RB#0	22.19	21.37	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	1RB#49	22.77	21.93	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	1RB#99	22.61	21.82	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	50RB#0	21.55	20.63	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	50RB#25	21.64	20.62	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	50RB#50	21.71	20.72	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20175	100RB#0	21.60	20.62	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	1RB#0	22.31	21.49	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	1RB#49	22.75	21.91	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	1RB#99	22.34	21.51	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	50RB#0	21.86	20.86	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	50RB#25	21.83	20.90	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	50RB#50	21.79	20.88	22.0±1.0	21.0±1.0
NTNV	Band4	20MHz	20300	100RB#0	21.75	20.80	22.0±1.0	21.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band5	1.4MHz	20407	1RB#0	22.86	22.02	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20407	1RB#2	22.87	22.24	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20407	1RB#5	22.90	22.08	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20407	3RB#0	22.93	22.00	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20407	3RB#1	22.95	21.91	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20407	3RB#3	22.94	22.01	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20407	6RB#0	21.86	20.76	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20525	1RB#0	22.83	22.07	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20525	1RB#2	23.03	22.30	22.5±1.0	21.5±1.0



NTNV	Band5	1.4MHz	20525	1RB#5	22.93	22.13	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20525	3RB#0	23.00	21.96	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20525	3RB#1	22.99	21.98	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20525	3RB#3	22.99	21.97	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20525	6RB#0	21.91	20.99	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	1RB#0	23.04	21.93	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	1RB#2	23.24	22.18	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	1RB#5	23.12	22.02	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	3RB#0	23.11	22.04	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	3RB#1	23.16	22.01	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	3RB#3	23.22	22.04	22.5±1.0	21.5±1.0
NTNV	Band5	1.4MHz	20643	6RB#0	22.08	21.10	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	1RB#0	22.90	22.14	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	1RB#8	22.92	22.11	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	1RB#14	22.95	22.11	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	8RB#0	21.87	20.94	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	8RB#4	21.90	20.95	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	8RB#7	21.94	21.00	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20415	15RB#0	21.88	20.96	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	1RB#0	22.97	22.16	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	1RB#8	22.95	22.13	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	1RB#14	23.03	22.15	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	8RB#0	21.93	20.97	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	8RB#4	21.91	20.99	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	8RB#7	21.92	20.96	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20525	15RB#0	21.93	20.94	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	1RB#0	23.07	21.95	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	1RB#8	23.10	22.01	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	1RB#14	23.16	22.08	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	8RB#0	22.15	21.15	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	8RB#4	22.11	21.21	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	8RB#7	22.12	21.12	22.5±1.0	21.5±1.0
NTNV	Band5	3MHz	20635	15RB#0	22.09	21.01	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20425	1RB#0	22.96	21.97	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20425	1RB#12	23.09	22.16	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20425	1RB#24	22.96	22.04	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20425	12RB#0	21.89	20.96	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20425	12RB#6	21.91	20.94	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20425	12RB#13	21.91	21.00	22.5±1.0	21.5±1.0



NTNV	Band5	5MHz	20425	25RB#0	21.99	21.02	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	1RB#0	22.92	22.01	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	1RB#12	23.03	22.11	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	1RB#24	23.04	22.13	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	12RB#0	21.90	20.96	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	12RB#6	21.90	20.94	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	12RB#13	21.87	21.01	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20525	25RB#0	22.05	21.04	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	1RB#0	23.03	22.32	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	1RB#12	23.16	22.39	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	1RB#24	23.12	22.34	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	12RB#0	22.03	21.17	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	12RB#6	21.99	21.13	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	12RB#13	21.88	20.97	22.5±1.0	21.5±1.0
NTNV	Band5	5MHz	20625	25RB#0	22.01	21.06	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	1RB#0	22.75	22.01	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	1RB#24	23.01	22.18	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	1RB#49	22.85	22.14	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	25RB#0	22.00	20.97	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	25RB#12	21.97	20.98	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	25RB#25	21.99	21.06	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20450	50RB#0	22.02	20.99	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	1RB#0	22.87	22.05	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	1RB#24	22.89	22.22	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	1RB#49	23.02	22.27	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	25RB#0	21.97	20.98	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	25RB#12	21.93	20.99	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	25RB#25	21.95	21.03	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20525	50RB#0	21.95	20.95	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	1RB#0	23.02	21.94	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	1RB#24	23.19	22.13	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	1RB#49	23.11	22.02	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	25RB#0	22.13	21.23	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	25RB#12	22.12	21.22	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	25RB#25	21.94	21.01	22.5±1.0	21.5±1.0
NTNV	Band5	10MHz	20600	50RB#0	22.04	21.07	22.5±1.0	21.5±1.0



Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band12	1.4MHz	23017	1RB#0	23.52	22.74	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	1RB#2	23.70	22.87	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	1RB#5	23.57	22.70	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	3RB#0	23.73	22.61	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	3RB#1	23.71	22.63	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	3RB#3	23.72	22.57	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23017	6RB#0	22.60	21.70	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	1RB#0	23.55	22.65	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	1RB#2	23.59	22.84	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	1RB#5	23.52	22.69	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	3RB#0	23.57	22.52	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	3RB#1	23.57	22.54	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	3RB#3	23.60	22.54	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23095	6RB#0	22.52	21.39	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	1RB#0	23.25	22.17	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	1RB#2	23.42	22.37	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	1RB#5	23.32	22.20	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	3RB#0	23.43	22.25	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	3RB#1	23.41	22.29	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	3RB#3	23.47	22.25	23.0±1.0	22.0±1.0
NTNV	Band12	1.4MHz	23173	6RB#0	22.36	21.34	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	1RB#0	23.59	22.83	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	1RB#8	23.61	22.74	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	1RB#14	23.60	22.74	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	8RB#0	22.68	21.74	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	8RB#4	22.64	21.72	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	8RB#7	22.63	21.67	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23025	15RB#0	22.65	21.67	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	1RB#0	23.54	22.77	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	1RB#8	23.59	22.76	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	1RB#14	23.48	22.71	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	8RB#0	22.57	21.58	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	8RB#4	22.54	21.58	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	8RB#7	22.48	21.54	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23095	15RB#0	22.52	21.49	23.0±1.0	22.0±1.0



NTNV	Band12	3MHz	23165	1RB#0	23.49	22.32	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	1RB#8	23.33	22.25	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	1RB#14	23.38	22.31	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	8RB#0	22.39	21.45	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	8RB#4	22.43	21.39	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	8RB#7	22.43	21.42	23.0±1.0	22.0±1.0
NTNV	Band12	3MHz	23165	15RB#0	22.34	21.28	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	1RB#0	23.63	22.63	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	1RB#12	23.66	22.67	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	1RB#24	23.62	22.61	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	12RB#0	22.67	21.69	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	12RB#6	22.67	21.74	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	12RB#13	22.59	21.58	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23035	25RB#0	22.66	21.74	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	1RB#0	23.59	22.77	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	1RB#12	23.70	22.83	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	1RB#24	23.42	22.69	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	12RB#0	22.57	21.68	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	12RB#6	22.57	21.67	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	12RB#13	22.50	21.61	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23095	25RB#0	22.61	21.54	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	1RB#0	23.52	22.49	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	1RB#12	23.49	22.54	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	1RB#24	23.30	22.36	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	12RB#0	22.37	21.47	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	12RB#6	22.36	21.41	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	12RB#13	22.32	21.36	23.0±1.0	22.0±1.0
NTNV	Band12	5MHz	23155	25RB#0	22.39	21.45	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	1RB#0	23.60	22.81	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	1RB#24	23.66	22.91	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	1RB#49	23.53	22.75	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	25RB#0	22.81	21.80	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	25RB#12	22.83	21.77	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	25RB#25	22.60	21.62	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23060	50RB#0	22.72	21.69	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	1RB#0	23.56	22.72	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	1RB#24	23.70	22.95	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	1RB#49	23.46	22.66	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	25RB#0	22.69	21.76	23.0±1.0	22.0±1.0



NTNV	Band12	10MHz	23095	25RB#12	22.72	21.76	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	25RB#25	22.68	21.70	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23095	50RB#0	22.71	21.75	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	1RB#0	23.56	22.43	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	1RB#24	23.76	22.54	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	1RB#49	23.38	22.32	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	25RB#0	22.50	21.55	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	25RB#12	22.52	21.59	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	25RB#25	22.50	21.59	23.0±1.0	22.0±1.0
NTNV	Band12	10MHz	23130	50RB#0	22.49	21.53	23.0±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band13	5MHz	23205	1RB#0	23.08	22.11	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23205	1RB#12	23.32	22.32	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23205	1RB#24	23.13	22.18	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23205	12RB#0	22.23	21.32	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23205	12RB#6	22.29	21.34	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23205	12RB#13	22.14	21.23	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23205	25RB#0	22.28	21.27	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	1RB#0	23.15	22.36	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	1RB#12	23.27	22.46	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	1RB#24	23.08	22.25	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	12RB#0	22.12	21.26	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	12RB#6	22.13	21.22	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	12RB#13	22.29	21.32	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23230	25RB#0	22.32	21.24	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	1RB#0	23.17	22.16	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	1RB#12	23.31	22.25	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	1RB#24	23.11	22.14	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	12RB#0	22.02	21.07	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	12RB#6	21.97	21.08	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	12RB#13	22.20	21.27	22.5±1.0	21.5±1.0
NTNV	Band13	5MHz	23255	25RB#0	22.11	21.19	22.5±1.0	21.5±1.0
NTNV	Band13	10MHz	23230	1RB#0	23.11	22.31	22.5±1.0	21.5±1.0
NTNV	Band13	10MHz	23230	1RB#24	23.29	22.41	22.5±1.0	21.5±1.0
NTNV	Band13	10MHz	23230	1RB#49	23.07	22.32	22.5±1.0	21.5±1.0
NTNV	Band13	10MHz	23230	25RB#0	22.31	21.36	22.5±1.0	21.5±1.0



NTNV	Band13	10MHz	23230	25RB#12	22.33	21.31	22.5±1.0	21.5±1.0
NTNV	Band13	10MHz	23230	25RB#25	22.43	21.40	22.5±1.0	21.5±1.0
NTNV	Band13	10MHz	23230	50RB#0	22.39	21.40	22.5±1.0	21.5±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band17	5MHz	23755	1RB#0	23.60	22.53	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	1RB#12	23.66	22.69	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	1RB#24	23.50	22.53	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	12RB#0	22.56	21.64	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	12RB#6	22.57	21.62	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	12RB#13	22.55	21.57	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23755	25RB#0	22.62	21.62	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	1RB#0	23.46	22.71	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	1RB#12	23.58	22.75	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	1RB#24	23.45	22.65	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	12RB#0	22.49	21.53	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	12RB#6	22.52	21.53	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	12RB#13	22.51	21.58	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23790	25RB#0	22.54	21.53	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	1RB#0	23.44	22.40	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	1RB#12	23.55	22.56	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	1RB#24	23.33	22.36	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	12RB#0	22.37	21.42	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	12RB#6	22.37	21.45	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	12RB#13	22.32	21.42	23.0±1.0	22.0±1.0
NTNV	Band17	5MHz	23825	25RB#0	22.39	21.47	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	1RB#0	23.51	22.74	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	1RB#24	23.64	22.77	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	1RB#49	23.43	22.64	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	25RB#0	22.69	21.72	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	25RB#12	22.66	21.66	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	25RB#25	22.69	21.73	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23780	50RB#0	22.66	21.72	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	1RB#0	23.57	22.75	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	1RB#24	23.63	22.91	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	1RB#49	23.32	22.53	23.0±1.0	22.0±1.0



NTNV	Band17	10MHz	23790	25RB#0	22.61	21.67	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	25RB#12	22.65	21.62	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	25RB#25	22.64	21.67	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23790	50RB#0	22.61	21.67	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	1RB#0	23.55	22.42	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	1RB#24	23.64	22.45	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	1RB#49	23.35	22.26	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	25RB#0	22.51	21.59	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	25RB#12	22.51	21.64	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	25RB#25	22.55	21.67	23.0±1.0	22.0±1.0
NTNV	Band17	10MHz	23800	50RB#0	22.58	21.60	23.0±1.0	22.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band41	5MHz	40065	1RB#0	22.42	21.59	22.0±1.0	21.0±1.0
NTNV	Band41	5MHz	40065	1RB#12	22.43	21.61	22.0±1.0	21.0±1.0
NTNV	Band41	5MHz	40065	1RB#24	22.41	21.74	22.0±1.0	21.0±1.0
NTNV	Band41	5MHz	40065	12RB#0	21.52	20.63	22.0±1.0	21.0±1.0
NTNV	Band41	5MHz	40065	12RB#6	21.52	20.44	22.0±1.0	21.0±1.0
NTNV	Band41	5MHz	40065	12RB#13	21.58	20.58	22.0±1.0	21.0±1.0
NTNV	Band41	5MHz	40065	25RB#0	21.55	20.61	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	1RB#0	21.42	20.83	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	1RB#12	21.55	20.97	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	1RB#24	21.39	20.77	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	12RB#0	20.45	19.50	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	12RB#6	20.40	19.52	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	12RB#13	20.49	19.48	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	40590	25RB#0	20.53	19.54	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	1RB#0	21.43	20.74	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	1RB#12	21.59	20.90	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	1RB#24	21.42	20.68	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	12RB#0	20.51	19.62	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	12RB#6	20.55	19.61	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	12RB#13	20.51	19.64	21.0±1.0	20.0±1.0
NTNV	Band41	5MHz	41215	25RB#0	20.57	19.60	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40090	1RB#0	22.25	21.41	22.0±1.0	21.0±1.0
NTNV	Band41	10MHz	40090	1RB#24	22.57	21.56	22.0±1.0	21.0±1.0



NTNV	Band41	10MHz	40090	1RB#49	22.42	21.26	22.0±1.0	21.0±1.0
NTNV	Band41	10MHz	40090	25RB#0	21.44	20.40	22.0±1.0	21.0±1.0
NTNV	Band41	10MHz	40090	25RB#12	21.43	20.46	22.0±1.0	21.0±1.0
NTNV	Band41	10MHz	40090	25RB#25	21.42	20.45	22.0±1.0	21.0±1.0
NTNV	Band41	10MHz	40090	50RB#0	21.42	20.48	22.0±1.0	21.0±1.0
NTNV	Band41	10MHz	40590	1RB#0	21.59	20.47	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40590	1RB#24	21.71	20.56	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40590	1RB#49	21.48	20.40	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40590	25RB#0	20.60	19.60	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40590	25RB#12	20.60	19.59	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40590	25RB#25	20.61	19.70	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	40590	50RB#0	20.61	19.67	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	1RB#0	21.55	20.59	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	1RB#24	21.85	20.85	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	1RB#49	21.61	20.56	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	25RB#0	20.68	19.69	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	25RB#12	20.67	19.71	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	25RB#25	20.69	19.72	21.0±1.0	20.0±1.0
NTNV	Band41	10MHz	41190	50RB#0	20.66	19.69	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40115	1RB#0	22.53	21.40	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40115	1RB#38	22.50	21.30	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40115	1RB#74	22.39	21.34	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40115	38RB#0	21.56	21.55	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40115	38RB#18	21.55	21.55	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40115	38RB#37	21.55	21.55	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40115	75RB#0	21.55	20.46	22.0±1.0	21.0±1.0
NTNV	Band41	15MHz	40590	1RB#0	21.62	20.61	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40590	1RB#38	21.61	20.67	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40590	1RB#74	21.48	20.50	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40590	38RB#0	20.60	20.60	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40590	38RB#18	20.57	20.60	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40590	38RB#37	20.64	20.57	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	40590	75RB#0	20.57	19.57	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	41165	1RB#0	21.47	20.44	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	41165	1RB#38	21.70	20.67	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	41165	1RB#74	21.51	20.51	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	41165	38RB#0	20.63	20.66	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	41165	38RB#18	20.71	20.68	21.0±1.0	20.0±1.0
NTNV	Band41	15MHz	41165	38RB#37	20.70	20.71	21.0±1.0	20.0±1.0



NTNV	Band41	15MHz	41165	75RB#0	20.70	19.67	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40140	1RB#0	22.41	21.42	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40140	1RB#49	22.55	21.63	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40140	1RB#99	22.20	21.45	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40140	50RB#0	21.58	20.51	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40140	50RB#25	21.58	20.55	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40140	50RB#50	21.48	20.54	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40140	100RB#0	21.59	20.55	22.0±1.0	21.0±1.0
NTNV	Band41	20MHz	40590	1RB#0	21.43	20.04	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40590	1RB#49	21.66	20.27	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40590	1RB#99	21.24	19.93	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40590	50RB#0	20.53	19.58	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40590	50RB#25	20.53	19.58	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40590	50RB#50	20.55	19.63	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	40590	100RB#0	20.52	19.59	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	1RB#0	21.23	20.16	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	1RB#49	21.78	20.68	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	1RB#99	21.39	20.30	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	50RB#0	20.46	19.47	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	50RB#25	20.45	19.46	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	50RB#50	20.69	19.67	21.0±1.0	20.0±1.0
NTNV	Band41	20MHz	41140	100RB#0	20.55	19.59	21.0±1.0	20.0±1.0

Condition	Band	Channel Bandwidth	Channel	RB Configure	Result (dBm)		Tune-Up	
					QPSK	16QAM	QPSK	16QAM
NTNV	Band66	1.4MHz	131979	1RB#0	22.00	21.20	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	131979	1RB#2	22.12	21.27	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	131979	1RB#5	22.04	21.23	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	131979	3RB#0	22.14	21.11	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	131979	3RB#1	22.14	21.15	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	131979	3RB#3	22.16	21.09	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	131979	6RB#0	21.10	20.14	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	1RB#0	22.70	21.63	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	1RB#2	22.80	21.75	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	1RB#5	22.63	21.51	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	3RB#0	22.74	21.63	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	3RB#1	22.69	21.66	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	3RB#3	22.73	21.61	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132322	6RB#0	21.69	20.67	22.0±1.0	21.0±1.0



NTNV	Band66	1.4MHz	132665	1RB#0	22.64	21.75	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132665	1RB#2	22.76	21.93	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132665	1RB#5	22.70	21.77	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132665	3RB#0	22.72	21.70	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132665	3RB#1	22.74	21.69	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132665	3RB#3	22.75	21.70	22.0±1.0	21.0±1.0
NTNV	Band66	1.4MHz	132665	6RB#0	21.77	20.79	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	1RB#0	22.03	21.29	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	1RB#8	22.08	21.27	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	1RB#14	22.10	21.24	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	8RB#0	21.08	20.14	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	8RB#4	21.10	20.16	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	8RB#7	21.11	20.15	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	131987	15RB#0	21.10	20.12	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	1RB#0	22.63	21.91	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	1RB#8	22.63	21.80	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	1RB#14	22.60	21.79	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	8RB#0	21.69	20.73	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	8RB#4	21.67	20.69	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	8RB#7	21.68	20.67	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132322	15RB#0	21.67	20.62	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	1RB#0	22.70	21.61	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	1RB#8	22.76	21.64	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	1RB#14	22.71	21.68	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	8RB#0	21.76	20.79	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	8RB#4	21.83	20.74	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	8RB#7	21.81	20.79	22.0±1.0	21.0±1.0
NTNV	Band66	3MHz	132657	15RB#0	21.71	20.66	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	1RB#0	22.02	21.06	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	1RB#12	22.12	21.22	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	1RB#24	22.07	21.20	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	12RB#0	21.07	20.08	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	12RB#6	21.05	20.04	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	12RB#13	21.13	20.16	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	131997	25RB#0	21.11	20.15	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132322	1RB#0	22.64	21.95	22.0±1.0	21.5±1.0
NTNV	Band66	5MHz	132322	1RB#12	22.72	22.05	22.0±1.0	21.5±1.0
NTNV	Band66	5MHz	132322	1RB#24	22.60	21.83	22.0±1.0	21.5±1.0
NTNV	Band66	5MHz	132322	12RB#0	21.67	20.75	22.0±1.0	21.0±1.0



NTNV	Band66	5MHz	132322	12RB#6	21.74	20.74	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132322	12RB#13	21.72	20.71	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132322	25RB#0	21.71	20.69	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	1RB#0	22.56	21.60	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	1RB#12	22.75	21.80	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	1RB#24	22.68	21.75	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	12RB#0	21.69	20.78	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	12RB#6	21.75	20.78	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	12RB#13	21.68	20.74	22.0±1.0	21.0±1.0
NTNV	Band66	5MHz	132647	25RB#0	21.74	20.76	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	1RB#0	22.02	21.27	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	1RB#24	22.23	21.47	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	1RB#49	22.22	21.45	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	25RB#0	21.13	20.12	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	25RB#12	21.14	20.17	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	25RB#25	21.33	20.38	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132022	50RB#0	21.22	20.18	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	1RB#0	22.66	21.93	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	1RB#24	22.78	21.94	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	1RB#49	22.55	21.80	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	25RB#0	21.84	20.83	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	25RB#12	21.81	20.87	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	25RB#25	21.77	20.80	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132322	50RB#0	21.78	20.76	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	1RB#0	22.51	21.46	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	1RB#24	22.84	21.67	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	1RB#49	22.77	21.71	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	25RB#0	21.86	20.89	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	25RB#12	21.82	20.88	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	25RB#25	21.68	20.72	22.0±1.0	21.0±1.0
NTNV	Band66	10MHz	132622	50RB#0	21.74	20.71	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	1RB#0	21.99	21.24	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	1RB#38	22.24	21.45	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	1RB#74	22.32	21.59	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	38RB#0	21.32	21.30	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	38RB#18	21.29	21.30	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	38RB#37	21.31	21.31	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132047	75RB#0	21.31	20.25	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132322	1RB#0	22.58	21.91	22.0±1.0	21.0±1.0



NTNV	Band66	15MHz	132322	1RB#38	22.69	21.98	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132322	1RB#74	22.47	21.80	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132322	38RB#0	21.76	21.79	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132322	38RB#18	21.76	21.77	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132322	38RB#37	21.74	21.74	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132322	75RB#0	21.75	20.77	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	1RB#0	22.35	21.28	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	1RB#38	22.65	21.58	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	1RB#74	22.70	21.64	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	38RB#0	21.69	21.69	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	38RB#18	21.70	21.66	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	38RB#37	21.66	21.68	22.0±1.0	21.0±1.0
NTNV	Band66	15MHz	132597	75RB#0	21.67	20.66	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	1RB#0	21.88	20.97	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	1RB#49	22.57	21.53	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	1RB#99	22.42	21.47	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	50RB#0	21.10	20.12	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	50RB#25	21.09	20.10	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	50RB#50	21.50	20.50	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132072	100RB#0	21.30	20.33	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132322	1RB#0	22.44	21.70	22.0±1.0	21.5±1.0
NTNV	Band66	20MHz	132322	1RB#49	22.85	22.15	22.0±1.0	21.5±1.0
NTNV	Band66	20MHz	132322	1RB#99	22.35	21.67	22.0±1.0	21.5±1.0
NTNV	Band66	20MHz	132322	50RB#0	21.82	20.84	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132322	50RB#25	21.85	20.89	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132322	50RB#50	21.71	20.73	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132322	100RB#0	21.77	20.76	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	1RB#0	22.07	21.16	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	1RB#49	22.56	21.70	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	1RB#99	22.43	21.58	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	50RB#0	21.48	20.54	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	50RB#25	21.51	20.58	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	50RB#50	21.37	20.45	22.0±1.0	21.0±1.0
NTNV	Band66	20MHz	132572	100RB#0	21.47	20.51	22.0±1.0	21.0±1.0



<WLAN 2.4GHz Conducted Power>

Mode	Channel	Frequency (MHz)	Conducted Peak Output Power(dBm)	Conducted Average Output Power(dBm)	Tune-up power(dBm)
802.11b	1	2412	16.19	15.33	17.50
	6	2437	19.33	17.45	17.50
	11	2462	18.27	16.38	17.50
802.11g	1	2412	17.18	15.75	18.50
	6	2437	22.08	18.47	18.50
	11	2462	20.51	16.73	18.50
802.11n(HT20)	1	2412	17.18	15.46	18.50
	6	2437	21.81	18.27	18.50
	11	2462	20.59	16.67	18.50
802.11n(HT40)	3	2422	17.72	15.12	17.50
	6	2437	19.84	17.33	17.50
	9	2452	18.04	16.04	17.50

<WLAN 5GHz Conducted Power>

Band 1:

Mode	Channel Frequency (MHz)	Average Power output (dBm)	Tune-up power(dBm)
802.11a	5180	13.82	14.00
	5200	13.29	14.00
	5240	12.65	14.00
802.11n (HT20)	5180	13.65	14.00
	5200	9.28	14.00
	5240	12.25	14.00
802.11ac (HT20)	5180	13.41	14.00
	5200	12.81	14.00
	5240	12.18	14.00
802.11n (HT40)	5190	13.65	14.00
	5230	9.28	14.00
802.11ac (HT40)	5190	13.04	14.00
	5230	12.47	14.00



Band 4:

Mode	Channel Frequency (MHz)	Average Power output (dBm)	Tune-up power(dBm)
802.11a	5745	11.95	13.00
	5785	12.98	13.00
	5825	12.28	13.00
802.11n (HT20)	5745	12.69	13.00
	5785	12.28	13.00
	5825	11.99	13.00
802.11ac (HT20)	5745	11.72	12.00
	5785	11.85	12.00
	5825	11.86	12.00
802.11n (HT40)	5755	12.30	13.00
	5795	12.14	13.00
802.11ac (HT40)	5755	12.58	13.00
	5795	12.88	13.00

Note:

1. Per KDB 447498 D01, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2. Base on the result of note1, RF exposure evaluation of 2.4G/5.2G/5.8G WIFI mode is required.

3. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion.

4. Per KDB 248227 D01, In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. SAR is not required for the following 2.4 GHz OFDM conditions:

1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.

2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.



<Bluetooth Conducted Power>

Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Tune-up power(dBm)
BT BDR (GFSK)	00	2402	4.83	5.00
	39	2441	4.39	5.00
	78	2480	3.52	5.00
BT EDR (Π/4DQPSK)	00	2402	4.14	4.50
	39	2441	3.77	4.50
	78	2480	2.93	4.50
BT EDR (8DPSK)	00	2402	4.21	4.50
	39	2441	3.89	4.50
	78	2480	3.02	4.50
BT BLE_1M (GFSK)	00	2402	4.81	5.00
	19	2440	4.40	5.00
	39	2480	3.51	5.00

Note:

Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation


The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
5.00	5	2.48	0.996

Per KDB 447498 D01, when the minimum test separation distance is <10 mm, a distance of 10 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.996 which is ≤ 3 , SAR testing is not required.



11. Antenna Location



Distance of The Antenna to the EUT surface and edge

Antennas	Front	Back	Top Side	Bottom Side	Left Side	Right Side
BT&WLAN	<25mm	<25mm	<25mm	>25mm	>25mm	<25mm
WWAN	<25mm	<25mm	>25mm	<25mm	<25mm	>25mm



Positions for SAR tests; Body and Hotspot mode

Antennas	Front	Back	Top Side	Bottom Side	Left Side	Right Side
BT&WLAN	Yes	Yes	Yes	No	No	Yes
WWAN	Yes	Yes	No	Yes	Yes	No

General Note: According with FCC KDB 447498 D01, appendix A, <SAR test exclusion thresholds for 100MHz~6GHz and≤50mm> table, this device SAR test configurations considerations are shown in the table above.

Per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.



12. SAR Test Results Summary

General Note:

1.Per KDB 447498 D01v05r01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.

Scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.

Reported SAR(W/kg)= Measured SAR(W/kg) Scaling Factor*

2.Per KDB 447498 D01v05r01, for each exposure position, if the highest output channel reported $SAR \leq 0.8W/kg$, other channels SAR testing are not necessary

3.Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.

4.Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.

5.Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are $\leq 0.8 W/kg$. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is $> 1.45 W/kg$, the remaining required test channels must also be tested.

6.Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is $\leq 1.45 W/kg$; Per KDB 941225 D05, 16QAM SAR testing is not required.

7.Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is $\leq 1.45 W/kg$; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.

8.Per KDB865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8W/Kg$; if the deviation among the repeated measurement is $\leq 20\%$, and the measured SAR $< 1.45W/Kg$, only one repeated measurement is required.

9.When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



12.1. Body-worn and Hotspot SAR Results

<LTE>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR _{1g} (W/kg)	Reported SAR _{1g} (W/kg)
	LTE Band 2	20MHz/1RB	Front	10	18700	1860	23.25	23.5	1.059	-0.07	0.367	0.389
	LTE Band 2	20MHz/50RB	Front	10	18700	1860	21.93	23.5	1.435	-0.03	0.195	0.280
#1	LTE Band 2	20MHz/1RB	Back	10	18700	1860	23.25	23.5	1.059	0.11	0.603	0.639
	LTE Band 2	20MHz/50RB	Back	10	18700	1860	21.93	23.5	1.435	0.09	0.417	0.599
	LTE Band 2	20MHz/1RB	Left Side	10	18700	1860	23.25	23.5	1.059	0.18	0.479	0.507
	LTE Band 2	20MHz/50RB	Left Side	10	18700	1860	21.93	23.5	1.435	0.06	0.256	0.367
	LTE Band 2	20MHz/1RB	Right Side	10	18700	1860	23.25	23.5	1.059	N/A	N/A	N/A
	LTE Band 2	20MHz/50RB	Right Side	10	18700	1860	21.93	23.5	1.435	N/A	N/A	N/A
	LTE Band 2	20MHz/1RB	Top Side	10	18700	1860	23.25	23.5	1.059	N/A	N/A	N/A
	LTE Band 2	20MHz/50RB	Top Side	10	18700	1860	21.93	23.5	1.435	N/A	N/A	N/A
	LTE Band 2	20MHz/1RB	Bottom Side	10	18700	1860	23.25	23.5	1.059	0.10	0.581	0.615
	LTE Band 2	20MHz/50RB	Bottom Side	10	18700	1860	21.93	23.5	1.435	0.10	0.373	0.535
	LTE Band 5	10MHz/1RB	Front	10	20600	844	23.19	23.5	1.074	0.05	0.376	0.404
	LTE Band 5	10MHz/25RB	Front	10	20600	844	22.13	23.5	1.371	0.13	0.192	0.263
#2	LTE Band 5	10MHz/1RB	Back	10	20600	844	23.19	23.5	1.074	-0.02	0.596	0.640
	LTE Band 5	10MHz/25RB	Back	10	20600	844	22.13	23.5	1.371	0.11	0.346	0.474
	LTE Band 5	10MHz/1RB	Left Side	10	20600	844	23.19	23.5	1.074	0.08	0.331	0.355
	LTE Band 5	10MHz/25RB	Left Side	10	20600	844	22.13	23.5	1.371	-0.06	0.175	0.240
	LTE Band 5	10MHz/1RB	Right Side	10	20600	844	23.19	23.5	1.074	N/A	N/A	N/A
	LTE Band 5	10MHz/25RB	Right Side	10	20600	844	22.13	23.5	1.371	N/A	N/A	N/A
	LTE Band 5	10MHz/1RB	Top Side	10	20600	844	23.19	23.5	1.074	N/A	N/A	N/A
	LTE Band 5	10MHz/25RB	Top Side	10	20600	844	22.13	23.5	1.371	N/A	N/A	N/A
	LTE Band 5	10MHz/1RB	Bottom Side	10	20600	844	23.19	23.5	1.074	0.06	0.567	0.609
	LTE Band 5	10MHz/25RB	Bottom Side	10	20600	844	22.13	23.5	1.371	0.03	0.308	0.422



	LTE Band 12	10MHz/1RB	Front	10	23130	711	23.76	24.0	1.057	0.16	0.488	0.516
	LTE Band 12	10MHz/25RB	Front	10	23130	711	22.52	24.0	1.406	0.07	0.294	0.413
#3	LTE Band 12	10MHz/1RB	Back	10	23130	711	23.76	24.0	1.057	-0.09	0.613	0.648
	LTE Band 12	10MHz/25RB	Back	10	23130	711	22.52	24.0	1.406	-0.06	0.439	0.617
	LTE Band 12	10MHz/1RB	Left Side	10	23130	711	23.76	24.0	1.057	-0.04	0.396	0.418
	LTE Band 12	10MHz/25RB	Left Side	10	23130	711	22.52	24.0	1.406	-0.07	0.261	0.367
	LTE Band 12	10MHz/1RB	Right Side	10	23130	711	23.76	24.0	1.057	N/A	N/A	N/A
	LTE Band 12	10MHz/25RB	Right Side	10	23130	711	22.52	24.0	1.406	N/A	N/A	N/A
	LTE Band 12	10MHz/1RB	Top Side	10	23130	711	23.76	24.0	1.057	N/A	N/A	N/A
	LTE Band 12	10MHz/25RB	Top Side	10	23130	711	22.52	24.0	1.406	N/A	N/A	N/A
	LTE Band 12	10MHz/1RB	Bottom Side	10	23130	711	23.76	24.0	1.057	0.08	0.599	0.633
	LTE Band 12	10MHz/25RB	Bottom Side	10	23130	711	22.52	24.0	1.406	-0.01	0.423	0.595
	LTE Band 13	10MHz/1RB	Front	10	23230	782	23.29	23.5	1.050	-0.16	0.344	0.361
	LTE Band 13	10MHz/25RB	Front	10	23230	782	22.43	23.5	1.279	-0.03	0.231	0.296
#4	LTE Band 13	10MHz/1RB	Back	10	23230	782	23.29	23.5	1.050	-0.12	0.549	0.576
	LTE Band 13	10MHz/25RB	Back	10	23230	782	22.43	23.5	1.279	0.08	0.437	0.559
	LTE Band 13	10MHz/1RB	Left Side	10	23230	782	23.29	23.5	1.050	0.05	0.241	0.253
	LTE Band 13	10MHz/25RB	Left Side	10	23230	782	22.43	23.5	1.279	-0.12	0.102	0.130
	LTE Band 13	10MHz/1RB	Right Side	10	23230	782	23.29	23.5	1.050	N/A	N/A	N/A
	LTE Band 13	10MHz/25RB	Right Side	10	23230	782	22.43	23.5	1.279	N/A	N/A	N/A
	LTE Band 13	10MHz/1RB	Top Side	10	23230	782	23.29	23.5	1.050	N/A	N/A	N/A
	LTE Band 13	10MHz/25RB	Top Side	10	23230	782	22.43	23.5	1.279	N/A	N/A	N/A
	LTE Band 13	10MHz/1RB	Bottom Side	10	23230	782	23.29	23.5	1.050	-0.12	0.517	0.543
	LTE Band 13	10MHz/25RB	Bottom Side	10	23230	782	22.43	23.5	1.279	0.08	0.396	0.507
	LTE Band 41	20MHz/1RB	Front	10	40140	2545	22.55	23.0	1.109	0.11	0.451	0.500
	LTE Band 41	20MHz/50RB	Front	10	40140	2545	21.58	23.0	1.387	-0.15	0.323	0.448
#5	LTE Band 41	20MHz/1RB	Back	10	40140	2545	22.55	23.0	1.109	0.03	0.635	0.704
	LTE Band 41	20MHz/50RB	Back	10	40140	2545	21.58	23.0	1.387	-0.06	0.472	0.655
	LTE Band 41	20MHz/1RB	Left Side	10	40140	2545	22.55	23.0	1.109	0.08	0.377	0.418
	LTE Band 41	20MHz/50RB	Left Side	10	40140	2545	21.58	23.0	1.387	0.15	0.195	0.270
	LTE Band 41	20MHz/1RB	Right	10	40140	2545	22.55	23.0	1.109	N/A	N/A	N/A

