



FCC TEST REPORT

FCC ID: 2A9LB-HUG01

On Behalf of

Eugeria

HUG electronics

Model No.: HUG01

Prepared for : Eugeria
Address : 4020 St Ambroise Street, Local 497, Montreal, Quebec H4C 2C7,
Canada

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2209019-C01-R08
Date of Receipt : September 17, 2022
Date of Test : September 17, 2022- November 8, 2022
Date of Report : November 9, 2022
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information.....	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility.....	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. Maximum Peak Output power	12
3.1. Limit.....	12
3.2. Test Procedure	12
3.3. Test Setup.....	12
3.4. Test Result.....	12
4. Bandwidth	13
4.1. Limit.....	13
4.2. Test Procedure	13
4.3. Test Result.....	13
5. Carrier Frequency Separation	23
5.1. Limit.....	23
5.2. Test Procedure	23
5.3. Test Result.....	23
6. Number Of Hopping Channel	25
6.1. Limit.....	25
6.2. Test Procedure	25
6.3. Test Result.....	25
7. Dwell Time	27
7.1. Test limit.....	27
7.2. Test Procedure	27
7.3. Test Result.....	27
8. Radiated emissions	33
8.1. Limit.....	33
8.2. Block Diagram of Test setup.....	34
8.3. Test Procedure	35
8.4. Test Result.....	35
9. Band Edge Compliance	46

9.1. Block Diagram of Test Setup	46
9.2. Limit	46
9.3. Test Procedure	46
9.4. Test Result	46
10. Power Line Conducted Emissions.....	56
10.1. Block Diagram of Test Setup	56
10.2. Limit	56
10.3. Test Procedure	56
10.4. Test Result	57
12. Antenna Requirements	60
12.1. Limit	60
12.2. Result	60
13. Test Setup Photo	61
13.1. Photos of Radiated emission.....	61
13.2. Photos of Conducted Emission test	62
14. EUT photo.....	63

TEST REPORT DECLARATION

Applicant : Eugeria
Address : 4020 St Ambroise Street, Local 497, Montreal, Quebec H4C 2C7, Canada
Manufacturer : Ravencourt Ltd
Address : Ravencourt Ltd, Cobbs Nook Buildings, Newstead Road, Stamford, Lincolnshire, PE9 4JJ, UK
EUT Description : HUG electronics
(A) Model No. : HUG01
(B) Trademark : N/A

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247,
ANSI C63.10-2013**

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....: Yannis Wen
Project Engineer



Approved by (name + signature).....: Jack Xu
Project Manager



Date of issue.....: November 9, 2022

Revision History

Revision	Issue Date	Revisions	Revised By
V0	November 9, 2022	Initial released Issue	Yannis Wen

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1)	P
Bandwidth	FCC Part 15: 15.215	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1)	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)	P
Dwell Time	FCC Part 15: 15.247(a)(1)	P
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d)	P
Band Edge Compliance	FCC Part 15: 15.247(d)	P
Power Line Conducted Emissions	FCC Part 15: 15.207	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

2. General Information

2.1. Description of Device (EUT)

Description/PMN : HUG electronics

Model :
Number/HVIN(s) : HUG01
Diff. : N/A

Trademark : N/A

Test Voltage : DC 5V from adapter, DC 3.7V from Battery

Radio Technology : Bluetooth EDR

Operation : 2402MHz-2480MHz
frequency

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK

Channel No. : 79 Channels

Channel Separation : 1MHz

Antenna Type : PCB Antenna, max gain -0.58dBi.

Software version : V1.0

Hardware version : V1.0

Remark:

1. The worst-case simultaneous transmission configuration was evaluated with no non-compliance found. Results in this report are only for Bluetooth EDR function, and there is no other transmitter involved.


2.2. Accessories of Device (EUT)

Accessories	: SWITCHING ADAPTER
Manufacturer	: Dong Guan City GangQi Electronic Co., Ltd
Model	: GQ06-050100-AUU
Input	: 100-240V~50/60Hz 0.3A Max
Output	: 5.0V = 1.0A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	Notebook PC	Lenovo	ThinkPad E14	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

The test software “FCC_assist_1.0.1.2.app” was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK / Pi/4-DQPSK/8DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK / Pi/4-DQPSK/8DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480

Setting output power (Max)		
GFSK	$\pi/4$ -DQPSK	8DPSK
0±2dBm	0±2dBm	0±1dBm

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	25°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd

Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission

Registration Number: 293961

Designation Number: CN1236

July 15, 2019 Certificated by IC

Registration Number: CN0085

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2022.05.17	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2022.08.22	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2022.08.22	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-10 2082-Wa	2022.08.22	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2022.08.22	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2021.08.30	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2021.08.30	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00059	2021.08.30	2Year
RF Cable	Resenberger	Cable 1	/	RE1	2022.08.22	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2022.08.22	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2022.08.22	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2022.08.22	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2022.08.22	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2022.08.22	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2022.08.23	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	/	00946	2021.08.30	2 Year
Preamplifier	SKET	LNPA_1840 -50	/	SK2018101801	2022.08.22	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2022.08.22	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2022.08.22	1 Year
Temp. & Humid. Chamber	Wei Huang	WHTH-1000 -40-880	/	100631	2022.08.22	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2022.08.22	1 Year
Adjustable attenuator	MWRFtest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

3. Maximum Peak Output Power

3.1. Limit


Please refer FCC part 15.247...

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Mode	Freq (MHz)	PK Output Power (dBm)	Limit (dBm)	Result
GFSK	2402	-1.473	21	Pass
	2441	-0.335	21	Pass
	2480	0.505	21	Pass
$\pi/4$ DQPSK	2402	-1.359	21	Pass
	2441	-0.755	21	Pass
	2480	0.367	21	Pass
8DPSK	2402	-0.719	21	Pass
	2441	-0.319	21	Pass
	2480	0.388	21	Pass
Conclusion: PASS				

4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant 1	0.937	1.002	/	Pass
NVNT	1-DH1	2441	Ant 1	0.949	1.026	/	Pass
NVNT	1-DH1	2480	Ant 1	0.975	1.034	/	Pass
NVNT	2-DH1	2402	Ant 1	1.213	1.326	/	Pass
NVNT	2-DH1	2441	Ant 1	1.183	1.224	/	Pass
NVNT	2-DH1	2480	Ant 1	1.205	1.264	/	Pass
NVNT	3-DH1	2402	Ant1	1.183	1.226	/	Pass
NVNT	3-DH1	2441	Ant1	1.173	1.296	/	Pass
NVNT	3-DH1	2480	Ant1	1.183	1.24	/	Pass

OBW NVNT 1-DH1 2402MHz Ant1




Date: 30.SEP.2022 05:53:27

-20 dB BW NVNT 1-DH1 2402MHz Ant1




Date: 30.SEP.2022 05:53:35

OBW NVNT 1-DH1 2441MHz Ant1




Date: 30.SEP.2022 06:15:47

-20 dB BW NVNT 1-DH1 2441MHz Ant1




Date: 30.SEP.2022 06:15:55

OBW NVNT 1-DH1 2480MHz Ant1




Date: 30.SEP.2022 06:50:32

-20 dB BW NVNT 1-DH1 2480MHz Ant1




Date: 30.SEP.2022 06:50:40

OBW NVNT 2-DH1 2402MHz Ant1




Date: 30.SEP.2022 10:05:10

-20 dB BW NVNT 2-DH1 2402MHz Ant1




Date: 30.SEP.2022 10:05:19

OBW NVNT 2-DH1 2441MHz Ant1




Date: 30.SEP.2022 10:06:50

-20 dB BW NVNT 2-DH1 2441MHz Ant1




Date: 30.SEP.2022 10:07:00

OBW NVNT 2-DH1 2480MHz Ant1




Date: 30.SEP.2022 10:18:54

-20 dB BW NVNT 2-DH1 2480MHz Ant1




Date: 30.SEP.2022 10:19:04

OBW NVNT 3-DH1 2402MHz Ant1




Date: 30.SEP.2022 10:37:01

-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1




Date: 30.SEP.2022 10:37:12

OBW NVNT 3-DH1 2441MHz Ant1




Date: 30.SEP.2022 10:39:36

-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1




Date: 30.SEP.2022 10:39:48

OBW NVNT 3-DH1 2480MHz Ant1



Date: 30.SEP.2022 10:47:34

-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1



Date: 30.SEP.2022 10:47:46

5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result


Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2440.907	2441.927	1.02	1.026	Fail
NVNT	2-DH1	Ant1	2440.776	2441.776	1	0.816	Pass
NVNT	3-DH1	Ant1	2440.776	2441.778	1.002	0.864	Pass

CFS NVNT 1-DH1 2441MHz Ant1




Date: 30.SEP.2022 12:07:07

CFS NVNT 2-DH1 2441MHz Ant1



Date: 30.SEP.2022 12:27:56

CFS NVNT 3-DH1 2441MHz Ant1



Date: 30.SEP.2022 13:11:24

6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result


Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH1	79	15	Pass
NVNT	2-DH1	79	15	Pass
NVNT	3-DH1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1




Date: 30.SEP.2022 11:11:43

Hopping No. NVNT 2-DH1 2441MHz Ant1



Date: 30.SEP.2022 12:31:32

Hopping No. NVNT 3-DH1 2441MHz Ant1



Date: 30.SEP.2022 13:15:01

7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247.

Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

PASS.

Detailed information please see the following page.

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.376	120.320	317	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.632	261.120	150	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.88	307.200	100	31600	400	Pass
NVNT	2-DH1	2441	Ant1	0.383	122.560	319	31600	400	Pass
NVNT	2-DH3	2441	Ant1	1.638	262.080	153	31600	400	Pass
NVNT	2-DH5	2441	Ant1	2.885	307.733	106	31600	400	Pass
NVNT	3-DH1	2441	Ant1	0.387	123.840	318	31600	400	Pass
NVNT	3-DH3	2441	Ant1	1.636	261.760	160	31600	400	Pass
NVNT	3-DH5	2441	Ant1	2.888	308.053	95	31600	400	Pass


Note: 1. A period time = 0.4 (s) * 79 = 31.6(s)

2. DH1 Dwell Time = Pulse Time * (1600/(2*79)) * A period time

DH3 Dwell Time = Pulse Time * (1600/(4*79)) * A period time


DH5 Dwell Time = Pulse Time * (1600/(6*79)) * A period time

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Date: 30.SEP.2022 11:11:57


Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Dwell NVNT 3-DH1 2441MHz Ant1 One Burst



Dwell NVNT 3-DH3 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



8. Radiated Emissions

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	


Note: The peak limit is 20 dB higher than the average limit

8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result


We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz: Conclusion: PASS


Vertical:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Margin dB	Antenna Height cm	Table Degree	Comment
1		39.0108	9.86	14.46	24.32	40.00	-15.68	peak		
2		71.8656	11.08	11.11	22.19	40.00	-17.81	peak		
3		155.1828	10.53	15.05	25.58	43.50	-17.92	peak		
4		323.9634	12.61	14.71	27.32	46.00	-18.68	peak		
5		569.2777	11.43	19.53	30.96	46.00	-15.04	peak		
6	*	894.4838	11.51	23.97	35.48	46.00	-10.52	peak		

Note: 1. *: Maximum data; x: Over limit; !: over margin.

2. Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Horizontal:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		42.1887	9.04	14.32	23.36	40.00	-16.64	peak		
2		70.4929	9.68	11.27	20.95	40.00	-19.05	peak		
3		143.6783	9.09	14.59	23.68	43.50	-19.82	peak		
4		226.3638	10.29	12.10	22.39	46.00	-23.61	peak		
5		340.9012	10.52	15.09	25.61	46.00	-20.39	peak		
6	*	639.8627	11.33	20.97	32.30	46.00	-13.70	peak		

Note:1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Remark: All modes have been tested, and only worst data of GFSK 2402MHz was listed in this report.

Test Mode: GFSK TX Low

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor

2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Note:

Test Mode: $\pi/4$ DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	45.65	V	33.95	10.18	34.26	55.52	74	-18.48	PK
4804	35.90	V	33.95	10.18	34.26	45.77	54	-8.23	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	47.73	H	33.95	10.18	34.26	57.60	74	-16.40	PK
4804	35.74	H	33.95	10.18	34.26	45.61	54	-8.39	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX Mid									
4882	43.04	V	33.93	10.2	34.29	52.88	74	-21.12	PK
4882	33.85	V	33.93	10.2	34.29	43.69	54	-10.31	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	46.45	H	33.93	10.2	34.29	56.29	74	-17.71	PK
4882	34.80	H	33.93	10.2	34.29	44.64	54	-9.36	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX High									
4960	45.77	V	33.98	10.22	34.25	55.72	74	-18.28	PK
4960	36.71	V	33.98	10.22	34.25	46.66	54	-7.34	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	44.71	H	33.98	10.22	34.25	54.66	74	-19.34	PK
4960	34.36	H	33.98	10.22	34.25	44.31	54	-9.69	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/

Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor



2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Test Mode: 8DPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	46.87	V	33.95	10.18	34.26	56.74	74	-17.26	PK
4804	37.84	V	33.95	10.18	34.26	47.71	54	-6.29	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	45.75	H	33.95	10.18	34.26	55.62	74	-18.38	PK
4804	35.47	H	33.95	10.18	34.26	45.34	54	-8.66	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: 8DPSK TX Mid									
4882	41.97	V	33.93	10.2	34.29	51.81	74	-22.19	PK
4882	35.23	V	33.93	10.2	34.29	45.07	54	-8.93	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	46.22	H	33.93	10.2	34.29	56.06	74	-17.94	PK
4882	34.80	H	33.93	10.2	34.29	44.64	54	-9.36	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: 8DPSK TX High									
4960	43.30	V	33.98	10.22	34.25	53.25	74	-20.75	PK
4960	36.61	V	33.98	10.22	34.25	46.56	54	-7.44	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	43.76	H	33.98	10.22	34.25	53.71	74	-20.29	PK
4960	33.12	H	33.98	10.22	34.25	43.07	54	-10.93	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/


Note:

1, Result = Read level + Antenna factor + cable loss-Amp factor


2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

Conducted RF Spurious Emission**Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission****Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission**


Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission




Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission




Date: 30.SEP.2022 10:07:24

Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission




Date: 30.SEP.2022 10:19:44


Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission




Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission



Date: 30.SEP.2022 10:48:30

9. Band Edge Compliance

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in FCC part 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with FCC part 15.209 limits.

9.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.



All restriction band and non- restriction band have been tested, only worse case is reported.

9.4. Test Result



PASS. (See below detailed test data)



Radiated Method:

Test Mode: GFSK-Low




Test Mode: GFSK-High




Test Mode: $\pi/4$ DQPSK-Low

$\pi/4$ DQPSK-High





hopping-off





hopping-on

Test Mode: 8DPSK-Low



Test Mode: 8DPSK-High



Note: 1. *:Maximum data; x:Over limit; !:over margin.


2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

Conducted Method


GFSK Mode:

Test channel:

Lowest channel




No-hopping mode




Hopping mode

Test channel:

Highest channel




No-hopping mode



Hopping mode


Pi/4QPSK Mode:

Test channel:




No-hopping mode

Lowest channel




Hopping mode

Test channel:



No-hopping mode

Highest channel




Hopping mode


8DPSK Mode:

Test channel:

Lowest channel




No-hopping mode




Hopping mode

Test channel:

Highest channel




No-hopping mode



Hopping mode

10. Power Line Conducted Emissions

10.1. Block Diagram of Test Setup



10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure


- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

10.4. Test Result

PASS. (See below detailed test data)

Note: If peak Result comply with AV limit, QP and AV Result is deemed to comply with AV limit

Line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.2129	31.41	9.93	41.34	63.09	-21.75	peak	
2		0.3180	29.99	9.93	39.92	59.76	-19.84	peak	
3		0.4470	33.04	9.95	42.99	56.93	-13.94	peak	
4	*	0.4738	34.71	9.95	44.66	56.45	-11.79	peak	
5		0.6300	25.97	9.92	35.89	56.00	-20.11	peak	
6		0.9240	24.43	9.96	34.39	56.00	-21.61	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Neutral:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1710	38.34	9.93	48.27	64.91	-16.64	peak	
2		0.4470	36.82	9.95	46.77	56.93	-10.16	peak	
3		0.4800	35.45	9.96	45.41	56.34	-10.93	QP	
4	*	0.4800	27.08	9.96	37.04	46.34	-9.30	AVG	
5		0.9000	32.14	9.97	42.11	56.00	-13.89	peak	
6		1.3528	30.93	9.89	40.82	56.00	-15.18	peak	
7		1.7129	28.92	9.89	38.81	56.00	-17.19	peak	

*:Maximum data x:Over limit !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Remark: All modes have been tested, and only worst data of GFSK 2402MHz 1Mbps was listed in this report.

11. Antenna Requirements

11.1.Limit



For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2.Result


The EUT antenna is PCB Antenna. It complies with the standard requirement.

12. Test Setup Photo

12.1. Photos of Radiated emission



12.2.Photos of Conducted Emission test






13. EUT Photo






















-----THE END OF REPORT-----