

RF Exposure Evaluation Report

Product : Rumen Bolus
Trade mark : JISHUO
Model/Type reference : JS-0140
Serial Number : N/A
Report Number : EED32P81236502
FCC ID : 2A9ON-JS0140
Date of Issue : Dec. 07, 2023
: 47 CFR Part 1.1307
: 47 CFR Part 1.1310
Test Standards : 47 CFR Part 2.1091(mobile devices)
: 47 CFR Part 2.1093(portable devices)
: 447498 D04 Interim General RF Exposure Guidance v01
Test result : PASS

Prepared for:

Inner Mongolia JiShuo Technology Co. LTD.
Room 305, Zone C, Floor 3, Tian Fu He Tao Headquarters , Linhe
District, Bayan Nur City, Inner Mongolia Autonomous Region, China.

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Reviewed by:

Tom Chen

Approved by:

Aaron Ma

Date:

Tom Chen
Dec. 07, 2023

Aaron Ma

Check No.: 1538080823



2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 GENERAL INFORMATION	3
3.1 CLIENT INFORMATION	3
3.2 GENERAL DESCRIPTION OF EUT	3
3.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	3
3.4 TEST LOCATION	4
3.5 DEVIATION FROM STANDARDS	4
3.6 ABNORMALITIES FROM STANDARD CONDITIONS	4
3.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Limits	5
4.1.2 Test Procedure	5
4.1.3 EUT RF Exposure Evaluation	6

3 General Information

3.1 Client Information

Applicant:	Inner Mongolia JiShuo Technology Co. LTD.
Address of Applicant:	Room 305, Zone C, Floor 3, Tian Fu He Tao Headquarters, Linhe District, Bayan Nur City, Inner Mongolia Autonomous Region, China.
Manufacturer:	Inner Mongolia JiShuo Technology Co. LTD.
Address of Manufacturer:	Room 305, Zone C, Floor 3, Tian Fu He Tao Headquarters, Linhe District, Bayan Nur City, Inner Mongolia Autonomous Region, China.
Factory:	Dongguan Qunhan Electronics Co.,Ltd
Address of Factory:	Room 101, No.3 Tai he road Huan Zhu Li Village Chang Ping Town Dong Guan City Guang Dong Province China

3.2 General Description of EUT

Product Name:	Rumen Bolus
Model No.:	JS-0140
Trade mark:	JISHUO

3.3 Product Specification subjective to this standard

Frequency Range:	902.3MHz~914.9MHz
Modulation Type:	LoRa
Test Power Grade:	Default
Antenna Type	Internal antenna
Antenna Gain	1.32 dBi
Power Supply:	DC 3.0V Battery
Sample Received Date:	Nov. 02, 2023
Sample tested Date:	Nov. 02, 2023 to Nov. 09, 2023
Remark:	Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

3.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.5 Deviation from Standards

None.

3.6 Abnormalities from Standard Conditions

None.

3.7 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

Frequency (MHz)	Separation distance (cm)	Maximum Peak Conducted Output Power(dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	Result
902.3	20	14.45	1.32	13.62	23.0144	≤1840.692	PASS

Note:

- ①EIRP=Maximum Peak Conducted Output Power+antenna gain;
- ②ERP=EIRP-2.15;
- ③The test data please refer to the report of EED32P81236501,and only the worst case data was recorded in the report.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***