

Temperature:	24.6°C	Relative Humidity:	49%																											
Test Voltage:	DC 14.4V																													
Test Mode:	802.11 n40 Mode TX 5755 MHz-MIMO																													
Remark:	Only worse case is reported.																													
Horizontal																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBμV)</th><th>Factor (dB/m)</th><th>Level (dBμV/m)</th><th>Limit (dBμV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>12016.000</td><td>42.45</td><td>1.46</td><td>43.91</td><td>68.30</td><td>-24.39</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>14753.000</td><td>41.89</td><td>3.40</td><td>45.29</td><td>68.30</td><td>-23.01</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	12016.000	42.45	1.46	43.91	68.30	-24.39	peak	P	2 *	14753.000	41.89	3.40	45.29	68.30	-23.01	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1	12016.000	42.45	1.46	43.91	68.30	-24.39	peak	P																						
2 *	14753.000	41.89	3.40	45.29	68.30	-23.01	peak	P																						
Vertical																														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBμV)</th><th>Factor (dB/m)</th><th>Level (dBμV/m)</th><th>Limit (dBμV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr> </thead> <tbody> <tr> <td>1</td><td>10894.000</td><td>43.60</td><td>-0.19</td><td>43.41</td><td>68.30</td><td>-24.89</td><td>peak</td><td>P</td></tr> <tr> <td>2 *</td><td>13444.000</td><td>42.31</td><td>2.14</td><td>44.45</td><td>68.30</td><td>-23.85</td><td>peak</td><td>P</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	10894.000	43.60	-0.19	43.41	68.30	-24.89	peak	P	2 *	13444.000	42.31	2.14	44.45	68.30	-23.85	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																						
1	10894.000	43.60	-0.19	43.41	68.30	-24.89	peak	P																						
2 *	13444.000	42.31	2.14	44.45	68.30	-23.85	peak	P																						
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G). 5. No report for the emission which more than 20dB below the prescribed limit. 6. The peak value<average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected. 																														



Temperature:	24.6°C		Relative Humidity:	49%																	
Test Voltage:	DC 14.4V																				
Test Mode:	802.11 n40 Mode TX 5795 MHz-MIMO																				
Remark:	Only worse case is reported.																				
Horizontal																					
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F													
1	10962.000	43.71	-0.04	43.67	68.30	-24.63	peak	P													
2 *	14107.000	41.34	2.72	44.06	68.30	-24.24	peak	P													
Vertical																					
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F													
1 *	12373.000	42.53	1.56	44.09	68.30	-24.21	peak	P													
2	14753.000	40.68	3.40	44.08	68.30	-24.22	peak	P													
Remark:																					
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																					
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																					
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																					
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).																					
5. No report for the emission which more than 20dB below the prescribed limit.																					
6. The peak value<average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected.																					



Temperature:	24.6°C	Relative Humidity:	49%												
Test Voltage:	DC 14.4V														
Test Mode:	802.11 ac40 Mode TX 5190 MHz-MIMO														
Remark:	Only worse case is reported.														
Horizontal															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBμV)</th><th>Factor (dB/m)</th></tr> </thead> <tbody> <tr> <td>1</td><td>12424.000</td><td>42.14</td><td>1.58</td></tr> <tr> <td>2 *</td><td>14090.000</td><td>42.08</td><td>2.70</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	1	12424.000	42.14	1.58	2 *	14090.000	42.08	2.70
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)												
1	12424.000	42.14	1.58												
2 *	14090.000	42.08	2.70												
Vertical															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dBμV)</th><th>Factor (dB/m)</th></tr> </thead> <tbody> <tr> <td>1 *</td><td>10894.000</td><td>44.22</td><td>-0.19</td></tr> <tr> <td>2</td><td>13172.000</td><td>41.64</td><td>1.91</td></tr> </tbody> </table>				No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	1 *	10894.000	44.22	-0.19	2	13172.000	41.64	1.91
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)												
1 *	10894.000	44.22	-0.19												
2	13172.000	41.64	1.91												
Remark: <ol style="list-style-type: none"> 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV) 3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G). 5. No report for the emission which more than 20dB below the prescribed limit. 6. The peak value < average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected. 															



Temperature:	24.6°C	Relative Humidity:	49%			
Test Voltage:	DC 14.4V					
Test Mode:	802.11 ac40 Mode TX 5230 MHz-MIMO					
Remark:	Only worse case is reported.					
Horizontal						
Vertical						
Remark:	<ol style="list-style-type: none">1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).5. No report for the emission which more than 20dB below the prescribed limit.6. The peak value < average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected.					



Temperature:	24.6°C		Relative Humidity:	49%																																
Test Voltage:	DC 14.4V																																			
Test Mode:	802.11 ac40 Mode TX 5755 MHz-MIMO																																			
Remark:	Only worse case is reported.																																			
Horizontal																																				
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBμV)</th><th>Factor (dB/m)</th><th>Level (dBμV/m)</th><th>Limit (dBμV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>10962.000</td><td>44.03</td><td>-0.04</td><td>43.99</td><td>68.30</td><td>-24.31</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>14396.000</td><td>42.24</td><td>3.03</td><td>45.27</td><td>68.30</td><td>-23.03</td><td>peak</td><td>P</td></tr></tbody></table>										No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	10962.000	44.03	-0.04	43.99	68.30	-24.31	peak	P	2 *	14396.000	42.24	3.03	45.27	68.30	-23.03	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																												
1	10962.000	44.03	-0.04	43.99	68.30	-24.31	peak	P																												
2 *	14396.000	42.24	3.03	45.27	68.30	-23.03	peak	P																												
Vertical																																				
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBμV)</th><th>Factor (dB/m)</th><th>Level (dBμV/m)</th><th>Limit (dBμV/m)</th><th>Margin (dB)</th><th>Detector</th><th>P/F</th></tr></thead><tbody><tr><td>1</td><td>12118.000</td><td>42.85</td><td>1.49</td><td>44.34</td><td>68.30</td><td>-23.96</td><td>peak</td><td>P</td></tr><tr><td>2 *</td><td>14974.000</td><td>41.00</td><td>3.63</td><td>44.63</td><td>68.30</td><td>-23.67</td><td>peak</td><td>P</td></tr></tbody></table>										No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F	1	12118.000	42.85	1.49	44.34	68.30	-23.96	peak	P	2 *	14974.000	41.00	3.63	44.63	68.30	-23.67	peak	P
No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Level (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector	P/F																												
1	12118.000	42.85	1.49	44.34	68.30	-23.96	peak	P																												
2 *	14974.000	41.00	3.63	44.63	68.30	-23.67	peak	P																												
Remark: 1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB) 2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V) 3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m) 4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G). 5. No report for the emission which more than 20dB below the prescribed limit. 6. The peak value<average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected.																																				



Temperature:	24.6°C		Relative Humidity:	49%																		
Test Voltage:	DC 14.4V																					
Test Mode:	802.11 ac40 Mode TX 5795 MHz-MIMO																					
Remark:	Only worse case is reported.																					
Horizontal																						
No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	P/F														
1	11285.000	43.18	0.45	43.63	68.30	-24.67	peak	P														
2 *	14940.000	40.95	3.59	44.54	68.30	-23.76	peak	P														
Vertical																						
No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	P/F														
1 *	11251.000	43.07	0.40	43.47	68.30	-24.83	peak	P														
2	13342.000	41.22	2.06	43.28	68.30	-25.02	peak	P														
Remark:																						
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																						
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																						
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																						
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).																						
5. No report for the emission which more than 20dB below the prescribed limit.																						
6. The peak value<average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected.																						



Temperature:	24.6°C		Relative Humidity:	49%																		
Test Voltage:	DC 14.4V																					
Test Mode:	802.11 ac80 Mode TX 5210 MHz-MIMO																					
Remark:	Only worse case is reported.																					
Horizontal																						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F														
1 *	10911.000	44.63	-0.16	44.47	68.30	-23.83	peak	P														
2	14158.000	41.18	2.78	43.96	68.30	-24.34	peak	P														
Vertical																						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F														
1	11659.000	42.63	0.98	43.61	68.30	-24.69	peak	P														
2 *	14328.000	41.34	2.95	44.29	68.30	-24.01	peak	P														
Remark:																						
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																						
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																						
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																						
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).																						
5. No report for the emission which more than 20dB below the prescribed limit.																						
6. The peak value<average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected.																						



Temperature:	24.6°C		Relative Humidity:	49%																
Test Voltage:	DC 14.4V																			
Test Mode:	802.11 ac80 Mode TX 5775 MHz-MIMO																			
Remark:	Only worse case is reported.																			
Horizontal																				
No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	P/F												
1	10928.000	43.97	-0.12	43.85	68.30	-24.45	peak	P												
2 *	13240.000	41.93	1.96	43.89	68.30	-24.41	peak	P												
Vertical																				
No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	P/F												
1	12288.000	41.70	1.54	43.24	68.30	-25.06	peak	P												
2 *	14872.000	40.53	3.53	44.06	68.30	-24.24	peak	P												
Remark:																				
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)																				
2. Peak/AVG (dB μ V/m)= Corr. (dB/m)+ Read Level (dB μ V)																				
3. Margin (dB) = Peak/AVG (dB μ V/m)-Limit PK/AVG(dB μ V/m)																				
4. The tests evaluated 1-40GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency or 40GHz. Test with highpass filter (Pass Frequency:8-25G).																				
5. No report for the emission which more than 20dB below the prescribed limit.																				
6. The peak value<average limit, So only show the peak value. and 18GHz-40GHz is the noise, No other signals were detected.																				

-----END OF THE REPORT-----

