

FCC PART 15.247


TEST REPORT

For

PURSPEC Technology (China) Ltd.

501 and 601, G4 Building, No.88 Jinjihu Avenue, Suzhou Industrial Park, Suzhou, Jiangsu, China

FCC ID: 2A9POOM01ZIGB1

Report Type: Original Report	Product Name: Communication Adapter
Report Number: RKSC250716001-00B	
Report Date: 2025-08-12	
Reviewed By:	Bard Liu 
Approved By:	Kyle Xu 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY	4
GENERAL INFORMATION	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION.....	7
EUT EXERCISE SOFTWARE.....	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	8
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	9
TEST EQUIPMENT LIST.....	11
SUMMARY OF TEST RESULTS.....	12
§1.1310 & §2.1093 - RF EXPOSURE	13
FCC §15.203 – ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD.....	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD.....	15
TEST SYSTEM SETUP.....	15
EMI TEST RECEIVER SETUP	15
TEST PROCEDURE	16
TEST RESULTS SUMMARY	16
TEST DATA: SEE APPENDIX.....	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD.....	17
TEST SYSTEM SETUP.....	17
EMI TEST RECEIVER SETUP	18
TEST PROCEDURE	18
TEST RESULTS SUMMARY	19
TEST DATA: SEE APPENDIX.....	19
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	20
APPLICABLE STANDARD.....	20
TEST PROCEDURE	20
TEST DATA: SEE APPENDIX.....	20
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	21
APPLICABLE STANDARD.....	21
TEST PROCEDURE	21
TEST DATA: SEE APPENDIX.....	21
FCC §15.247(d) – BAND EDGE	22

APPLICABLE STANDARD.....	22
TEST PROCEDURE	22
TEST DATA: SEE APPENDIX.....	22
FCC §15.247(e) - POWER SPECTRAL DENSITY.....	23
APPLICABLE STANDARD.....	23
TEST PROCEDURE	23
TEST DATA: SEE APPENDIX.....	23
APPENDIX - TEST DATA.....	24
AC LINE CONDUCTED EMISSIONS.....	24
SPURIOUS EMISSIONS	27
6 dB EMISSION BANDWIDTH.....	37
MAXIMUM CONDUCTED OUTPUT POWER.....	38
BAND EDGE.....	40
POWER SPECTRAL DENSITY	41
CONDUCTED SPURIOUS EMISSION	42
EUT PHOTOGRAPHS.....	43
TEST SETUP PHOTOGRAPHS.....	44

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSC250716001-00B	R1V1	2025-08-12	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	PURSPEC Technology (China) Ltd.
Tested Model:	OM01ZIGB
Product Name:	Communication Adapter
Power Supply:	DC 5V
RF Function:	Zigbee
Maximum Output Power:	6.98 dBm
Operating Band /Frequency:	2405-2480 MHz
Modulation Type:	OQPSK
Channel Number:	16
Antenna Type:	FPC antenna
★Maximum Antenna Gain:	3.15 dBi

Note: The maximum antenna gain is provided by the applicant.

All measurement and test data in this report was gathered from production sample serial number: RKSC250716001-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2025-07-16.)

Objective

This report is prepared for *PURSPEC Technology (China) Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emissions	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	2435	25	2475
18	2440	26	2480

EUT was tested with channel 11, 18, 25 and 26.

EUT Exercise Software

RF Test Tool: EMI_Test_Tool

Mode	★Power Level			
	2405 MHz	2440 MHz	2475 MHz	2480 MHz
Zigbee	-15.8	-15.8	-15.8	-21.1

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.


Equipment Modifications

No modification was made to the EUT tested.

Duty Cycle:

Test Date:	2025-08-07
Temperature:	25.9 °C
Relative Humidity:	50 %
ATM Pressure:	100.8 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Middle Channel



ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 7.AUG.2025 16:55:56

Mode	Duty Cycle (%)	T _{on} (ms)	T _{on+off} (ms)	10log(1/x)(dB)
Zigbee	100	100	100	0

Note:

1. “x” means the Duty Cycle.
2. Offset(10.5dB) = Attenuator(10dB)+Cable loss(0.5dB)

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Notebook	Y7000P2020H	Unknown
/	Adapter	/	/
/	Debug board	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To Port
Power Cable	1.5	Adapter	LISN/AC Source
Data Cable	0.2	EUT	Debug Board
USB Cable 1	1.0/1.5	Debug Board	Notebook
USB Cable 2	1.0/1.5	EUT	Notebook

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1 GHz):



For Radiated Emissions(Above 1 GHz):



TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Sunol Sciences	Hybrid Antenna	JB3	A090314-2	2024-10-29	2027-10-28
BACL	Active Loop Antenna	1313-1A	4041511	2024-11-22	2027-11-21
Narda	6 dB Attenuator	771-6	10690812-2-1	2024-10-29	2027-10-28
Sonoma Instrument	Pre-amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems,inc	Amplifier	PAM-0118P	512	2025-04-09	2026-04-09
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2025-04-09	2026-04-09
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
SELECTOR	Amplifier	EM18G40G	60726	2025-04-09	2026-04-08
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-11	011	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-12	012	2025-04-09	2026-04-08
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2025-04-09	2026-04-08
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
XHFDZ	RG178 Coaxial Cable	SMA-178	XHF-1102	Each time	N/A
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	101746	2025-04-08	2026-04-07
Rohde & Schwarz	LISN	ENV216	101115	2025-04-08	2026-04-07
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse Limiter	ESH3-Z2	0357.8810.54	2025-04-08	2026-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2025-04-09	2026-04-08

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1093	RF exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

§1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

According to §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

1. f (GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Calculated Data:

Mode	Max Tune-up Conducted Power★		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
Zigbee	7.0	5.01	5	1.6	3.0	Yes

Note:

1. For the above tune up power were declared by the manufacturer.

Result: No SAR test is required.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an FPC antenna for ZigBee, and the antenna gain is 3.15 dBi, which permanently attached to EUT, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW
150 kHz – 30 MHz	9 kHz	30 kHz

Test Procedure

ANSI C63.10-2020 clause 6.2

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Level (dBμV) = Read level (dBμV) + Factor (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Level (dBμV) - Limit (dBμV)



Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

Test System Setup**9 kHz - 30 MHz:****30 MHz - 1 GHz:**

Above 1 GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	200 Hz	QP/Average	Peak/QP/Average
150 kHz – 30 MHz	9 kHz	30 kHz	9 kHz	QP/ Average	Peak/QP/Average
30 MHz – 1000 MHz	100 kHz	300 kHz	/	Peak	Peak
	/	/	120 kHz	QP	QP
Above 1GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	3 MHz	/	Average	Average

For 9 kHz-30 MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Note: The QuasiPeak (dB μ V/m), MaxPeak (dB μ V/m), Average (dB μ V/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.8.1

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “–6 dB down amplitude”. If a marker is below this “–6 dB down amplitude” value, then it shall be as close as possible to this value.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 * \text{RBW}$.
3. Set span $\geq 3 * \text{RBW}$
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

FCC §15.247(d) – BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2020 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 * \text{RBW}$.
3. Set the span to > 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

APPENDIX - TEST DATA


AC LINE CONDUCTED EMISSIONS

Environmental Conditions & Test Information

Test Date:	2025-07-21
Temperature:	28.3 °C
Relative Humidity:	60 %
ATM Pressure:	101.1 kPa
Test Result:	Pass
Test Engineer:	Myles Miao


EUT operation mode: Transmitting in Zigbee low channel (maximum output power mode)

Line:



Site : CE
Condition : limit\FCC PART 15.207
: DET:Peak
Project No. : RKSC250716001
Model : OM01ZIGB
Phase : L
Voltage : 120V/60Hz
Mode : Mode 1
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 28.3℃
Humidity : 60%
Atmospheric pressure: 101.1kPa
Test Engineer : Myles Miao

	Freq	Read		Limit	Over	
	MHz	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.179	31.91	20.14	52.05	64.51	-12.46 Peak
2	0.196	29.48	20.15	49.63	63.76	-14.13 Peak
3	0.242	24.62	20.16	44.78	62.03	-17.25 Peak
4	0.298	18.51	20.20	38.71	60.29	-21.58 Peak
5	0.477	15.08	20.22	35.30	56.40	-21.10 Peak
6	0.562	14.67	20.20	34.87	56.00	-21.13 Peak

Neutral:

Site : CE
Condition : limit\FCC PART 15.207
: DET:Peak
Project No. : RKSC250716001
Model : OM01ZIGB
Phase : N
Voltage : 120V/60Hz
Mode : Mode 1
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 28.3℃
Humidity : 60%
Atmospheric pressure: 101.1kPa
Test Engineer : Myles Miao

		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.170	31.70	20.13	51.83	64.97	-13.14	Peak
2	0.227	24.45	20.16	44.61	62.56	-17.95	Peak
3	0.282	18.70	20.19	38.89	60.74	-21.85	Peak
4	0.343	14.98	20.22	35.20	59.13	-23.93	Peak
5	0.458	13.42	20.26	33.68	56.73	-23.05	Peak
6	0.568	13.62	20.20	33.82	56.00	-22.18	Peak



SPURIOUS EMISSIONS**Environmental Conditions & Test Information**

Test Item:	9 kHz - 30 MHz	30 MHz - 1 GHz	1 GHz - 18 GHz	18 GHz - 25 GHz
Test Date:	2025-07-18	2025-08-07	2025-07-23	2025-07-24
Temperature:	23.2 °C	25.9 °C	27.8 °C	23.4 °C
Relative Humidity:	41 %	50 %	49 %	60 %
ATM Pressure:	100.4 kPa	100.8 kPa	101.3 kPa	100.8 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Link Xia	Link Xia	Destine Hu	Hugh Wu

Test Result: Compliant.

EUT operation mode: Transmitting

After pre-scan in the X, Y and Z axes of orientation, the worst case in the Y axes of orientation is below:

9 kHz-30 MHz: (Transmitting maximum output power Zigbee Mode low channel)**Parallel(worst case)****9 kHz-150 kHz****150 kHz-30 MHz**

Project No.RKSC250716001

Tester:Link Xia

Date: 18.JUL.2025 11:57:18

Project No.RKSC250716001

Tester:Link Xia

Date: 18.JUL.2025 12:08:07

9 kHz - 150 kHz:


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.01097	60.55	PK	-0.52	126.80	66.25
0.02056	58.37	PK	-0.56	121.34	62.97
0.07160	54.93	PK	-6.33	110.51	55.58
0.12800	59.78	PK	-10.40	105.46	45.68

150 kHz - 30 MHz:

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.26940	68.45	PK	-16.41	99.00	30.55
0.56790	59.03	PK	-23.27	72.52	13.49
1.10520	54.22	PK	27.96	66.74	12.52
4.32900	48.80	PK	-31.96	69.54	20.74

30 MHz-1 GHz (Transmitting in maximum output power low channel):**Low Channel: 2405 MHz****Common Information**

Project No: RKSC250716001
EUT Model: OM01ZIGB
Test Mode: Transmitting in ZigBee mode low channel
Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 25.9 °C
Humidity: 50%
Barometric Pressure: 100.8 kPa
Test Engineer: Link Xia
Test Date: 2025/8/7

**Critical_Freqs**


Frequency (MHz)	MaxPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
32.182500	26.99	40.00	13.01	V	-6.2
39.215000	22.10	40.00	17.90	H	-10.8
119.118750	23.29	43.50	20.21	V	-11.0
173.802500	22.83	43.50	20.67	H	-12.7
204.478750	26.96	43.50	16.54	H	-12.4
942.285000	35.96	46.00	10.04	V	1.7

1GHz-18GHz:

Low Channel: 2405 MHz

Common Information

Project No.:	RKSC250716001
EUT Model:	OM01ZIGB
Test Mode:	ZigBee
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	27.8℃
Humidity:	49%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/7/23


Fundamental test with Band
Reject Filter**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1958.800000	---	22.75	54.00	31.25	V	-10.3
1958.800000	33.85	---	74.00	40.15	V	-10.3
3543.200000	---	29.21	54.00	24.79	V	-6.2
3543.200000	38.97	---	74.00	35.03	V	-6.2
4808.000000	---	42.73	54.00	11.27	H	-3.4
4808.000000	50.16	---	74.00	23.84	H	-3.4
5998.000000	---	38.81	54.00	15.19	V	-0.6
5998.000000	47.13	---	74.00	26.87	V	-0.6
7215.200000	---	47.57	54.00	6.43	H	2.1
7215.200000	57.78	---	74.00	16.22	H	2.1
14586.400000	---	45.58	54.00	8.42	V	11.7
14586.400000	56.71	---	74.00	17.29	V	11.7

Middle Channel: 2440 MHz**Common Information**

Project No.: RKSC250716001
 EUT Model: OM01ZIGB
 Test Mode: ZigBee
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 27.8℃
 Humidity: 49%
 Atmospheric Pressure: 101.3kPa
 Test Engineer: Destine Hu
 Test Date: 2025/7/23

Fundamental test with Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	---	25.72	54.00	28.28	V	-10.1
1989.400000	36.59	---	74.00	37.41	V	-10.1
2992.400000	---	29.21	54.00	24.79	V	-8.1
2992.400000	39.72	---	74.00	34.28	V	-8.1
4879.400000	---	41.67	54.00	12.33	H	-3.2
4879.400000	48.69	---	74.00	25.31	H	-3.2
7320.600000	---	44.94	54.00	9.06	H	2.4
7320.600000	54.50	---	74.00	19.50	H	2.4
14069.600000	53.78	---	74.00	20.22	V	11.2
14069.600000	---	46.08	54.00	7.92	V	11.2
14460.600000	55.42	---	74.00	18.58	H	11.9
14460.600000	---	45.39	54.00	8.61	H	11.9

High Channel: 2480 MHz**Common Information**

Project No.: RKSC250716001
 EUT Model: OM01ZIGB
 Test Mode: ZigBee
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 27.8℃
 Humidity: 49%
 Atmospheric Pressure: 101.3kPa
 Test Engineer: Destine Hu
 Test Date: 2025/7/23

Fundamental test with Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1401.200000	---	21.58	54.00	32.42	H	-13.8
1401.200000	35.29	---	74.00	38.71	H	-13.8
1992.800000	---	27.56	54.00	26.44	V	-10.1
1992.800000	38.80	---	74.00	35.20	V	-10.1
4961.000000	---	37.30	54.00	16.70	H	-3.0
4961.000000	47.65	---	74.00	26.35	H	-3.0
5998.000000	---	39.36	54.00	14.64	V	-0.6
5998.000000	47.58	---	74.00	26.42	V	-0.6
14032.200000	54.23	---	74.00	19.77	H	11.1
14032.200000	---	46.32	54.00	7.68	H	11.1
14049.200000	55.95	---	74.00	18.05	V	11.2
14049.200000	---	45.63	54.00	8.37	V	11.2

Restricted Bands Emission:**Left Side****Common Information**

Project No.: RKSC250716001
EUT Model: OM01ZIGB
Test Mode: ZigBee
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 27.8°C
Humidity: 49%
Atmospheric Pressure: 101.3kPa
Test Engineer: Destine Hu
Test Date: 2025/7/23

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2389.968000	---	39.97	54.00	14.03	V	0.2
2389.968000	55.93	---	74.00	18.07	V	0.2

Right Side (2475 MHz)**Common Information**

Project No.: RKSC250716001
EUT Model: OM01ZIGB
Test Mode: ZigBee
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 27.8℃
Humidity: 49%
Atmospheric Pressure: 101.3kPa
Test Engineer: Destine Hu
Test Date: 2025/7/23

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2485.456000	---	41.92	54.00	12.08	H	0.4
2485.456000	55.39	---	74.00	18.61	H	0.4


Right Side (2480 MHz)**Common Information**

Project No.: RKSC250716001
EUT Model: OM01ZIGB
Test Mode: ZigBee
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 27.8℃
Humidity: 49%
Atmospheric Pressure: 101.3kPa
Test Engineer: Destine Hu
Test Date: 2025/7/23

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2483.536000	55.24	---	74.00	18.76	H	0.4
2483.536000	---	46.51	54.00	7.49	H	0.4
2483.776000	53.73	---	74.00	20.27	H	0.4
2483.776000	---	47.24	54.00	6.76	H	0.4

18 GHz - 25 GHz (Transmitting in maximum output power low channel):

Project No.: RKSC250716001
 Date: 24.JUL.2025 19:40:56

Tester: Hugh Wu



Project No.: RKSC250716001
 Date: 24.JUL.2025 20:13:20

Tester: Hugh Wu

Frequency (GHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
20.22	---	38.84	54	15.16	H	12.48
20.22	49.17	---	74	24.83	H	12.48
20.21	---	38.63	54	15.37	V	12.47
20.21	48.7	---	74	25.3	V	12.47


Note: The test distance is 3m. The limit is 74dBμV/m(Peak) and 54dBμV/m(Average).

6 dB EMISSION BANDWIDTH


Environmental Conditions & Test Information

Test Date:	2025-07-28 to 2025-08-07
Temperature:	25-26 °C
Relative Humidity:	58-62 %
ATM Pressure:	100.2-101.5 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou


Mode	Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
ZigBee	Low	2405	1.572	≥0.5
	Middle	2440	1.506	≥0.5
	High	2480	1.542	≥0.5



ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 7.AUG.2025 16:41:21



ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 7.AUG.2025 16:56:31



ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 28.JUL.2025 09:55:06

MAXIMUM CONDUCTED OUTPUT POWER**Environmental Conditions & Test Information**


Test Date:	2025-07-28 to 2025-08-07
Temperature:	25-26 °C
Relative Humidity:	58-62 %
ATM Pressure:	100.2-101.5 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Test Result: Compliant.

EUT operation mode: Transmitting


Mode	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
ZigBee	2405	6.98	30	Pass
	2440	6.21	30	Pass
	2475	5.99	30	Pass
	2480	-1.70	30	Pass

2405 MHz




ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 7.AUG.2025 16:43:25

2440 MHz




ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 7.AUG.2025 16:57:47

2475 MHz



ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 7.AUG.2025 17:05:58

2480 MHz



ProjectNo.:RKSC250716001 Tester:Neil Zhou
Date: 28.JUL.2025 09:55:46

Environmental Conditions & Test Information

EUT operation mode: Transmitting

ProjectNo.:RKSC250716001 Tester:Neil Zhou

POWER SPECTRAL DENSITY

Environmental Conditions & Test Information


Test Date:	2025-07-28 to 2025-08-07
Temperature:	25-26 °C
Relative Humidity:	58-62 %
ATM Pressure:	100.2-101.5 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Test Result: Compliant.

EUT operation mode: Transmitting


Mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
ZigBee	Low	2405	-6.52	≤8
	Middle	2440	-7.02	≤8
	High	2480	-16.01	≤8

Low Channel




ProjectNo.:RKSC250716001 Tester:Neil Zhou

Middle Channel



ProjectNo.:RKSC250716001 Tester:Neil Zhou

High Channel



ProjectNo.:RKSC250716001 Tester:Neil Zhou

Date: 28.JUL.2025 09:57:28


CONDUCTED SPURIOUS EMISSION

Environmental Conditions & Test Information


Test Date:	2025-07-28 to 2025-08-07
Temperature:	25-26 °C
Relative Humidity:	58-62 %
ATM Pressure:	100.2-101.5 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Channel	Result (dB)	Limit (dB)	Verdict
Low	30.15	20	Pass
Middle	31.92	20	Pass
High	32.56	20	Pass


Low Channel



Middle Channel



High Channel



EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******