

TEST REPORT

Applicant:

Shenzhen Dimidou Technology Co., Ltd.

Address of Applicant:11B Haining Plaza, Dalang Street, Longhua District, SHENZH
EN PRC**Manufacturer/Factory:**

Shenzhen Dimidou Technology Co., Ltd.

Address of**Manufacturer/Factory:**11B Haining Plaza, Dalang Street, Longhua District, SHENZH
EN PRC**Equipment Under Test (EUT)**

Product Name: PET WATER DISPENSER

Model No.: MY01

Add. Model No.: MY01S,MY01A,MY01SA,MY01E,MY01SE

Trade Mark:

DMDPET**Applicable standards:**

FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt:

2022-12-09

Date of Test:

2022-12-12 to 2022-12-15

Date of report issued:

2023-01-04

Test Result :

Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:


**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	January 04, 2023	Original

Prepared by:



Date:

January 04, 2023

Project Engineer

Reviewed by:



Date:

January 04, 2023

Reviewer

3 Contents

1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY	4
5	GENERAL INFORMATION	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE AND TEST VOLTAGE	5
5.3	DESCRIPTION OF SUPPORT UNITS	5
5.4	DEVIATION FROM STANDARDS	5
5.5	ABNORMALITIES FROM STANDARD CONDITIONS	5
5.6	TEST FACILITY	5
5.7	TEST LOCATION	5
6	TEST INSTRUMENTS LIST	6
7	TEST RESULTS AND MEASUREMENT DATA	8
7.1	RADIATED EMISSION	8
8	TEST SETUP PHOTO	14
9	EUT CONSTRUCTIONAL DETAILS	14

4 Test Summary

Test Item	Test Requirement	Test Method	Class / Severity	Result
Conducted Emission	FCC Part15.107	ANSI C63.4	Class B	N/A
Radiated Emissions #	FCC Part15.109	ANSI C63.4	Class B	PASS

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A: Not applicable
3. # Refer to FCC Part 15.33 (b)(1) conditional testing procedure :

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product name:	PET WATER DISPENSER
Trade Mark:	DMDPET
Model No.:	MY01
Add. Model No.:	MY01S,MY01A,MY01SA,MY01E,MY01SE
Power Supply:	DC 5V1A

Note:

Models (MY01,MY01S) and models (MY01A,MY01SA,MY01E,MY01SE) the difference is only the appearance difference, and the circuit principle, safety structure and key parts are all the same. The difference does not affect the safety and emc performance of the product.

5.2 Test mode and Test voltage

Test mode:	
Operation mode	Keep the EUT in the operation status.
Test voltage:	
AC 120V/60Hz	

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
XIAOMI	USB Charger	MDY-10-EH	N/A

5.4 Deviation from Standards

None.
None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:
• FCC —Registration No.: 381383
Designation Number: CN5029
Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.
• IC —Registration No.: 9079A
CAB identifier: CN0091
The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.
• NVLAP (LAB CODE:600179-0)
Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

Tests were performed at:
Global United Technology Services Co., Ltd.
Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480 Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 02, 2020	July 01, 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 22, 2022	April 21, 2023
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 21, 2022	March 20, 2023
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June 12, 2022	June 11, 2023
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 23, 2022	June 22, 2023
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	April 22, 2022	April 21, 2023
9	Coaxial Cable	GTS	N/A	GTS211	April 22, 2022	April 21, 2023
10	Coaxial cable	GTS	N/A	GTS210	April 22, 2022	April 21, 2023
11	Coaxial Cable	GTS	N/A	GTS212	April 22, 2022	April 21, 2023
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	April 22, 2022	April 21, 2023
13	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 23, 2022	June 22, 2023
14	Band filter	Amindeon	82346	GTS219	June 23, 2022	June 22, 2023
15	Power Meter	Anritsu	ML2495A	GTS540	June 23, 2022	June 22, 2023
16	Power Sensor	Anritsu	MA2411B	GTS541	June 23, 2022	June 22, 2023
17	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 22, 2022	April 21, 2023
18	Splitter	Agilent	11636B	GTS237	June 23, 2022	June 22, 2023
19	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 29, 2022	Nov. 28, 2023
20	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 22, 2022	April 21, 2023
21	Breitband hornantenna	SCHWARZBECK	BBHA 9170	GTS579	Oct. 16, 2022	Oct. 15, 2023
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 16, 2022	Oct. 15, 2023
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 16, 2022	Oct. 15, 2023
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June 23, 2022	June 22, 2023
25	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 22, 2022	April 21, 2023

GTS

Report No.: GTS202301050007F01

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May 14, 2022	May 13, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 24, 2022	April 23, 2023
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 23, 2022	June 22, 2023
4	ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	GTS226	April 22, 2022	April 21, 2023
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	JINCHUANG	GSP-8A	GTS639	April 28, 2022	April 27, 2023
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	April 15, 2022	April 14, 2023
9	ISN	SCHWARZBECK	NTFM 8158	GTS565	April 22, 2022	April 21, 2023
10	High voltage probe	SCHWARZBECK	TK9420	GTS537	April 22, 2022	April 21, 2023

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	April 25, 2022	April 24, 2023
2	Barometer	KUMAO	SF132	GTS647	July 26, 2022	July 25, 2023

Global United Technology Services Co., Ltd.



No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960

Page 7 of 14

7 Test Results and Measurement Data


7.1 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																									
Test Method:	ANSI C63.4:2014																									
Test Frequency Range:	30MHz to 18GHz																									
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																									
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>120kHz</td> <td>300kHz</td> <td>Quasi-peak</td> </tr> <tr> <td rowspan="2">Above 1GHz</td><td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Value	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak	Above 1GHz	Peak	1MHz	3MHz	Peak	Peak	1MHz	10Hz	Average		
Frequency	Detector	RBW	VBW	Value																						
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak																						
Above 1GHz	Peak	1MHz	3MHz	Peak																						
	Peak	1MHz	10Hz	Average																						
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Limit (dBμV/m @3m)</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td> <td>40.00</td> <td>Quasi-peak</td> </tr> <tr> <td>88MHz-216MHz</td> <td>43.50</td> <td>Quasi-peak</td> </tr> <tr> <td>216MHz-960MHz</td> <td>46.00</td> <td>Quasi-peak</td> </tr> <tr> <td>960MHz-1GHz</td> <td>54.00</td> <td>Quasi-peak</td> </tr> <tr> <td>1GHz-18GHz</td> <td>54.00</td> <td>Average</td> </tr> <tr> <td>1GHz-18GHz</td> <td>74.00</td> <td>Peak</td> </tr> </tbody> </table>					Frequency	Limit (dB μ V/m @3m)	Value	30MHz-88MHz	40.00	Quasi-peak	88MHz-216MHz	43.50	Quasi-peak	216MHz-960MHz	46.00	Quasi-peak	960MHz-1GHz	54.00	Quasi-peak	1GHz-18GHz	54.00	Average	1GHz-18GHz	74.00	Peak
Frequency	Limit (dB μ V/m @3m)	Value																								
30MHz-88MHz	40.00	Quasi-peak																								
88MHz-216MHz	43.50	Quasi-peak																								
216MHz-960MHz	46.00	Quasi-peak																								
960MHz-1GHz	54.00	Quasi-peak																								
1GHz-18GHz	54.00	Average																								
1GHz-18GHz	74.00	Peak																								
Test setup:	<p>For radiated emissions from 30MHz to 1GHz</p>  <p>For radiated emissions above 1GHz</p> 																									

Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 				
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1 012mbar				
Test Instruments:	Refer to section 6 for details				
Test mode:	Refer to section 5.2 for details and only show the worst case.				
Test results:	Pass				


Measurement Data Below 1GHz

Test mode:	Operation mode	Antenna Polarity:	Horizontal
------------	----------------	-------------------	------------



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.9586	28.50	-0.46	28.04	40.00	-11.96	QP
2	40.0173	28.67	-2.05	26.62	40.00	-13.38	QP
3	50.4614	29.34	-6.85	22.49	40.00	-17.51	QP
4	116.4476	29.17	-7.02	22.15	40.00	-17.85	QP
5	132.1489	29.23	-6.73	22.50	40.00	-17.50	QP
6	240.1442	29.27	-6.91	22.36	47.00	-24.64	QP

Test mode:	Operation mode	Antenna Polarity:	Vertical
------------	----------------	-------------------	----------




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.6392	27.37	-0.14	27.23	40.00	-12.77	QP
2	36.0139	28.21	-1.45	26.76	40.00	-13.24	QP
3	50.8172	35.57	-6.88	28.69	40.00	-11.31	QP
4	108.5455	32.49	-7.63	24.86	40.00	-15.14	QP
5	118.9285	31.82	-6.77	25.05	40.00	-14.95	QP
6	198.6424	29.33	-7.56	21.77	40.00	-18.23	QP

GTS

Report No.: GTS202301050007F01


Above 1GHz

Test mode:	Operation mode	Antenna Polarity:	Horizontal
------------	----------------	-------------------	------------



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1011.652	47.83	1.58	49.41	74.00	-24.59	peak
2	1011.652	31.78	1.58	33.36	54.00	-20.64	AVG
3	1328.199	23.47	24.23	47.70	74.00	-26.30	peak
4	1328.199	8.26	24.23	32.49	54.00	-21.51	AVG
5	2468.482	23.82	26.45	50.27	74.00	-23.73	peak
6	2468.482	6.41	26.45	32.86	54.00	-21.14	AVG
7	4975.246	15.38	30.45	45.83	74.00	-28.17	peak
8	4975.246	1.88	30.45	32.33	54.00	-21.67	AVG
9	6763.012	12.30	35.04	47.34	74.00	-26.66	peak
10	6763.012	-0.21	35.04	34.83	54.00	-19.17	AVG
11	8235.116	10.28	36.72	47.00	74.00	-27.00	peak
12	8235.116	-4.92	36.72	31.80	54.00	-22.20	AVG

Test mode:	Operation mode	Antenna Polarity:	Vertical
------------	----------------	-------------------	----------



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1017.529	47.36	1.67	49.03	74.00	-24.97	peak
2	1017.529	34.69	1.67	36.36	54.00	-17.64	AVG
3	1359.332	24.25	24.26	48.51	74.00	-25.49	peak
4	1359.332	9.81	24.26	34.07	54.00	-19.93	AVG
5	1946.665	22.33	25.54	47.87	74.00	-26.13	peak
6	1946.665	7.47	25.54	33.01	54.00	-20.99	AVG
7	2903.127	20.06	27.23	47.29	74.00	-26.71	peak
8	2903.127	5.51	27.23	32.74	54.00	-21.26	AVG
9	3811.519	18.18	28.67	46.85	74.00	-27.15	peak
10	3811.519	2.77	28.67	31.44	54.00	-22.56	AVG
11	7002.185	14.89	35.80	50.69	74.00	-23.31	peak
12	7002.185	-5.68	35.80	30.12	54.00	-23.88	AVG

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

For Radiated Emission above 18GHz, there was not any unwanted emission detected, so no need to report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II & III** for details

-----End-----