

Product Introduction:

This Product usee 2.4G wirelessdigital remote control technology,remote control one-to-one control,simple and convenient Operation,Strong anti-interference adility.

Receivng method:RF2.4G

Remote control distance:8-20 meters

Remote control dattery:NO.7 1.5V X2

Remote control matching code:

Turn on the power and Press and hold the light pairing key within 5 seconds of the ight on,When you hear a beep or a light flashes,thecode match is successful, Lf you need to match the code a second time, you need to wait 30 seconds before turning on the power and repeat the above operation

Press FAN/OFF pairing within 5 seconds after power on

CAUTION:

The electronic switch is not an isolated product ant needs to be operated by professional personnel during installation.

The electronic switch is triggered by the remote control, and the wireless frequency of the remote control transmitter is 2.4GHz



FCC Caution:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-- Reorient or relocate the receiving antenna.

-- Increase the separation between the equipment and receiver.

-- Connect the equipment into an outlet on a circuit different

from that to which the receiver is connected.

-- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.