

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

10.3-INCH reader

Model No.: SHERD-01-9BA, SHERD-0X-9BA

(X indicates the serial number from 1 to 10000, and B indicates color A to Z)

FCC ID: 2A9YMSHERD-01

Trademark: N/A

Report No.: E01A23010214F00102

Issue Date: February 22, 2023

Prepared for

Guangdong SID Technology CO.,LTD

**Room 101, Building 5, No. 21, Dongke Road, Dongcheng Street,
Dongguan City, Guangdong**

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

**1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake
Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr.,
China.**

**This report shall not be reproduced, except in full, without the written approval of
Dong Guan Anci Eleaactronic Technology Co., Ltd.**

VERIFICATION OF COMPLIANCE

Applicant:	Guangdong SID Technology CO.,LTD Room 101, Building 5, No. 21, Dongke Road, Dongcheng Street, Dongguan City, Guangdong
Manufacturer:	Guangdong SID Technology CO.,LTD Room 101, Building 5, No. 21, Dongke Road, Dongcheng Street, Dongguan City, Guangdong
Product Description:	10.3-INCH reader
Trade Mark:	N/A
Model Number:	SHERD-01-9BA, SHERD-0X-9BA (X indicates the serial number from 1 to 10000, and B indicates color A to Z) (All models are the same except for the model name and color of appearance, we choose model: SHERD-01-9BA for all tests.)
Sample number:	A23010214 003


We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2022).

Date of Test : January 07, 2023 to February 20, 2023



Prepared by : Duke Liu/Editor



Reviewer & Authorized
Signer : Tiger Xu/ Supervisor

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	E01A23010214F00102

Table of Contents

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 TEST METHODOLOGY	5
2. SYSTEM TEST CONFIGURATION.....	6
2.1 EUT CONFIGURATION	6
2.2 EUT EXERCISE	6
2.3 TEST PROCEDURE	6
2.4 CONFIGURATION OF TESTED SYSTEM.....	6
3. DESCRIPTION OF TEST MODES	7
4. SUMMARY OF TEST RESULTS.....	8
5. TEST FACILITY.....	11
6. CONDUCTED EMISSIONS TEST	12
6.1 MEASUREMENT PROCEDURE:	12
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	12
6.3 MEASUREMENT EQUIPMENT USED:	12
6.4 CONDUCTED EMISSION LIMIT	12
6.5 MEASUREMENT RESULT:.....	13
7. RADIATED EMISSION TEST	15
7.1 MEASUREMENT PROCEDURE	15
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	16
7.3 MEASUREMENT EQUIPMENT USED	17
7.4 RADIATED EMISSION LIMIT	18
7.5 MEASUREMENT RESULT	19
8. 6DB BANDWIDTH TEST	24
8.1 MEASUREMENT PROCEDURE	24
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	24
8.3 MEASUREMENT EQUIPMENT USED	24
8.4 MEASUREMENT RESULTS.....	24
9. MAXIMUM PEAK OUTPUT POWER TEST	25
9.1 MEASUREMENT PROCEDURE	32
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	32
9.3 MEASUREMENT EQUIPMENT USED	32
9.4 PEAK POWER OUTPUT LIMIT	32
9.5 MEASUREMENT RESULTS.....	32
10. BAND EDGE TEST	33
10.1 MEASUREMENT PROCEDURE	33
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	34
10.3 MEASUREMENT EQUIPMENT USED	34
10.4 MEASUREMENT RESULTS.....	34
11. POWER DENSITY	44
11.1 TEST EQUIPMENT	44
11.2 MEASURING INSTRUMENTS AND SETTING.....	44
11.3 TEST PROCEDURES.....	44
11.4 BLOCK DIAGRAM OF TEST SETUP	44
11.5 LIMIT	44
11.6 TEST RESULT	45
12. ANTENNA PORT EMISSION	52

12.1	TEST EQUIPMENT	52
12.2	MEASURING INSTRUMENTS AND SETTING.....	52
12.3	TEST PROCEDURES.....	52
12.4	BLOCK DIAGRAM OF TEST SETUP.....	52
12.5	TEST RESULT	52
13.	ANTENNA APPLICATION	66
13.1	ANTENNA REQUIREMENT.....	66
13.2	RESULT	66
14.	PHOTOS OF EUT	67

1. General Information

1.1 Product Description

Characteristics	Description
Product Name	10.3-INCH reader
Model number	SHERD-01-9BA
Power Supply	DC 5V, 2A
Test Power Supply	DC 5V from adapter and Battery 3.8V
Modulation	802.11b: DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM(BPSK/QPSK/16QAM/64QAM)
Operating Frequency Range	2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40);
Number of Channels	11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40);
Transmit Power Max	802.11b: 6.25dBm 802.11g: 6.13dBm 802.11n(HT20): 6.19dBm 802.11n(HT40): 5.96dBm
Antenna Type	Internal antenna
Antenna Gain	2.14dBi
Sample receipt date	January 07, 2023

Note: for more details, please refer to the User's manual of the EUT.

1.2 Test Methodology

All the test program has follow FCC new test procedure KDB 558074 D01 15.247 Meas Guidance v05r02 and in accordance with the procedures given in ANSI C63.10-2013.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	10.3-INCH reader	N/A	SHERD-01-9BA	2A9YMSHERD-01	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition and Only the worst case data were reported. The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting mode is programmed. EUT is connected by com port, and transmit the control instruction via test software(realtek wifi test tool.apk).

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11 n (HT40):


Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452


Operated Mode for Worst Duty cycle:

Duty Cycle:

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
802.11b	2412	98.99	0
802.11b	2437	99.01	0
802.11b	2462	98.99	0
802.11g	2412	98.94	0
802.11g	2437	98.94	0
802.11g	2462	98.87	0
802.11n(HT20)	2412	98.94	0
802.11n(HT20)	2437	98.79	0
802.11n(HT20)	2462	98.94	0
802.11n(HT40)	2422	98.78	0
802.11n(HT40)	2437	98.78	0
802.11n(HT40)	2452	98.78	0

All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages:





4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	N/A
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass
N/A (Not Applicable). EUT powered by battery.		

5. Test Facility

Site Description

EMC Lab. : Accredited by FCC, May 30, 2019
Designation Number: CN1230
Test Firm Registration Number: 991798


Name of Firm : Dong Guan Anci Electronic Technology Co., Ltd.
Site Location : 1-2 Floor, Building A, No.11, Headquarters 2 Road,
Songshan, Lake Hi-tech Industrial Development
Zone, Dongguan City, Guangdong Pr., China.

6. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

Item	EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
1.	LISN	ROHDE&SCHWARZ	ENV216	101413	2023-10-07
2.	RF Cable	N/A	ZT06S-NJ-NJ-2.5M	19044022	2023-05-12
3.	EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2023-05-12
4.	1# Shielded Room	chengyu	8m*4m*3.3m	N/A	2025-11-21
5.	Test Software	Farad	EZ-EMC (Ver.ANCI-3A1)	N/A	N/A

6.4 Conducted Emission Limit

(7) Conducted Emission

Frequency(MHz)

0.15-0.5

0.5-5.0

5.0-30.0

Quasi-peak

66-56

56

60

Average

56-46

46


50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.5 Measurement Result:

All the modulation modes were tested the data of the worst mode (802.11 b TX2412) are recorded in the following pages and the others modulation methods do not exceed the limits. Please refer to following pages.




Site:	843	Phase:	L1	Temperature(C):	26(C)
Limit:	FCC PART 15C Conduction(QP)	Test Time:		Humidity(%):	60%
EUT:	10.3-INCH reader	Power Rating:			
M/N.:	SHERD-01-9BA	Test Engineer:			
Mode:	WIFI TX2412				
Note:					

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.2175	12.02	9.55	21.57	62.91	-41.34	QP	
2	0.2175	4.73	9.55	14.28	52.91	-38.63	AVG	
3	0.3704	12.31	9.73	22.04	58.49	-36.45	QP	
4	0.3704	2.48	9.73	12.21	48.49	-36.28	AVG	
5	2.7239	12.18	10.07	22.25	56.00	-33.75	QP	
6	2.7239	2.60	10.07	12.67	46.00	-33.33	AVG	
7	3.2505	14.14	10.05	24.19	56.00	-31.81	QP	
8	3.2505	4.97	10.05	15.02	46.00	-30.98	AVG	
9	4.8975	16.46	10.08	26.54	56.00	-29.46	QP	
10	4.8975	9.49	10.08	19.57	46.00	-26.43	AVG	
11	7.9080	22.25	10.11	32.36	60.00	-27.64	QP	
12	7.9080	17.78	10.11	27.89	50.00	-22.11	AVG	

*:Maximum data x:Over limit !:over margin

Global Testing , Great Quality.



Site:	843	Phase:	N	Temperature(C):	26(C)
Limit:	FCC PART 15C Conduction(QP)	Test Time:		Humidity(%):	60%
EUT:	10.3-INCH reader	Power Rating:		2023-01-09	
M/N.:	SHERD-01-9BA	Test Engineer:		AC 120V/60Hz	
Mode:	WIFI TX2412			Sunshine	
Note:					

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measurement(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1	0.1995	9.37	9.60	18.97	63.63	-44.66	QP	
2	0.1995	5.05	9.60	14.65	53.63	-38.98	AVG	
3	0.7756	6.62	9.80	16.42	56.00	-39.58	QP	
4	0.7756	-1.63	9.80	8.17	46.00	-37.83	AVG	
5	2.5266	8.80	10.05	18.85	56.00	-37.15	QP	
6	2.5266	3.49	10.05	13.54	46.00	-32.46	AVG	
7	3.3225	11.17	10.02	21.19	56.00	-34.81	QP	
8	3.3225	5.91	10.02	15.93	46.00	-30.07	AVG	
9	7.5750	21.75	10.13	31.88	60.00	-28.12	QP	
10	7.5750	18.53	10.13	28.66	50.00	-21.34	AVG	
11	12.6915	20.65	10.12	30.77	60.00	-29.23	QP	
12	12.6915	18.06	10.12	28.18	50.00	-21.82	AVG	

*:Maximum data x:Over limit !:over margin

7. Radiated Emission Test

7.1 Measurement Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

7.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
6.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2022-11-12
7.	Pre-Amplifier	HP	8447D	2727A06172	2023-05-12
8.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2023-05-12
9.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2022-11-12
10.	Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
11.	Low noise Amplifiers	A-INFO	LA1018N4009	J101313052400 1	2023-05-12
12.	Horn antenna	A-INFO	LB-10180-SF	J203109061212 3	2023-05-12
13.	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX10 0KHz-40GHz	J101313052400 1	2022-11-12
14.	DRG Horn Antenna	A.H.SYSTEMS	SAS-574	J203109061212 3	2022-11-12
15.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-2m	N/A	2022-11-12
16.	RF Cable	Gigalink Microwave	ZT40-2.92J-2. 92J-0.3m	N/A	2022-11-12
17.	RF Cable	N/A	N/A	6#	2023-05-12
18.	RF Cable	N/A	N/A	1-1#	2023-05-12
19.	RF Cable	N/A	N/A	1-2#	2023-05-12
20.	RF Cable	N/A	N/A	7#	2023-05-12
21.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2023-05-12
22.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

: 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	2023-01-09
Frequency Range:	9KHz~30MHz	Temperature :	26°C
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	Sunshine

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (TX 802.11b 2412MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:



Site:	LAB	Antenna::Horizontal	Temperature(C):26(C)
Limit:	FCC Part 15 C 3m Radiation		Humidity(%):60%
EUT:	10.3-INCH reader	Test Time:	2023-01-09
M/N.:	SHERD-01-9BA	Power Rating:	Battery 3.8V
Mode:	TX2412	Test Engineer:	Sunshine
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1 *	43.5057	24.49	-4.39	20.10	40.00	-19.90	QP	
2	51.3005	22.85	-4.25	18.60	40.00	-21.40	QP	
3	56.9912	23.10	-4.60	18.50	40.00	-21.50	QP	
4	105.6415	22.46	-4.66	17.80	43.50	-25.70	QP	
5	125.0066	23.97	-6.37	17.60	43.50	-25.90	QP	
6	213.0151	22.66	-4.86	17.80	43.50	-25.70	QP	

Note: 1. Result Level = Read Level+ Antenna Factor+ Cable Loss- Amp. Factor



Site:	LAB	Antenna::Vertical	Temperature(C):26(C)
Limit:	FCC Part 15 C 3m Radiation		Humidity(%):60%
EUT:	10.3-INCH reader	Test Time:	2023-01-09
M/N.:	SHERD-01-9BA	Power Rating:	Battery 3.8V
Mode:	TX2412	Test Engineer:	Sunshine
Note:			

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1 *	31.2893	28.59	-7.49	21.10	40.00	-18.90	QP	
2	46.3402	24.69	-4.29	20.40	40.00	-19.60	QP	
3	60.0691	25.32	-4.82	20.50	40.00	-19.50	QP	
4	77.3212	25.63	-10.43	15.20	40.00	-24.80	QP	
5	114.1138	22.83	-4.93	17.90	43.50	-25.60	QP	
6	203.5228	23.19	-4.99	18.20	43.50	-25.30	QP	

Note: 1. Result Level = Read Level+ Antenna Factor+ Cable Loss- Amp. Factor

Above 1GHz:

All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits. The frequency range from 1GHz to 25GHz is investigated.

Operation Mode: 802.11b Lowest
Test Voltage: Battery 3.8V

Test Date : 2023-01-09
Test by: Sunshine

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	63.25	43.25	74	54	-10.75	-10.75
7236	V	62.25	42.14	74	54	-11.75	-11.86
9648	V	62.14	42.26	74	54	-11.86	-11.74
12060	V	62.02	42.58	74	54	-11.98	-11.42
14472	V	62.15	42.19	74	54	-11.85	-11.81
16884	V	62.36	42.36	74	54	-11.64	-11.64
4824	H	62.41	45.27	74	54	-11.59	-8.73
7236	H	62.58	42.52	74	54	-11.42	-11.48
9648	H	62.31	42.32	74	54	-11.69	-11.68
12060	H	62.12	42.52	74	54	-11.88	-11.48
14472	H	60.32	41.03	74	54	-13.68	-12.97
16884	H	58.96	39.52	74	54	-15.04	-14.48

Operation Mode: 802.11b Middle
Test Voltage: Battery 3.8V

Test Date : 2023-01-09
Test by: Sunshine

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874	V	63.58	43.25	74	54	-10.42	-10.75
7311	V	62.17	42.68	74	54	-11.83	-11.32
9688	V	62.32	42.14	74	54	-11.68	-11.86
12185	V	63.58	43.25	74	54	-10.42	-10.75
14622	V	61.52	41.35	74	54	-12.48	-12.65
17059	V	60.32	40.23	74	54	-13.68	-13.77
4874	H	62.14	42.23	74	54	-11.86	-11.77
7311	H	62.47	42.41	74	54	-11.53	-11.59
9688	H	62.14	42.02	74	54	-11.86	-11.98
12185	H	63.05	43.52	74	54	-10.95	-10.48
14622	H	61.58	41.25	74	54	-12.42	-12.75
17059	H	60.36	40.25	74	54	-13.64	-13.75

Operation Mode: 802.11b Highest

Test Date : 2023-01-09

Test Voltage: Battery 3.8V

Test by: Sunshine

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924	V	63.25	43.81	74	54	-10.75	-10.19
7386	V	63.14	43.25	74	54	-10.86	-10.75
9848	V	63.51	43.26	74	54	-10.49	-10.74
12310	V	62.62	42.32	74	54	-11.38	-11.68
14772	V	62.58	43.02	74	54	-11.42	-10.98
17234	V	62.14	43.26	74	54	-11.86	-10.74
4924	H	62.32	42.74	74	54	-11.68	-11.26
7386	H	62.47	42.36	74	54	-11.53	-11.64
9848	H	62.55	42.52	74	54	-11.45	-11.48
12310	H	61.36	41.35	74	54	-12.64	-12.65
14772	H	61.17	41.32	74	54	-12.83	-12.68
17234	H	60.33	40.23	74	54	-13.67	-13.77

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

No others harmonics emissions are higher than 20 dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


8. 6dB Bandwidth Test

8.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function. The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02 .

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
RF Test Software	MWRF-test	MTS 8310	N/A	N/A
Radio Frequency control box	MWRF-test	MW200-RFCB	MW220111ANCI	2023-05-12

8.4 Measurement Results


6db Bandwidth Test Data Chart:


Refer to attached data chart.


Spectrum Detector: PK
 Test By: Sunshine
 Humidity : 60%


Test Date : January 12, 2023
 Temperature : 26°C


Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
b	2412	Ant1	10.083	0.5	Pass
b	2437	Ant1	10.08	0.5	Pass
b	2462	Ant1	10.095	0.5	Pass
g	2412	Ant1	16.536	0.5	Pass
g	2437	Ant1	16.53	0.5	Pass
g	2462	Ant1	16.527	0.5	Pass
n20	2412	Ant1	17.607	0.5	Pass
n20	2437	Ant1	17.598	0.5	Pass
n20	2462	Ant1	17.628	0.5	Pass
n40	2422	Ant1	36.372	0.5	Pass
n40	2437	Ant1	36.384	0.5	Pass
n40	2452	Ant1	36.402	0.5	Pass














9. Maximum Peak Output Power Test

9.1 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used

EQUIPMENT TYPE	Manufacturer	Model No.	Serial Number	Calibrated until.
USB RF Power sensor	RadiPower	RPR3006W	17I00015SNO88	2022-11-12
RF Test Software	MAIWEI	MTS 8310	N/A	N/A

9.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

9.5 Measurement Results

Spectrum Detector:	PK	Test Date :	January 12, 2023
Test By:	Sunshine	Temperature :	26°C
Test Result:	PASS	Humidity :	60%

Test Channel	Peak Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	6.25	6.05	6.14	5.96	30	Pass
Middle	6.15	6.12	6.16	5.84		
Highest	6.15	6.05	6.19	5.87		

10. Band Edge Test

10.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 5558074 D01 15.247 Meas Guidance v05r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 5558074 D01 15.247 Meas Guidance v05r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.


When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
RF Test Software	MWRF-test	MTS 8310	N/A	N/A
Radio Frequency control box	MWRF-test	MW200-RFCB	MW220111ANCI	2023-05-12


10.4 Measurement Results


1. Conducted Test


Please refer to the following pages.


Spectrum Detector:	PK	Test Date :	January 12, 2023
Test By:	Sunshine	Temperature :	26°C
Test Result:	PASS	Humidity :	60%


2. Test Graphs
Band Edge NVNT b 2412MHz Antl Ref




















3. Radiated emission Test

Spectrum Detector:

PK/AV

Test Date :

2023-01-09

Test By:

Sunshine

Temperature :

28 °C

Humidity :

65 %

IEEE 802.11b SISO										
Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
<2400	H	86.62	68.04	-26.3	60.32	41.74	74	54	-13.68	-12.26
<2400	V	85.46	66.49	-26.1	59.36	40.39	74	54	-14.64	-13.61
>2483.5	H	86.44	67.66	-26.3	60.14	41.36	74	54	-13.86	-12.64
>2483.5	V	85.43	66.35	-26.1	59.33	40.25	74	54	-14.67	-13.75

IEEE 802.11g SISO										
Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
<2400	H	88.62	68.66	-26.3	62.32	42.36	74	54	-11.68	-11.64
<2400	V	86.27	66.28	-26.1	60.17	40.18	74	54	-13.83	-13.82
>2483.5	H	87.62	68.04	-26.3	61.32	41.74	74	54	-12.68	-12.26
>2483.5	V	86.38	66.34	-26.1	60.28	40.24	74	54	-13.72	-13.76

IEEE 802.11n(HT20) SISO										
Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
<2400	H	88.69	68.66	-26.3	62.39	42.36	74	54	-11.61	-11.64
<2400	V	86.24	67.9	-26.1	60.14	41.8	74	54	-13.86	-12.2
>2483.5	H	88.52	68.66	-26.3	62.22	42.36	74	54	-11.78	-11.64
>2483.5	V	86.57	66.35	-26.1	60.47	40.25	74	54	-13.53	-13.75

IEEE 802.11n(HT40) SISO										
Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
<2400	H	88.62	68.95	-26.3	62.32	42.65	74	54	-11.68	-11.35
<2400	V	87.32	67.46	-26.1	61.22	41.36	74	54	-12.78	-12.64
>2483.5	H	86.82	66.49	-26.3	60.52	40.19	74	54	-13.48	-13.81
>2483.5	V	86.7	66.35	-26.1	60.6	40.25	74	54	-13.4	-13.75

11. Power Density

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
RF Test Software	MWRF-test	MTS 8310	N/A	N/A
Radio Frequency control box	MWRF-test	MW200-RFCB	MW220111ANCI	2023-05-12

11.2 Measuring Instruments and Setting

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3kHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

11.3 Test Procedures

The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02.

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set analyzer center frequency to DTS channel center frequency.
- Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- Set the RBW ≥ 3 kHz. Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

11.4 Block Diagram of Test Setup



11.5 Limit


The transmitted power density averaged over any 1 second interval shall not be


greater +8dBm in any 3 kHz bandwidth.


11.6 Test Result


Spectrum Detector: PK Test Date : January 12, 2023
 Test By: Sunshine Temperature : 26°C
 Test Result: PASS Humidity : 60%


Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
b	2412	Ant1	-6.16	0	-6.16	8	Pass
b	2437	Ant1	-5.72	0	-5.72	8	Pass
b	2462	Ant1	-5.48	0	-5.48	8	Pass
g	2412	Ant1	-28.57	0	-28.57	8	Pass
g	2437	Ant1	-28.46	0	-28.46	8	Pass
g	2462	Ant1	-28.56	0	-28.56	8	Pass
n20	2412	Ant1	-27.33	0	-27.33	8	Pass
n20	2437	Ant1	-27.1	0	-27.1	8	Pass
n20	2462	Ant1	-27.27	0	-27.27	8	Pass
n40	2422	Ant1	-28.63	0	-28.63	8	Pass
n40	2437	Ant1	-28.22	0	-28.22	8	Pass
n40	2452	Ant1	-29.11	0	-29.11	8	Pass














12. Antenna Port Emission

12.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-12
RF Test Software	MWRF-test	MTS 8310	N/A	N/A
Radio Frequency control box	MWRF-test	MW200-RFCB	MW220111ANCI	2023-05-12

12.2 Measuring Instruments and Setting

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

12.3 Test Procedures

The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05r02 .

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

12.4 Block Diagram of Test setup




12.5 Test Result


PASS.


Please refer to following pages.


Spectrum Detector: PK Test Date : January 12, 2023
Test By: Sunshine Temperature : 26°C
Test Result: PASS Humidity : 60%


Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	Ant1	-44.14	-20	Pass
b	2437	Ant1	-46.17	-20	Pass
b	2462	Ant1	-46.12	-20	Pass
g	2412	Ant1	-36.52	-20	Pass
g	2437	Ant1	-37.72	-20	Pass
g	2462	Ant1	-36.39	-20	Pass
n20	2412	Ant1	-36.65	-20	Pass
n20	2437	Ant1	-36.87	-20	Pass
n20	2462	Ant1	-37.64	-20	Pass
n40	2422	Ant1	-34.46	-20	Pass
n40	2437	Ant1	-34.27	-20	Pass
n40	2452	Ant1	-34.12	-20	Pass
































13. Antenna Application

13.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2 Result

The EUT'S antenna is an internal antenna. The antenna's gain is 2.14dBi and meets the requirement.

14. Photos of EUT

Please refer to the test report: E01A23010214F00102

---The end of report---