

FCC SAR Exclusion Report

FCC ID: 2A9ZJ-B322P

Report No. : BTL-FCCP-2-2212G030
Equipment : Wearable Bluetooth Device
Model Name : B322P
Series Mode : X##Y(The "X" "Y" in the model name can be A to Z, a to z, "#" can be 0 to 9)
Brand Name : Aspire Motion, Aspire Balance, Aspire Motion Connect, Aspire Sensor,步固登峰
Applicant : Booguu Company Limited
Address : FLAT/RM 225A 2/F Core Building2,1 Science Park West Avenue HKSTP SHATIN NT
FCC Rule Part(s) : FCC CFR Title 47, Part 2, Subpart J (§2.1093)
KDB 447498 D04 General RF Exposure Guidance v01
Date of Receipt : 2023/1/16
Date of Test : 2023/1/16 ~ 2023/2/18
Issued Date : 2023/3/2

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by

: Eric Lee
Eric Lee, Engineer



Approved by

: Jerry Chuang
Jerry Chuang, Supervisor

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-2-2212G030	R00	Original Report.	2023/3/2	Valid

According to KDB 447498 D04 Interim General RF Exposure Guidance v01

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

Table for Filed Antenna:

Ant.	Brand Name	Model Name	Type	Connector	Frequency (MHz)	Gain (dBi)
1	Unictron	CW201	Chip	N/A	2400-2500	-1.76

Note: The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Maximum RF output power:

Mode	Maximum Output Power (dBm)	Tolerance (dB)	Maximum Tune-up Power (dBm)
LE	0	+/- 0.5	0.50

Therefore RF Exposure Evaluation:

Distance (mm)	Frequency (MHz)	Maximum Tune-up Power (dBm)	Maximum Tune-up Power (mW)	SAR Exclusion Threshold (mW)	Test Required
5.00	2480	0.50	1.12	2.72	No

Therefore, standalone SAR measurements are not required for both head and body.

End of Test Report