

RF Exposure Compliance

RESULT:

Pass

Test standard : FCC Part 1.1091
Limit : Table 1 of 47 CFR FCC Part 1.1310
Kind of test site : Shielded room

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore MPE measurement or computational modelling should be used to determine compliance.

MPE Calculation is based on the conducted power, and considering maximum power and Antenna gain. The following formula is used to MPE evaluation.

$$P_d = \frac{P_{out} * G}{4R^2\pi}$$

Where

P_d = power density in mW/cm^2 or W/m^2

P_{out} = output power to antenna in mW or W

G_{num} = Antenna gain in numeric

$\pi = 3.14159$

R = Distance between observation point and the center of radiator in cm or m

FCC Part 1.1310, Part 2.1091

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

MPE-Based Evaluation:

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	MPE (mW/cm ²)	Limit (mW/cm ²)	Verdict
2.4GHz SRD	-3.50*	20	0.0001	1.0	Pass
The Max fundamental is 91.69dBuV/m@3m (Refer to report CN23UPI8 001), i.e. -3.54dBm when converted to EIRP.					

Inclusion: The MPE is much lower than the limit.