

FCC / ISED – TEST REPORT

Report Number : **60.790.25.006.01R01** Date of Issue: **March 24, 2025**

Model/HVIN : **FM II Power Flex**

Product Type : **Merchandise Theft Deterrent System**

Applicant : **Mobile Technologies Inc.**

Address : **2345 NE Overlook Drive, Hillsboro OR 97006 United States of America.**

Production Facility (1) : **Shenzhen Xia Zi Tang Electronic Manufacturing Co Ltd.**

Address : **3F, Building B, No. 80 Shilong Avenue, ShuiTian Community, Shiyan Street, Baoan District, Shenzhen, China.**

Production Facility (2) : **Dinh Sang Technology Company Limited**

Address : **No 9 Street, Tam Phuoc Industrial Park, BienHoa City, DongNai Province, Vietnam.**

Test Result : **n Positive** o Negative

Total pages including Appendices : **46**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.

1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards.....	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups.....	8
8	Systems Test Configuration	10
9	Technical Requirement.....	11
9.1	Conducted Emission	11
9.2	Conducted Peak Output Power & EIRP	14
9.3	Power Spectral Density.....	16
9.4	6 dB Bandwidth.....	18
9.5	99% bandwidth	20
9.6	Spurious RF Conducted Emissions	22
9.7	Band Edge	26
9.8	Spurious Radiated Emissions for Transmitter	28
10	Test Equipment List	45
11	System Measurement Uncertainty.....	46



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu, Nantou, Nanshan District
Shenzhen 518052
P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 8828 5299

FCC Registration No.: 514049

FCC Deignation No.: CN5009

IC Registration No.: 10320A

ISED CAB Identifier: CN0077

3 Description of the Equipment Under Test

Description of the Equipment Under Test

Product:	Merchandise Theft Deterrent System
Model no.:	FM II Power Flex
Hardware Version Identification No. (HVIN)	FM II Power Flex
Product Marketing Name (PMN)	Merchandise Theft Deterrent System
Brand name:	N/A
FCC ID:	2AA2X-15000362
IC:	24439-15000362
Rating:	Power by Adaptor 5 VDC, 3 A or 9 VDC, 3 A or 12 VDC, 3 A 15 VDC, 3 A or 20 VDC, 3 A Internal Backup Battery 3.7 VDC (Internal rechargeable Li-ion battery) Output Port – USB-C 5 VDC, 3 A or 9 VDC, 3 A or 12 VDC, 3 A 15 VDC, 3 A or 20 VDC, 3 A
RF Transmission Frequency:	Zigbee: 2405MHz – 2480MHz
No. of Operated Channel:	16
Modulation:	O-QPSK
Antenna Type:	SMD Antenna
Antenna	Gain: 1.5 dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Merchandise Theft Deterrent System which support Zigbee function and 125 kHz near field card access function. Only Zigbee measurement included in this report.

NOTE:

1. The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + Amendment 1 March 2019 + Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 3 August 2023	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE- LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C/ RSS-247 Issue 3 / RSS-Gen Issue 5 + A1 + A2						
Test Condition		Test Site	Test Result			Test Environment
			Pass	Fail	N/A	
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
RSS-247 5.4(d)	Equivalent Isotropic Radiated Power	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
§15.247(a)(2) & RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
§15.247(e) & RSS-247 5.2(b)	Power spectral density	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
§15.247(d) & RSS-247 5.5	Band edge	Site 1	☒	☐	☐	T: 24.8°C H: 53.7%
§15.247(d) & §15.209 & §15.205 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	Site 1	☒	☐	☐	T: 24.7°C H: 49.3%
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 2	☒	☐	☐	--

Note 1: N/A=Not Applicable.

Note 2: The EUT uses a Patch antenna, which gain is 1.5 dBi. In accordance to §15.203 & RSS-Gen 6.8, it is considered sufficiently to comply with the provisions of this section.

Note 3: T :Temperature, H: Humidity

6 General Remarks

Remarks

This submittal(s) (test report) is intended for **FCC ID: 2AA2X-15000362**,
IC: 24439-15000362, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15,
Subpart C rules and RSS-247, RSS-GEN.

SUMMARY:

All tests according to the regulations cited on page 5 were

n - Performed

o - **Not** Performed

The Equipment under Test

n - **Fulfills** the general approval requirements.

o - **Does not** fulfill the general approval requirements.

Sample Received Date: February 25, 2025

Testing Start Date: February 27, 2025

Testing End Date: March 21, 2025

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -


Reviewed by:

Prepared by:

Tested by:



Eric LI
Section Manager



Kevin DU
EMC Project Engineer




Carry Cai
Test Engineer


7 Test Setups

7.1 Radiated test setups


9kHz - 30MHz




30MHz - 1GHz




Above 1GHz



7.2 Conducted RF test setups



7.3 AC Power Line Conducted Emission test setups



8 Systems Test Configuration

Auxiliary Equipment Used during Test:

Description	Manufacturer	Model NO.	Remark
Laptop	Lenovo	X220	0A72168
MTI Connect HUB	MTI	---	System Monitoring
Adaptor Power	W&T	W&T-PD2060A-CK 	Provided by Manufacturer

Cables Used During Test:

Cable	Length	Shielded/unshielded	With / without ferrite
---	---	---	---

The system was configured to non-hopping mode, testing channel 11, 18, 26.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

Only the worst case transmitter rate data mode is recorded in the report.

The Multiple Voltage Input is mainly to provide the Power for the connected accessories by the USB-C Output Port. So, the device which is adapted to operate by 5 VDC input.

Tested by provided Adaptor of 5 VDC, 3 A without loading connection.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit

According to §15.207 & RSS-GEN 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50


*Decreasing linearly with logarithm of the frequency

Test result: PASS

Conducted Emission at AC Power Line

EUT: FM II Power Flex
 Op Condition: Communication Mode
 Test Specification: FCC 15.207, RSS GEN 8.8
 Comment: 120V AC 60Hz, L Line

Test Result	
☒	Passed
☐	Not Passed




Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.162000	51.07	---	65.36	14.29	L1	9.67
0.434000	33.87	---	57.18	23.31	L1	9.67
1.154000	29.62	---	56.00	26.38	L1	9.70
3.102000	27.13	---	56.00	28.87	L1	9.76
6.246000	29.72	---	60.00	30.28	L1	9.85
9.046000	34.42	---	60.00	25.58	L1	9.91

Conducted Emission at AC Power Line

EUT: FM II Power Flex
 Op Condition: Communication Mode
 Test Specification: FCC 15.207, RSS GEN 8.8
 Comment: 120V AC 60Hz, N Line

Test Result	
☒	Passed
☐	Not Passed



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.158000	52.50	---	65.57	13.07	N	9.67
0.266000	36.33	---	61.24	24.91	N	9.66
0.698000	29.48	---	56.00	26.52	N	9.67
2.198000	31.97	---	56.00	24.03	N	9.71
5.338000	31.40	---	60.00	28.60	N	9.80
8.878000	37.08	---	60.00	22.92	N	9.89

9.2 Conducted Peak Output Power & EIRP

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following test receiver settings:
Span = approximately 5 times the 6dB bandwidth, centered on a channel need to test,
RBW > the 6dB bandwidth of the emission being measured, VBW $\geq$ 3RBW,
Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power and record the results in the test report.
5. Repeat above procedures until all frequencies measured were complete.

Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

According to & RSS-247 5.4(d), EIRP limit as below:


Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 4	≤ 36

Test result


Frequency MHz	Conducted Peak Output Power dBm	Antenna Gain dBi	EIRP dBm	Result
Bottom channel 2405MHz	-3.72	1.5	-2.22	Pass
Middle channel 2440MHz	-3.34	1.5	-1.84	Pass
Top channel 2480MHz	-3.74	1.5	-2.24	Pass

Test Graphs as below:


Zigbee_LCH_2405MHz_Ant1_NTNV



Zigbee_MCH_2440MHz_Ant1_NTNV



Zigbee_HCH_2480MHz_Ant1_NTNV



9.3 Power Spectral Density

Test Method

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
4. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
5. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
6. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz]


≤ 8

Test result


Frequency MHz	Power spectral density dBm/3kHz	Result
Bottom channel 2405MHz	-18.80	Pass
Middle channel 2440MHz	-19.58	Pass
Top channel 2480MHz	-20.49	Pass

Test Graphs as below:


Zigbee_LCH_2405MHz_Ant1_NTNV



Zigbee_MCH_2440MHz_Ant1_NTNV



Zigbee_HCH_2480MHz_Ant1_NTNV



9.4 6 dB Bandwidth

Test Method

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set center frequency to the nominal EUT channel center frequency
3. Set RBW =1% to 5% of the OBW but not less than 100kHz, VBW $\geq 3 \times$ RBW Detector = Peak. Trace mode = max hold. Sweep = auto Trace = max hold
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
5. Record the results in the test report.

Limit

Limit [kHz]


≥ 500

Test result


Frequency MHz	6dB bandwidth MHz	Result
Bottom channel 2405MHz	1.538	Pass
Middle channel 2440MHz	1.511	Pass
Top channel 2480MHz	1.559	Pass

Test Graphs as below:


Zigbee_LCH_2405MHz_Ant1_NTNV



Zigbee_MCH_2440MHz_Ant1_NTNV



Zigbee_HCH_2480MHz_Ant1_NTNV





9.5 99% bandwidth

Test Method

- 1. Set center frequency to the nominal EUT channel center frequency
- 2. Set span = 1.5 times to 5.0 times the OBW. Set RBW = 1 % to 5 % of the OBW
Set VBW ≥ 3 RBW Trace mode = max hold. Sweep = auto couple.
Allow the trace to stabilize.
- 3. Use the 99 % power bandwidth function of the instrument.
- 4. Record the results in the test report.

Limit

Limit [kHz]


--

Test result


Frequency MHz	99% bandwidth MHz	Result
Bottom channel 2405MHz	2.286	Pass
Middle channel 2440MHz	2.298	Pass
Top channel 2480MHz	2.359	Pass

Test Graphs as below:


Zigbee_LCH_2405MHz_Ant1_NTNV



Zigbee_MCH_2440MHz_Ant1_NTNV



Zigbee_HCH_2480MHz_Ant1_NTNV



9.6 Spurious RF Conducted Emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span. RBW = 100 kHz, VBW ≥ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.

Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

Test result


Test Mode	Antenna	Channel (MHz)	Frequency Range (MHz)	Reference Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
Zigbee	Ant0	2405	30~26500	-7.18	-51.97	-27.18	PASS
		2440	30~26500	-7.11	-45.97	-27.11	PASS
		2480	30~26500	-6.47	-42.09	-26.47	PASS

Remark: - The emissions exceed limit is fundamental signal.


Test Graphs as below:



Zigbee_LCH_2405MHz_Ant1_NTNV




Zigbee_LCH_2405MHz_Ant1_NTNV






Zigbee_MCH_2440MHz_Ant1_NTNV




Zigbee_MCH_2440MHz_Ant1_NTNV






Zigbee_HCH_2480MHz_Ant1_NTNV



Zigbee_HCH_2480MHz_Ant1_NTNV



9.7 Band Edge

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
5. The level displayed must comply with the limit specified in this Section. Submit these plots.
6. Repeat above procedures until all frequencies measured were complete.

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS-247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.

Frequency Range MHz	Limit (dBc)
30-25000	-20


Test result

Test Mode	Antenna	Channel	Channel (MHz)	Reference Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
Zigbee	Ant0	Low	2402	-7.18	-47.20	≤ -27.18	PASS
		High	2480	-6.47	-51.29	≤ -26.47	PASS


Test Graphs as below:



Zigbee_LCH_2405MHz_Ant1_NTNV



Zigbee_HCH_2480MHz_Ant1_NTNV



9.8 Spurious Radiated Emissions for Transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

Procedure for Unwanted Emissions Measurements Below 1000 MHz

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 KHz to 120KHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) VBW \ [3 × RBW].
- c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2. Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission(AV) at frequency above 1GHz.

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under § 15.247(b)(3) and RSS 247 section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in § 15.209(a) and RSS-Gen is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a) and RSS-Gen section 8.9, must also comply with the radiated emission limits specified in § 15.209(a) and RSS-Gen section 8.10.

Frequency MHz	Field Strength $\mu\text{V/m}$	Field Strength dB $\mu\text{V/m}$	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	AV	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit 3m(dB $\mu\text{V/m}$)=Limit 300m(dB $\mu\text{V/m}$)+40Log(300m/3m) (Below 30MHz)

Note 2: Limit 3m(dB $\mu\text{V/m}$)=Limit 30m(dB $\mu\text{V/m}$)+40Log(30m/3m) (Below 30MHz)

ISED Limit:

According to RSS-Gen 8.9 field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Frequency MHz	Field Strength $\mu\text{A/m}$	Field Strength $\text{dB}\mu\text{A/m}$	Detector	Measurement distance meters
0.009-0.490	6.37/F(kHz)	77.00-42.28	AV	3
0.490-1.705	63.7/F(kHz)	22.27-11.45	AV	3
1.705-30	0.08	18.06	AV	3
Frequency MHz	Field Strength $\mu\text{V/m}$	Field Strength $\text{dB}\mu\text{V/m}$	Detector	Measurement distance meters
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

(a) The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Note 1: $\text{Limit } 3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 300\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(300\text{m}/3\text{m})$ (Below 30MHz)

Note 2: $\text{Limit } 3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 30\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(30\text{m}/3\text{m})$ (Below 30MHz)


Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case test result is listed in the report.

Transmitting spurious emission test result as below:


FCC Test Result
Test data_9kHz to 30MHz
Zigbee _Low Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.026484	61.81	119.13	57.32	H	182.0	19.87
0.055248	57.74	112.75	55.00	H	9.0	19.92
0.125231	51.55	105.64	54.09	H	200.0	19.92
0.229600	50.77	100.38	49.61	H	0.0	19.88
0.468400	39.28	94.19	54.91	H	173.0	19.89
1.552950	33.63	63.81	30.18	H	1.0	20.00


FCC Test Result
 Test data_9kHz to 30MHz
 Zigbee _Low Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.027659	62.85	118.75	55.90	V	5.0	19.88
0.055295	58.00	112.74	54.74	V	350.0	19.92
0.101966	48.81	107.43	58.61	V	350.0	19.93
0.125231	42.18	105.64	63.46	V	313.0	19.92
0.358950	39.55	96.50	56.96	V	0.0	19.90
1.572850	32.13	63.70	31.56	V	118.0	20.00


ISED Test Result
 Test data_9kHz to 30MHz
 Zigbee _Low Channel:



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuA/m)	Limit (dBuA/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.026531	11.28	67.61	56.32	H	213.0	-31.66
0.055342	8.57	61.22	52.65	H	358.0	-31.61
0.125278	0.23	54.12	53.89	H	213.0	-31.61
0.224625	-0.65	49.05	49.70	H	0.0	-31.65
0.468400	-11.32	42.66	53.98	H	110.0	-31.64
1.642500	-17.42	11.48	28.91	H	2.0	-31.52


ISED Test Result
 Test data_9kHz to 30MHz
 Zigbee _Low Channel:



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuA/m)	Limit (dBuA/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.027659	11.29	67.25	55.95	V	176.0	-31.65
0.055342	6.81	61.22	54.41	V	176.0	-31.61
0.102013	-2.65	55.91	58.55	V	222.0	-31.60
0.125278	-9.36	54.12	63.48	V	313.0	-31.61
0.164925	-5.21	51.73	56.95	V	0.0	-31.64
0.582825	-16.41	20.72	37.13	V	178.0	-31.63


FCC and ISSED Test Result
 Test data_30MHz to 1000MHz
 Zigbee _Low Channel:



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.546875	19.26	40.00	20.74	100.0	H	0.0	17.27
118.633750	36.71	43.50	6.79	200.0	H	344.0	16.96
152.098750	28.88	43.50	14.62	200.0	H	0.0	15.39
213.451250	29.79	43.50	13.71	100.0	H	241.0	18.73
244.794375	35.71	46.00	10.29	100.0	H	65.0	20.43
293.476250	37.17	46.00	8.83	100.0	H	35.0	21.40


FCC and ISCED Test Result
 Test data_30MHz to 1000MHz
 Zigbee _Low Channel:



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
44.186250	23.51	40.00	16.49	100.0	V	72.0	20.46
69.224375	23.34	40.00	16.67	100.0	V	21.0	16.94
117.118125	38.48	43.50	5.02	100.0	V	72.0	17.35
148.703750	28.82	43.50	14.68	100.0	V	133.0	15.27
244.673125	32.47	46.00	13.53	100.0	V	155.0	20.42
391.446250	31.68	46.00	14.32	100.0	V	346.0	23.86

FCC and ISSED Test Result
 Test data 1GHz to 18GHz:
 Zigbee _Low Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2479.500000	46.92	74.00	27.08	150.0	H	258.0	-4.49
3192.500000	53.64	74.00	20.36	150.0	H	36.0	-0.03
4301.500000	49.57	74.00	24.43	150.0	H	124.0	4.02
5536.000000	51.60	74.00	22.40	150.0	H	172.0	7.08
9618.500000	55.01	74.00	18.99	150.0	H	205.0	12.76
17198.000000	50.89	74.00	23.11	150.0	H	356.0	24.92


Final Result

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3192.500000	49.89	54.00	4.11	150.0	H	36.0	-0.03
5536.000000	46.13	54.00	7.87	150.0	H	172.0	7.08
9618.500000	50.64	54.00	3.36	150.0	H	205.0	12.76

FCC and ISSED Test Result

Test data 1GHz to 18GHz:

Zigbee _Low Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1992.000000	42.03	74.00	31.97	150.0	V	169.0	-6.14
3186.000000	45.73	74.00	28.27	150.0	V	74.0	-0.07
3800.500000	48.09	74.00	25.91	150.0	V	253.0	1.78
4865.000000	50.79	74.00	23.21	150.0	V	181.0	5.66
5537.500000	50.97	74.00	23.03	150.0	V	289.0	7.09
9618.500000	49.93	74.00	24.07	150.0	V	252.0	12.76


Final Result

Frequency (MHz)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5537.500000	51.27	74.00	22.73	150.0	V	289.0	7.09

FCC and ISSED Test Result

Test data 1GHz to 18GHz:

Zigbee _Middle Channel:




Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3168.000000	45.57	74.00	28.43	150.0	H	132.0	-0.19
4374.000000	50.10	74.00	23.90	150.0	H	288.0	3.92
4905.500000	50.53	74.00	23.47	150.0	H	240.0	5.77
5466.500000	50.73	74.00	23.27	150.0	H	240.0	6.68
9762.000000	50.79	74.00	23.21	150.0	H	200.0	12.75
14484.500000	46.93	74.00	27.07	150.0	H	78.0	18.67

FCC and ISED Test Result

Test data 1GHz to 18GHz:

Zigbee _Middle Channel:




Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2131.500000	41.16	74.00	32.84	150.0	V	219.0	-5.87
3199.500000	46.28	74.00	27.72	150.0	V	39.0	0.02
4309.000000	48.96	74.00	25.04	150.0	V	267.0	4.07
5093.500000	50.77	74.00	23.23	150.0	V	63.0	5.89
9762.000000	45.67	74.00	28.33	150.0	V	28.0	12.75
15228.500000	48.08	74.00	25.92	150.0	V	150.0	19.93

FCC and ISSED Test Result

Test data 1GHz to 18GHz:

Zigbee _High Channel:




Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2412.000000	45.10	74.00	28.90	150.0	H	207.0	-4.66
3183.000000	47.03	74.00	26.97	150.0	H	243.0	-0.09
3867.000000	48.23	74.00	25.77	150.0	H	338.0	1.89
4857.000000	50.24	74.00	23.76	150.0	H	267.0	5.58
11150.000000	42.79	74.00	31.21	150.0	H	329.0	13.97
15775.000000	49.29	74.00	24.71	150.0	H	329.0	20.60

FCC and ISED Test Result

Test data 1GHz to 18GHz:


Zigbee _High Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2112.000000	40.65	74.00	33.35	150.0	V	280.0	-5.74
3059.500000	45.44	74.00	28.56	150.0	V	86.0	-0.98
4050.000000	47.98	74.00	26.02	150.0	V	26.0	2.23
5239.000000	50.95	74.00	23.05	150.0	V	62.0	5.64
8865.500000	41.83	74.00	32.17	150.0	V	180.0	12.29
14992.500000	47.85	74.00	26.15	150.0	V	80.0	19.51


FCC and ISSED Test Result
 Test data 18GHz to 40GHz:
 Zigbee _Low Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Corr. (dB)
22088.562500	40.00	74.00	34.00	150.0	H	4.0	-1.30	---
28265.062500	41.36	74.00	32.64	150.0	H	94.0	0.12	---
30478.125000	44.26	74.00	29.74	150.0	H	292.0	1.00	---
34904.937500	44.47	74.00	29.53	150.0	H	109.0	2.03	---

FCC and ISSED Test Result
 Test data 18GHz to 40GHz:
 Zigbee _Low Channel:



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Corr. (dB)
19106.875000	39.45	74.00	34.55	150.0	V	155.0	-4.35	---
21702.875000	40.54	74.00	33.46	150.0	V	109.0	-1.75	---
26027.250000	40.22	74.00	33.78	150.0	V	170.0	0.84	---
30909.187500	41.99	74.00	32.01	150.0	V	216.0	0.70	---

Remark:

- (1) We test both rates for Low channel, Middle channel and High channel separately, only the worst case recorded in this report.
- (2) Corrected Amplitude = Read level + Corrector factor
 Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
 Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
 (The Reading Level is recorded by software which is not shown in the sheet)

10 Test Equipment List

Radiated Emission Test 1# (9kHz – 1GHz)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	2025-5-13
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	2025-7-2
Loop Antenna	Rohde & Schwarz	HFH2-Z2	68-4-80-14-006	100398	2025-7-24
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	2025-5-11
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	2025-7-2
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	2025-7-17
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	2025-5-11
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A

Radiated Emission 2# Test (1GHz – 40GHz)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	2025-5-13
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	2026-3-10
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	2025-5-11
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	2025-7-2
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	2025-7-17
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	2025-5-11
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A

Conducted RF Test System

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	2025-5-11
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157W	68-4-93-14-003	101226/100929	2025-5-11
Power Splitter	Weinschel	1580	68-4-85-14-001	SC319	2025-5-11
10dB Attenuator	Weinschel	4M-10	68-4-81-14-003	43152	2025-5-11
10dB Attenuator	R&S	DNF	68-4-81-14-004	DNF-001	2025-5-11
10dB Attenuator	R&S	DNF	68-4-81-14-005	DNF-002	2025-5-11
10dB Attenuator	R&S	DNF	68-4-81-14-006	DNF-003	2025-5-11
10dB Attenuator	R&S	DNF	68-4-81-14-007	DNF-004	2025-5-11
Test software	Tonscend	System for BT/WIFI	68-4-74-14-006-A13	Version 2.6.77.0518	N/A
Shielding Room	TDK	TS8997	68-4-90-19-003	----	2025-10-15

Conducted Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-14-001	101782	2025-5-13
LISN	Rohde & Schwarz	ENV432	68-4-87-16-001	101318	2025-5-12
Test software	Rohde & Schwarz	EMC32	68-4-90-14-003-A10	Version9.15.00	N/A
Shielding Room	TDK	CSR #1	68-4-90-19-004	----	2025-10-15

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV432 or ENV4200)	3.57dB
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.70dB
Uncertainty for Radiated Emission in new 3m chamber 30MHz-1000MHz	Horizontal: 4.59dB; Vertical: 4.75dB
Uncertainty for Radiated Emission in new 3m 1000MHz-18000MHz	Horizontal: 5.08dB; Vertical: 5.09dB;
Uncertainty for Radiated Emission 18000MHz-40000MHz	Horizontal: 4.52dB; Vertical: 4.51dB
Uncertainty for Conducted RF test	RF Power Conducted: 1.31dB Frequency test involved: 0.6×10^{-8} or 1%

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3 and 4.3.4.

---THE END OF REPORT---