

588 West Jindu Road, Songjiang District, Shanghai, China

Telephone: +86 (0) 21 6191 5666

Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM130900187303  
Page: 1 of 9

## 1 Cover Page

# FCC MPE REPORT

<b>Application No.:</b>	SHEM1309001873RF
<b>Applicant:</b>	Robotime Technology (Suzhou) Co., Ltd.
<b>Manufacturer:</b>	Not supplied by the client.
<b>Factory:</b>	Not supplied by the client.
<b>FCC ID:</b>	2AA4AW002

**Equipment Under Test (EUT):****NOTE:** The following sample(s) submitted was/were identified on behalf of the client as

<b>Product Name:</b>	Adult pleasure object
<b>Model No.(EUT):</b>	Amanda-W002
<b>Brand Name:</b>	EFEELINK
<b>Standards:</b>	FCC Rules 47 CFR §2.1093 KDB 447498D01 General RF Exposure Guidance v05
<b>Date of Receipt:</b>	September 24, 2013
<b>Date of Test:</b>	September 25, 2013 to September 28, 2013
<b>Date of Issue:</b>	October 09, 2013
<b>Test Result:</b>	<b>Pass*</b>

\* In the configuration tested, the EUT complied with the standards specified above.

**E&I Section Manager****SGS-CSTC (Shanghai) Co., Ltd.**

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	/	October 09, 2013	/	Original

<b>Authorized for issue by:</b>				
<b>Engineer</b>		Eddy Zong		
<b>Clerk</b>		Susie Liu		
<b>Reviewer</b>		Keny Xu		

### **3 Contents**

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 CONTENTS.....</b>	<b>3</b>
<b>4 GENERAL INFORMATION .....</b>	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF E.U.T. .....	4
4.3 TECHNICAL SPECIFICATIONS: .....	4
4.4 ACCESSORIES OF PRODUCT: .....	4
4.5 TEST LOCATION.....	5
4.6 TEST FACILITY .....	5
<b>5 RF EXPOSURE COMPLIANCE REQUIREMENT.....</b>	<b>6</b>
5.1 STANDARD REQUIREMENT .....	6
5.2 LIMIT .....	6
<b>6 RF EXPOSURE EVALUATION RESULT .....</b>	<b>9</b>
<b>7 EUT CONSTRUCTIONAL DETAILS .....</b>	<b>9</b>

## 4 General Information

### 4.1 Client Information

Applicant:	Robotime Technology (Suzhou) Co., Ltd.
Address of Applicant:	Room 607, Building A, 5# XingHan Road, Suzhou
Manufacturer:	Not supplied by the client.
Address of Manufacturer:	Not supplied by the client.
Factory:	Not supplied by the client.
Address of Factory:	Not supplied by the client.

### 4.2 General Description of E.U.T.

Product Name:	Adult pleasure object
Model No.(EUT):	Amanda-W002
Brand Name:	EFEELINK
Product Description:	Portable Product

### 4.3 Technical Specifications:

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	2.0+EDR
Modulation Technique:	FHSS (GFSK, π/4DQPSK, 8DPSK)
Number of Channel:	79
Antenna Type	Integral
Antenna Gain	0dBi

### 4.4 Accessories of Product:

USB Input:	DC 5V Via Adaptor(USB cable length about 80cm)
Rated AC Input:	AC 120V 60Hz
Battery:	DC 3.7V, 420mA (Supply the EUT with a new or fully charged Li-on Rechargeable Battery during the testing.)
Engineering Mode:	Using test software to control EUT working in continuous transmitting, and select channel and modulation type.

#### **4.5 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

No.588 West Jindu Road, Songjiang District, Shanghai, China. 201612.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

#### **4.6 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2014-07-26.

- FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2015-02-22.

- Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A. Expiry Date: 2014-09-20.

- VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868 and C-4336 respectively. Date of Registration: 2012-05-29. Date of Expiry: 2015-05-28.

## **5 RF Exposure Compliance Requirement**

### **5.1 Standard Requirement**

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **5.2 Limit**

According to KDB 447498D01 General RF Exposure Guidance v05 <Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies>.

**SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq$  50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test Exclusion Threshold (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

**Note:** 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

**SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm**

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table.

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	mW
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	

## **6 RF Exposure Evaluation Result**

The Max. Conducted Peak Output Power is 4.32dBm (2.70mW) based on the FCC RF report <SHEM130900187302>.

The best case gain of the antenna is 0dBi (convert to numeric 0).

According to the formula calculate the EIRP test result:

$$\text{EIRP} = P \cdot G = 2.70 \cdot 0 = 0 \text{mW} \quad ①$$

SAR test exclusion power threshold is 10mW (at 5 mm distance, on 2450MHz band.) ②

① < ②

So the SAR test is not required.

## **7 EUT Constructional Details**

Refer to the < Amanda-W002\_External Photos > & < Amanda-W002\_Internal Photos >.

**--End of the Report--**