

VARIANT FCC TEST REPORT (15.247)

REPORT NO.: RF130814C33B-3

MODEL NO.: NeverLost® 6 Tablet

FCC ID: 2AA4L-HTZNLTABLET

RECEIVED: Jun. 09, 2014

TESTED: Jun. 21, 2014 ~ Jun. 22, 2014

ISSUED: Jul. 01, 2014

APPLICANT: MiTAC International Corp.

ADDRESS: Building B, No. 209, Sec. 1, Nan Gang Rd., Nan Gang Dist.,

Taipei 11568, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,

New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELE	ASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3.	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	DESCRIPTION OF SUPPORT UNITS	11
3.3.1	CONFIGURATION OF SYSTEM UNDER TEST	11
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS	11
4.	TEST TYPES AND RESULTS (FOR 2.4GHZ BAND)	12
4.1	RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.2	TEST INSTRUMENTS	13
4.1.3	TEST PROCEDURES	14
4.1.4	DEVIATION FROM TEST STANDARD	14
4.1.5	TEST SETUP	15
4.1.6	EUT OPERATING CONDITIONS	
4.1.7	TEST RESULTS	
5.	TEST TYPES AND RESULTS (FOR 5.0GHZ BAND)	
5.1	RADIATED EMISSION MEASUREMENT	19
5.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	
5.1.2	TEST INSTRUMENTS	20
5.1.3	TEST PROCEDURES	
5.1.4	DEVIATION FROM TEST STANDARD	
5.1.5	TEST SETUP	
5.1.6	EUT OPERATING CONDITIONS	
5.1.7	TEST RESULTS	
6.	PHOTOGRAPHS OF THE TEST CONFIGURATION	
7.	INFORMATION ON THE TESTING LABORATORIES	25
8.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING	CHANGES
	TO THE EUT BY THE LAB	26

2 of 26



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130814C33B-3	Original release	Jul. 01, 2014

3 of 26

Report No.: RF130814C33B-3

Reference No.: 140609C17



1. CERTIFICATION

PRODUCT: Automotive Navigation Device

MODEL NO.: NeverLost® 6 Tablet

BRAND: Hertz

APPLICANT: MiTAC International Corp.

TESTED: Jun. 21, 2014 ~ Jun. 22, 2014

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

This report is issued as a supplementary report to BV ADT report no.: RF130814C33-3. This report shall be used by combining with its original report.

PREPARED BY : _______, DATE : _______, Jul. 01, 2014

Gina Liu / Specialist

APPROVED BY : ______, DATE : _____ Jul. 01, 2014

Sam Chen / Senior Project Engineer



2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)				
STANDARD SECTION	TEST TYPE	RESULT	REMARK	
15.207	AC Power Conducted Emission	NA	Refer to Note	
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -2.24dB at 2390MHz.	
15.247(d)	Band Edge Measurement	NA	Refer to Note	
15.247(a)(2)	6dB bandwidth	NA	Refer to Note	
15.247(b) Conducted power		NA	Refer to Note	
15.247(e)	Power Spectral Density	NA	Refer to Note	
15.203	Antenna Requirement	NA	Refer to Note	

NOTE: Only radiated emissions test was performed for this addendum. Refer to original report for other test data.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
De diete de eniesiese	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
Radiated emissions	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

5 of 26



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Automotive Navigation Device	
MODEL NO.	NeverLost® 6 Tablet	
POWER SUPPLY	12Vdc (battery)	
MODIII ATION TYPE	CCK, DQPSK, DBPSK for DSSS	
MODULATION TYPE	64QAM, 16QAM, QPSK, BPSK for OFDM	
MODULATION TECHNOLOGY	DSSS, OFDM	
	802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps	
TRANCEED DATE	802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps	
TRANSFER RATE	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps	
	802.11n: up to 300.0Mbps	
ODED ATIMO EDECUENCY	2.4GHz : 2412 ~ 2462MHz	
OPERATING FREQUENCY	5.0GHz : 5745 ~ 5825MHz	
	2.4GHz:	
	11 for 802.11b, 802.11g, 802.11n (20MHz)	
NUMBER OF CHANNEL	7 for 802.11n (40MHz)	
NUMBER OF CHANNEL	5.0GHz:	
	5 for 802.11a, 802.11n (20MHz)	
	2 for 802.11n (40MHz)	
	2.4GHz:	
ANTENNA TYPE	PIFA antenna with 1.5dBi gain	
ANTENNATTPE	5.0GHz:	
	PIFA antenna with 3.1dBi gain	
ANTENNA CONNECTOR	NA	
DATA CABLE	Refer to Note as below	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Refer to Note as below	



NOTE:

- 1. This report is issued as a supplementary report to BV ADT report no.: RF130814C33-3. The difference compared with original report is update Main board. Therefore, only radiated emissions test was performed and presented in the test report.
- 2. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

MODULATION MODE	TX FUNCTION
802.11b	1TX
802.11g	1TX
802.11a	1TX
802.11n (20MHz)	2TX
802.11n (40MHz)	2TX

3. The EUT contains following accessory devices.

ITEM	BRAND	MODEL	DESCRIPTION
Battery	Tian Yu	N425	Rating: 3.7Vdc, 920mAh
WWAN Module	CINTERION	PHS8-P	
WLAN Module	nFore	NF3301	
NFC Module	Jogtek	TM-007A	
BT Module	nFore	NF3301	

7 of 26

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



3.2 DESCRIPTION OF TEST MODES

FOR 2.4GHz:

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

FOR 5.0GHz (5745 ~ 5825MHz):

5 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
151	5755MHz	159	5795MHz



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

FOR 2.4GHz:

EUT CONFIGURE	APPLICA	ABLE TO	DESCRIPTION
MODE	RE≥1G	RE<1G	
А	√	-	Chain 0 only
В	V	V	Chain 0 + Chain 1

Where

RE≥1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

NOTE:

The antenna of the EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
А	802.11g	1 to 11	1	OFDM	BPSK	6.0
В	802.11n (20MHz)	1 to 11	1	OFDM	BPSK	MCS8

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
В	802.11n (20MHz)	1 to 11	1	OFDM	BPSK	MCS8

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Peter Weng
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Peter Weng

9 of 26



FOR 5.0GHz (5745 ~ 5825MHz):

EUT CONFIGURE	APPLICA	ABLE TO	DESCRIPTION
MODE	RE≥1G	RE<1G	
А	√	-	Chain 0 only
В	V	V	Chain 0 + Chain 1

Where

RE≥1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

NOTE:

The antenna of the EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
Α	802.11a	149 to 165	149	OFDM	BPSK	6.0
В	802.11n (40MHz)	151 to 159	159	OFDM	BPSK	MCS8

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
В	802.11n (40MHz)	151 to 159	159	OFDM	BPSK	MCS8

TEST CONDITION:


TO LOCKETHON			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Peter Weng
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Peter Weng



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) 558074 D01 DTS Meas Guidance v03r01 662911 D01 Multiple Transmitter Output v02 ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Sep. 09, 2013	Sep. 08, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU 43	100115	Dec. 18, 2013	Dec. 17, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Feb. 26, 2014	Feb. 25, 2015
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2014	Jan. 04, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 15, 2013	Jul. 14, 2014
Loop Antenna	HFH2-Z2	100070	Mar. 06, 2014	Mar. 05, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Power Meter	ML2495A	1012010	Jul. 31, 2013	Jul. 30, 2014
Power Sensor	MA2411B	1315050	Jul. 31, 2013	Jul. 30, 2014

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 3. The test was performed in HwaYa Chamber 10.
- 4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 5. The FCC Site Registration No. is 690701.
- 6. The IC Site Registration No. is IC 7450F-10.



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz(Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Plugged the EUT into a notebook through a convertible board and placed on a test table.
- b. The notebook ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.



4.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

MODE A

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER (SYSTEM)	1120\/ac 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Peter Weng	

									_	
	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	50.46	57.53	54	-3.54	26.91	3.54	37.52	118	259	Average
2390	69.12	76.19	74	-4.88	26.91	3.54	37.52	118	259	Peak
2412	97.59	104.61			26.96	3.54	37.52	118	259	Average
2412	107.47	114.49			26.96	3.54	37.52	118	259	Peak
2484	36.26	42.83	54	-17.74	27.15	3.6	37.32	118	259	Average
2484	56.37	62.94	74	-17.63	27.15	3.6	37.32	118	259	Peak
	Α	NTENN	A POLAR	ITY & TE	ST DISTA	NCE: V	ERTICAL	. AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	46.83	53.9	54	-7.17	26.91	3.54	37.52	103	276	Average
2390	64.74	71.81	74	-9.26	26.91	3.54	37.52	103	276	Peak
2412	93.65	100.67			26.96	3.54	37.52	103	276	Average
2412	103.28	110.3			26.96	3.54	37.52	103	276	Peak
2484	35.47	42.04	54	-18.53	27.15	3.6	37.32	103	276	Average
2484	56.11	62.68	74	-17.89	27.15	3.6	37.32	103	276	Peak

16 of 26

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin Value = Emission Level - Limit Value
- 2. 2412MHz: Fundamental frequency.



MODE B

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 1	FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER (SYSTEM)	1120\/ac 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Peter Weng	

	ΔN'	TFNNΔ	POI ARIT	Y & TFS	T DISTAN	CE: HO	RIZONT A	ΔI ΔT 3 IV	1	
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT	TABLE ANGLE (Degree)	REMARK
2390	50.68	57.75	54	-3.32	26.91	3.54	37.52	117	260	Average
2390	68.79	75.86	74	-5.21	26.91	3.54	37.52	117	260	Peak
2412	96.33	103.35			26.96	3.54	37.52	117	260	Average
2412	106.43	113.45			26.96	3.54	37.52	117	260	Peak
2484	36.29	42.86	54	-17.71	27.15	3.6	37.32	117	260	Average
2484	55.81	62.38	74	-18.19	27.15	3.6	37.32	117	260	Peak
	Α	NTENN	A POLAR	ITY & TE	ST DISTA	NCE: V	ERTICAL	AT 3 M		
FREQ.	EMISSION LEVEL	READ	LIMIT	MARGIN	ANTENNA	CABLE	PREAMP	ANTENNA	TABLE	
(MHz)	(dBuV/m)	(dBuV)	(dBuV/m)	(dB)	FACTOR (dB/m)	LOSS (dB)	FACTOR (dB)	HEIGHT (cm)	ANGLE (Degree)	REMARK
(MHz) 2390			(dBuV/m)	(dB) -2.24				_	_	
	(dBuV/m)	(dBuV)	` ,	. ,	(dB/m)	(dB)	(dB)	(cm)	(Degree)	
2390	(dBuV/m) 51.76	(dBuV) 58.83	54	-2.24	(dB/m) 26.91	(dB) 3.54	(dB) 37.52	(cm) 100	(Degree) 91	Average
2390 2390	(dBuV/m) 51.76 71.49	(dBuV) 58.83 78.56	54	-2.24	(dB/m) 26.91 26.91	(dB) 3.54 3.54	(dB) 37.52 37.52	(cm) 100 100	91 91	Average Peak
2390 2390 2412	(dBuV/m) 51.76 71.49 96.55	(dBuV) 58.83 78.56 103.57	54	-2.24	(dB/m) 26.91 26.91 26.96	(dB) 3.54 3.54 3.54	(dB) 37.52 37.52 37.52	(cm) 100 100 100	91 91 91 91	Average Peak Average

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin Value = Emission Level - Limit Value
- 2. 2412MHz: Fundamental frequency.



BELOW 1GHz WORST-CASE DATA:

MODE B

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 1	FREQUENCY RANGE	30MHz ~ 1GHz		
INPUT POWER (SYSTEM)	1120\/ac 60 Hz	DETECTOR FUNCTION	Peak (PK) QP		
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Peter Weng		

	ΔN	TENNΔ	POI ARIT	V & TFS	T DISTAN	CE: HO	RIZONT/	N ΔΤ 3 M	1	
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT	TABLE ANGLE (Degree)	REMARK
32.7	17.06	35.1	40	-22.94	12.47	0.58	31.09	140	177	Peak
143.13	18.78	36.63	43.5	-24.72	12.47	1.31	31.63	100	343	Peak
275.16	24.07	41.83	46	-21.93	12.22	1.94	31.92	126	93	Peak
330.1	30.72	46.71	46	-15.28	13.66	2.16	31.81	109	358	Peak
418.3	27.02	40.87	46	-18.98	15.7	2.49	32.04	100	299	Peak
750.1	26.33	32.54	46	-19.67	21.52	3.57	31.3	124	76	Peak
	Α	NTENN	A POLAR	ITY & TE	ST DISTA	NCE: V	ERTICAL	AT 3 M		
FREQ.	EMISSION	READ			ANTENNA	CABLE	PREAMP	ANTENNA	TABLE	
(MHz)	LEVEL (dBuV/m)	LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	FACTOR (dB/m)	LOSS (dB)	FACTOR (dB)	HEIGHT	ANGLE (Degree)	REMARK
-		LEVEL		_	FACTOR	LOSS	FACTOR	HEIGHT	ANGLE	
(MHz)	(dBuV/m)	LEVEL (dBuV)	(dBuV/m)	(dB)	FACTOR (dB/m)	LOSS (dB)	FACTOR (dB)	HEIGHT (cm)	ANGLE (Degree)	
(MHz) 30.81	(dBuV/m) 28.03	LEVEL (dBuV) 46.44	(dBuV/m) 40	(dB)	FACTOR (dB/m) 12.14	LOSS (dB)	FACTOR (dB) 31.12	HEIGHT (cm) 121	ANGLE (Degree)	Peak
(MHz) 30.81 165	(dBuV/m) 28.03 18.37	LEVEL (dBuV) 46.44 36.51	(dBuV/m) 40 43.5	(dB) -11.97 -25.13	FACTOR (dB/m) 12.14 12.25	LOSS (dB) 0.57 1.42	FACTOR (dB) 31.12 31.81	HEIGHT (cm) 121 100	ANGLE (Degree) 77 30	Peak Peak
30.81 165 241.95	(dBuV/m) 28.03 18.37 23.26	LEVEL (dBuV) 46.44 36.51 42.13	(dBuV/m) 40 43.5 46	(dB) -11.97 -25.13 -22.74	FACTOR (dB/m) 12.14 12.25 11.15	LOSS (dB) 0.57 1.42 1.8	FACTOR (dB) 31.12 31.81 31.82	HEIGHT (cm) 121 100 109	77 30 329	Peak Peak Peak

REMARKS:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin Value = Emission Level - Limit Value



5. TEST TYPES AND RESULTS (FOR 5.0GHz BAND)

5.1 RADIATED EMISSION MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



5.1.2 TEST INSTRUMENTS

Same as item 4.1.2.

5.1.3 TEST PROCEDURES

Same as item 4.1.3.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP

Same as item 4.1.5.

5.1.6 EUT OPERATING CONDITIONS

Same as item 4.1.6.



5.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA:

MODE A

802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 149	FREQUENCY RANGE	1GHz ~ 40GHz		
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)		
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Peter Weng		

	AN	TENNA	POLARIT	Y & TES	T DISTAN	CE: HO	RIZONTA	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	62.76	62.64	75.31	-12.55	31.96	5.59	37.43	107	175	Average
5725	76.7	76.58	83.68	-6.98	31.96	5.59	37.43	107	175	Peak
5745	95.31	95.19			31.99	5.6	37.47	107	175	Average
5745	103.68	103.56			31.99	5.6	37.47	107	175	Peak
5850	38.86	38.56	75.31	-36.45	32.15	5.66	37.51	107	175	Average
5850	57.69	57.39	83.68	-25.99	32.15	5.66	37.51	107	175	Peak
	Α	NTENN	A POLAR	ITY & TE	ST DISTA	NCE: V	ERTICAL	. AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	62.76	62.64	75.31	-12.55	31.96	5.59	37.43	107	175	Average
5725	76.7	76.58	83.68	-6.98	31.96	5.59	37.43	107	175	Peak
5745	95.31	95.19			31.99	5.6	37.47	107	175	Average
5745	103.68	103.56			31.99	5.6	37.47	107	175	Peak
5850	38.86	38.56	75.31	-36.45	32.15	5.66	37.51	107	175	Average
5850	57.69	57.39	83.68	-25.99	32.15	5.66	37.51	107	175	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin Value = Emission Level - Limit Value
- 2. 5745MHz: Fundamental frequency.
- 3. 5725MHz & 5850MHz: Out of restricted band



MODE B

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 159	FREQUENCY RANGE	1GHz ~ 40GHz		
INPUT POWER (SYSTEM)	1120\/ac 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)		
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Peter Weng		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	55.72	55.6	68.28	-12.56	31.96	5.59	37.43	100	68	Average
5725	67.14	67.02	77.5	-10.36	31.96	5.59	37.43	100	68	Peak
5795	88.28	88.12			32.07	5.63	37.54	100	68	Average
5795	97.5	97.34			32.07	5.63	37.54	100	68	Peak
5850	53	52.7	68.28	-15.28	32.15	5.66	37.51	100	68	Average
5850	67.11	66.81	77.5	-10.39	32.15	5.66	37.51	100	68	Peak
	Α	NTENN.	A POLAR	ITY & TE	ST DISTA	NCE: V	ERTICAL	. AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
5725	60.04	59.92	73.36	-13.32	31.96	5.59	37.43	120	41	Average
5725	72.45	72.33	83.22	-10.77	31.96	5.59	37.43	120	41	Peak
5795	93.36	93.2			32.07	5.63	37.54	120	41	Average
5795	103.22	103.06			32.07	5.63	37.54	120	41	Peak
5850	58.91	58.61	73.36	-14.45	32.15	5.66	37.51	120	41	Average
5850	71.43	71.13	83.22	-11.79	32.15	5.66	37.51	120	41	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin Value = Emission Level - Limit Value
- 2. 5795MHz: Fundamental frequency.
- 3. 5725MHz & 5850MHz: Out of restricted band



BELOW 1GHz WORST-CASE DATA:

MODE B

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 159	FREQUENCY RANGE	30MHz ~ 1GHz		
INPUT POWER (SYSTEM)	1120\/ac 60 Hz	DETECTOR FUNCTION	Peak (PK) QP		
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Peter Weng		

	AN	TENNA	POLARIT	TY & TES	ST DISTAN	ICE: HO	RIZONTA	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
55.92	16.94	35.13	40	-23.06	12.35	0.8	31.34	104	21	Peak
153.93	19.13	36.77	43.5	-24.37	12.72	1.36	31.72	106	64	Peak
264.09	25.76	43.92	46	-20.24	11.88	1.88	31.92	100	111	Peak
330.1	30.53	46.52	46	-15.47	13.66	2.16	31.81	109	263	Peak
505.8	24.62	35.96	46	-21.38	17.46	2.8	31.6	105	340	Peak
759.2	27.42	33.6	46	-18.58	21.66	3.6	31.44	101	292	Peak
	А	NTENN	A POLAR	ITY & TE	ST DISTA	NCE: V	ERTICAL	AT 3 M	-	
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
30.81	27.69	46.1	40	-12.31	12.14	0.57	31.12	127	80	Peak
153.93	18.67	36.31	43.5	-24.83	12.72	1.36	31.72	100	289	Peak
285.96	25.18	42.38	46	-20.82	12.54	1.99	31.73	110	115	Peak
330.1	22.56	38.55	46	-23.44	13.66	2.16	31.81	100	217	Peak
461.7	28.95	41.71	46	-17.05	16.56	2.65	31.97	124	264	Peak

REMARKS:

 Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin Value = Emission Level - Limit Value



6. PHOTOGRAPHS OF THE TEST CONFIGURATION
Please refer to the attached file (Test Setup Photo).



7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---