

VARIANT FCC TEST REPORT (PART 22)

REPORT NO.: RF130814C33B

MODEL NO.: NeverLost® 6 Tablet

FCC ID: 2AA4L-HTZNLTABLET

RECEIVED: Jun. 09, 2014

TESTED: Jun. 20, 2014

ISSUED: Jul. 01, 2014

APPLICANT: MiTAC International Corp.

ADDRESS: Building B, No. 209, Sec. 1, Nan Gang Rd., Nan Gang Dist.,

Taipei 11568, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Report No.: RF130814C33B 1 of 16 Report Format Version 5.0.0 Reference No.: 140609C17



TABLE OF CONTENTS

RELEAS	SE CONTROL RECORD	3
1	CERTIFICATION	
2	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
2.2	TEST SITE AND INSTRUMENTS	
3	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	CONFIGURATION OF SYSTEM UNDER TEST	8
3.3	DESCRIPTION OF SUPPORT UNITS	8
3.4	TEST ITEM AND TEST CONFIGURATION	8
3.5	EUT OPERATING CONDITIONS	9
3.6	GENERAL DESCRIPTION OF APPLIED STANDARDS	
4	TEST TYPES AND RESULTS	10
4.1	RADIATED EMISSION MEASUREMENT	10
4.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT	_
4.1.2	TEST PROCEDURES	
4.1.3	DEVIATION FROM TEST STANDARD	
4.1.4	TEST SETUP	11
4.1.5	TEST RESULTS	12
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	
6	INFORMATION ON THE TESTING LABORATORIES	15
7	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHATHE EUT BY THE LAB	



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130814C33B	Original release	Jul. 01, 2014

 Report No.: RF130814C33B
 3 of 16
 Report Format Version 5.0.0

 Reference No.: 140609C17
 3 of 16
 Report Format Version 5.0.0



1 CERTIFICATION

PRODUCT: Automotive Navigation Device

MODEL: NeverLost® 6 Tablet

BRAND: Hertz

APPLICANT: MiTAC International Corp.

TESTED: Jun. 20, 2014

TEST SAMPLE: Production Unit

STANDARDS: FCC PART 22, Subpart H

This report is issued as a supplementary report to BV ADT report no.: RF130814C33.

This report shall be used by combining with its original report.

PREPARED BY: , DATE: Jul. 01, 2014

Gina Liu / Specialist

APPROVED BY: Jul. 01, 2014

Sam Chen / Senior Project Engineer



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

	APPLIED STANDARD: FCC Part 22 & Part 2					
STANDARD SECTION	TEST TYPE	RESULT	REMARK			
2.1046 22.913 (a)	Effective radiated power	NA	Refer to Note			
2.1055 22.355	Frequency Stability	NA	Refer to Note			
2.1049	Occupied Bandwidth	NA	Refer to Note			
22.917	Band Edge Measurements	NA	Refer to Note			
2.1051 22.917	Conducted Spurious Emissions	NA	Refer to Note			
2.1053 22.917	Radiated Spurious Emissions		Meet the requirement of limit. Minimum passing margin is -27.23dB at 44.04MHz.			

Note: Only RSE test were performed for this addendum. Refer to original report for other test data.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
	30MHz ~ 200MHz	2.93 dB
Radiated emissions	200MHz ~1000MHz	2.95 dB
Radiated emissions	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Sep. 09, 2013	Sep. 08, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU 43	100115	Dec. 18, 2013	Dec. 17, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Feb. 26, 2014	Feb. 25, 2015
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2014	Jan. 04, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 15, 2013	Jul. 14, 2014
Loop Antenna	HFH2-Z2	100070	Mar. 06, 2014	Mar. 05, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

^{2.} The test was performed in HwaYa Chamber 10.

^{3.} The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

^{4.} The FCC Site Registration No. is 690701.

^{5.} The IC Site Registration No. is IC 7450F-10.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Automotive Navigation Device			
MODEL NO.	NeverLost [®] 6 Tablet			
POWER SUPPLY	3.7Vdc (battery)			
	GSM/GPRS	GMSK		
MODULATION TYPE	EDGE	8PSK		
	WCDMA	BPSK		
FREQUENCY RANGE	GSM/GPRS/EDGE	824.2MHz ~ 848.8MHz		
FREQUENCY RANGE	WCDMA	826.4MHz ~ 846.6MHz		
MULTI-SLOTS CLASS	12			
WCDMA RELEASE VERSION	6			
ANTENNA TYPE	Fixed Internal Antenna wi	th 1dBi gain		
I/O PORTS	Refer to users' manual			
DATA CABLE	Refer to NOTE as below			
ACCESSORY DEVICES	Refer to NOTE as below			

NOTE:

- 1. This report is issued as a supplementary report to BV ADT report no.:RF130814C33. The difference compared with original report is update Main board.
- 2. The EUT contains following accessory devices.

ITEM	BRAND	MODEL	DESCRIPTION
Battery	Tian Yu	N425	Rating: 3.7Vdc, 920mAh
WWAN Module	CINTERION	PHS8-P	
WLAN Module	nFore	NF3301	
NFC Module	Jogtek	TM-007A	
BT Module	nFore	NF3301	


3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

7 of 16



3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case was found when positioned on X-plane for ERP and radiated emission. Following channel(s) was (were) selected for the final test as listed below:

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
-	RADIATED EMISSION	128 to 251	189	GSM

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin

8 of 16



3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2 FCC 47 CFR Part 22 ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



4 TEST TYPES AND RESULTS

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$. The emission limit equal to -13dBm.

4.1.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power 2.15dBi.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).




4.1.5 TEST RESULTS

GSM:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5

Condition: PART22/24 3m HORIZONTAL

Remark : GPRS850 Link Tested by: Anson Lin

Plane : X


			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
99 <u>-</u>	MHz	dBm/m	dBm	dBm/m	dB	dB/m	60
1	43.77	-50.90	-49.64	-13.00	-37.90	-1.26	Peak
2	133.41	-53.82	-46.60	-13.00	-40.82	-7.22	Peak
3	220.08	-66.19	-59.16	-13.00	-53.19	-7.03	Peak
4	330.10	-65.26	-59.10	-13.00	-52.26	-6.16	Peak
5	505.80	-67.04	-64.11	-13.00	-54.04	-2.93	Peak
6	757.80	-59.21	-61.05	-13.00	-46.21	1.84	Peak
7 pp	1672.80	-44.94	-31.10	-13.00	-31.94	-13.84	Peak
8	2509.20	-48.09	-38.10	-13.00	-35.09	-9.99	Peak

Report No.: RF130814C33B 12 of 16 Report Format Version 5.0.0 Reference No.: 140609C17





Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch



Site : 966 Chamber 5

Condition: PART22/24 3m VERTICAL

Remark : GPRS850 Link Tested by: Anson Lin

Plane : X

	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	3
1 pp	44.04	-40.23	-38.97	-13.00	-27.23	-1.26	Peak
2	133.68	-55.82	-48.60	-13.00	-42.82	-7.22	Peak
3	189.03	-65.23	-58.53	-13.00	-52.23	-6.70	Peak
4	316.10	-67.46	-61.20	-13.00	-54.46	-6.26	Peak
5	506.50	-65.46	-62.53	-13.00	-52.46	-2.93	Peak
6	640.20	-63.62	-63.99	-13.00	-50.62	0.37	Peak
7	1672.80	-46.24	-32.40	-13.00	-33.24	-13.84	Peak

Read Limit Over

Report No.: RF130814C33B 13 of 16 Report Format Version 5.0.0 Reference No.: 140609C17



5 PHOTOGRAPHS OF THE TEST CONFIGURATION
Please refer to the attached file (Test Setup Photo).



6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Hsin Chu EMC/RF Lab:

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

15 of 16



7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING

CHANGES TO THE EUT BY THE LAB
No any modifications were made to the EUT by the lab during the test.
END