

# RF Exposure Evaluation Declaration

Product Name : Driving Recorder

Model No. : GoSafe WiFi

FCC ID. : 2AA58GOSAFEWIFI

Applicant: PAPAGO INC.

Address: 4F., No.200, Gangcian Rd., Neihu Dist., Taipei City

114, Taiwan (R.O.C.)

Date of Receipt : 2013/08/23

Date of Declaration: 2013/09/27

Report No. : 138469R-RF-US-Exp

Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.



## 1. RF Exposure Evaluation

## 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

## LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm <sup>2</sup> )	(Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500			F/300	6
1500-100,000			5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500			F/1500	6
1500-100,000			1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.



# 1.3. Test Result of RF Exposure Evaluation

Product	Driving Recorder
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

## **Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.71dBi or 2.61 in linear scale.

## **Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	24.7172	0.01283
6	2437	24.3220	0.01263
11	2462	22.8034	0.01184

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	27.5423	0.01430
6	2437	27.0396	0.01404
11	2462	25.4097	0.01319

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.



Product	Driving Recorder
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

## **Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 4.71dBi or 2.61 in linear scale.

# **Output Power into Antenna & RF Exposure Evaluation Distance:**

IEEE 802.11n (20MHz) ANT 0			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm²)
1	2412	11.8577	0.00616
6	2437	20.1837	0.01048
11	2462	18.7499	0.00974

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.