



FCC 47 CFR PART 15 SUBPART B

TEST REPORT

For

Applicant: Dreamax Ltd.

Address: UNIT 04 7-F BRIGHT WAY TOWER NO.33 MONG KOK ROAD KL,
HongKong

Product Name: MID

Model Name: DMX-ST7A,DMX-ST7A-ST7Z

Brand Name: N/A

FCC ID: 2AA59DREAMAX01

Report No.: STS130914F2

Date of Issue: October 11,2013

Issued by: Shenzhen Super Test Service Technology Co., Ltd.

Address: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan,
Shenzhen, Guangdong, China

Tel: 86-755-2795 8522

Fax: 86-755-2795 8022

The report consists 32 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by STS. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY.....	3
2. GENERAL INFORMATION.....	4
2.1 PRODUCT INFORMATION.....	4
2.2 OBJECTIVE.....	5
2.3 TEST STANDARDS AND RESULTS.....	5
2.4 ENVIRONMENTAL CONDITIONS.....	5
3. TEST FACILITY.....	6
4. TEST EQUIPMENT LIST.....	7
5. 47 CFR PART 15B REQUIREMENTS.....	9
5.1 GENERAL INFORMATION.....	9
6. LINE CONDUCTED EMISSION TEST.....	10
6.1. LIMITS OF LINE CONDUCTED EMISSION TEST.....	10
6.2. BLOCK DIAGRAM OF TEST SETUP.....	10
6.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	11
6.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	11
6.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....	12
7. RADIATED EMISSION TEST.....	14
7.1. LIMITS OF RADIATED DISTURBANCES AT 3M DISTANCES FOR CLASS B.....	14
7.2 TEST DESCRIPTION.....	14
7.3 TEST RESULT.....	16
APPENDIX 1.....	20
PHOTOGRAPHS OF TEST SETUP.....	20
APPENDIX 2.....	23
PHOTOGRAPHS OF EUT.....	23

1. VERIFICATION OF CONFORMITY

Equipment Under Test: MID
Brand Name: N/A
Model Number: DMX-ST7A
Series Model Name: DMX-ST7A-ST7Z
Series Model Difference description: The same PCB, only the model name is different.
FCC ID: 2AA59DREAMAX01
Applicant: Dreamax Ltd.
UNIT 04 7-F BRIGHT WAY TOWER NO.33 MONG KOK ROAD KL,
HongKong
Manufacturer: Shenzhen John ward technology Co., LTD
No.201, Building C, Hongshengyuan Industrial Park, No.339
Bulong Road , Ma An hall community, Bantian Street, Longgang District,
Shenzhen, Guangdong, China
Technical Standards: FCC Part 15 B
File Number: STS130914F2
Date of test: September 25,2013~ October 11,2013
Deviation: None
Condition of Test Sample: Normal
Test Result: PASS

The above equipment was tested by Shenzhen Super Test Service Technology Co., Ltd. for compliance with the requirements set forth in FCC Part 15 and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):




Zhang Ling October 11,2013

Review by (+ signature):



July Wen October 11,2013

Approved by (+ signature):



Terry Yang October 11,2013

2. GENERAL INFORMATION

2.1 PRODUCT INFORMATION

EUT- MID	
Description:	MID
Model Name:	DMX-ST7A
Power Supply:	DC 5V by AC/DC adapter 100~240V 50/60Hz DC 3.7V by Lithium-ion Battery
Frequency Range:	IEEE 802.11b/g mode:2412MHz – 2472MHz IEEE 802.11n-20 mode:2412MHz – 2462MHz
Number of Channels:	IEEE 802.11b/g/n mode: 11 Channels
Transmit Power	IEEE 802.11b mode: 12.5+/-2 dBm IEEE 802.11g mode: 12.0+/-2 dBm IEEE 802.11n mode: 12.0+/-2 dBm
Modulation Technique:	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mbps) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mbps) IEEE 802.11n Standard-20 MHz Channel mode: OFDM (6.5, 13, 19.5, 26, 39, 52, 58.5, 65.0Mbps)
Antenna Gain:	0dBi
Temperature Range:	-20°C ~ +50°C

NOTE:

1. Please refer to Appendix 2 for the photographs of the EUT. For a more detailed features description about the EUT, please refer to User's Manual.

2.2 OBJECTIVE

Perform FCC Part 15 Subpart B tests for FCC Marking.

2.3 TEST STANDARDS AND RESULTS

Test items and the results are as bellow:

EMISSION				
Standard	Item		Result	Remarks
FCC 47 CFR Part 15 Subpart B (10-1-11 Edition)	§15.107	Conducted Emission	PASS	Meet Class B limit
	§15.109	Radiated Emission	PASS	Meet Class B limit

Note: 1. The test result judgment is decided by the limit of measurement standard
2. The information of measurement uncertainty is available upon the customer's request.

2.4 ENVIRONMENTAL CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa

3. TEST FACILITY

3.1 TEST FACILITY

Test Site: Compliance Certification Services Inc. (Kun shan) Laboratory

Location: No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4 and CISPR 16 requirements.

The FCC Registration Number is **238958**.

The **CNAS** Registration Number is **CNAS L4354**.

Site Filing: The site description is on file with the Federal Communications Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna. It has no holes or gaps having longitudinal dimensions larger than one-tenth of a wavelength at the highest frequency of measurement up to 1GHz.

3.2 GENERAL TEST PROCEDURES

EUT Function and Test Mode

The EUT has been tested under normal operating (TX) and standby (RX) condition.

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis).

The following data show only with the worst case setup.

The worst case of X axis was reported.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

4. TEST EQUIPMENT LIST

4.1 SUPPORT EQUIPMENT

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
Micro SD CARD	Kingston	1G	0907T139090	N/A	
Notebook	DELL	E4446A	E5430	Sheild 1.5m	
Adapter	DELL	42T4420	N/A	Sheild 1.5m	

Remark:

All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 EUT TECHNICAL SPECIFICATION

Name	Type	Parameter	Manufacturer
CPU	RK3168	1.2GHz/1.20V	Rockchip
DDR3	H5TQ2G63DFR-H9C	512MB	Elixir
Flash	TC58TEG5DCJTA00	4GB	TOSHIBA
System Power	TPS659102	--	TI
WIFI Module	RL-UM02BS	802.11b/g/n	RF-Link

4.3 TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at CCS for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2014-5-12
EMI Test Receiver	R&S	ESCI	1166.5950.03	2014-8-13
Pre-Amplifier	Miteq	NSP4000-NF	870629	2014-5-12
Bilog Antenna	Sunol	JB1	A110204-2	2014-5-12
Horn-antenna	SCHWARZBECK	BBHA9120D	D:266	2014-6-7
Loop-antenna	ZHINAN	ZN30900A	N/A	2014-6-7
Turn Table	CT	CT123	4165	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R
Controller	CT	CT100	95637	N.C.R
EMI TEST RECEIVER	R&S	ESCI	100781	2014-3-14
V (V-LISN)	R&S	ENV216	101604	2014-5-21
Pulse Limiter	R&S	ESH3-Z2	100524	2014-9-24
Temperature Chamber	Guangzhou Gongwen	GDS-250	N/A	2014-9-24
Test Software	EZ-EMC			

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR PART 15B REQUIREMENTS

5.1 GENERAL INFORMATION

EUT Function and Test Mode

Mode 1: Idle Mode

The MID was set up on the table and turn on the power.

The EUT configuration of the emission test was **MID + Charger +USB calbe +Notebook.**

Mode 2: USB Mode

During the test, the MID was connected with the notebook and made the data transmission function continuously.

The EUT configuration of the emission test was **MID + Charger + SD Card+ USB Cable+ Notebook.**

Note: Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse mode is reported by this report.

6. LINE CONDUCTED EMISSION TEST


6.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P. (dBuV)	Average (dBuV)
150kHz-500kHz	66-56	56-46
500kHz-5MHz	56	46
5MHz-30MHz	60	50

****Note:** 1. the lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

6.2. BLOCK DIAGRAM OF TEST SETUP



6.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.
- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT received DC 5V by AC/DC adapter or USB port of notebook which through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.
- 9) The following test mode(s) were scanned during the preliminary test:

Preliminary Conducted Emission Test				
Frequency Range Investigated		150KHz TO 30 MHz		
Mode of operation	Date	Report No.	Data#	Worst Mode
Idle Mode	2013-9-29	STS130914F2	1_(L, N)	<input type="checkbox"/>
USB Mode	2013-9-29	STS130914F2	2_(L, N)	<input checked="" type="checkbox"/>

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

6.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


EUT and support equipment was set up on the test bench as per step 9 of the preliminary test.

A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.


The test data of the worst case condition(s) was reported on the Summary Data page.

6.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1	0.5218	22.22	17.11	19.85	42.07	36.96	56.00	46.00	-13.93	-9.04	Pass
2	0.7830	22.85	17.39	19.83	42.68	37.22	56.00	46.00	-13.32	-8.78	Pass
3*	1.5632	23.84	18.54	19.90	43.74	38.44	56.00	46.00	-12.26	-7.56	Pass
4	1.6924	22.60	17.04	19.92	42.52	36.96	56.00	46.00	-13.48	-9.04	Pass
5	2.3467	18.90	11.54	20.01	38.91	31.55	56.00	46.00	-17.09	-14.45	Pass
6	4.6287	19.08	10.21	20.26	39.34	30.47	56.00	46.00	-16.66	-15.53	Pass

(Line: Neutral)



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.6513	26.15	17.18	19.83	45.98	37.01	56.00	46.00	-10.02	-8.99	Pass
2	0.9098	24.89	16.01	19.84	44.73	35.85	56.00	46.00	-11.27	-10.15	Pass
3	1.5572	24.89	11.56	19.89	44.78	31.45	56.00	46.00	-11.22	-14.55	Pass
4*	1.6232	28.02	19.11	19.90	47.92	39.01	56.00	46.00	-8.08	-6.99	Pass
5	2.2764	24.14	10.89	19.96	44.10	30.85	56.00	46.00	-11.90	-15.15	Pass
6	4.7493	17.37	5.93	20.27	37.84	26.22	56.00	46.00	-18.16	-19.78	Pass

(Line: L1)

7. RADIATED EMISSION TEST

7.1. LIMITS OF RADIATED DISTURBANCES AT 3M DISTANCES FOR CLASS B

According to FCC section 15.109, except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

NOTE:

1. Field Strength ($\text{dB}\mu\text{V/m}$) = $20 \times \log[\text{Field Strength } (\mu\text{V/m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.

7.2 TEST DESCRIPTION

Test Setup:



The EUT is powered by the Battery charged with the AC Adapter which is powered by 120V, 60Hz AC mains supply. The Module is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading. During the measurement, the EUT is activated and transmitting with the other Bluetooth device (Supply by the Applicant) during the test.

For the Test Antenna:

(a) In the frequency range of 9 kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.

(b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.


Preliminary Radiated Emission Test				
Frequency Range Investigated			30 MHz TO 1000 MHz	
Mode of operation	Date	Report No.	Data#	Worst Mode
Idle Mode	2013-9-29	STS130914F2	1_(H, V)	<input type="checkbox"/>
USB Mode	2013-9-29	STS130914F2	2_(H, V)	<input checked="" type="checkbox"/>

7.3 TEST RESULT

Form 9KHz to 30MHz:


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Form 30MHz to 1000MHz:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	42.6100	21.14	13.84	34.98	40.00	-5.02	201	189	peak
2	128.9400	13.28	15.68	28.96	43.50	-14.54	100	201	peak
3	384.0500	17.03	17.61	34.64	46.00	-11.36	201	341	peak
4	544.1000	15.12	21.05	36.17	46.00	-9.83	201	220	peak
5	717.7300	14.95	22.78	37.73	46.00	-8.27	103	361	peak
6	767.9855	19.61	23.38	42.99	46.00	-3.01	98	247	QP
7	768.1700	19.18	23.39	42.57	46.00	-3.43	100	247	peak

(Ant.Polar.: Vertical)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	128.9400	13.68	15.68	29.36	43.50	-14.14	201	58	peak
2	265.7100	15.52	14.46	29.98	46.00	-16.02	201	103	peak
3	440.3100	14.55	19.11	33.66	46.00	-12.34	201	225	peak
4	589.6900	15.64	20.37	36.01	46.00	-9.99	201	154	peak
6	768.1700	22.84	23.39	44.23	46.00	-1.77	100	29	peak
7	869.0500	15.22	24.95	40.17	46.00	-5.83	201	250	peak


(Ant.Polar.: Horizontal)

Form 1000MHz to 18000MHz:


Freq. (MHz)	Ant. Pol H/V	Reading (dBuV)	Ant./CL	Actual Fs (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Mark
			CF (dB)				
1910.50	H	17.25	27.02	44.27	54.00	-9.73	Peak
2780.15	H	11.41	29.29	40.70	54.00	-13.30	Peak
N/A							
1890.10	V	16.98	27.01	43.99	54.00	-10.01	Peak
2790.05	V	11.64	29.29	40.93	54.00	-13.07	Peak
N/A							

APPENDIX 1
PHOTOGRAPHS OF TEST SETUP

CE TEST SETUP



RE TEST SETUP





APPENDIX 2
PHOTOGRAPHS OF EUT


FRONT VIEW OF SAMPLE




BACK VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



RIGHT VIEW OF SAMPLE



TOP VIEW OF SAMPLE



BOTTOM VIEW OF SAMPLE




PHOTO OF POWER SUPPLY



PHOTO OF USB



INTERNAL PHOTO OF SAMPLE – 1




INTERNAL PHOTO OF SAMPLE -2



INTERNAL PHOTO OF SAMPLE – 3



INTERNAL PHOTO OF SAMPLE – 4



INTERNAL PHOTO OF SAMPLE –5



INTERNAL PHOTO OF SAMPLE -6




INTERNAL PHOTO OF SAMPLE -7



INTERNAL PHOTO OF ADAPTER -1



INTERNAL PHOTO OF ADAPTER -2



-----END OF REPORT-----