

FCC 47 CFR PART 22 SUBPART H TEST REPORT

For

Applicant: Cybercell Communications

Room 1023, Gelin Wangyuan Zhenxing Road, Futian District,

Shenzhen City, China.

Product Name: GSM Mobile Phone

Model Name: CYA35, CYA43, CYA45, CYA32, CYA47, CYA35, CYA50, CYA60,

CYA61, CYA34, CYA52

Brand Name: Cybercell

FCC ID: 2AA5Y-CYA35

Report No.: DPH20130931F03

Date of Issue: October 15, 2013

Issued by: Shenzhen Top-cert Service Co., Ltd.

Room 506, Hongyu Commercial Building, Gushu 2nd Road, Address:

Baoan District, Shenzhen, China

Tel: 0755-61196328

Fax: 0755-61196328

E-mail: service@top-cert.com

Web: www.top-cert.com

The report consists 45 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Top-cert. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1 Product Information	5
2.2 Objective	6
2.3 Test Standards and Results	
2.4 Environmental Conditions	
3. TEST FACILITY	7
4. TEST EQUIPMENT LIST	8
5. 47 CFR Part 2, Part 22H Requirements	9
5.1 General Information	9
6. CONDUCTED RF OUTPUT POWER	12
6.1 Requirement	12
6.2 Test Procedure	12
6.3 Test Result	12
7. OCCUPIED BANDWIDTH	16
7.1 Occupied Bandwidth Definition	16
7.2 Test Procedure	16
7.3 Test Result	16
8. CONDUCTED SPURIOUS EMISSION	20
8.1 Requirement	20
8.2 Test Procedure	20
8.3 Test Result	21
9. Transmitter Radiated Power (EIRP/ERP)	31
9.1 Requirement	31
9.2 Test Procedure	31
9.3 Test Result	31
10. Radiated Spurious Emission	32
10.1 Requirement	32
10.2 Test Procedure	
10.3 Test Result	32
11. Frequency Stability	34
11.1 Frequency Stability Requirement	34
11.2 Test Procedure	34

FCC ID: 2AA5Y-CYA35

11.3 Test Result	35
APPENDIX 1	36
PHOTOGRAPHS OF TEST SETUP	36
APPENDIX 2	38
PHOTOGRAPHS OF EUT	38

	Revision History	
Issue	Date	Reason for Revision
1.0	October 15, 2013	First edition

1. VERIFICATION OF CONFORMITY

Equipment Under Test:	GSM Mobile Phone	
Brand Name:	Cybercell	
Model Number:	CYA35	
Series Model Name:	CYA43, CYA45, CYA32, CYA47, CYA35, CYA50, CYA60, CYA61, CYA34, CYA5	
Difference description:	Only the model name is different.	
FCC ID:	2AA5Y-CYA35	
Applicant:	Cybercell Communications	
	Room 1023, Gelin Wangyuan Zhenxing Road, Futian District, Shenzhen City, China.	
Manufacturer:	Begin Industrial (H.K.) Co., Ltd.	
	C6-1701, Heng-Feng industrial city ,xixiang Town, Baoan District, shenzhen, china	
Technical Standards:	47 CFR Part 2	
rechnical Standards:	47 CFR Part 22 Subpart H	
File Number:	DPH1300931F03	
Date of test:	September 10,2013 ~ October 15, 2013	
Date of issue:	October 15, 2013	
Condition of Test Sample:	Normal	
Test Result:	PASS	

The above equipment was tested by Shenzhen Top-cert Service Co., Ltd. for compliance with the requirement set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):

Rex Luo

Test Engineer

Approved by (+ signature):

Joe Jia

Manager

2. GENERAL INFORMATION

2.1 Product Information

EUT1- Mobile Phone			
Description:	GSM Mobile Phone		
Brand Name:	Cybercell		
Model Name:	CYA35		
Hardware Version:	N/A		
Software Version:	N/A		
F	Tx: 824.2-848.8 MHz 1850.2-1909.8 MHz		
Frequency:	Rx: 849.2-893.8 MHz 1930.2-1989.8 MHz		
Ancillary Equipment – Pow	ver Supply		
Description:	Travel Charger		
Brand Name:	N/A		
Model Name:	CYA35		
Rated Input:	AC 100-240V, 50/60Hz, 0.15A		
Rated Output:	DC 5V, 0.5A		
Length USB cable:	1.0m		
Ancillary Equipment – Batt	ery		
Description:	Lithium-ion Battery		
Brand Name:	N/A		
Model Name:	AIRUS		
Capacitance:	1500 mAh		
Rated Voltage:	3.7V		
Charge Limit:	4.2V		

NOTE:

- 1. The EUT is a GSM Mobile Station, here only Cellular 850MHz band was tested in this report.
- 2. The transmitter (Tx) frequency arrangement of the Cellular 850MHz band for the EUT can be represented with a formula F(n)=824.2+0.2*(n-128), $128 \le n \le 251$.
- 3. The normal, high and low voltage supply for the Battery of the EUT is separately 3.7V, 4.2V and 3.6V, which are specified by the applicant.
- 4. Please refer to Appendix 2 for the photographs of the EUT. For a more detailed features description about the EUT, please refer to User's Manual.

2.2 Objective

The objective of the report is to perform tests according to 47 CFR Part 2, Part 22 for FCC ID Certification:

No.	Identity	Document Title	
1	47 CFR Part 2 (10-1-05 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations	
2	47 CFR Part 22 (10-1-05 Edition)	Public Mobile Services	

2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Rules	Test Type	Result	Date of Test
1	§2.1046	Conducted RF Output Power at Antenna Terminal	PASS	2013-09-13
2	§2.1049	Occupied Bandwidth	PASS	2013-09-13
3	§2.1051 §2.1057 §22.917	Conducted Spurious Emission at Antenna Terminal	PASS	2013-09-13
4	§22.913	Transmitter Radiated Power (EIPR/ERP)	PASS	2013-09-13
5	§2.1053 §2.1057 §22.917	Radiated Spurious Emission	PASS	2013-09-13
6	§2.1055 §22.355	Frequency Stability	PASS	2013-09-13

Note: 1. The test result judgment is decided by the limit of measurement standard

2. The information of measurement uncertainty is available upon the customer's request.

2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C

- Humidity: 30-60 %

- Atmospheric pressure: 86-106 kPa

3. TEST FACILITY

Test Site:	BZT Testing Technology Co., Ltd.	
Location:	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,	
	Bao'an District, Shenzhen P.R. China.	
Description:	There is one 3m semi-anechoic an area test sites and two line conducted lal for final test. The Open Area Test Sites and the Line Conducted labs a constructed and calibrated to meet the FCC requirements in documents AN C63.4:2009 and CISPR 16 requirements. The FCC Registration Number is 701733	
Site Filing:	The site description is on file with the Federal Communications	
	Commission, 7435 Oakland Mills Road, Columbia, MD 21046.	
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16 requirements that meet industry regulatory agency and accreditation agency requirement.	
Ground Plane:	Two conductive reference ground planes were used during the Line Conducted Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire area between the EUT and the antenna.	

4. TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

ii iSti ui	nentation from 10 kmz to	1.0 GHZ OF ADOVE.				
No.	Equipment	Manufacturer	Model No.	S/N	Calibration	Calibration
	_qaipo.it	- Mariardotaro.			date	due date
1	Test Receiver	Rohde & Schwarz	ESCI	100492	2013/03/10	2014/03/09
2	Test Receiver	Rohde & Schwarz	ESPI	101202	2013/03/10	2014/03/09
3	Bi-Log Antenna	Sunol	JB3	A121206	2013/03/03	2014/03/02
4	Test Antenna – Bi-Log	Schwarzbeck	VULB 9163		2013/03/03	2014/03/02
5	Horn Antenna	ETS	3115		2013/03/03	2014/03/02
6	Test Antenna - Horn	Schwarzbeck	BBHA 9120C		2013/03/03	2014/03/02
7	Cable	Resenberger	N/A	NO.1	N/A	N/A
8	Cable	SchwarzBeck	N/A	NO.2	N/A	N/A
9	Cable	SchwarzBeck	N/A	NO.3	N/A	N/A
10	Power Splitter	Weinschel	1506A	NW521	N/A	N/A
11	Spectrum Analyzer	Agilent	4408B	MY41440460	2013/03/10	2014/03/09
12	Spectrum Analyzer	RS	FSL	103640/003	2013/05/12	2014/05/11
13	Coaxial Switch	Anritsu Corp	MP59B	6200283933	N/A	N/A
14	Signal Generator	IFR	2032	203002/100	2013/03/10	2014/03/09
15	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2013/03/10	2014/03/09
16	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2013/03/10	2014/03/09
17	Temperature Chamber	Guangzhou Gongwen	GDS-250	N/A	N/A	N/A
18	DC Power Supply	Good Will	GPS-3030DD	EF920938	2013/03/10	2014/03/09
19	Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2013/03/10	2014/03/09


NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 2, Part 22H Requirements

5.1 General Information

5.1.1 Conducted Related Tests

Based on ANSI/TIA-603-C-2004




- 1. The EUT is coupled to the Spectrum Analyzer and the System Simulator with the suitable Attenuators through the Power Splitter; the path loss is calibrated to correct the reading.
- 2. The EUT is configured here as MS + Battery.
- 3. Set the spectrum analyzer to measure peak hold with the required settings.
- 4. Set the signal generator to a known output power and record the path loss in dB (LOSS) for frequencies up to the tenth harmonic of the EUT's carrier frequency. LOSS = Generator Output Power (dBm) Analyzer reading (dBm).
- 5. Replace the signal generator with the EUT.
- 6. Adjust the settings of the Digital Radio communication Tester (DRT) to set the EUT to its maximum power at the required channel.
- 7. Set the spectrum analyzer to measure peak hold with the required settings. Offset the spectrum analyzer reference level by the path loss measured above.
- 8. Measure and record all spurious emissions up to the tenth harmonic of the carrier frequency.
- Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.
- 10. If necessary steps 6 and 7 may be performed with the spectrum analyzer set to average detector. Note: Step 4 above is performed prior to testing and LOSS is recorded by test software. Steps 3, 7, and 8 above are performed with test software.


5.1.2 Radiated Power and Spurious Emission Tests

Based on ANSI/TIA-603-C-2004

Setup 1:



Setup 2:




- 1. The test is performed in a full-Anechoic Chamber, the air loss of the site and the factors of the test system are using the substitution method.
- 2. Connect the equipment as shown in setup 1.
- 3. Adjust the setting of System Simulator to set the EUT to its maximum power at the require channel.

4. Set the Spectrum Analyzer to the channel frequency, set the analyzer to measure peak hold with the required setting.

- 5. Rotate the EUT 360 degree, recorded the peak level in dBm(LVL).
- 6. The EUT is substituted by a half wave dipole or known gain antenna. The center of the antenna should be at the same location as the center of the EUT's antenna.
- 7. Connect the antenna to a signal generator and adjust the output power level of the signal generator (SGP) to get same received power recorded in step 5 on the Spectrum Analyze.
- 8. Determine the ERP using the following equation: ERP(dBm)=SGP(dBm)+Gain(dB)- Cable Loss(dB)
- 9. Determine the EiRP using the following equation: EIRP(dBm)= ERP(dBm)+2.14(dB)
- Measurements are to be performed with the EUT set to the low, middle and high channel of each frequency band.

5.1.3 Frequency Stability Test



- 1. The test is performed in a Temperature Chamber.
- 2. The EUT is configured as MS + DC Power Supply.

6. Conducted RF Output Power

6.1 Requirement

According to FCC §2.1046 (a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in §2.1033 (c)(8). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.

6.2 Test Procedure

- 1. Perform test system setup as section 5.1.1. (The radio frequency load attached to the EUT antenna terminal is 50Ω).
- 2. The resolution bandwidth of the Spectrum Analyzer is set to be comparable to the emission bandwidth of the transmitter, e.g. for GSM modulated signal (here used): RBW=VBW=1MHz, for CDMA modulated signal: RBW=VBW=3MHz.
- 3. The low, middle and the high channels are selected to perform tests respectively. Set the TCH number to 128 as the low channel.
- 4. Set the frequency range of the Spectrum Analyzer suitably to capture the waveform; search peak and mark it; finally record the peak and the plot.
- 5. Set the TCH number to 190 as the middle channel, then repeat step 4.
- 6. Set the TCH number to 251 as the high channel, then repeat step 4.

6.3 Test Result


A. Test Verdict:

Test Mode	Channal Number	Phonnal Number Frequency	Measured Power		Rated Power	
rest wode	Channel Number	(MHz)	dBm	W	dBm	W
	128	824.2	32.25	1.678	33	2
GSM 850	190	836.6	32.28	1.690	33	2
	251	848.8	32.30	1.698	33	2
	128	824.2	30.84	1.213	33	2
GPRS 850	190	836.6	30.89	1.227	33	2
	251	848.8	30.95	1.244	33	2

B. Test Plots:


GSM 850:

1. Plot when the TCH number set to 128:




Date: 13.SEP.2013 17:32:40

2. Plot when the TCH number set to 190:



Date: 13.SEP.2013 17:33:35


3. Plot when the TCH number set to 251:



Date: 13.SEP.2013 17:35:05


GPRS 850:

1. Plot when the TCH number set to 128:




Date: 13.SEP.2013 18:39:33

2. Plot when the TCH number set to 190:



Date: 13.SEP.2013 18:40:57

3. Plot when the TCH number set to 251:



Date: 13.SEP.2013 18:40:32

7. OCCUPIED BANDWIDTH

7.1 Occupied Bandwidth Definition

According to FCC §2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Occupied bandwidth is also known as the 99% emission bandwidth, or 20dB bandwidth (10*log1% is equal to 20dB) taking the total RF output power as reference.

7.2 Test Procedure

- 1. Perform test system setup as section 5.1.1
- 2. The resolution bandwidth of the Spectrum Analyzer is set to at least one percent of the emission bandwidth, e.g. for GSM modulated signal (here used): RBW=VBW=3 kHz, for CDMA modulated signal: RBW=VBW=30 kHz.
- 3. The low, middle and the high channels are selected to perform tests respectively. Set the TCH number to 128 as the low channel.
- 4. Set the frequency range of the Spectrum Analyzer suitably to capture the waveform; search peak; measurement and record the 99% occupied bandwidth.
- 5. Set the TCH number to 190 as middle channel, then repeat step 4.
- 6. Set the TCH number to 251 as high channel, then repeat step 4.

7.3 Test Result


A. Test Verdict:

Test Mode	Channel	Frequency (MHz)	Measured Occupied Bandwidth (kHz)
	128	824.2	255.2550
GSM 850	190	836.6	250.4808
	251	848.8	254.7724
	128	824.2	252.4615
GPRS 850	190	836.6	250.0294
	251	848.8	250.7778


B. Test Plots:

GSM 850:


1. Plot when the TCH number set to 128:



2. Plot when the TCH number set to 190:




3. Plot when the TCH number set to 251:




GPRS 850:


1. Plot when the TCH number set to 128:



2. Plot when the TCH number set to 190:



3. Plot when the TCH number set to 251:



8. CONDUCTED SPURIOUS EMISSION

8.1 Requirement

According to FCC §22.917(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

According to FCC §22.917 (a), in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. Thus the 26dB emission bandwidth is measurement for showing compliance at the band-edge.

8.2 Test Procedure

- 1. Perform test system setup as section 5.1.1.
- 2. Make a limit line whose value is -13dBm on the Spectrum Analyzer.
- 3. The lowest, middle and the highest channels are selected to perform tests respectively. Set the TCH number to 128 as the lowest channel.
- 4. Set the RBW of the Spectrum Analyzer to 1MHz, and the measuring frequency range from 9kHz to 10th harmonic of the fundamental frequency (here used 26.5GHz); mark the fundamental frequency and the harmonics thereof; finally record the harmonics and the plot. Note, the measuring frequency range can be divided into several parts to perform tests.
- 5. In the 1MHz bands immediately outside and adjacent to the frequency black, the RBW of the Spectrum Analyzer was set to at least one percent of the emission bandwidth of the fundamental emission of the transmitter, e.g. for GSM modulated signal (here used): RBW=3kHz, for CDMA modulated signal: RBW=30kHz.
- 6. Set the TCH number to 190 as the middle channel, then repeat step 4.
- 7. Set the TCH number to 251 as the highest channel, then repeat step 4 and 5.

8.3 Test Result

Table for the Harmonics and Plots for the Spurious Emission

1. Table for the Harmonics:

NOTE: "---" in the table following means that the emission power was too small to be measured and was at least 12dB below the limit.

No.	Frequency (MHz)	Emission Power (dBm)	Limit (dBm)
		-TCH number set to 128 (824.20MHz	<u> </u>
1	1648.40		-13
2	2472.60		-13
3	3296.80		-13
4	4121.00		-13
5	4945.20		-13
6	5769.40		-13
7	6593.60		-13
8	7417.80		-13
9	8242.00		-13
	GSM 850	-TCH number set to 190 (836.60MHz)
1	1673.20		-13
2	2509.80		-13
3	3346.40		-13
4	4183.00		-13
5	5019.60		-13
6	5856.20		-13
7	6692.80		-13
8	7529.40		-13
9	8366.00		-13
	GSM 850	-TCH number set to 251 (848.80MHz)
1	1697.60		-13
2	2546.40		-13
3	3395.20		-13
4	4244.00		-13
5	5092.80		-13
6	5941.60		-13
7	6790.40		-13
8	7639.20		-13
9	8488.00		-13
	GPRS 850	-TCH number set to 128 (824.20MHz	<u> </u>
1	1648.40		-13
2	2472.60		-13
3	3296.80		-13
4	4121.00		-13
5	4945.20		-13
6	5769.40		-13
7	6593.60		-13
8	7417.80		-13
9	8242.00		-13
	GPRS 850	0-TCH number set to 190 (836.60MHz	<u></u>
1	1673.20		-13
2	2509.80		-13
3	3346.40		-13
4	4183.00		-13

5	5019.60		-13
6	5856.20		-13
7	6692.80		-13
8	7529.40		-13
9	8366.00		-13
	GPRS	S 850-TCH number set to 190 (836.60	MHz)
1	1697.60		-13
2	2546.40		-13
3	3395.20		-13
4	4244.00		-13
5	5092.80		-13
6	5941.60		-13
7	6790.40		-13
8	7639.20		-13
9	8488.00		-13


2. Plot for Spurious Emission:


The measuring frequency range was from 9 kHz to 10GHz.

NOTE: The marker points are the Mobile Phone and/or System Simulator transmitting frequencies which should be ignored.


GSM 850:


Plot when the TCH number set to 128:







2. Plot when the TCH number set to 190:






3. Plot when the TCH number set to 251:







GPRS 850:


Plot when the TCH number set to 128:







2. Plot when the TCH number set to 190:





3. Plot when the TCH number set to 251:







Plot for Band-edge

GSM 850:

Plot when the TCH number set to 128:




Plot when the TCH number set to 251:




GPRS 850:

Plot when the TCH number set to 128:







9. Transmitter Radiated Power (EIRP/ERP)

9.1 Requirement

According to FCC §22.913, the ERP of Cellular mobile transmitters must not exceed 7 Watts (38.5dBm).

9.2 Test Procedure

See the section 5.1.2.

9.3 Test Result

Test Mode	Channel	hannel Frequency (MHz)	Measured ERP		Limit ERP		Result
rest wode			dBm	W	dBm	W	Nesuit
	128	824.20	31.87	1.538	< 38.5	< 7	PASS
GSM 850	190	836.60	31.77	1.503	< 38.5	< 7	PASS
	251	848.80	31.36	1.368	< 38.5	< 7	PASS
	128	824.20	30.29	1.069	< 38.5	< 7	PASS
GPRS 850	190	836.60	30.15	1.035	< 38.5	< 7	PASS
	251	848.80	30.55	1.135	< 38.5	< 7	PASS

10. Radiated Spurious Emission

10.1 Requirement

According to FCC §22.917(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

10.2 Test Procedure

See the section 5.1.2.

10.3 Test Result

NOTE: "---" in th The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

Table for the Harmonics

No.	Frequency (MHz)	Emission	Limit (dBm)						
NO.	Frequency (WITIZ)	Test Antenna Vertical Test Antenna Horizontal		Lillit (dBill)					
	GSM 850 TCH number set to 128 (824.20MHz)								
1	1648.40	-38.23	-41.28	-13					
2	2472.60			-13					
3	3296.80			-13					
4	4121.00			-13					
5	4945.20			-13					
6	5769.40			-13					
7	6593.60			-13					
8	7417.80			-13					
9	8242.00			-13					
		GSM 850 TCH number set to	190 (836.60MHz)						
10	1673.20	-38.36	-39.12	-13					
11	2509.80			-13					
12	3346.40			-13					
13	4183.00			-13					
14	5019.60			-13					
15	5856.20			-13					
16	6692.80			-13					
17	7529.40			-13					
18	8366.00			-13					
		GSM 850 TCH number set to	251 (848.80MHz)						
19	1697.60	-38.17	-39.51	-13					
20	2546.40			-13					
21	3395.20			-13					
22	4244.00			-13					
23	5092.80			-13					
24	5941.60			-13					
25	6790.40			-13					
26	7639.20			-13					
27	8488.00			-13					

Ma	Francisco (8811-)	Limit (dD)						
No.	Frequency (MHz)	Test Antenna Vertical	Test Antenna Horizontal	Limit (dBm)				
GPRS 850-TCH number set to 128 (824.20MHz)								
1	1648.40	-37.39	-39.75	-13				
2	2472.60			-13				
3	3296.80			-13				
4	4121.00			-13				
5	4945.20			-13				
6	5769.40			-13				
7	6593.60			-13				
8	7417.80			-13				
9	8242.00			-13				
GPRS 850-TCH number set to 190 (836.60MHz)								
10	1673.20	-38.31	-41.29	-13				
11	2509.80			-13				
12	3346.40			-13				
13	4183.00			-13				
14	5019.60			-13				
15	5856.20			-13				
16	6692.80			-13				
17	7529.40			-13				
18	8366.00			-13				
	(SPRS 850-TCH number set to 2	251 (848.80MHz)					
19	1697.60	-38.62	-41.62	-13				
20	2546.40			-13				
21	3395.20			-13				
22	4244.00			-13				
23	5092.80			-13				
24	5941.60			-13				
25	6790.40			-13				
26	7639.20			-13				
27	8488.00			-13				

NOTE: "---" in the table following means that the emission power was too small to be measured and was at least 12dB below the limit.

11. Frequency Stability

11.1 Frequency Stability Requirement

According to FCC §22.355, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to FCC §2.1055, the test conditions are:

(a) Temperature:

The temperature is varied from -30°C to +50°C at intervals of not more than 10°C.

(b) Primary Supply Voltage:

For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

11.2 Test Procedure

- 1. Perform test system setup as section 5.1.3.
- 2. Set the voltage of the DC Power Supply to normal supply voltage (here used 3.7V) and the temperature of the Temperature Chamber to vary from -30°C to +50°C at intervals of 10°C.
- 3. At each temperature level, the EUT is powered off and kept in the Temperature Chamber for two hours.
- 4. After sufficient stabilization, turn on the EUT, command it via the System Simulator (SS) to operate at the maximum output power i.e. Power Control Level (PCL) = 0 and Power Class = 1, and then establish a communication link between the EUT and the SS.
- 5. The low, middle and the high channels are selected to perform tests respectively. Set the TCH number to 128 as the low channel.
- 6. The frequency deviation is measured (directly read from the SS, which can report the parameter) within three minutes.
- 7. Set the TCH number to 190 as the middle channel, then repeat step 5.
- 8. Set the TCH number to 251 as the high channel, then repeat step 5.
- 9. Adjust the temperature of the Temperature Chamber as specified in step 2, then repeat step 3 to 7.
- 10. Set the voltage of the DC Power Supply to high extreme supply voltage (here used 4.2V) and the temperature of the Temperature Chamber to normal (here used +22°C), then repeat step 3 to 8.
- 11. Set the voltage of the DC Power Supply to low extreme supply voltage (here used 3.6V) and the temperature of the Temperature Chamber to normal (here used +22°C), then repeat step 3 to 8.

11.3 Test Result

Band	Test Conditions		Frequency Deviation (Hz) at Channels Used				
Danu	Voltage	Temperature	128	190	251		Limit (±2.5ppm)
		-30°C	4.19	-28.39	26.55		
		-20°C	6.59	1.23	19.06		
	V-nor	-10°C	-8.66	-12.87	6.37		
		0°C	-25.25	-23.09	-20.88	(b) ±2096Hz for 190	
GSM		+10°C	-29.78	1.26	25.52		±2060Hz for 128 Channel
850		+20°C	20.18	-4.92	-19.33		±2096Hz for 190 Channel
000		+30°C	-13.07	-27.33	-12.42		±3055Hz for 251 Channel
		+40°C	-0.88	0.69	23.84		
		+50°C	19.91	-21.86	10.66		
	V-high	+22°C	-3.69	11.08	-0.52		
	V-low	+22°C	-28.75	17.08	-15.47		
- W							


Result: PASS

11000111 11100								
Band	Test Conditions		Frequency Deviation (Hz) at Channels Used					
Dallu	Voltage	Temperature	128	190	251	Limit (±2.5ppm)		
		-30°C	-7.93	14.24	-8.30			
		-20°C	-21.73	7.75	-15.40			
	V-nor	-10°C	-10.97	-7.55	-16.04			
		0°C	-6.46	27.10	-21.69			
GPRS		+10°C	7.73	-4.09	18.53	(a) ±2060Hz for 128 Channel		
850		+20°C	-1.81	-19.11	25.04	(b) ±2096Hz for 190 Channel		
000		+30°C	-23.48	-10.49	22.47	(c) ±3055Hz for 251 Channel		
		+40°C	-11.24	21.50	8.23			
		+50°C	26.65	-9.72	11.30			
	V-high	+22°C	16.22	-25.06	-14.51			
	V-low	+22°C	-12.79	22.31	-1.39			
D. I. DAGO								


Result: PASS

FCC ID: 2AA5Y-CYA35		Report No.: DPH130931F03
	APPENDIX 1	
	PHOTOGRAPHS OF TEST SETUP	

CONDUCTED TEST SETUP



RADIATED EMISSION TEST SETUP




FCC ID: 2AA5Y-CYA35		Report No.: DPH130931F03
FCC ID: 2AA5Y-CYA35		Report No.: DPH130931F03
	APPENDIX 2	
	PHOTOGRAPHS OF EUT	





BACK VIEW OF SAMPLE







RIGHT VIEW OF SAMPLE







DOWN VIEW OF SAMPLE






INTERNAL PHOTO OF SAMPLE - 1




INTERNAL PHOTO OF SAMPLE -2



INTERNAL PHOTO OF SAMPLE - 3




INTERNAL PHOTO OF SAMPLE - 4



INTERNAL PHOTO OF SAMPLE - 5



INTERNAL PHOTO OF SAMPLE - 6



-----END OF REPORT-----