

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594 Report No.: SZEM161201106701

Email: ee.shenzhen@sgs.com Page: 1 of 42

FCC REPORT

Application No: SZEM1612011067CR

Applicant: LANKE XUNTONG TECHNOLOGY CO.,LTD

Manufacturer: LANKE XUNTONG TECHNOLOGY CO.,LTD

Factory: LANKE XUNTONG TECHNOLOGY CO.,LTD

Product Name: Bluetooth low energy 4.0 modules

Model No.(EUT): PTR5528
Trade Mark: XUNTONG

FCC ID: 2AA72-PTR5528

Standards: 47 CFR Part 15, Subpart C (2015)

Date of Receipt: 2016-12-26

Date of Test: 2016-12-28 to 2017-01-09

Date of Issue: 2017-01-10

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM161201106701

Page: 2 of 42

2 Version

Revision Record						
Version Chapter Date Modifier Remark						
01		2017-01-10		Original		

Authorized for issue by:		
Tested By	(Bill Chen) /Project Engineer	2017-01-09 Date
Checked By	Eric Fu (Eric Fu) /Reviewer	2017-01-10 Date



Report No.: SZEM161201106701

Page: 3 of 42

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS



Report No.: SZEM161201106701

Page: 4 of 42

4 Contents

			Page
1	CC	OVER PAGE	1
2	VE	ERSION	2
3		EST SUMMARY	
4	CC	ONTENTS	4
5	GF	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	7
	5.5	TEST LOCATION	7
	5.6	TEST FACILITY	
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TE	EST RESULTS AND MEASUREMENT DATA	11
	6.1	Antenna Requirement	11
	6.2	CONDUCTED PEAK OUTPUT POWER	
	6.3	6DB OCCUPY BANDWIDTH	
	6.4	POWER SPECTRAL DENSITY	
	6.5	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.6	Spurious RF Conducted Emissions	
	6.7	RADIATED SPURIOUS EMISSION	
	_	7.1 Spurious Emissions	
	6.8	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
7	PH	HOTOGRAPHS - EUT TEST SETUP	42
	7.1	RADIATED EMISSION	42
	7.2	RADIATED SPURIOUS EMISSION	42
Q	DL	HOTOGRADUS - ELIT CONSTRUCTIONAL DETAILS	42



Report No.: SZEM161201106701

Page: 5 of 42

5 General Information

5.1 Client Information

Applicant:	LANKE XUNTONG TECHNOLOGY CO.,LTD
Address of Applicant:	Room 7A-B, Block B of Wanlian Building, Net Valley, No.12 of Yanshan Road, Nanshan district, Shenzhen
Manufacturer:	LANKE XUNTONG TECHNOLOGY CO.,LTD
Address of Manufacturer:	Room 7A-B, Block B of Wanlian Building, Net Valley, No.12 of Yanshan Road, Nanshan district, Shenzhen
Factory:	LANKE XUNTONG TECHNOLOGY CO.,LTD
Address of Factory:	Room 7A-B, Block B of Wanlian Building, Net Valley, No.12 of Yanshan Road, Nanshan district, Shenzhen

5.2 General Description of EUT

Product Name:	Bluetooth low energy 4.0 modules
Model No.:	PTR5528
Trade Mark:	XUNTONG
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0 BLE
Modulation Type:	GFSK
Number of Channel:	40
Sample Type:	Mobile production
Antenna Type:	PCB
Antenna Gain:	0dBi
Power Supply:	DC 3V



Report No.: SZEM161201106701

Page: 6 of 42

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency	
The lowest channel (CH0)	2402MHz	
The middle channel (CH19)	2440MHz	
The highest channel (CH39)	2480MHz	



Report No.: SZEM161201106701

Page: 7 of 42

5.3 Test Environment

Operating Environment:				
Temperature:	25.0 °C			
Humidity:	53 % RH			
Atmospheric Pressure:	1010mbar			

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Laptop	Lenovo	T430u
Test board	Supply to SGS	FT232

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM161201106701

Page: 8 of 42

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM161201106701

Page: 9 of 42

5.10 Equipment List

	RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)	
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2016-05-13	2017-05-13	
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2016-10-09	2017-10-09	
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01	
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17	
5	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24	
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2016-04-25	2017-04-25	
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A	
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09	
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13	

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24
7	Horn Antenna(26GHz- 40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2015-02-12	2018-02-12
8	Low Noise Amplifier	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2016-10-09	2017-10-09
9	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A



Report No.: SZEM161201106701

Page: 10 of 42

	RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
2	Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
3	Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
4	Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



Report No.: SZEM161201106701

Page: 11 of 42

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:




The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



Report No.: SZEM161201106701

Page: 12 of 42

6.2 Conducted Peak Output Power



Measurement Data

	GFSK mode									
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result							
Lowest	0.56	30.00	Pass							
Middle	1.02	30.00	Pass							
Highest	1.41	30.00	Pass							




Report No.: SZEM161201106701


Page: 13 of 42

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Middle






Report No.: SZEM161201106701

Page: 14 of 42








Report No.: SZEM161201106701

Page: 15 of 42

6.3 6dB Occupy Bandwidth



Measurement Data

GFSK mode									
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result						
Lowest	0.693	≥500	Pass						
Middle	0.699	≥500	Pass						
Highest	0.714	≥500	Pass						




Report No.: SZEM161201106701


Page: 16 of 42

Test plot as follows:

Test mode: GFSK Test channel: Lowest




Test mode: GFSK Test channel: Middle






Report No.: SZEM161201106701

Page: 17 of 42








Report No.: SZEM161201106701

Page: 18 of 42

6.4 Power Spectral Density



Measurement Data

	GFSK mode									
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result							
Lowest	-14.68	≤8.00	Pass							
Middle	-14.28	≤8.00	Pass							
Highest	-14.18	≤8.00	Pass							




Report No.: SZEM161201106701


Page: 19 of 42

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM161201106701

Page: 20 of 42








Report No.: SZEM161201106701

Page: 21 of 42

6.5 Band-edge for RF Conducted Emissions






Report No.: SZEM161201106701


Page: 22 of 42

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Highest





Report No.: SZEM161201106701

Page: 23 of 42

6.6 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)					
Test Method:	ANSI C63.10: 2013 Section 11.11					
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table					
	Ground Reference Plane					
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test Mode:	Transmitting with GFSK modulation.					
Instruments Used:	Refer to section 5.10 for details.					
Test Results:	Pass					





Report No.: SZEM161201106701

Page: 24 of 42

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM161201106701

Page: 25 of 42










Report No.: SZEM161201106701

Page: 26 of 42






Report No.: SZEM161201106701

Page: 27 of 42








Report No.: SZEM161201106701

Page: 28 of 42



Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.



Report No.: SZEM161201106701

Page: 29 of 42

6.7 Radiated Spurious Emission


6.7.1 Spurious Emiss	sions								
Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10 :2013 Section 11.12								
Test Site:	Below 1GHz:								
	Measurement Distance Above 1GHz:	Measurement Distance: 3m (Semi-Anechoic Chamber) Above 1GHz:							
	Measurement Distance	: 3n	n (Full-Anecho	oic Chambe	r)				
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark			
	0.009MHz-0.090MH	Z	Peak	10kHz	30kHz	Peak			
	0.009MHz-0.090MH	Z	Average	10kHz	30kHz	Average			
	0.090MHz-0.110MH	Z	Quasi-peak	10kHz	30kHz	Quasi-peak			
	0.110MHz-0.490MH	Z	Peak	10kHz	30kHz	Peak			
	0.110MHz-0.490MH	z	Average	10kHz	30kHz	Average			
	0.490MHz -30MHz		Quasi-peak	10kHz	30kHz	Quasi-peak			
	30MHz-1GHz		Quasi-peak	100 kHz	300kHz	Quasi-peak			
	Above 1GHz		Peak	1MHz	3MHz	Peak			
	Above Tariz		Peak	1MHz	10Hz	Average			
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)			
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300			
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30			
	1.705MHz-30MHz		30	-	-	30			
	30MHz-88MHz		100	40.0	Quasi-peak	3			
	88MHz-216MHz		150	43.5	Quasi-peak	3			
	216MHz-960MHz		200	46.0	Quasi-peak	3			
	960MHz-1GHz		500	54.0	Quasi-peak	3			
	Above 1GHz	500	54.0	Average	3				
	Note: 15.35(b), frequency emissions is limit applicable to the e peak emission level rad	20c quip	IB above the oment under t	maximum p est. This pe	ermitted ave	rage emission			



Report No.: SZEM161201106701

Page: 30 of 42

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB

This document is issued by the Company subject to its General Conditions of Service printed overleaf,-available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, foregry or fasification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tasted and such sample(s) are national for 30 days only.



Report No.: SZEM161201106701

Page: 31 of 42


	margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel (2402MHz),the middle channel (2440MHz),the Highest channel (2480MHz) i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with GFSK modulation. Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation.
	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case.
	For below 1GHz part, through pre-scan, the worst case is the lowest channel.
	Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass



Report No.: SZEM161201106701

Page: 32 of 42

Radiated Emission below 1GHz							
30MHz~1GHz (QP)							
Test mode: Transmitting mode Vertical							



Condition: 3m VERTICAL Job No. : 111067CR Test mode: TX mode


		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	——dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
			,					
1	225.31	1.55	11.51	26.78	41.08	27.36	46.00	-18.64
2	324.46	1.98	14.78	26.74	35.86	25.88	46.00	-20.12
3	383.93	2.16	16.11	27.03	41.73	32.97	46.00	-13.03
4	511.84	2.61	18.13	27.52	40.77	33.99	46.00	-12.01
5	576.64	2.68	19.15	27.73	40.04	34.14	46.00	-11.86
6 pp	768.75	3.11	21.92	27.46	38.02	35.59	46.00	-10.41



Report No.: SZEM161201106701

Page: 33 of 42

Test mode: Transmitting mode Horizontal



Condition: 3m HORIZONTAL

Job No. : 111067CR Test mode: TX mode

	Freq			Preamp Factor				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	225.31	1.55	11.51	26.78	47.42	33.70	46.00	-12.30
2	287.99	1.85	13.37	26.63	45.47	34.06	46.00	-11.94
3	324.46	1.98	14.78	26.74	48.08	38.10	46.00	-7.90
4	372.00	2.12	15.75	26.97	46.81	37.71	46.00	-8.29
5 pp	396.24	2.19	16.25	27.08	48.40	39.76	46.00	-6.24
6	467.24	2.48	17.52	27.37	42.22	34.85	46.00	-11.15



Report No.: SZEM161201106701

Page: 34 of 42

Transmitter Emission above 1GHz										
Test mode:		GFSK	Tes	t channel:	Lowest	Rema	ark:	Peak		
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3960.700	7.80	33.50	38.00	44.73	48.03	74.00	-25.97	Vertical		
4804.000	8.87	34.16	38.40	43.82	48.45	74.00	-25.55	Vertical		
5913.378	10.32	34.65	38.32	43.75	50.40	74.00	-23.60	Vertical		
7206.000	10.68	36.42	37.11	41.42	51.41	74.00	-22.59	Vertical		
9608.000	12.50	37.52	35.10	37.53	52.45	74.00	-21.55	Vertical		
12120.390	14.46	38.67	35.89	36.34	53.58	74.00	-20.42	Vertical		
3574.015	7.66	32.42	37.96	45.00	47.12	74.00	-26.88	Horizontal		
4804.000	8.87	34.16	38.40	43.33	47.96	74.00	-26.04	Horizontal		
5828.433	10.08	34.60	38.33	44.10	50.45	74.00	-23.55	Horizontal		
7206.000	10.68	36.42	37.11	41.65	51.64	74.00	-22.36	Horizontal		
9608.000	12.50	37.52	35.10	37.57	52.49	74.00	-21.51	Horizontal		
12279.260	14.33	38.77	36.27	37.06	53.89	74.00	-20.11	Horizontal		

Test mode:		GFSK	Test channel:		Middle	Rem	nark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3831.060	7.75	33.15	37.98	44.15	47.07	74.00	-26.93	Vertical
4880.000	8.97	34.29	38.44	42.09	46.91	74.00	-27.09	Vertical
6202.582	10.30	34.87	38.10	43.58	50.65	74.00	-23.35	Vertical
7320.000	10.72	36.37	37.01	41.17	51.25	74.00	-22.75	Vertical
9760.000	12.58	37.55	35.02	37.07	52.18	74.00	-21.82	Vertical
12243.770	14.36	38.75	36.19	36.54	53.46	74.00	-20.54	Vertical
3776.027	7.73	33.00	37.98	43.37	46.12	74.00	-27.88	Horizontal
4880.000	8.97	34.29	38.44	41.37	46.19	74.00	-27.81	Horizontal
5964.939	10.46	34.68	38.31	43.84	50.67	74.00	-23.33	Horizontal
7320.000	10.72	36.37	37.01	41.06	51.14	74.00	-22.86	Horizontal
9760.000	12.58	37.55	35.02	37.79	52.90	74.00	-21.10	Horizontal
12033.020	14.53	38.62	35.68	36.25	53.72	74.00	-20.28	Horizontal



Report No.: SZEM161201106701

Page: 35 of 42

Test mode:		GFSK	Test	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3563.687	7.65	32.39	37.96	45.04	47.12	74.00	-26.88	Vertical
4960.000	9.09	34.43	38.48	44.24	49.28	74.00	-24.72	Vertical
6060.637	10.48	34.75	38.24	43.42	50.41	74.00	-23.59	Vertical
7440.000	10.77	36.32	36.90	40.93	51.12	74.00	-22.88	Vertical
9920.000	12.67	37.58	34.94	36.91	52.22	74.00	-21.78	Vertical
12102.870	14.47	38.66	35.85	36.33	53.61	74.00	-20.39	Vertical
3711.030	7.71	32.81	37.97	44.73	47.28	74.00	-26.72	Horizontal
4960.000	9.09	34.43	38.48	42.70	47.74	74.00	-26.26	Horizontal
5913.378	10.32	34.65	38.32	44.15	50.80	74.00	-23.20	Horizontal
7440.000	10.77	36.32	36.90	41.20	51.39	74.00	-22.61	Horizontal
9920.000	12.67	37.58	34.94	36.94	52.25	74.00	-21.75	Horizontal
12067.890	14.50	38.64	35.76	36.44	53.82	74.00	-20.18	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM161201106701

Page: 36 of 42

6.8 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2013 Section	11.12					
Test Site:	Below 1GHz: Measurement Distance: 3m (Semi-Anechoic Chamber) Above 1GHz:						
	Measurement Distance: 3m	(Full-Anechoic Chamber)					
Limit:	Frequency	Limit (dBuV/m @3m)	Remark				
	30MHz-88MHz	40.0	Quasi-peak Value				
	88MHz-216MHz	43.5	Quasi-peak Value				
	216MHz-960MHz	46.0	Quasi-peak Value				
	960MHz-1GHz	54.0	Quasi-peak Value				
	Ab 4011-	54.0	Average Value				
	Above 1GHz	74.0	Peak Value				
Test Setup:							






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz

Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel

This document is issued by the Company subject to its General Conditions of Service printed overleaf,-available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only



Report No.: SZEM161201106701

Page: 37 of 42

Test Mode:	 h. Test the EUT in the lowest channel, the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Transmitting with GFSK modulation. Transmitting mode
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass




Report No.: SZEM161201106701

Page: 38 of 42

Test plot as follows:

Test channel:	Lowest	Remark:	Peak	Vertical
---------------	--------	---------	------	----------



Condition: 3m VERTICAL Job No: : 11067CR

Mode: : 2402 Bandedge

: BLE

1 2


		Cable	Ant	Preamp	Kead		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
-	MHz	dB	dB/m	——dB	dBuV	dBuV/m	dBuV/m	——dB
	2389.052	5.34	29.07	37.96	57.15	53.60	74.00	-20.40
	2389.963	5.34	29.08	37.96	52.43	48.89	74.00	-25.11
pp	2401.741	5.35	29.11	37.96	94.89	91.39	74.00	17.39



Report No.: SZEM161201106701

Page: 39 of 42

Test channel: Lowest Remark: Peak Horizontal



Condition: 3m HORIZONTAL

Job No: : 11067CR

Mode: : 2402 Bandedge

: BLE


Ant Preamp Cable Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit MHz dB dB/m dBuV dBuV/m dBuV/m 2390.000 5.34 29.08 37.96 48.67 45.13 74.00 -28.87 5.35 29.11 37.96 92.13 88.63 74.00 14.63 2 pp 2401.843



Report No.: SZEM161201106701

Page: 40 of 42

Test channel:	Highest	Remark:	Peak	Vertical
---------------	---------	---------	------	----------



Condition: 3m VERTICAL
Job No: : 11067CR

Mode: : 2480 Bandedge

: BLE

Cable

Limit	Line	Level	Level	Factor	Factor	Loss	Freq	
dB	dBuV/m	dBuV/m	dBuV	dB	dB/m	dB	MHz	
16.05	74.00	90.05	93.25	37.95	29.34	5.41	p 2480.254	1 pp
-30.34	74.00	43.66	46.85	37.95	29.35	5.41	2483.500	2
-23.08	74.00	50.92	54.09	37.95	29.37	5.41	2490.771	3

Read

Limit

0ver


Ant Preamp



Report No.: SZEM161201106701

41 of 42 Page:

Test channel:	Highest	Remark:	Peak	Horizontal
---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No: : 11067CR

Mode: : 2480 Bandedge

: BLE

	Cable	Ant	Preamp	Read		Limit	0ver
Freq	Loss	Factor	Factor	Level	Level	Line	Limit
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 2480.304	5.41	29.34	37.95	90.88	87.68	74.00	13.68
2 2483.500	5.41	29.35	37.95	44.46	41.27	74.00	-32.73
3 2491.923	5.41	29.38	37.95	48.03	44.87	74.00	-29.13

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor




Report No.: SZEM161201106701

Page: 42 of 42


7 Photographs - EUT Test Setup

Test model No.: PTR5528

7.1 Radiated Emission



7.2 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1612011067CR.