

RF EXPOSURE EVALUATION METHOD

FCC ID: 2AA85M-295

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$
 $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

WIFI:

TX 802.11b Mode				
Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	Maximum Conducted Output Power(AV)
		(dBm)	(dBm)	mW
TX 802.11b Mode				
CH01	2412	12.13	9.01	7.96
CH06	2437	11.81	8.98	7.91
CH11	2462	11.65	8.69	7.40
TX 802.11g Mode				
CH01	2412	12.04	8.17	6.56
CH06	2437	11.71	8.69	7.40
CH11	2462	11.40	8.73	7.46
TX 802.11n(20M) Mode				
CH01	2412	11.84	7.68	5.86
CH06	2437	11.36	7.41	5.51
CH11	2462	11.80	7.23	5.28
TX 802.11n(40M) Mode				
CH03	2422	9.15	6.62	4.59
CH06	2437	9.32	6.37	4.34
CH09	2452	9.06	6.05	4.03

Remark: The best case gain of the antenna is 1.0dBi.

1.0 dBi logarithmic terms convert to numeric result is nearly 1.26

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

WIFI:

Mode	[(max. power of channel, including tune-up tolerance, mW)]	(min. test separation distance,mm)]	[√ f(GHz)]	Result	Limit
802.11b					
CH01	7.96	5	2.412	2.47	3
CH06	7.91	5	2.437	2.47	3
CH11	7.40	5	2.462	2.32	3
802.11g					
CH01	6.56	5	2.412	2.04	3
CH06	7.40	5	2.437	2.31	3
CH11	7.46	5	2.462	2.34	3
802.11n(20)					
CH01	5.86	5	2.412	1.82	3
CH06	5.51	5	2.437	1.72	3
CH11	5.28	5	2.462	1.66	3
802.11n(40)					
CH03	4.59	5	2.422	1.43	3
CH06	4.34	5	2.437	1.36	3
CH09	4.03	5	2.452	1.26	3

The test Result is less than 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.