

RADIO FREQUENCY EXPOSURE

According to KDB 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances

≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$
 $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Worse case is as below: [Output power is **-3.87dBm (0.41mW)** at **2440MHz**]

According to the formula.calculate the EIRP test result:

$[(\text{max.power of channel including tune-up tolerance, mW}) / (\text{min.test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 $(0.41\text{mW} / 5\text{mm}) \cdot [\sqrt{2.440(\text{GHz})}] = \mathbf{0.128} < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

A101, No.65, Zhuji Highway, Tianhe District, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service