

# FCC PART 15.249 **TEST REPORT**

For

## TelergyHD BV

6 1217 AP Hilversum, Netherlands

FCC ID: 2AA9TTHD601DC0002

Report Type: Product Type:

Original Report RF Remote Control

**Test Engineer:** Candy Li

**Report Number:** RSZ140418551-00

**Report Date:** 2014-04-24

Alvin Huang

**Reviewed By:** RF Leader

Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F, the 3rd Phase of WanLi Industrial Building,

ShiHua Road, FuTian Free Trade Zone Prepared By:

Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	4
JUSTIFICATION	4
EQUIPMENT MODIFICATIONS	
BLOCK DIAGRAM OF TEST SETUP	4
SUMMARY OF TEST RESULTS	5
FCC§15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
Antenna Connector Construction	
FCC §15.205, §15.209 & §15.249 - RADIATED EMISSIONS	7
APPLICABLE STANDARD	7
MEASUREMENT UNCERTAINTY	
TEST EQUIPMENT SETUP	7
EUT SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	8
TEST EQUIPMENT LIST AND DETAILS	9
TEST RESULTS SUMMARY TEST DATA	
FCC §15.215(C) - 20 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	12

### **GENERAL INFORMATION**

### **Product Description for Equipment under Test (EUT)**

The *TelergyHD BV* 's product, model number: *THD-AIR1 (FCC ID: 2AA9TTHD601DC0002)* or the "EUT" in this report was a *RF Remote control*, which was measured approximately: 17.32 cm (L) x 5.41 cm (W) x 1.87 cm (H), rated input voltage: DC 2\*1.5V battery.

Report No.: RSZ140418551-00

\*All measurement and test data in this report was gathered from production sample serial number: 1404005 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2014-04-18.

### **Objective**

This type approval report is prepared on behalf of *TelergyHD BV* in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

### **Related Submittal(s)/Grant(s)**

No related submittal.

## **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

### **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.249 Page 3 of 14

## **SYSTEM TEST CONFIGURATION**


### **Justification**

The system was configured in a testing mode which provided by manufacturer.

## **Equipment Modifications**

No modifications were made to the unit tested.

## **Block Diagram of Test Setup**



Report No.: RSZ140418551-00

FCC Part 15.249 Page 4 of 14

## **SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Not Applicable*
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.215(c)	20dB Emission Bandwidth	Compliance

Report No.: RSZ140418551-00

Not Applicable\*: Battery power supply only.

FCC Part 15.249 Page 5 of 14

## FCC§15.203 - ANTENNA REQUIREMENT

## **Applicable Standard**

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Report No.: RSZ140418551-00

## **Antenna Connector Construction**

The EUT has a PCB antenna arrangement, which was permanently attached, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliant.

FCC Part 15.249 Page 6 of 14

## FCC'§15.205, §15.209 & §15.249 - RADIATED EMISSIONS

### **Applicable Standard**

As per FCC §15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Report No.: RSZ140418551-00

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

## **Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz, 4.92 dB for above 1GHz, and it will not be taken into consideration for the test data recorded in the report

## **Test Equipment Setup**

The spectrum analyzer or receiver is set as:

Below 1000MHz:


RBW = 100 kHz / VBW = 300 kHz / Sweep = Auto

Above 1000MHz:

Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

FCC Part 15.249 Page 7 of 14

#### **EUT Setup**



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

#### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 mete, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.249 Page 8 of 14

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
НР	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
Mini-Circuits	Pre-amplifier	ZVA-183-S+	5969001149	2014-04-03	2015-04-03
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12

Report No.: RSZ140418551-00

### **Test Results Summary**

According to the data in the following table, the worst margin reading as below:

## 8.29 dB at 2369.8 MHz in the Horizontal polarization

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

in BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Candy Li on 2014-04-22.

Test Mode: Transmitting

FCC Part 15.249 Page 9 of 14

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

## **30 MHz to 25 GHz:**

Frequency	Receiver		Turntable	Rx An	tenna		Corrected	FCC 15.249/15.2	
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Low Channel (2402 MHz)								
352.0	39.27	QP	142	2.0	Н	12.7	26.57	46	19.43
2402.0	83.52	PK	165	2.0	Н	5.48	89.00	114	25
2402.0	83.02	Ave.	165	2.0	Н	5.48	88.50	94	5.5
2402.0	85.83	PK	103	1.9	V	5.48	91.31	114	22.69
2402.0	85.15	Ave.	103	1.9	V	5.48	90.63	94	3.37
2337.8	40.97	PK	25	2.4	Н	4.99	45.96	74	28.04
2337.8	36.70	Ave.	25	2.4	Н	4.99	41.69	54	12.31
2369.8	43.58	PK	113	1.2	Н	5.48	49.06	74	24.94
2369.8	40.23	Ave.	113	1.2	Н	5.48	45.71	54	8.29
2498.2	38.94	PK	253	2.1	V	7.21	46.15	74	27.85
2498.2	32.56	Ave.	253	2.1	V	7.21	39.77	54	14.23
4804.0	37.86	PK	207	2.3	V	12.44	50.30	74	23.70
4804.0	22.52	Ave.	207	2.3	V	12.44	34.96	54	19.04
7206.0	36.02	PK	7	2.0	Н	17.06	53.08	74	20.92
7206.0	20.06	Ave.	7	2.0	Н	17.06	37.12	54	16.88
9608.0	34.66	PK	83	2.1	Н	19.28	53.94	74	20.06
9608.0	20.33	Ave.	83	2.1	Н	19.28	39.61	54	14.39
	·		Middle (	Channel	(2436 N	ИHz)	•		
352.0	38.88	QP	213	1.8	Н	12.7	26.18	46	19.82
2436.0	85.70	PK	127	1.4	Н	6.13	91.83	114	22.17
2436.0	85.41	Ave.	127	1.4	Н	6.13	91.54	94	2.46
2436.0	81.30	PK	166	1.6	V	6.13	87.43	114	26.57
2436.0	81.03	Ave.	166	1.6	V	6.13	87.16	94	6.84
2339.9	40.04	PK	102	1.7	V	5.48	45.52	74	28.48
2339.9	35.92	Ave.	102	1.7	V	5.48	41.40	54	12.60
2371.9	41.90	PK	316	2.4	Н	5.48	47.38	74	26.62
2371.9	38.46	Ave.	316	2.4	Н	5.48	43.94	54	10.06
2500.0	41.40	PK	298	2.3	Н	7.21	48.61	74	25.39
2500.0	37.14	Ave.	298	2.3	Н	7.21	44.35	54	9.65
4872.0	35.76	PK	347	2.1	Н	12.4	48.16	74	25.84
4872.0	21.74	Ave.	347	2.1	Н	12.4	34.14	54	19.86
7308.0	35.11	PK	217	1.9	V	16.62	51.73	74	22.27
7308.0	20.59	Ave.	217	1.9	V	16.62	37.21	54	16.79
9744.0	35.87	PK	353	1.8	Н	19.4	55.27	74	18.73
9744.0	19.82	Ave.	353	1.8	Н	19.4	39.22	54	14.78

Report No.: RSZ140418551-00

FCC Part 15.249 Page 10 of 14

Frequency	R	eceiver	Turntable	Rx An	itenna		rected Corrected		Part 205/15.209
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
			High C	hannel (	2479 M	Hz)			
352.0	39.05	QP	139	1.7	Н	12.7	26.35	46	19.65
2479.0	86.49	PK	216	2.4	Н	7.21	93.70	114	20.3
2479.0	85.98	Ave.	216	2.4	Н	7.21	93.19	94	0.81
2479.0	86.90	PK	314	2.1	V	7.21	94.11	114	19.89
2479.0	85.71	Ave.	314	2.1	V	7.21	92.92	94	1.08
2350.9	39.62	PK	236	2.4	Н	5.48	45.10	74	28.90
2350.9	34.73	Ave.	236	2.4	Н	5.48	40.21	54	13.79
2383.3	41.39	PK	274	1.5	Н	5.48	46.87	74	27.13
2383.3	37.78	Ave.	274	1.5	Н	5.48	43.26	54	10.74
2483.5	42.81	PK	251	1.5	V	7.21	50.02	74	23.98
2483.5	27.95	Ave.	251	1.5	V	7.21	35.16	54	18.84
4958.0	37.53	PK	31	2.1	Н	12.5	50.03	74	23.97
4958.0	22.01	Ave.	31	2.1	Н	12.5	34.51	54	19.49
7437.0	34.83	PK	80	1.8	Н	15.91	50.74	74	23.26
7437.0	21.38	Ave.	80	1.8	Н	15.91	37.29	54	16.71
9916.0	35.35	PK	161	2.3	V	19.39	54.74	74	19.26
9916.0	20.44	Ave.	161	2.3	V	19.39	39.83	54	14.17

Report No.: RSZ140418551-00

### Note:

Corrected Amplitude = Corrected Factor + Reading
Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor
Margin = Limit – Corr. Amplitude

FCC Part 15.249 Page 11 of 14

## FCC'§15.215(c) - 20'dB EMISSION BANDWIDTH

#### **Applicable Standard**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Report No.: RSZ140418551-00

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that indicated 20dB bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	25 ℃
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Candy Li on 2014-04-22.

Test Mode: Transmitting


Pleas refer to the following plots.

FCC Part 15.249 Page 12 of 14

#### Low Channel




### **Middle Channel**



FCC Part 15.249 Page 13 of 14

#### Report No.: RSZ140418551-00

## **High Channel**



\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15.249 Page 14 of 14